

```
In [1]: # Here I import all packages I will need
import warnings
warnings.filterwarnings('ignore')
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
%matplotlib inline
import seaborn as sns
from sklearn.model_selection import train_test_split
from sklearn.impute import SimpleImputer
from statsmodels.tools.tools import add_constant
from sklearn.ensemble import BaggingClassifier
from sklearn.ensemble import RandomForestClassifier
from sklearn.ensemble import AdaBoostClassifier, GradientBoostingClassifier
from xgboost import XGBClassifier
from sklearn.ensemble import StackingClassifier
from sklearn.tree import DecisionTreeClassifier
from sklearn import metrics
from sklearn.metrics import confusion_matrix, classification_report, accuracy_score, p
from sklearn.model_selection import GridSearchCV
from scipy.stats import uniform
from sklearn import linear_model, datasets
from sklearn.model_selection import RandomizedSearchCV
```

```
In [2]: # Here I am loading in my csv file into a dataframe
df = pd.read_csv('/Users/conne/Downloads/EasyVisa.csv')
```

```
In [3]: # Here I create a copy in order to preserve my original data
data = df.copy()
```

```
In [4]: data.head()
```

```
Out[4]:
```

	case_id	continent	education_of_employee	has_job_experience	requires_job_training	no_of_employe
0	EZYV01	Asia	High School	N	N	145
1	EZYV02	Asia	Master's	Y	N	24
2	EZYV03	Asia	Bachelor's	N	Y	444
3	EZYV04	Asia	Bachelor's	N	N	
4	EZYV05	Africa	Master's	Y	N	10

```
In [5]: data.tail()
```

```
Out[5]:
```

	case_id	continent	education_of_employee	has_job_experience	requires_job_training	no_of_
<b>25475</b>	EZYV25476	Asia	Bachelor's	Y	Y	
<b>25476</b>	EZYV25477	Asia	High School	Y	N	
<b>25477</b>	EZYV25478	Asia	Master's	Y	N	
<b>25478</b>	EZYV25479	Asia	Master's	Y	Y	
<b>25479</b>	EZYV25480	Asia	Bachelor's	Y	N	

We see we have 12 different variables but only 11 of them will be relevant as case\_id has no statistical value.

```
In [6]: data.shape
```

```
Out[6]: (25480, 12)
```

```
In [7]: data.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 25480 entries, 0 to 25479
Data columns (total 12 columns):
#   Column                                Non-Null Count  Dtype
---  -
0   case_id                               25480 non-null  object
1   continent                             25480 non-null  object
2   education_of_employee                 25480 non-null  object
3   has_job_experience                    25480 non-null  object
4   requires_job_training                 25480 non-null  object
5   no_of_employees                      25480 non-null  int64
6   yr_of_estab                          25480 non-null  int64
7   region_of_employment                 25480 non-null  object
8   prevailing_wage                      25480 non-null  float64
9   unit_of_wage                         25480 non-null  object
10  full_time_position                   25480 non-null  object
11  case_status                          25480 non-null  object
dtypes: float64(1), int64(2), object(9)
memory usage: 2.3+ MB
```

As we can see we have no missing values but we do have 9 columns that are objects that will need to be converted to categorical variables.

```
In [8]: cols = data.select_dtypes(['object'])
        cols.columns
```

```
Out[8]: Index(['case_id', 'continent', 'education_of_employee', 'has_job_experience',
              'requires_job_training', 'region_of_employment', 'unit_of_wage',
              'full_time_position', 'case_status'],
              dtype='object')
```

This is a list of all columns we'll need to convert

```
In [9]: data.describe().T
```

Out[9]:

	count	mean	std	min	25%	50%	75%	
<b>no_of_employees</b>	25480.0	5667.043210	22877.928848	-26.0000	1022.00	2109.00	3504.0000	60
<b>yr_of_estab</b>	25480.0	1979.409929	42.366929	1800.0000	1976.00	1997.00	2005.0000	
<b>prevailing_wage</b>	25480.0	74455.814592	52815.942327	2.1367	34015.48	70308.21	107735.5125	31

no\_of\_employees may have a mean that is skewed due to some large outliers. These outliers shouldn't be removed though as they are valid data points. The yr\_of\_estab ranges between 1800 and 2016 with an average of 1979. prevailing\_wage has an unusually small min when compared to the other numbers in the 5 number summary. This min should be examined further.

```
In [10]: print(df.value_counts(subset='continent'))
print(df.value_counts(subset='education_of_employee'))
print(df.value_counts(subset='has_job_experience'))
print(df.value_counts(subset='requires_job_training'))
print(df.value_counts(subset='no_of_employees'))
print(df.value_counts(subset='yr_of_estab'))
print(df.value_counts(subset='region_of_employment'))
print(df.value_counts(subset='prevailing_wage'))
print(df.value_counts(subset='unit_of_wage'))
print(df.value_counts(subset='full_time_position'))
print(df.value_counts(subset='case_status'))
```

```

continent
Asia          16861
Europe        3732
North America 3292
South America 852
Africa         551
Oceania        192
dtype: int64
education_of_employee
Bachelor's    10234
Master's      9634
High School   3420
Doctorate     2192
dtype: int64
has_job_experience
Y      14802
N      10678
dtype: int64
requires_job_training
N      22525
Y       2955
dtype: int64
no_of_employees
183      18
854      16
724      16
766      15
1476     15
..
6129      1
6130      1
6137      1
6138      1
602069     1
Length: 7105, dtype: int64
yr_of_estab
1998     1134
2005     1051
2001     1017
2007      994
1999      870
...
1807      6
1822      4
1846      4
1810      3
1824      2
Length: 199, dtype: int64
region_of_employment
Northeast   7195
South       7017
West        6586
Midwest     4307
Island       375
dtype: int64
prevailing_wage
60948.15     2
88664.77     2
82560.28     2
105.96       2

```

```

87751.88      2
..
46738.47      1
46727.57      1
46725.85      1
46719.75      1
319210.27     1
Length: 25454, dtype: int64
unit_of_wage
Year      22962
Hour      2157
Week      272
Month      89
dtype: int64
full_time_position
Y      22773
N      2707
dtype: int64
case_status
Certified    17018
Denied       8462
dtype: int64

```

We can see a majority of positions are full time. Most people were paid a salary wage. The Workers are fairly evenly spread except for the Island region. 1999 was the year with the highest number of businesses were established with 1134 businesses being established that year.

```

In [11]: for feature in data.columns:
          if data[feature].dtype == 'object':
              data[feature] = pd.Categorical(data[feature])
          data.head(10)

```

```

Out[11]:
   case_id  continent  education_of_employee  has_job_experience  requires_job_training  no_of_employo
0  EZYV01      Asia      High School          N                N                145
1  EZYV02      Asia      Master's          Y                N                24
2  EZYV03      Asia      Bachelor's          N                Y                444
3  EZYV04      Asia      Bachelor's          N                N                30
4  EZYV05      Africa      Master's          Y                N                10
5  EZYV06      Asia      Master's          Y                N                25
6  EZYV07      Asia      Bachelor's          N                N                49
7  EZYV08      North America      Bachelor's          Y                N                30
8  EZYV09      Asia      Bachelor's          N                N                48
9  EZYV10      Europe      Doctorate          Y                N                22

```

Here I convert all objects in categories.

```

In [12]: def histogram_boxplot(data, feature, figsize=(15, 10), kde=False, bins=None):
          """

```

## Boxplot and histogram combined

```

data: dataframe
feature: dataframe column
figsize: size of figure (default (15,10))
kde: whether to show the density curve (default False)
bins: number of bins for histogram (default None)
"""

f2, (ax_box2, ax_hist2) = plt.subplots(
    nrows=2, # Number of rows of the subplot grid= 2
    sharex=True, # x-axis will be shared among all subplots
    gridspec_kw={"height_ratios": (0.25, 0.75)},
    figsize=figsize,
) # creating the 2 subplots
sns.boxplot(
    data=data, x=feature, ax=ax_box2, showmeans=True, color="violet"
) # boxplot will be created and a triangle will indicate the mean value of the co
sns.histplot(
    data=data, x=feature, kde=kde, ax=ax_hist2, bins=bins
) if bins else sns.histplot(
    data=data, x=feature, kde=kde, ax=ax_hist2
) # For histogram
ax_hist2.axvline(
    data[feature].mean(), color="green", linestyle="--"
) # Add mean to the histogram
ax_hist2.axvline(
    data[feature].median(), color="black", linestyle="--"
) # Add median to the histogram

```

```

In [13]: def labeled_barplot(data, feature, perc=False, n=None):
    """
    Barplot with percentage at the top

    data: dataframe
    feature: dataframe column
    perc: whether to display percentages instead of count (default is False)
    n: displays the top n category levels (default is None, i.e., display all levels)
    """

    total = len(data[feature]) # Length of the column
    count = data[feature].nunique()
    if n is None:
        plt.figure(figsize=(count + 2, 6))
    else:
        plt.figure(figsize=(n + 2, 6))

    plt.xticks(rotation=90, fontsize=15)
    ax = sns.countplot(
        data=data,
        x=feature,
        palette="Paired",
        order=data[feature].value_counts().index[:n],
    )

    for p in ax.patches:
        if perc == True:
            label = "{:.1f}%".format(
                100 * p.get_height() / total
            ) # percentage of each class of the category

```

```

else:
    label = p.get_height() # count of each level of the category

    x = p.get_x() + p.get_width() / 2 # width of the plot
    y = p.get_height() # height of the plot

    ax.annotate(
        label,
        (x, y),
        ha="center",
        va="center",
        size=12,
        xytext=(0, 5),
        textcoords="offset points",
    ) # annotate the percentage

plt.show() # show the plot

```

```

In [14]: def stacked_barplot(data, predictor, target):
        """
        Print the category counts and plot a stacked bar chart

        data: dataframe
        predictor: independent variable
        target: target variable
        """


        count = data[predictor].nunique()
        sorter = data[target].value_counts().index[-1]
        tab1 = pd.crosstab(data[predictor], data[target], margins=True).sort_values(
            by=sorter, ascending=False
        )
        print(tab1)
        print("-" * 120)
        tab = pd.crosstab(data[predictor], data[target], normalize="index").sort_values(
            by=sorter, ascending=False
        )
        tab.plot(kind="bar", stacked=True, figsize=(count + 1, 5))
        plt.legend(
            loc="lower left",
            frameon=False,
        )
        plt.legend(loc="upper left", bbox_to_anchor=(1, 1))
        plt.show()

```

```

In [15]: labeled_barplot(data, "requires_job_training", perc=True)


```



It seems as though most jobs don't require job training.


```
In [16]: labeled_barplot(data, "continent", perc=True)
```






Most workers came from asia with asians making up 66.2% of visas submitted

```
In [17]: labeled_barplot(data, "education_of_employee", perc=True)
```




It appears only 13.4% of applicants weren't college educated.

```
In [18]: labeled_barplot(data, "case_status", perc=True)
```




It seems around 2/3 of people were certified.

```
In [19]: labeled_barplot(data, "unit_of_wage", perc=True)
```




Salary was by far the most popular unit of wage as it makes up 90.1%

```
In [20]: labeled_barplot(data, "region_of_employment", perc=True)
```




The Northeast and South seem to have the highest rates of visa employment with the West in a close third.

```
In [21]: labeled_barplot(data, "full_time_position", perc=True)
```



Most visa jobs are full time positions/

```
In [22]: labeled_barplot(data, "has_job_experience", perc=True)
```




Just over half of visa applicants had job experience.

```
In [23]: labeled_barplot(data, "yr_of_estab", perc=True)
```



```
In [24]: plt.figure(figsize=(20,10))
sns.heatmap(data.corr(),annot=True,vmin=-1,vmax=1,fmt='.2f',cmap="Spectral")
plt.show()
```



We found no correlation


```
In [25]: stacked_barplot(data, "full_time_position", "case_status")
```

case_status	Certified	Denied	All
full_time_position			
All	17018	8462	25480
Y	15163	7610	22773
N	1855	852	2707

-----

-----






Full time positions don't seem to really effect case status.

In [26]: `stacked_barplot(data, "has_job_experience", "case_status")`

case_status	Certified	Denied	All
has_job_experience			
All	17018	8462	25480
N	5994	4684	10678
Y	11024	3778	14802

-----

-----




Question 3. Yes, if you have previous job experience you stand a much better chance at getting a visa.

Job experience seems to positively affect case status as having job experience increased the rate in which a visa was certified.

In [27]: `stacked_barplot(data, "region_of_employment", "case_status")`


case_status	Certified	Denied	All
region_of_employment			
All	17018	8462	25480
Northeast	4526	2669	7195
West	4100	2486	6586
South	4913	2104	7017
Midwest	3253	1054	4307
Island	226	149	375



The Midwest has a slightly lower rate of denial thus meaning it will have minor importance in predicting case status.

In [28]: `stacked_barplot(data, "unit_of_wage", "case_status")`

case_status	Certified	Denied	All
unit_of_wage			
All	17018	8462	25480
Year	16047	6915	22962
Hour	747	1410	2157
Week	169	103	272
Month	55	34	89




Question 4. Year or salary is most likely to be certified for a visa.

Salary has a much lower rate of denial thus meaning unit of wage will have importance in predicting case status.

In [29]: `stacked_barplot(data, "education_of_employee", "case_status")`

case_status	Certified	Denied	All
education_of_employee			
All	17018	8462	25480
Bachelor's	6367	3867	10234
High School	1164	2256	3420
Master's	7575	2059	9634
Doctorate	1912	280	2192




Question 1. Yes, education plays a large role in increasing the rate of certification.

Rate of denial drops greatly as the level of education increases meaning education of employee will be a valuable variable when trying to predict visa status.

In [30]: `stacked_barplot(data, "continent", "case_status")`

case_status	Certified	Denied	All
continent			
All	17018	8462	25480
Asia	11012	5849	16861
North America	2037	1255	3292
Europe	2957	775	3732
South America	493	359	852
Africa	397	154	551
Oceania	122	70	192




Question 2. visa status is a bit higher in Europe but fairly consistent throughout.

Europe has a slightly lower rate of denial thus meaning it will have minor importance in predicting case status.

In [31]: `stacked_barplot(data, "requires_job_training", "case_status")`


case_status	Certified	Denied	All
requires_job_training			
All	17018	8462	25480
N	15012	7513	22525
Y	2006	949	2955



There is no change in the rate of denial when looking at requires\_job\_training which means it will have less importance in predicting case status.

```
In [32]: sns.boxplot(data, x='prevailing_wage', y="case_status")
```

```
Out[32]: <Axes: xlabel='prevailing_wage', ylabel='case_status'>
```




Question 5. The prevailing wage doesn't seem to have much of an impact on case status.

```
In [33]: numeric_columns = data.select_dtypes(include=np.number).columns.tolist()

plt.figure(figsize=(15, 12))

for i, variable in enumerate(numeric_columns):
    plt.subplot(6, 4, i + 1)
    plt.boxplot(data[variable], whis=1.5)
    plt.tight_layout()
    plt.title(variable)

plt.show()
```



We can see we have quite a few outliers but they are valid data point and will help us when predicting case status.

```
In [34]: data_half = data.sample(frac=0.40)
```

```
In [35]: data_half.shape
```



Out[35]: (10192, 12)

```
In [36]: data_half.drop('case_id', axis=1, inplace=True)
cols = ["case_status"]
data_half[cols] = data_half[cols].replace("Certified", 1)
data_half[cols] = data_half[cols].replace("Denied", 0)
```

```
In [37]: X = data_half.drop(["case_status"], axis=1)
y = data_half["case_status"]
X = add_constant(X)
X = pd.get_dummies(X, drop_first=True)
X_train, X_test, y_train, y_test = train_test_split(
    X, y, test_size=0.30, random_state=1, stratify=y)
```

```
In [38]: y.value_counts(1)
```

```
Out[38]: 1    0.669937
0    0.330063
Name: case_status, dtype: float64
```

```
In [39]: y_test.value_counts(1)
```

```
Out[39]: 1    0.670046
0    0.329954
Name: case_status, dtype: float64
```

```
In [40]: def confusion_matrix_sklearn(model, predictors, target):
    """
    To plot the confusion_matrix with percentages

    model: classifier
    predictors: independent variables
    target: dependent variable
    """
    y_pred = model.predict(predictors)
    cm = confusion_matrix(target, y_pred)
    labels = np.asarray(
        [
            ["{0:0.0f}".format(item) + "\n{0:.2%}".format(item / cm.flatten().sum())]
            for item in cm.flatten()
        ]
    ).reshape(2, 2)

    plt.figure(figsize=(6, 4))
    sns.heatmap(cm, annot=labels, fmt="")
    plt.ylabel("True label")
    plt.xlabel("Predicted label")
```

```
In [41]: def get_metrics_score(model, flag=True):
    """
    model : classifier to predict values of X

    """
    score_list=[]

    pred_train = model.predict(X_train,y_train)
    pred_test = model.predict(X_test,y_test)

    train_acc = model.score(X_train,y_train)
```

```

test_acc = model.score(X_test,y_test)

train_recall = metrics.recall_score(y_train,pred_train, pos_label=1)
test_recall = metrics.recall_score(y_test,pred_test)

train_precision = metrics.precision_score(y_train,pred_train)
test_precision = metrics.precision_score(y_test,pred_test)

score_list.extend((train_acc,test_acc,train_recall,test_recall,train_precision,test_precision))

if flag == True:
    print("Accuracy on training set : ",model.score(X_train,y_train))
    print("Accuracy on test set : ",model.score(X_test,y_test))
    print("Recall on training set : ",metrics.recall_score(y_train,pred_train))
    print("Recall on test set : ",metrics.recall_score(y_test,pred_test))
    print("Precision on training set : ",metrics.precision_score(y_train,pred_train))
    print("Precision on test set : ",metrics.precision_score(y_test,pred_test))

return score_list

```

```

In [42]: def model_performance_classification_sklearn(model, predictors, target):
        """
        Function to compute different metrics to check classification model performance

        model: classifier
        predictors: independent variables
        target: dependent variable
        """

        pred = model.predict(predictors)

        acc = accuracy_score(target, pred)
        recall = recall_score(target, pred,pos_label=1)
        precision = precision_score(target, pred,pos_label=1)
        f1 = f1_score(target, pred,pos_label=1)

        df_perf = pd.DataFrame(
            {
                "Accuracy": acc,
                "Recall": recall,
                "Precision": precision,
                "F1": f1,
            },
            index=[0],
        )

        return df_perf

```

```


In [43]: ab_classifier = AdaBoostClassifier(random_state=1)
ab_classifier.fit(X_train,y_train)

ab_classifier_model_train_perf=model_performance_classification_sklearn(ab_classifier,X_train,y_train)
print(ab_classifier_model_train_perf)
ab_classifier_model_test_perf=model_performance_classification_sklearn(ab_classifier,X_test,y_test)
print(ab_classifier_model_test_perf)

confusion_matrix_sklearn(ab_classifier,X_test,y_test)

```

	Accuracy	Recall	Precision	F1
0	0.737454	0.881147	0.763416	0.818067
	Accuracy	Recall	Precision	F1
0	0.741007	0.878965	0.768017	0.819754




```
In [44]: gbc = GradientBoostingClassifier(random_state=1)
gbc.fit(X_train,y_train)
```

```
Out[44]: ▾ GradientBoostingClassifier
GradientBoostingClassifier(random_state=1)
```

```
In [45]: gb_classifier_model_train_perf=model_performance_classification_sklearn(gbc,X_train,y_
print("Training performance:\n",gb_classifier_model_train_perf)
gb_classifier_model_test_perf=model_performance_classification_sklearn(gbc,X_test,y_te
print("Testing performance:\n",gb_classifier_model_test_perf)
```

```
Training performance:
  Accuracy  Recall  Precision    F1
0  0.762265  0.884076  0.787218  0.832841
Testing performance:
  Accuracy  Recall  Precision    F1
0  0.743296  0.866276  0.776465  0.818916
```

```
In [46]: confusion_matrix_sklearn(gbc,X_test,y_test)
```



We can see that the gradient boosting training and testing models was fairly accurate and robust but it might still be improved through tuning the model.

```
In [47]: xgb_classifier = XGBClassifier(random_state=1, eval_metric='logloss')
xgb_classifier.fit(X_train,y_train)

xgb_classifier_model_train_perf=model_performance_classification_sklearn(xgb_classifier,X_train,y_train)
print("Training performance:\n",xgb_classifier_model_train_perf)
xgb_classifier_model_test_perf=model_performance_classification_sklearn(xgb_classifier,X_test,y_test)
print("Testing performance:\n",xgb_classifier_model_test_perf)


confusion_matrix_sklearn(xgb_classifier,X_test,y_test)
```

Training performance:

	Accuracy	Recall	Precision	F1
0	0.908747	0.966311	0.904072	0.934156

Testing performance:

	Accuracy	Recall	Precision	F1
0	0.716481	0.830161	0.766216	0.796908




We can see that the XGB test was fairly accurate and robust but it might still be improved through tuning the model. We can see that the XGB train suffered from overfitting but it might be improved through tuning the model.

```
In [48]: bagging_classifier = BaggingClassifier(random_state=1)
bagging_classifier.fit(X_train,y_train)

bagging_classifier_model_train_perf=model_performance_classification_sklearn(bagging_c
print(bagging_classifier_model_train_perf)
bagging_classifier_model_test_perf=model_performance_classification_sklearn(bagging_cl
print(bagging_classifier_model_test_perf)

confusion_matrix_sklearn(bagging_classifier,X_test,y_test)
```

	Accuracy	Recall	Precision	F1
0	0.983459	0.984934	0.990322	0.987621
	Accuracy	Recall	Precision	F1
0	0.691956	0.763787	0.773604	0.768664



```
In [49]: bagging_estimator_tuned = BaggingClassifier(random_state=1)

parameters = {'max_samples': [0.7,0.8,0.9,1],
              'max_features': [0.7,0.8,0.9,1],
              'n_estimators': [10,20,30,40,50],
              }

scorer = metrics.make_scorer(metrics.f1_score)

grid_obj = RandomizedSearchCV(bagging_estimator_tuned, parameters, scoring=scorer,cv=5)
grid_obj = grid_obj.fit(X_train, y_train)

bagging_estimator_tuned = grid_obj.best_estimator_


bagging_estimator_tuned.fit(X_train, y_train)
```

```
Out[49]: ▼ BaggingClassifier
BaggingClassifier(max_features=0.7, max_samples=0.7, n_estimators=40,
                 random_state=1)
```

```
In [50]: bagging_estimator_tuned_model_train_perf=model_performance_classification_sklern(baggi
print(bagging_estimator_tuned_model_train_perf)
bagging_estimator_tuned_model_test_perf=model_performance_classification_sklern(baggi
print(bagging_estimator_tuned_model_test_perf)

confusion_matrix_sklern(bagging_estimator_tuned,X_test,y_test)
```

	Accuracy	Recall	Precision	F1
0	0.985001	0.997908	0.980066	0.988906
	Accuracy	Recall	Precision	F1
0	0.724657	0.876037	0.753252	0.810018



```
In [51]: abc_tuned = AdaBoostClassifier(random_state=1)

parameters = {
    "base_estimator": [DecisionTreeClassifier(max_depth=1), DecisionTreeClassifier(max_c
                        DecisionTreeClassifier(max_depth=3)],
    "n_estimators": np.arange(10,110,10),
    "learning_rate": np.arange(0.1,2,0.1)
}

scorer = metrics.make_scorer(metrics.f1_score)

grid_obj = RandomizedSearchCV(abc_tuned, parameters, scoring=scorer, cv=5)
grid_obj = grid_obj.fit(X_train, y_train)

abc_tuned = grid_obj.best_estimator_


abc_tuned.fit(X_train, y_train)
```

```
Out[51]: ▸ AdaBoostClassifier
  ▸ base_estimator: DecisionTreeClassifier
    ▸ DecisionTreeClassifier
```

```
In [52]: abc_tuned_model_train_perf=model_performance_classification_sklearn(abc_tuned,X_train,
print(abc_tuned_model_train_perf)
abc_tuned_model_test_perf=model_performance_classification_sklearn(abc_tuned,X_test,y_
print(abc_tuned_model_test_perf)

confusion_matrix_sklearn(abc_tuned,X_test,y_test)
```

	Accuracy	Recall	Precision	F1
0	0.730726	0.914417	0.742945	0.819811
	Accuracy	Recall	Precision	F1
0	0.726292	0.91264	0.739715	0.817129



The test abc model performed well and is fairly robust. We saw slight improvements with tuning.

```
In [54]: gbc_tuned = GradientBoostingClassifier(init=AdaBoostClassifier(random_state=1), random_
parameters = {
    "n_estimators": [100, 150, 200, 250],
    "subsample": [0.8, 0.9, 1],
    "max_features": [0.7, 0.8, 0.9, 1]
}

scorer = metrics.make_scorer(metrics.f1_score)

grid_obj = RandomizedSearchCV(gbc_tuned, parameters, scoring=scorer, cv=5)
grid_obj = grid_obj.fit(X_train, y_train)

gbc_tuned = grid_obj.best_estimator_

gbc_tuned.fit(X_train, y_train)
```

```
Out[54]: ▸ GradientBoostingClassifier
          ▸ init: AdaBoostClassifier
            ▸ AdaBoostClassifier
```

```
In [55]: gbc_tuned_model_train_perf=model_performance_classification_sklearn(gbc_tuned,X_train,
print("Training performance:\n",gbc_tuned_model_train_perf)
gbc_tuned_model_test_perf=model_performance_classification_sklearn(gbc_tuned,X_test,y
print("Testing performance:\n",gbc_tuned_model_test_perf)
```




```
confusion_matrix_sklern(gbc_tuned,X_test,y_test)
```

Training performance:

	Accuracy	Recall	Precision	F1
0	0.762826	0.882821	0.788451	0.832971

Testing performance:

	Accuracy	Recall	Precision	F1
0	0.742315	0.86286	0.777143	0.817761



```
In [56]: xgb_tuned = XGBClassifier(random_state=1,eval_metric='logloss')

# Grid of parameters to choose from
## add from
parameters = {
    "n_estimators": np.arange(10,100,20),
    "scale_pos_weight": [0,1,2,5],
    "subsample": [0.5,0.7,0.9,1],
    "learning_rate": [0.01,0.1,0.2,0.05],
    "gamma": [0,1,3],
    "colsample_bytree": [0.5,0.7,0.9,1],
    "colsample_bylevel": [0.5,0.7,0.9,1]
}

# Type of scoring used to compare parameter combinations
acc_scorer = metrics.make_scorer(metrics.recall_score)

# Run the grid search
grid_obj = RandomizedSearchCV(xgb_tuned, parameters,scoring=acc_scorer,cv=5)
grid_obj = grid_obj.fit(X_train, y_train)

# Set the clf to the best combination of parameters
xgb_tuned = grid_obj.best_estimator_

# Fit the best algorithm to the data.
xgb_tuned.fit(X_train, y_train)
```

Out[56]:

```

XGBClassifier
XGBClassifier(base_score=None, booster=None, callbacks=None,
               colsample_bylevel=0.7, colsample_bynode=None,
               colsample_bytree=0.7, device=None, early_stopping_rounds=None,
               enable_categorical=False, eval_metric='logloss',
               feature_types=None, gamma=1, grow_policy=None,
               importance_type=None, interaction_constraints=None,
               learning_rate=0.01, max_bin=None, max_cat_threshold=None,
               max_cat_to_onehot=None, max_delta_step=None, max_depth=None,
               max_leaves=None, min_child_weight=None, missing=nan,
               monotone_constraints=None, multi_strategy=None, n_estimators=

```

In [58]:

```

xgb_tuned_model_train_perf=model_performance_classification_sklearn(xgb_tuned,X_train,
print("Training performance:\n",xgb_tuned_model_train_perf)
xgb_tuned_model_test_perf=model_performance_classification_sklearn(xgb_tuned,X_test,y
print("Testing performance:\n",xgb_tuned_model_test_perf)

confusion_matrix_sklearn(xgb_tuned,X_test,y_test)


```

Training performance:

	Accuracy	Recall	Precision	F1
0	0.669891	1.0	0.669891	0.802317

Testing performance:

	Accuracy	Recall	Precision	F1
0	0.670046	1.0	0.670046	0.802428



In [63]:

```

models_test_comp_df = pd.concat(
    [
        bagging_classifier_model_test_perf.T, bagging_estimator_tuned_model_test_perf.T,
        abc_tuned_model_test_perf.T, gb_classifier_model_test_perf.T, gbc_tuned_model_test_
        xgb_tuned_model_test_perf.T],
    axis=1,
)

```

```
models_test_comp_df.columns = [  
    "Bagging Classifier",  
    "Bagging Estimator Tuned",  
    "Adaboost Classifier",  
    "Adabosst Classifier Tuned",  
    "Gradient Boost Classifier",  
    "Gradient Boost Classifier Tuned",  
    "XGBoost Classifier",  
    "XGBoost Classifier Tuned"]  
print("Testing performance comparison:")  
models_test_comp_df
```

Testing performance comparison:

Out[63]:

	Bagging Classifier	Bagging Estimator Tuned	Adaboost Classifier	Adabosst Classifier Tuned	Gradient Boost Classifier	Gradient Boost Classifier Tuned	XGBoost Classifier	XGBoost Classifier Tuned
Accuracy	0.691956	0.724657	0.741007	0.726292	0.743296	0.742315	0.716481	0.670046
Recall	0.763787	0.876037	0.878965	0.912640	0.866276	0.862860	0.830161	1.000000
Precision	0.773604	0.753252	0.768017	0.739715	0.776465	0.777143	0.766216	0.670046
F1	0.768664	0.810018	0.819754	0.817129	0.818916	0.817761	0.796908	0.802428

It seems bagging tuned preformed the best overall I would recommend that the business look at prior job experience and education when evaluating visas.