




规格说明:Specifications:

电气特性:Electrical:

1. 额定电流: Current Rating
1.5A/contact terminal
2. 额定电压: Voltage Rating
30V DC
3. 接触阻抗:Contact Resistance
30 milliohms MAX
4. 耐电压:Dielectnic Withstanding Voitage:
500 V AC AT Sea Levl
5. 绝缘阻抗:Lnsulation Resistance:
1000MEGA ohms MIN

物理性能:Mechanical:

1. 插拔力: Cnector Mate and Unmate Force
Mate force:3.75kgf (MAX)
Unmate force:1.02kgf (MIN)
2. 端子保持力: Terminal Retenion
1.2kgf (MIN)

原材料:Material:

1. 塑胶:Housing:
Hing Temperature Tnermaplastics,
U1 94V-0 PBT/LCP White/Black
2. 端子:Contact:Copper Alloy C2680
3. 外壳:Shell: Copper Alloy C2680/SPCC

电镀:Finish:

1. 端子:Contact: Piated Gold in Mating Area;
Tin On Solder Talls
2. 外壳:Shell:
Nickel Plating

 首韩® SHOUHAN 深圳市首韩科技有限公司	图号 (DWG NO)		单位 (UNIT): MM
	版本 (REV)	A/0	比例 (SCALE) 1:1
	日期 (DATE)	2018. 07. 10	 
	设计 (DESIGN)	李春风	未注公差 TOLERANCE UNSPECIFIED
品名 (ITEM NO)	AM90	审核 (CHECKED)	钟华华
料号 (PART NO)		核准 (APPROVED)	罗孝金
模号 (MODEL NO)			