



ONNX Development Lab: Run ONNX ResNet in Tensorflow

Winnie Tsang, Chin Huang, Cognitive OpenTech

*Data and AI
Open Source Dojo*

Outline

- ❖ Unit 1: Setup and verify development dependencies
- ❖ Unit 2: Convert and Inspect ResNet model
- ❖ Unit 3: Run ResNet model

Unit 1: Setup development dependencies

- **Goal of the unit:** At the end of unit 1, you will learn how to install and verify the projects that are required for the ONNX Tensorflow converter development
- Development dependencies
 - System packages
 - ONNX master
 - Tensorflow 2.1
 - ONNX-TF master
- Step 1.1: Please make sure you have finished the setup and verified the dependencies in the earlier “Development Environment” session. If not, please go to https://github.com/chinhuang007/onnx-dojo/blob/master/docs/day1_afternoon/onnx_dev_env_dojo_2020.pdf and complete the setup.

Unit 2: Convert and inspect ResNet model

- **Goal of the unit:** At the end of unit 2, you will learn how to visualize an ONNX model and convert it to a Tensorflow model using CLI and code
- Step 2.1: Download ONNX model
 - Create a folder for lab “resnet” and we will do our exercises in the folder.
 - Download ResNet model for ResNet-152 version2 into “resnet” folder, find the right image, file name=resnet152-v2-7.onnx, from link, <https://github.com/onnx/models/tree/master/vision/classification/resnet> (ResNet-152, version 2)
 - Observe ResNet models following link above
 - Performs image classification, reformulate the layers as learning residual functions with reference to the layer inputs
 - Trained on ImageNet dataset which contains images from 1000 classes
 - ResNet-152 has 152 layers

Unit 2: Convert and inspect ResNet model

- Step 2.2: Visualize ONNX model
 - Netron, a model viewer that supports ONNX and TensorFlow, can be installed, but we will use the browser version, <https://lutzroeder.github.io/netron/>
 - Make the model file resnet152-v2-7.onnx available on the machine with a browser
 - Open model file resnet152-v2-7.onnx in Netron from browser and inspect the model as following
 - Click on menu->properties
 - Observe model inputs (an image): type=float32, shape=[1, 3, 224, 224]
 - Observe model outputs (scores for 1000 classes): type=float32, shape=[1, 1000]
 - Click on some nodes
 - Observe the node/operator name, type, inputs, outputs, and attributes
 - Observe the values for attributes and some inputs for this well trained model

Unit 2: Convert and inspect ResNet model

- Step 2.3: Use CLI to convert ONNX to Tensorflow
 - There are two ways to convert an ONNX to a Tensorflow computational graph file in protobuf format (pb) for inference, CLI “onnx-tf” and python code. We cover CLI in step 2.3 and python code in step 2.4
 - CLI onnx-tf takes a few arguments
 - Input file is resnet152-v2-7.onnx
 - Output file is resnet152v2.pb
 - Use the optional ‘logging_level’ argument to suppress the ‘INFO’ messages
 - Run ‘*onnx-tf convert -i resnet152-v2-7.onnx -o resnet152v2.pb --logging_level WARN*’
 - Use Netron to view the converted Tensorflow graph
 - Open the Tensorflow file resnet152v2.pb in Netron. Click Yes if prompted with “Large model detected”.
 - Observe the graph structure and nodes

Unit 2: Convert and inspect ResNet model

- Step 2.4: Use python code to convert ONNX to Tensorflow
 - Now write short python code, **convert_model.py**, to convert resnet152-v2-7.onnx into Tensorflow pb file
 - Import onnx, and onnx_tf (using *import onnx*, and *import onnx_tf*)
 - Load the onnx model, using onnx.load() API
 - *model = onnx.load("resnet152-v2-7.onnx")*
 - Convert the model, using onnx_tf.backend.prepare() API
 - *tf_rep = onnx_tf.backend.prepare(model, logging_level="WARN")*
 - Print the inputs and outputs for the converted model
 - *print("inputs=", tf_rep.inputs)*
 - *print("outputs=", tf_rep.outputs)*
 - (optional) Print all tensors in the converted model
 - *print("tensor_dict=", tf_rep.tensor_dict)*

Unit 2: Convert and inspect ResNet model

- Save the Tensorflow graph as a pb file
 - `tf_rep.export_graph('./resnet152v2_frompython.pb')`
- Save and run the python code
 - `python convert_model.py` (ignore the warnings)
 - Observe the printed inputs and outputs.
 - (optional) Observe tensor_dict, which is long for a large model.
 - A new pb file is created. Not surprisingly identical as the file generated earlier using CLI!

Unit 3: Run ResNet model

- **Goal of the unit:** At the end of unit 3, you will learn how to convert a ResNet model from ONNX to Tensorflow and run inference with sample data.
- Step 3.1: Download data
 - Stay in the folder for lab “resnet”
 - Download index json file, https://github.com/USCDataScience/dl4j-kerasimport-examples/blob/master/dl4j-import-example/data/imagenet_class_index.json
 - Contains 1000 image class indices and names for ImageNet dataset
 - Copy sample data for inference from ~/onnx-dojo/lab_resnet/*.jpg
 - Two image files for lab exercise
 - (optional) Create your own images for inference following, <https://github.com/onnx/models/tree/master/vision/classification/resnet#preprocessing>

Unit 3: Run ResNet model

- Step 3.2: Observe the data
 - Take a look at the image files. Observe the different dimensions, colors, backgrounds, and sizes.
 - Open json file and search “ant” and “bee” for their class IDs (between 0-999)
- Step 3.3: Write code to convert ONNX to Tensorflow and run inference. In the live lab session, **please copy run_model.py from ~/onnx-dojo/lab_resnet to your resnet folder instead of type in the code in step 3.3.**
 - Now write another short python code, for ex. **run_model.py**, to convert resnet152-v2-7.onnx and run model with sample data
 - *import numpy, json, Tensorflow, onnx, and onnx_tf*
 - Load the onnx model, using onnx.load() API (same as step 2.4)
 - Convert the model, using onnx-tf.backend.prepare() API (same as step 2.4)

Unit 3: Run ResNet model

- Prepare the images and indices. Copy the following code:

```
images = ['ant.jpg', 'bee.jpg']
index_json_file='imagenet_class_index.json'
with open(index_json_file) as f:
    class_index = json.load(f)
def _central_crop(image, crop_height, crop_width):
    shape = tf.shape(image)
    height, width = shape[0], shape[1]
    crop_top = (height - crop_height) // 2
    crop_left = (width - crop_width) // 2
    image = tf.image.crop_to_bounding_box(image,
        crop_top, crop_left,
        crop_height, crop_width)
    return image
```

Unit 3: Run ResNet model

- Now for each image, we go through data pre-processing, run model, and print outputs in class ID and class name. Copy the following code.

for image_path in images:

load the image file, decode jpeg, and crop to the size 224x224

img = tf.io.read_file(image_path)

img = tf.image.decode_jpeg(img, channels=3)

img = tf.image.convert_image_dtype(img, tf.float32)

img = tf.image.resize(img, (256, 256))

img = _central_crop(img, 224, 224)

img = tf.transpose(img, perm=[2, 0, 1])

img = tf.expand_dims(img, 0)

use numpy() to produce the python input

input_image=img.numpy()

run the model with the processed image

tf_output = tf_rep.run(input_image)

Unit 3: Run ResNet model

```
# use argmax to get the index/class ID with highest value in output  
output = np.argmax(tf_output)  
# print the input image file name  
print('The image file is ', image_path)  
# the output is the classification code  
print('predicted class ID = ', output)  
# the class name is coming from the index json file  
print('predicted class name = ', class_index[str(output)][1])
```

Unit 3: Run ResNet model

- Save and run the python code
 - `python run_model.py` (ignore the warnings)
 - Observe the predicted results for our sample images, ant.jpg and bee.jpg, from executing the ResNet model in Tensorflow



Input: ant.jpg
Class id: 310
Class name: ant



Input: bee.jpg
Class id: 309
Class name: bee