

# CSE574 Introduction to Machine Learning

## Support Vector Machine

Jue Guo

University at Buffalo

January 30, 2024

This section is an adaptation of Andrew Ng's Machine Learning Course on SVM.

CSE574

Introduction  
to Machine  
Learning

Jue Guo

Alternative  
View of  
Logistic  
Regression

Support  
Vector  
Machine

Large Margin  
Intuition

The  
Mathematics  
behind Large  
Margin  
Classification

## 1 Alternative View of Logistic Regression

## 2 Support Vector Machine

- Large Margin Intuition
- The Mathematics behind Large Margin Classification

# Alternative View of Logistic Regression

CSE574

Introduction  
to Machine  
Learning

Jue Guo

Alternative  
View of  
Logistic  
Regression


Support  
Vector  
Machine

Large Margin  
Intuition

The  
Mathematics  
behind Large  
Margin  
Classification

A quick review:  $h_{\theta}(x) = \frac{1}{1+e^{-\theta^T x}}$

- if  $y = 1$ , we want  $h_{\theta}(x) \approx 1$ ,  
 $\theta^T x \gg 0$
- if  $y = 0$ , we want  $h_{\theta}(x) \approx 0$ ,  
 $\theta^T x \ll 0$





The cost of a single example:

$$\begin{aligned} & - (y \log h_{\theta}(x) + (1 - y) \log (1 - h_{\theta}(x))) \\ &= - y \log \frac{1}{1 + e^{-\theta^T x}} - (1 - y) \log \left( 1 - \frac{1}{1 + e^{-\theta^T x}} \right) \end{aligned}$$

$$-y \log \frac{1}{1 + e^{-\theta^T x}} - (1 - y) \log \left( 1 - \frac{1}{1 + e^{-\theta^T x}} \right)$$

if  $y = 1$  (want  $\theta^T x \gg 0$ )

if  $y = 0$  (want  $\theta^T x \ll 0$ )



## Cost Function of Logistic Regression

$$\begin{aligned} \min_{\theta} \frac{1}{m} & \left[ \sum_{i=1}^m y^{(i)} \left( -\log h_{\theta} \left( x^{(i)} \right) \right) \right. \\ & \left. + \left( 1 - y^{(i)} \right) \left( -\log \left( 1 - h_{\theta} \left( x^{(i)} \right) \right) \right) \right] \\ & + \frac{\lambda}{2m} \sum_{j=1}^n \theta_j^2 \end{aligned}$$


## Cost Function of Support Vector Machine

$$\min_{\theta} C \sum_{i=1}^m \left[ y^{(i)} \text{cost}_1 \left( \theta^T x^{(i)} \right) + \left( 1 - y^{(i)} \right) \text{cost}_0 \left( \theta^T x^{(i)} \right) \right] + \frac{1}{2} \sum_{i=1}^n \theta_j^2$$


# Large Margin Intuition

## Support Vector Machine

$$\min_{\theta} C \sum_{i=1}^m \left[ y^{(i)} \text{cost}_1 \left( \theta^T x^{(i)} \right) + \left( 1 - y^{(i)} \right) \text{cost}_0 \left( \theta^T x^{(i)} \right) \right] + \frac{1}{2} \sum_{j=1}^n \theta_j^2$$



If  $y = 1$ , we want  $\theta^T x \geq 1$  (not just  $\geq 0$ )



If  $y = 0$ , we want  $\theta^T x \leq -1$  (not just  $< 0$ )

# A very large $C$

## Support Vector Machine

$$\min_{\theta} C \sum_{i=1}^m \left[ y^{(i)} \text{cost}_1 \left( \theta^T x^{(i)} \right) + \left( 1 - y^{(i)} \right) \text{cost}_0 \left( \theta^T x^{(i)} \right) \right] + \frac{1}{2} \sum_{j=1}^n \theta_j^2$$

Given that  $C$  is a very large value, we want that the first term to be 0. Let's try to understand the optimization problem in the context of what would it take to make this first term in the objective equal to 0.

Whenever  $y^{(i)} = 1$ ,  $\theta^T x^{(i)} \geq 1$ ;

Whenever  $y^{(i)} = 0$ ,  $\theta^T x^{(i)} \leq -1$

Now, the optimization problem can be written as:

$$\begin{aligned} \min & C \cdot 0 + \frac{1}{2} \sum_{j=1}^n \theta_j^2 \\ \text{s.t. } & \theta^T x^{(i)} \geq 1 \quad \text{if } y^{(i)} = 1 \\ & \theta^T x^{(i)} \leq -1 \quad \text{if } y^{(i)} = 0 \end{aligned}$$



# SVM Decision Boundary: Linearly separable case





Figure: Linearly Separable Case

## Large margin classifier in presence of outliers



# The Mathematics behind Large Margin Classification

CSE574

Introduction  
to Machine  
Learning

Jue Guo

Alternative  
View of  
Logistic  
Regression

Support  
Vector  
Machine

Large Margin  
Intuition

The  
Mathematics  
behind Large  
Margin  
Classification

## Vector Inner Product

# Questions?