
PyCell4Klayout

Release 0.1

IHP Authors

Jun 06, 2024

CONTENTS:

1	Referenced documents	2
2	Introduction	3
2.1	Basic Structure	3
3	Implementation Details	4
3.1	Klayout	4
3.2	Synopsys PyCell API	4
3.3	Wrapper solution approach	5
3.4	PDK technology information handling	6
4	API Reference	7
4.1	font	7
4.2	namemapper	8
4.3	box	8
4.4	grouping	11
4.5	shape	12
4.6	dlo	13
4.7	path	14
4.8	paramarray	14
4.9	ulist	15
4.10	location	15
4.11	termtype	16
4.12	point	17
4.13	tech	18
4.14	orientation	19
4.15	constants	19
4.16	pathstyle	20
4.17	pointlist	20
4.18	dlogen	21
4.19	transform	22
4.20	rect	23
4.21	geo	23
4.22	shapefilter	25
4.23	polygon	25
4.24	numeric	26
4.25	instance	28
4.26	signaltype	29
4.27	text	29
4.28	layer	30

4.29	<code>term</code>	31
4.30	<code>pin</code>	32
4.31	<code>physicalComponent</code>	33
4.32	<code>net</code>	34
5	Indices and tables	36
	Python Module Index	37
	Index	38

PyCell4Klayout is a Python library for supporting the PyCell API under the layout tool [Klayout](#).

Note: This project is under active development.

REFERENCED DOCUMENTS

No.	Doc ID-Number	Title
[1]	2021.09	Synopsys 'Python API Reference Manual'

INTRODUCTION

This reference manual documents the PyCell4Klayout API (Application Programming Interface) which is used to create parameterized cells within the [Klayout](#) design environment. This Klayout design environment makes use of the popular open-source Python programming language to provide a highly productive design environment for creating parameterized cells for analog layout design purposes. This PyCell4Klayout API provides a large number of classes and methods which are specialized for layout designs. By using these Python classes to provide powerful, high-level layout design abstractions, the Klayout design environment is extremely productive.

2.1 Basic Structure

The basic PyCell4Klayout system is built upon a set of base classes, from which the basic design and layout objects are generated through the PyCell Python API. These base classes are made accessible through the PyCell Python API, but do not have their own creation methods. Instead, other objects which are derived from these base classes can be constructed through the use of the PyCell Python API.

IMPLEMENTATION DETAILS

3.1 Klayout

Klayout is an open-source EDA layout tool with a rich set of functionalities like layout editing, DRC, LVS, PCells, scripting and so on. The feature set and the Klayout GUI are implemented in an object oriented C++ core using the Qt library. Klayout supports the programming languages Ruby and Python for scripting. The overall principle is that most of the C++ core classes have pendants with the same name in both the Ruby and Python scripting world. In the scripting world these pendants are just proxies which delegates an API-call to the C++ pendant which implements the API-call (language binding). This mechanism also covers the needed object lifetime management as well as the parameter type conversion back- and forward in the both directions between C++- and scripting-world (Marshalling).

3.1.1 PCell support

Klayout uses an own schema for supporting parametrized cells. The creation of PCells are covered in principle by the C++ core class PCellDeclaration. This class is also available in the Klayout Python namespace. The class PCellDeclaration as a PCell base class defines an API with some virtual function which must be implemented by a subclass to build a new PCell. This implemented functions are then called by the Klayout runtime engine to create/manage a new PCell. The most important of these functions are:

- *get_parameters*: Returns a list of parameter declarations for the PCell
- *coerce_parameters*: Modifies the parameters to match the requirements of the PCell
- *produce*: The production callback which creates the PCell layout

One method to create a PCell is subclassing a new class from PCellDeclaration and implement this set of specific function. This can be done in a Ruby- as well as Python-script.

3.2 Synopsys PyCell API

The PyCell API is build by a hierarchy of Python classes with a defined API [1]. The PyCell API classes can be roughly divided into the following groups:

- Basic geometry classes: Point, Box, Segement, Font, ...
- Physical component classes: Shape, Arc, Line, Dot,...
- Physical component related classes: Contact, AbutContact, Bar, DeviceContact, Via, ...
- Physical component reference classes: GroupingRef, InstanceRef, PolygonRef, ...
- Connectivity classes: SignalType, TermType, Net, Term, Pin, Layer, Tech, ...
- Parameter classes: ParamArray, ChoiceConstraint, RangeConstraint, ...

- PCell creation classes: Dlo, DloGen, Lib

3.2.1 PyCell creation principle

The DloGen class is the base class for all types of PCell generators. Any PCell generator would be derived from this base class. A PCell generator class which is derived from the DloGen base class must implement the following methods:

- *defineParamSpecs*: defines the parameters, including default values and constraints, for this PyCell
- *setupParams*: extracts the value for the parameters specified by the user for this PyCell
- *genLayout*: generates the actual physical layout for this PyCell

3.3 Wrapper solution approach




Fig. 1: PyCell wrapper structural architecture overview

3.4 PDK technology information handling

All parameters of a specific technology are encoded as JSON and can be found in a PDK specific file *technology_tech.json*, e.g. *sg13g2_tech.json*. The layer properties name, value and purpose are acquired from a XML file *technology.lyp*, e.g. *sg13g2.lyp*. The lyp-files are so called *layer property files* and will be used by Klayout for naming layer, coloring etc., for details see the Klayout documentation. The lyp-files are expected under the path *path_to_technology_tech.json/../../tech/*. A different lyp-file can be set with the environment variable *KLAY-OUT_LYP_FILE*.

API REFERENCE

This page contains auto-generated API reference documentation¹.

4.1 font

4.1.1 Module Contents

Classes

Font

```
class font.Font
    Bases: object
    EURO_STYLE = 1
    FIXED = 2
    GOTHIC = 3
    MATH = 4
    MIL_SPEC = 5
    ROMAN = 6
    SCRIPT = 7
    STICK = 8
    SWEDISH = 9
    classmethod getMembers()
    calcBBox(text, origin, height, location=Location.UPPER_LEFT, orient=Orientation.R0, overbar=False)
```

¹ Created with sphinx-autoapi

4.2 namemapper

4.2.1 Module Contents

Classes

NameMapper

```
class namemapper.NameMapper(obj: object = None)
    Bases: object
```

4.3 box

4.3.1 Module Contents

Classes

Box

```
class box.Box(l=INT_MAX, b=INT_MAX, r=INT_MIN, t=INT_MIN)
    Bases: object
    property bottom
    property left
    property right
    property top
    abut(refBox, align=True)
    alignEdge(refBox, refDir=None, offset=None)
    alignEdgeToCoord(coord)
    alignEdgeToPoint(point)
    alignLocation(refBox, refLoc=None, offset=None)
    alignLocationToPoint(pt)
    centerCenter()
    centerLeft()
    centerRight()
```

clone(*nameMap: cni.namemapper.NameMapper = NameMapper(), netMap: cni.namemapper.NameMapper = NameMapper()*)

contains(*incEdges=True*)

containsPoint(*incEdges=True*)

destroy()

expand()

expandDir(*coord*)

expandForMinArea(*minArea, grid=None*)

expandForMinWidth(*minWidth, grid=None*)

expandToGrid(*dir=None*)

fix()

getArea()

getCenter()

getCenterX()

getCenterY()

getCoord()

getDimension()

getHeight()

getLeft()

getLocationPoint()

getLocationPoint()

getPoints()

getRange()

getRangeX()

getRangeY()

getRight()

getSpacing(*refBox*)

getTop()

getWidth()

hasNoArea()

init()

intersect()
intersect(*dir*)
isInverted()
isNormal()
limit()
lowerCenter()
lowerLeft()
lowerRight()
merge(*dir*)
mergePoint()
mirrorX()
mirrorY()
moveBy(*dx: float, dy: float*) → None
moveTo(*loc=Location.CENTER_CENTER*)
moveTowards(*d*)
overlaps(*incEdges=True*)
place(*refBox, distance, align=True*)
removeRegion()
rotate90()
rotate180()
rotate270()
set()
set(*dir=None*)
set(*upperRight*)
set(*bottom, right, top*)
setBottom()
setCenter()
setCenterY()
setCoord(*coord*)
setDimension(*dir*)
setBottom()

```

setHeight()
setLocationPoint(pt)
setRange(range)
setRangeX()
setRangeY()
setRect(rect)
setRight()
setTop()
setWidth()
snap(snapType=None)
snapX(snapType=None)
snapY(snapType=None)
snapTowards(dir)
transform(transform: cni.transform.Transform) → None
upperCenter()
upperLeft()
upperRight()

```

4.4 grouping

4.4.1 Module Contents

Classes

<i>Grouping</i>	Helper class that provides a standard way to create an ABC using
-----------------	--

```

class grouping.Grouping(name: str = "", components: cni.physicalComponent.PhysicalComponent = None)
    Bases: cni.physicalComponent.PhysicalComponent
    Helper class that provides a standard way to create an ABC using inheritance.
    __iter__()
    __next__()
    add(components: cni.physicalComponent.PhysicalComponent) → None
    addToRegion(region: pya.Region)

```

clone(*nameMap*: *cni.physicalComponent.NameMapper* = *NameMapper()*, *netMap*:
cni.physicalComponent.NameMapper = *NameMapper()*)

destroy()

getComps() → list

getComp(*index*: int) → *cni.physicalComponent.PhysicalComponent*

moveBy(*dx*: float, *dy*: float) → None

toString()

transform(*transform*: *cni.physicalComponent.Transform*) → None

4.5 shape

4.5.1 Module Contents

Classes

Shape

Helper class that provides a standard way to create an ABC using

class *shape.Shape*(*layer*: *cni.shapefilter.Layer*, *bbox*: *cni.box.Box*)

Bases: *cni.physicalComponent.PhysicalComponent*

Helper class that provides a standard way to create an ABC using inheritance.

property *bbox*

The bounding box for this Shape

property *layer*

The Layer associated with this Shape

classmethod *getCell*() → *pya.Cell*

set_shape(*shape*: *Shape*)

getShape()

getBBox(*filter*: *cni.shapefilter.ShapeFilter* = *ShapeFilter()*) → *cni.box.Box*

getLayer() → *cni.shapefilter.Layer*

getNet() → *Net*

getPin() → *Pin*

setPin(*pin*: *Pin*) → None

4.6 dlo

4.6.1 Module Contents

Classes

<i>ChoiceConstraint</i>	Built-in mutable sequence.
<i>RangeConstraint</i>	
<i>PyCellContext</i>	
<i>PCellWrapper</i>	

class `dlo.ChoiceConstraint`(*choices*, *action=REJECT*)

Bases: `list`

Built-in mutable sequence.

If no argument is given, the constructor creates a new empty list. The argument must be an iterable if specified.

class `dlo.RangeConstraint`(*low*, *high*, *resolution=None*, *action=REJECT*)

class `dlo.PyCellContext`(*tech*, *cell*, *impl*)

Bases: `object`

property `cell`

property `tech`

property `layout`

property `impl`

classmethod `getCurrentPyCellContext()` → *PyCellContext*

__enter__()

__exit__(**params*)

class `dlo.PCellWrapper`(*impl*, *tech*)

Bases: `pya.PCellDeclaration`

__call__(*name*, *value*, *description=None*, *constraint=None*)

get_parameters()

params_as_hash(*parameters*)

display_text(*parameters*)

produce(*layout*, *layers*, *parameters*, *cell*)

4.7 path

4.7.1 Module Contents

Classes

<i>Path</i>	Creates a path object, using the points list of points to define the path. The width
-------------	--

class `path.Path(arg1, arg2, arg3, arg4=None)`

Bases: `cni.shape.Shape`

Creates a path object, using the points list of points to define the path. The width parameter is used to specify the width of this path. The layer parameter is a Layer object, the width parameter is an integer value, and the points parameter is a Python list of Point objects.

Parameters

- **layer** (`Layer`) – Layer to place the path
- **width** (`float`) – width of the path
- **points** (`PointList`) – pointlist to define the path

addToRegion(*region: pya.Region*)

clone(*nameMap: cni.shape.NameMapper = NameMapper(), netMap: cni.shape.NameMapper = NameMapper()*)

destroy()

getPoints() → `cni.pointlist.PointList`

moveBy(*dx: float, dy: float*) → `None`

toString() → `str`

transform(*transform: cni.shape.Transform*) → `None`

4.8 paramarray

4.8.1 Module Contents

Classes

<i>ParamArray</i>	<code>dict()</code> -> new empty dictionary
-------------------	---

class `paramarray.ParamArray(*arg, **kw)`

Bases: `dict`

`dict()` -> new empty dictionary `dict(mapping)` -> new dictionary initialized from a mapping object's

(key, value) pairs

dict(iterable) -> new dictionary initialized as if via:

`d = {}` for `k, v` in iterable:

`d[k] = v`

dict(kwargs)** -> new dictionary initialized with the name=value pairs

in the keyword argument list. For example: `dict(one=1, two=2)`

4.9 ulist

4.9.1 Module Contents

Classes

<i>ulist</i>	Built-in mutable sequence.
--------------	----------------------------

Attributes

<i>T</i>

`ulist.T`

class `ulist.ulist`(*items=None*)

Bases: `list[T]`

Built-in mutable sequence.

If no argument is given, the constructor creates a new empty list. The argument must be an iterable if specified.

append(*item*) → None

Append object to the end of the list.

4.10 location

4.10.1 Module Contents

Classes

<i>Location</i>

class `location.Location`

Bases: `object`

`LOWER_LEFT = 1`

`CENTER_LEFT = 2`

```
UPPER_LEFT = 3
LOWER_CENTER = 4
CENTER_CENTER = 5
UPPER_CENTER = 6
LOWER_RIGHT = 7
CENTER_RIGHT = 8
UPPER_RIGHT = 9

mirrorX()
mirrorY()

rotate90()
rotate180()
rotate270()

transform(transform)
```

4.11 termtype

4.11.1 Module Contents

Classes

TermType

```
class termtype.TermType
    Bases: object
    INPUT = 1
    OUTPUT = 2
    INPUT_OUTPUT = 3
    SWITCH = 4
    JUMPER = 5
    UNUSED = 6
    TRISTATE = 7
```

4.12 point

4.12.1 Module Contents

Classes

Point

class point.**Point**(*x*, *y*)

Bases: object

property **x**

Returns the value of the x-coordinate for this point

property **y**

Returns the value of the y-coordinate for this point

classmethod **areColinearPoints**(*p1*, *p2*, *p3*)

Returns True if these three points are colinear or coincident, and returns False otherwise.

Parameters

- **p1** (*Point*) – first point.
- **p2** (*Point*) – second point.
- **p3** (*Point*) – third point.

Returns

whether all three points are collinear or coincident

Return type

boolean

copy()

getCoord(*dir*)

getSpacing(*dir*, *refPoint*)

getX()

getY()

invalid()

isBetween(*a*, *b*)

isValid()

place(*dir*, *refPoint*, *distance*, *align=True*)

set(*p*)

set(*_x*, *_y*)

setCoord(*dir*, *coord*)

```

setX(x)
setY(y)
snap(grid, snapType=None)
snapX(grid, snapType=None)
snapY(grid, snapType=None)
snapTowards(grid, dir)
toDiagAxes()
toOrthogAxes()
transform(trans)
__eq__(other)
    Return self==value.

```

4.13 tech

4.13.1 Module Contents

Classes

TechImpl

Tech

```

class tech.TechImpl

```

```

    Bases: object

```

```

class tech.Tech

```

```

    Bases: object

```

```

    techsByName

```

```

    techInUse =

```

```

    register()

```

```

    get()

```

4.14 orientation

4.14.1 Module Contents

Classes

Orientation

```
class orientation.Orientation
```

```
    Bases: object
```

```
    R0 = 0
```

```
    R90 = 1
```

```
    R180 = 2
```

```
    R270 = 3
```

```
    MY = 4
```

```
    MYR90 = 5
```

```
    MX = 6
```

```
    MXR90 = 7
```

```
    concat(other)
```

```
    getRelativeOrient(other)
```

4.15 constants

4.15.1 Module Contents

```
constants.REJECT = 1
```

```
constants.ACCEPT = 2
```

```
constants.USE_DEFAULT = 3
```

```
constants.INT_MAX
```

```
constants.INT_MIN
```

4.16 pathstyle

4.16.1 Module Contents

Classes

PathStyle

class pathstyle.**PathStyle**

Bases: object

TRUNCATE = 1

EXTEND = 2

ROUND = 3

VARIABLE = 4

4.17 pointlist

4.17.1 Module Contents

Classes

PointList

Built-in mutable sequence.

class pointlist.**PointList**(items=None)

Bases: cni.ulist.ulist[cni.point.Point]

Built-in mutable sequence.

If no argument is given, the constructor creates a new empty list. The argument must be an iterable if specified.

compress(isClose=True) → *PointList*

Compresses this PointList, by removing any extra (coincident and/or collinear) points from this PointList. The optional isClosed parameter is used to indicate whether this set of points is meant to represent a closed shape or not. If all points are collinear, then the first and last points will be the result of compressing this PointList. If the first and last points are coincident, then only the first point is returned

Parameters

isClose (boolean) – Whether represented shape is closed

Returns

see description above

Return type

PointList

containsPoint(point: cni.point.Point) → bool

4.18 dlogen

4.18.1 Module Contents

Classes

Dlo

DloGen

class dlogen.**Dlo**(*libName*, *cellName*, *viewName*='layout', *viewType*=None)

Bases: object

classmethod **exists**(*dloName*: str) → bool

Returns True if the dloName Dlo design object exists, and False otherwise. The dloName is a string of the form “<libName>/<cellName>/<viewName>”. If <viewName> is not specified, then the default value “layout” will be used.

Parameters

dloName (str) – name of dlo object

Returns

wether cell exists

Return type

bool

findPin(*name*: str) → cni.pin.Pin

hasPin(*name*: str) → bool

hasTerm(*name*: str) → bool

hasNet(*name*: str) → bool

findTerm(*name*: str) → cni.term.Term

class dlogen.**DloGen**

Bases: *Dlo*

classmethod **setLibName**(*libName*: str) → None

classmethod **getLibName**() → str

setTech(*tech*)

addPin(*pinName*: str, *termName*: str, *box*: cni.pin.Box, *layer*: cni.pin.Layer) → cni.pin.Pin

4.19 transform

4.19.1 Module Contents

Classes

<i>Transform</i>	The Transform class provides the ability to implement two-dimensional
------------------	---

class transform.Transform(*arg1, arg2, arg3, arg4=None*)

Bases: object

The Transform class provides the ability to implement two-dimensional transformations, consisting of orientation changes (rotations and mirroring about the coordinate axes), translation (offsets in the X and Y directions), and magnification of the X and Y coordinates, with the operations performed in the following order:

1. Rotation/Mirroring
2. Translation
3. Magnification

When rotation operations are performed on an object in the layout design, it is important to note that it may be necessary to first translate the object to the origin of the DLO coordinate system, apply the rotation operation, and then translate the object back to its original location. This would be necessary, because the center of rotation is the origin of the coordinate system, not the center of the object. With this approach, the object will be rotated about the center of the object. Otherwise, the resulting rotation may not produce the expected results. In order to more easily handle this situation, the rotate() methods are provided by this Transform class.

Creation:

The Transform object can be directly created using the desired x and y coordinate values for the translation operation, the desired orientation value, and the desired magnification value. The individual x and y coordinate values can be specified, or the corresponding Point object can be used instead. Thus, this Transform object can be created using either of the following forms:

Transform(Coord x, Coord y, Orientation o=R0, double mag=1.0)

Transform(Point offset, Orientation o=R0, double mag=1.0)

If these values are not specified, then default values will be generated and used.

property transform

returns the internal transform representation

property xOffset

returns the x-coordinate value of the offset for this Transform

property yOffset

returns the y-coordinate value of the offset for this Transform

property mag

returns the magnification value for this Transform

property orientation

returns the orientation value for this Transform

4.20 rect

4.20.1 Module Contents

Classes

<i>Rect</i>	Helper class that provides a standard way to create an ABC using
-------------	--

class `rect.Rect(layer: cni.layer.Layer, box: cni.box.Box)`

Bases: `cni.shape.Shape`

Helper class that provides a standard way to create an ABC using inheritance.

property `bottom`

property `left`

property `right`

property `top`

addToRegion(*region: cni.shape.pya.Region*)

clone(*nameMap: cni.shape.NameMapper = NameMapper()*, *netMap: cni.shape.NameMapper = NameMapper()*)

destroy()

moveBy(*dx: float, dy: float*) → None

toString() → str

transform(*transform: cni.shape.Transform*) → None

4.21 geo

4.21.1 Module Contents

Functions

<i>fgOr</i> (→ <i>cni.grouping.Grouping</i>)	Performs a logical OR operation for lists of physical components <code>comps1</code>
<i>fgAnd</i> ()	
<i>fgXor</i> (→ <i>cni.grouping.Grouping</i>)	Performs a logical XOR operation for lists of physical components <code>comps1</code>
<i>fgNot</i> ()	
<i>fgMerge</i> ()	

`geo.fgOr(components1: cni.grouping.ulist[cni.grouping.PhysicalComponent], components2: cni.grouping.ulist[cni.grouping.PhysicalComponent], resultLayer: Layer) → cni.grouping.Grouping`

Performs a logical OR operation for lists of physical components comps1 and comps2, by selecting those polygon areas which are in either list of physical components. The resulting merged polygon shapes are generated on the resultLayer layer. In addition, these polygon shapes are used to create a Grouping object, which is the return value for this method.

Parameters

- **components1** (*list of PhysicalCompent*) – first list of physical component derived objects
- **components2** (*list of PhysicalCompent*) – second list of physical component derived objects
- **resultLayer** (**Layer**) – layer where resulting shapes will be generated on

Returns

grouping object

Return type

Grouping

`geo.fgAnd()`

`geo.fgXor(components1: cni.grouping.ulist[cni.grouping.PhysicalComponent], components2: cni.grouping.ulist[cni.grouping.PhysicalComponent], resultLayer: Layer) → cni.grouping.Grouping`

Performs a logical XOR operation for lists of physical components comps1 and comps2, by selecting those polygon areas which are in either list of physical components, but not in both lists of physical components. The resulting merged polygon shapes are generated on the resultLayer layer. In addition, these polygon shapes are used to create a Grouping object, which is the return value for this method.

Parameters

- **components1** (*list of PhysicalCompent*) – first list of physical component derived objects
- **components2** (*list of PhysicalCompent*) – second list of physical component derived objects
- **resultLayer** (**Layer**) – layer where resulting shapes will be generated on

Returns

grouping object

Return type

Grouping

`geo.fgNot()`

`geo.fgMerge()`

4.22 shapefilter

4.22.1 Module Contents

Classes

<i>ShapeFilter</i>	Creates an empty ShapeFilter object, which would be used to indicate that all layers should be
--------------------	--

class shapefilter.**ShapeFilter**(*arg=None*)

Bases: object

Creates an empty ShapeFilter object, which would be used to indicate that all layers should be considered in any bounding box or placement calculations

Creates a ShapeFilter object, consisting of only a single layer. This single layer is the only layer which should be considered when the ShapeFilter object is passed to methods which perform bounding box and placement calculations.

Parameters

layer (*Layer*) – Layer to filter

Creates a ShapeFilter object, consisting of a list of Layer objects. These layers are the only layers which should be considered when the ShapeFilter is passed to methods which perform bounding box or placement calculations.

Parameters

layerList (*LayerList*) – Layers to filter

Creates a ShapeFilter object, consisting of the Layer objects which are specified by the shapeFilter ShapeFilter object. These layers are the only layers which should be considered when the ShapeFilter is passed to methods which perform bounding box or placement calculations.

Parameters

shapeFilter (*ShapeFilter*) – ShapeFilter to filter

isIncluded(*layer: cni.layer.Layer*) → bool

Returns true if the layer parameter is a layer which is in the list of layers considered by the ShapeFilter object, and returns False otherwise.

Parameters

layer (*Layer*) – Layer to check

Return type

bool

4.23 polygon

4.23.1 Module Contents

Classes

<i>Polygon</i>	Helper class that provides a standard way to create an ABC using
----------------	--

```
class polygon.Polygon(arg1, arg2, arg3=None)
```

```
    Bases: cni.shape.Shape
```

```
    Helper class that provides a standard way to create an ABC using inheritance.
```

```
    addToRegion(region: pya.Region)
```

```
    clone(nameMap: cni.shape.NameMapper = NameMapper(), netMap: cni.shape.NameMapper =  
        NameMapper())
```

```
    destroy()
```

```
    getPoints() → cni.pointlist.PointList
```

```
    moveBy(dx: float, dy: float) → None
```

```
    toString() → str
```

```
    transform(transform: cni.shape.Transform) → None
```

4.24 numeric

4.24.1 Module Contents

Classes

Numeric

The Numeric class is used to create a floating point number from a string

```
class numeric.Numeric
```

```
    Bases: float
```

The Numeric class is used to create a floating point number from a string representation, such as “10ns”. This string representation is composed of two parts: 1) a number part and 2) a scale factor part. Thus, this Numeric class can be used to represent a floating point number as a floating point number along with a scaling factor. Since this Numeric class is derived from the base Python float class, it can be used just like a regular floating point number in any numerical computation.

The number part of this Numeric class string representation can be any valid Python integer or floating point number; this Python floating point number can be represented using standard scientific notation, such as “1.23e-4”. The scaling factor part of this Numeric class string representation must be one of the following pre-defined scaling factor string values:

Character	Name	Multiplier
Y	Yotta	1e24
Z	Zetta	1e21
E	Exa	1e18
P	Peta	1e15
T	Tera	1e12
G	Giga	1e09
M	Mega	1e06
K or k	Kilo	1e03
‘	no scale factor	1.0
%	percent	1e-2
c	centi	1e-2
m	milli	1e-3
u	micron	1e-6
n	nano	1e-9
p	pico	1e-12
f	femto	1e-15
a	atto	1e-18
z	zepto	1e-21
y	yocto	1e-24

Note that any characters after the first character in the scaling factor are simply ignored. Thus, the scaling factor “mVolt” is the same as “m”. This capability can be used to create more descriptive scaling factors.

`Numeric(int | float | string)` – creates a `Numeric` object, based upon the specified number or string. The string must be a string of the form `<number><scaleFactor>`, where the `<scaleFactor>` is one of the pre-defined scaling factors in the above table of scaling factor strings. That is, this string representation must be composed of a number part and a scaling factor part, where the scaling factor is a pre-defined scaling factor string.

property `scaleFactor`

The default (original) scale factor

property `scale_factors`

List of all available scaling factors, along with their values

`scaleFormat(scaleFactor=None)`

Returns the floating point number formatted using the specified `scaleFactor` scaling value. If this `scaleFactor` parameter is not specified, then the floating point number is returned using the scale factor which was used when the `Numeric` class object was created.

Parameters

`scaleFactor` (*string or None*) – Optional scaling factor to use.

Returns

new scaled `Numeric` object

Return type

Numeric

4.25 instance

4.25.1 Module Contents

Classes

<i>Instance</i>	Creates an Instance object, where the dloName parameter specifies the Klayout name to be
-----------------	--

class instance.**Instance**(*dloName: str*)

Creates an Instance object, where the dloName parameter specifies the Klayout name to be used for this Instance object. The dloName parameter is a string of the form “libName/cellName/viewName”, where the libName and the viewName are optional. If the libName is not specified, then the library name associated with the current DloGen is used; if the viewName is not specified, then the default viewName is used (currently “layout”).

Parameters

dloName (*str*) – name of dlo object

getParams() → *cni.paramarray.ParamArray*

Returns the ParamArray which provides the explicit parameters and values which were used when this Instance object was created.

Returns

array of parameters

Return type

ParamArray

setParams(*params: cni.paramarray.ParamArray*) → None

Uses the passed ParamArray params to set the parameter values for this Instance.

Parameters

params (*ParamArray*) – parameters to set

setOrientation(*orientation: cni.orientation.Orientation*) → None

Sets the orientation for this Instance.

Parameters

orientation (*Orientation*) – orientation to set

setOrigin(*point: cni.shape.Point*) → None

Sets the Point point parameter to be the origin for this Instance.

Parameters

point (*Point*) – origin to set

4.26 signaltype

4.26.1 Module Contents

Classes

SignalType

class signaltype.SignalType

Bases: object

SIGNAL = 1

POWER = 2

GROUND = 3

CLOCK = 4

TIEOFF = 5

TIEHI = 6

TIELO = 7

ANALOG = 8

SCAN = 9

RESET = 10

4.27 text

4.27.1 Module Contents

Classes

Text

Helper class that provides a standard way to create an ABC using

class text.Text(layer: cni.rect.Layer, text: str, origin: cni.rect.Point, height: float)

Bases: cni.rect.Shape

Helper class that provides a standard way to create an ABC using inheritance.

addToRegion(region: pya.Region)

clone(nameMap: cni.rect.NameMapper = NameMapper(), netMap: cni.rect.NameMapper = NameMapper())

destroy()


```

moveBy(dx: float, dy: float) → None
setAlignment(location: cni.location.Location) → None
setOrientation(orient)
setDrafting(drafting)
transform(transform: cni.transform.Transform) → None

```

4.28 layer

4.28.1 Module Contents

Classes

Layer

```

class layer.Layer(name, purpose=None)
    Bases: object
    property name
    property number
    property purposeName
    property purposeNumber
    tech
    layout
    getAttrs()
    getGridResolution()
    getLayerAbove()
    getLayerAbove(layerMaterial)
    getLayerBelow()
    getLayerBelow(layerMaterial)
    getLayerName()
    getLayerNumber()
    getMaterial()
    getPurposeName()
    getPurposeNumber()

```

`getRoutingDir()``isAbove(layer)``isMaskLayer()`

4.29 term

4.29.1 Module Contents

Classes

<i>Term</i>	Creates a Term terminal object in the current design, using the termName parameter to name this
-------------	---

class `term.Term`(termName: str, termType: *cni.termtype.TermType* = *TermType.INPUT_OUTPUT*)

Bases: `object`

Creates a Term terminal object in the current design, using the termName parameter to name this newly created Term object. If there is already a net in the current design having the same name as this terminal, then this net will be connected to this terminal. Otherwise, a new net will be created, and connected to this terminal, using this termName string to name this newly created net. If the termName string parameter is empty, or is the name of an existing terminal in the design, then an exception is raised. In addition, the termType parameter is used to specify the terminal type for this terminal.

Parameters

- **termName** (*string*) – name of the new terminal
- **termType** (*Termtype*) – optional type of the new terminal

property name

Returns the name of this terminal

addPin(pin: *Pin*) → None

getName() → str

Returns the name for this terminal.

Returns

The name of the terminal

Return type

string

getNet() → *cni.net.Net*

Returns the net associated with this Term terminal object. If there is no associated net, then an exception is raised.

Returns

The associated net

Return type

Net

getPins() → list[Pin]

Returns a uniform list of all of the Pin objects associated with this Term terminal object.

Returns

List of Pin

Return type

list[Pin]

setName(name: str) → None

Sets the name for this terminal. Note that the name of the associated net for this terminal is also changed to have the same name as this terminal. This is done in order to ensure that any net connected to this terminal will always have the same name as this terminal. If this name string parameter is empty, or is the name of an existing terminal or net in the design, then an exception is raised.

Parameters

name (string) – The name of the terminal

4.30 pin

4.30.1 Module Contents

Classes

Pin	Creates a Pin object for the specified terminal in the current design, using the pinName
-----	--

class pin.Pin(pinName: str, termName: str, shape: cni.shape.Shape = None)

Bases: object

Creates a Pin object for the specified terminal in the current design, using the pinName parameter to name this newly created Pin object. If there is already a terminal in the current design having the same name as the termName parameter, then this terminal will be used to create this Pin object. Otherwise, a new terminal will be created, using this termName string to name this newly created terminal. If there is already a pin in the current design having the same name as the pinName string parameter, then an exception is raised. In addition, the shape parameter can optionally be used to associate a shape object with this pin.

Parameters

- **pinName** (string) – Name of the pin.
- **termName** (string) – second point.
- **shape** (Shape) – optional shape to associate

property name

Returns the name of this pin

addShape(arg)

getName() → str

Returns the name for this Pin object.

Returns

pin name

Return type

string

setBBox(*box: cni.box.Box, layer: cni.layer.Layer*) → None**getBBox**() → cni.box.Box**setName**(*name: str*) → None

Sets the name for this Pin object. If there is already a pin in the current design with the same name as the name parameter, an exception is raised.

Parameters**name** (*string*) – Name to set**setTerm**(*term: cni.term.Term*) → None

Associates the term terminal with this Pin object. Note that multiple Pin objects may be associated with a single terminal.

Parameters**Term** – Terminal to associate**getTerm**() → cni.term.Term

4.31 physicalComponent

4.31.1 Module Contents

Classes

PhysicalComponent

Helper class that provides a standard way to create an ABC using

class physicalComponent.**PhysicalComponent**

Bases: abc.ABC

Helper class that provides a standard way to create an ABC using inheritance.

abstract **addToRegion**(*region: pya.Region*)

abstract **clone**(*nameMap: cni.namemapper.NameMapper = NameMapper(), netMap: cni.namemapper.NameMapper = NameMapper()*)

fgOr(*component: PhysicalComponent, resultLayer: Layer*) → *Grouping*

Performs a logical or operation for this physical component and another physical component, by selecting those polygon areas which are in either physical component. The resulting merged polygon shapes are generated on the resultLayer layer. In addition, these polygon shapes are used to create a Grouping object, which is the return value for this method.

Parameters

- **component** (*PhysicalCompent*) – physical component derived object
- **resultLayer** (*Layer*) – layer where resulting shapes will be generated on

Returns

grouping object

Return type*Grouping***fgXor**(*component*: [PhysicalComponent](#), *resultLayer*: [Layer](#)) → *Grouping*

Performs a logical xor operation for this physical component and another physical component, by selecting those polygon areas which are in either physical component, but not in both lists of physical components. The resulting merged polygon shapes are generated on the resultLayer layer. In addition, these polygon shapes are used to create a Grouping object, which is the return value for this method.

Parameters

- **component** (*PhysicalCompent*) – physical component derived object
- **resultLayer** ([Layer](#)) – layer where resulting shapes will be generated on

Returns

grouping object

Return type*Grouping***abstract destroy**()**abstract moveBy**(*dx*: *float*, *dy*: *float*) → None**abstract transform**(*transform*: *cni.transform.Transform*) → None

4.32 net

4.32.1 Module Contents

Classes

Net	Creates a Net object in the current design, using the net-Name parameter to name this newly
---------------------	---

class net.Net(*netName*: *str*, *sigType*: *cni.signaltype.SignalType* = *SignalType.SIGNAL*, *isGlobal*: *bool* = *False*)

Bases: object

Creates a Net object in the current design, using the netName parameter to name this newly created Net object. If this netName string parameter is empty, or is the name of anexisting net in the design, then an exception is raised. In addition, the sigType parameter is used to specify the signal type for this net, and the isGlobal Boolean flag parameter should be set to True, when this net is a global net for the current design.

Parameters

- **netName** (*string*) – name of the new net
- **sigType** ([SignalType](#)) – optional signal type of the new net

property name

Returns the name of this terminal

addTerm(*term*: [Term](#)) → None

getName() → str

Returns the name for this Net.

Returns

The name of the Net

Return type

string

getPins() → list[Pin]

Returns a list of pins which are connected to any terminal associated with this Net object. All Pin objects associated with this terminal are returned in this list.

Returns

List of Pin

Return type

list[Pin]

setName(name: str) → None

Sets the name for this Net object. Note that the name of any associated terminal for this Net will also be changed to use this new name. This is done in order to ensure that any terminal connected to a net will always have the same name as the net. If this name string parameter is empty, or is the name of an existing net or terminal in the current design, then an exception is raised.

Parameters

name (*string*) – The name of the net

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

b

box, 8

c

constants, 19

d

dlo, 13

dlogen, 21

f

font, 7

g

geo, 23

grouping, 11

i

instance, 28

l

layer, 30

location, 15

n

namemapper, 8

net, 34

numeric, 26

o

orientation, 19

p

paramarray, 14

path, 14

pathstyle, 20

physicalComponent, 33

pin, 32

point, 17

pointlist, 20

polygon, 25

r

rect, 23

s

shape, 12

shapefilter, 25

signaltype, 29

t

tech, 18

term, 31

termtype, 16

text, 29

transform, 22

u

ulist, 15

Symbols

__call__() (*dlo.PCellWrapper* method), 13
 __enter__() (*dlo.PyCellContext* method), 13
 __eq__() (*point.Point* method), 18
 __exit__() (*dlo.PyCellContext* method), 13
 __iter__() (*grouping.Grouping* method), 11
 __next__() (*grouping.Grouping* method), 11

A

abut() (*box.Box* method), 8
 ACCEPT (*in module constants*), 19
 add() (*grouping.Grouping* method), 11
 addPin() (*dlogen.DloGen* method), 21
 addPin() (*term.Term* method), 31
 addShape() (*pin.Pin* method), 32
 addTerm() (*net.Net* method), 34
 addToRegion() (*grouping.Grouping* method), 11
 addToRegion() (*path.Path* method), 14
 addToRegion() (*physicalComponent.PhysicalComponent* method), 33
 addToRegion() (*polygon.Polygon* method), 26
 addToRegion() (*rect.Rect* method), 23
 addToRegion() (*text.Text* method), 29
 alignEdge() (*box.Box* method), 8
 alignEdgeToCoord() (*box.Box* method), 8
 alignEdgeToPoint() (*box.Box* method), 8
 alignLocation() (*box.Box* method), 8
 alignLocationToPoint() (*box.Box* method), 8
 ANALOG (*signaltype.SignalType* attribute), 29
 append() (*ulist.ulist* method), 15
 areColinearPoints() (*point.Point* class method), 17

B

bbox (*shape.Shape* property), 12
 bottom (*box.Box* property), 8
 bottom (*rect.Rect* property), 23
 box
 module, 8
 Box (*class in box*), 8

C

calcBBox() (*font.Font* method), 7

cell (*dlo.PyCellContext* property), 13
 CENTER_CENTER (*location.Location* attribute), 16
 CENTER_LEFT (*location.Location* attribute), 15
 CENTER_RIGHT (*location.Location* attribute), 16
 centerCenter() (*box.Box* method), 8
 centerLeft() (*box.Box* method), 8
 centerRight() (*box.Box* method), 8
 ChoiceConstraint (*class in dlo*), 13
 CLOCK (*signaltype.SignalType* attribute), 29
 clone() (*box.Box* method), 8
 clone() (*grouping.Grouping* method), 11
 clone() (*path.Path* method), 14
 clone() (*physicalComponent.PhysicalComponent* method), 33
 clone() (*polygon.Polygon* method), 26
 clone() (*rect.Rect* method), 23
 clone() (*text.Text* method), 29
 compress() (*pointlist.PointList* method), 20
 concat() (*orientation.Orientation* method), 19
 constants
 module, 19
 contains() (*box.Box* method), 9
 containsPoint() (*box.Box* method), 9
 containsPoint() (*pointlist.PointList* method), 20
 copy() (*point.Point* method), 17

D

destroy() (*box.Box* method), 9
 destroy() (*grouping.Grouping* method), 12
 destroy() (*path.Path* method), 14
 destroy() (*physicalComponent.PhysicalComponent* method), 34
 destroy() (*polygon.Polygon* method), 26
 destroy() (*rect.Rect* method), 23
 destroy() (*text.Text* method), 29
 display_text() (*dlo.PCellWrapper* method), 13
 dlo
 module, 13
 Dlo (*class in dlogen*), 21
 dlogen
 module, 21
 DloGen (*class in dlogen*), 21

E

EURO_STYLE (*font.Font* attribute), 7
 exists() (*dlogen.Dlo* class method), 21
 expand() (*box.Box* method), 9
 expandDir() (*box.Box* method), 9
 expandForMinArea() (*box.Box* method), 9
 expandForMinWidth() (*box.Box* method), 9
 expandToGrid() (*box.Box* method), 9
 EXTEND (*pathstyle.PathStyle* attribute), 20

F

fgAnd() (in module *geo*), 24
 fgMerge() (in module *geo*), 24
 fgNot() (in module *geo*), 24
 fgOr() (in module *geo*), 23
 fgOr() (*physicalComponent.PhysicalComponent* method), 33
 fgXor() (in module *geo*), 24
 fgXor() (*physicalComponent.PhysicalComponent* method), 34
 findPin() (*dlogen.Dlo* method), 21
 findTerm() (*dlogen.Dlo* method), 21
 fix() (*box.Box* method), 9
 FIXED (*font.Font* attribute), 7
 font
 module, 7
 Font (class in *font*), 7

G

geo
 module, 23
 get() (*tech.Tech* method), 18
 get_parameters() (*dlo.PCellWrapper* method), 13
 getArea() (*box.Box* method), 9
 getAttrs() (*layer.Layer* method), 30
 getBBox() (*pin.Pin* method), 33
 getBBox() (*shape.Shape* method), 12
 getCell() (*shape.Shape* class method), 12
 getCenter() (*box.Box* method), 9
 getCenterX() (*box.Box* method), 9
 getCenterY() (*box.Box* method), 9
 getComp() (*grouping.Grouping* method), 12
 getComps() (*grouping.Grouping* method), 12
 getCoord() (*box.Box* method), 9
 getCoord() (*point.Point* method), 17
 getCurrentPyCellContext() (*dlo.PyCellContext* class method), 13
 getDimension() (*box.Box* method), 9
 getGridResolution() (*layer.Layer* method), 30
 getHeight() (*box.Box* method), 9
 getLayer() (*shape.Shape* method), 12
 getLayerAbove() (*layer.Layer* method), 30
 getLayerBelow() (*layer.Layer* method), 30

getLayerName() (*layer.Layer* method), 30
 getLayerNumber() (*layer.Layer* method), 30
 getLeft() (*box.Box* method), 9
 getLibName() (*dlogen.DloGen* class method), 21
 getLocationPoint() (*box.Box* method), 9
 getMaterial() (*layer.Layer* method), 30
 getMembers() (*font.Font* class method), 7
 getName() (*net.Net* method), 34
 getName() (*pin.Pin* method), 32
 getName() (*term.Term* method), 31
 getNet() (*shape.Shape* method), 12
 getNet() (*term.Term* method), 31
 getParams() (*instance.Instance* method), 28
 getPin() (*shape.Shape* method), 12
 getPins() (*net.Net* method), 35
 getPins() (*term.Term* method), 31
 getPoints() (*box.Box* method), 9
 getPoints() (*path.Path* method), 14
 getPoints() (*polygon.Polygon* method), 26
 getPurposeName() (*layer.Layer* method), 30
 getPurposeNumber() (*layer.Layer* method), 30
 getRange() (*box.Box* method), 9
 getRangeX() (*box.Box* method), 9
 getRangeY() (*box.Box* method), 9
 getRelativeOrient() (*orientation.Orientation* method), 19
 getRight() (*box.Box* method), 9
 getRoutingDir() (*layer.Layer* method), 30
 getShape() (*shape.Shape* method), 12
 getSpacing() (*box.Box* method), 9
 getSpacing() (*point.Point* method), 17
 getTerm() (*pin.Pin* method), 33
 getTop() (*box.Box* method), 9
 getWidth() (*box.Box* method), 9
 getX() (*point.Point* method), 17
 getY() (*point.Point* method), 17
 GOTHIC (*font.Font* attribute), 7
 GROUND (*signaltype.SignalType* attribute), 29
 grouping
 module, 11
 Grouping (class in *grouping*), 11

H

hasNet() (*dlogen.Dlo* method), 21
 hasNoArea() (*box.Box* method), 9
 hasPin() (*dlogen.Dlo* method), 21
 hasTerm() (*dlogen.Dlo* method), 21

I

impl (*dlo.PyCellContext* property), 13
 init() (*box.Box* method), 9
 INPUT (*termtype.TermType* attribute), 16
 INPUT_OUTPUT (*termtype.TermType* attribute), 16
 instance

module, 28
 Instance (*class in instance*), 28
 INT_MAX (*in module constants*), 19
 INT_MIN (*in module constants*), 19
 intersect() (*box.Box method*), 9, 10
 invalid() (*point.Point method*), 17
 isAbove() (*layer.Layer method*), 31
 isBetween() (*point.Point method*), 17
 isIncluded() (*shapefilter.ShapeFilter method*), 25
 isInverted() (*box.Box method*), 10
 isMaskLayer() (*layer.Layer method*), 31
 isNormal() (*box.Box method*), 10
 isValid() (*point.Point method*), 17

J

JUMPER (*termtype.TermType attribute*), 16

L

layer
 module, 30
 Layer (*class in layer*), 30
 layer (*shape.Shape property*), 12
 layout (*dlo.PyCellContext property*), 13
 layout (*layer.Layer attribute*), 30
 left (*box.Box property*), 8
 left (*rect.Rect property*), 23
 limit() (*box.Box method*), 10
 location
 module, 15
 Location (*class in location*), 15
 LOWER_CENTER (*location.Location attribute*), 16
 LOWER_LEFT (*location.Location attribute*), 15
 LOWER_RIGHT (*location.Location attribute*), 16
 lowerCenter() (*box.Box method*), 10
 lowerLeft() (*box.Box method*), 10
 lowerRight() (*box.Box method*), 10

M

mag (*transform.Transform property*), 22
 MATH (*font.Font attribute*), 7
 merge() (*box.Box method*), 10
 mergePoint() (*box.Box method*), 10
 MIL_SPEC (*font.Font attribute*), 7
 mirrorX() (*box.Box method*), 10
 mirrorX() (*location.Location method*), 16
 mirrorY() (*box.Box method*), 10
 mirrorY() (*location.Location method*), 16
 module
 box, 8
 constants, 19
 dlo, 13
 dlogen, 21
 font, 7
 geo, 23

grouping, 11
 instance, 28
 layer, 30
 location, 15
 namemapper, 8
 net, 34
 numeric, 26
 orientation, 19
 paramarray, 14
 path, 14
 pathstyle, 20
 physicalComponent, 33
 pin, 32
 point, 17
 pointlist, 20
 polygon, 25
 rect, 23
 shape, 12
 shapefilter, 25
 signaltype, 29
 tech, 18
 term, 31
 termtype, 16
 text, 29
 transform, 22
 ulist, 15
 moveBy() (*box.Box method*), 10
 moveBy() (*grouping.Grouping method*), 12
 moveBy() (*path.Path method*), 14
 moveBy() (*physicalComponent.PhysicalComponent method*), 34
 moveBy() (*polygon.Polygon method*), 26
 moveBy() (*rect.Rect method*), 23
 moveBy() (*text.Text method*), 29
 moveTo() (*box.Box method*), 10
 moveTowards() (*box.Box method*), 10
 MX (*orientation.Orientation attribute*), 19
 MXR90 (*orientation.Orientation attribute*), 19
 MY (*orientation.Orientation attribute*), 19
 MYR90 (*orientation.Orientation attribute*), 19

N

name (*layer.Layer property*), 30
 name (*net.Net property*), 34
 name (*pin.Pin property*), 32
 name (*term.Term property*), 31
 namemapper
 module, 8
 NameMapper (*class in namemapper*), 8
 net
 module, 34
 Net (*class in net*), 34
 number (*layer.Layer property*), 30
 numeric

module, 26
 Numeric (class in numeric), 26

O

orientation
 module, 19
 Orientation (class in orientation), 19
 orientation (transform.Transform property), 22
 OUTPUT (termtype.TermType attribute), 16
 overlaps() (box.Box method), 10

P

paramarray
 module, 14
 ParamArray (class in paramarray), 14
 params_as_hash() (dlo.PCellWrapper method), 13
 path
 module, 14
 Path (class in path), 14
 pathstyle
 module, 20
 PathStyle (class in pathstyle), 20
 PCellWrapper (class in dlo), 13
 physicalComponent
 module, 33
 PhysicalComponent (class in physicalComponent), 33
 pin
 module, 32
 Pin (class in pin), 32
 place() (box.Box method), 10
 place() (point.Point method), 17
 point
 module, 17
 Point (class in point), 17
 pointlist
 module, 20
 PointList (class in pointlist), 20
 polygon
 module, 25
 Polygon (class in polygon), 25
 POWER (signaltype.SignalType attribute), 29
 produce() (dlo.PCellWrapper method), 13
 purposeName (layer.Layer property), 30
 purposeNumber (layer.Layer property), 30
 PyCellContext (class in dlo), 13

R

R0 (orientation.Orientation attribute), 19
 R180 (orientation.Orientation attribute), 19
 R270 (orientation.Orientation attribute), 19
 R90 (orientation.Orientation attribute), 19
 RangeConstraint (class in dlo), 13
 rect
 module, 23

Rect (class in rect), 23
 register() (tech.Tech method), 18
 REJECT (in module constants), 19
 removeRegion() (box.Box method), 10
 RESET (signaltype.SignalType attribute), 29
 right (box.Box property), 8
 right (rect.Rect property), 23
 ROMAN (font.Font attribute), 7
 rotate180() (box.Box method), 10
 rotate180() (location.Location method), 16
 rotate270() (box.Box method), 10
 rotate270() (location.Location method), 16
 rotate90() (box.Box method), 10
 rotate90() (location.Location method), 16
 ROUND (pathstyle.PathStyle attribute), 20

S

scale_factors (numeric.Numeric property), 27
 scaleFactor (numeric.Numeric property), 27
 scaleFormat() (numeric.Numeric method), 27
 SCAN (signaltype.SignalType attribute), 29
 SCRIPT (font.Font attribute), 7
 set() (box.Box method), 10
 set() (point.Point method), 17
 set_shape() (shape.Shape method), 12
 setAlignment() (text.Text method), 30
 setBBox() (pin.Pin method), 33
 setBottom() (box.Box method), 10
 setCenter() (box.Box method), 10
 setCenterY() (box.Box method), 10
 setCoord() (box.Box method), 10
 setCoord() (point.Point method), 17
 setDimension() (box.Box method), 10
 setDrafting() (text.Text method), 30
 setHeight() (box.Box method), 10
 setLibName() (dlogen.DloGen class method), 21
 setLocationPoint() (box.Box method), 11
 setName() (net.Net method), 35
 setName() (pin.Pin method), 33
 setName() (term.Term method), 32
 setOrientation() (instance.Instance method), 28
 setOrientation() (text.Text method), 30
 setOrigin() (instance.Instance method), 28
 setParams() (instance.Instance method), 28
 setPin() (shape.Shape method), 12
 setRange() (box.Box method), 11
 setRangeX() (box.Box method), 11
 setRangeY() (box.Box method), 11
 setRect() (box.Box method), 11
 setRight() (box.Box method), 11
 setTech() (dlogen.DloGen method), 21
 setTerm() (pin.Pin method), 33
 setTop() (box.Box method), 11
 setWidth() (box.Box method), 11

setX() (*point.Point* method), 17
 setY() (*point.Point* method), 18
 shape
 module, 12
 Shape (*class in shape*), 12
 shapefilter
 module, 25
 ShapeFilter (*class in shapefilter*), 25
 SIGNAL (*signaltype.SignalType* attribute), 29
 signaltype
 module, 29
 SignalType (*class in signaltype*), 29
 snap() (*box.Box* method), 11
 snap() (*point.Point* method), 18
 snapTowards() (*box.Box* method), 11
 snapTowards() (*point.Point* method), 18
 snapX() (*box.Box* method), 11
 snapX() (*point.Point* method), 18
 snapY() (*box.Box* method), 11
 snapY() (*point.Point* method), 18
 STICK (*font.Font* attribute), 7
 SWEDISH (*font.Font* attribute), 7
 SWITCH (*termtype.TermType* attribute), 16

T

T (*in module ulist*), 15
 tech
 module, 18
 Tech (*class in tech*), 18
 tech (*dlo.PyCellContext* property), 13
 tech (*layer.Layer* attribute), 30
 TechImpl (*class in tech*), 18
 techInUse (*tech.Tech* attribute), 18
 techsByName (*tech.Tech* attribute), 18
 term
 module, 31
 Term (*class in term*), 31
 termtype
 module, 16
 TermType (*class in termtype*), 16
 text
 module, 29
 Text (*class in text*), 29
 TIEHI (*signaltype.SignalType* attribute), 29
 TIELO (*signaltype.SignalType* attribute), 29
 TIEOFF (*signaltype.SignalType* attribute), 29
 toDiagAxes() (*point.Point* method), 18
 toOrthogAxes() (*point.Point* method), 18
 top (*box.Box* property), 8
 top (*rect.Rect* property), 23
 toString() (*grouping.Grouping* method), 12
 toString() (*path.Path* method), 14
 toString() (*polygon.Polygon* method), 26
 toString() (*rect.Rect* method), 23

transform
 module, 22
 Transform (*class in transform*), 22
 transform (*transform.Transform* property), 22
 transform() (*box.Box* method), 11
 transform() (*grouping.Grouping* method), 12
 transform() (*location.Location* method), 16
 transform() (*path.Path* method), 14
 transform() (*physicalComponent.PhysicalComponent* method), 34
 transform() (*point.Point* method), 18
 transform() (*polygon.Polygon* method), 26
 transform() (*rect.Rect* method), 23
 transform() (*text.Text* method), 30
 TRISTATE (*termtype.TermType* attribute), 16
 TRUNCATE (*pathstyle.PathStyle* attribute), 20

U

ulist
 module, 15
 ulist (*class in ulist*), 15
 UNUSED (*termtype.TermType* attribute), 16
 UPPER_CENTER (*location.Location* attribute), 16
 UPPER_LEFT (*location.Location* attribute), 15
 UPPER_RIGHT (*location.Location* attribute), 16
 upperCenter() (*box.Box* method), 11
 upperLeft() (*box.Box* method), 11
 upperRight() (*box.Box* method), 11
 USE_DEFAULT (*in module constants*), 19

V

VARIABLE (*pathstyle.PathStyle* attribute), 20

X

x (*point.Point* property), 17
 xOffset (*transform.Transform* property), 22

Y

y (*point.Point* property), 17
 yOffset (*transform.Transform* property), 22