

# Wazuh agent class

## \$ossec\_active\_response

Allows active response on this host.

*Default true*

## \$ossec\_rootcheck

Enable rootcheck on this host.

*Default true*

## \$ossec\_rootcheck\_frequency

Setup rootcheck frequency.

*Default 36000*

## \$ossec\_rootcheck\_checkports

Enable rootcheck checkports option.

*Default true*

## \$ossec\_rootcheck\_checkfiles

Enable rootcheck checkfiles option.

*Default true*

## \$ossec\_server\_ip

Wazuh Manager IP.

## \$ossec\_server\_hostname

Hostname of the server.

## \$ossec\_server\_port

Server port configuration.

*Default 1514*

## \$ossec\_scanpaths

Agents can be Linux or Windows. For this reason, don't have ossec\_scanpaths by default.

*Default []*

## \$ossec\_emailnotification

Whether to send email notifications or not.

*Default yes*

## \$ossec\_ignorepaths

Files/Directory list to ignore

*Default []*

## \$ossec\_local\_files

Files list for log analysis

This files are listed in params.pp in section \$default\_local\_files

## \$ossec\_syscheck\_frequency

Frequency that syscheck is executed default every 12 hours

*Default 43200*

## \$ossec\_prefilter

Command used to prevent prelinking from creating false positives.

This option can potentially impact performance negatively. The configured command will be run for each and every file checked.

*Default false*

**\$ossec\_service\_provider**

This option associate Operative System Family

**\$ossec\_config\_profiles**

Specify the agent.conf profile(s) to be used by the agent.

*Default []*

**\$selinux**

Whether to install a SELinux policy to allow rotation of OSSEC logs.

*Default false*

**\$agent\_name**

Configure agent host name of the system

*Default \$::hostname*

**\$agent\_ip\_address**

Configure agent IPv4 address for the default network interface.

*Default \$::ipaddress*

**\$manage\_repo**

Install Wazuh through Wazuh repositories.

*Default true*

**\$manage\_epel\_repo**

Install epel repo and inotify-tools

*Default true*

**\$agent\_package\_name**

Define package name defined in params.pp

**\$agent\_package\_version**

Define package version

*Default installed*

**\$agent\_service\_name**

Define service name defined in params.pps

**\$manage\_client\_keys**

Manage client keys option.

*Default export*

**\$agent\_auth\_password**

Define password for agent-auth

*Default undef*

**\$ar\_repeated\_offenders**

A comma separated list of increasing timeouts in minutes for repeat offenders.

There can be a maximum of 5 entries.

*Default empty*

**\$enable\_wodle\_openscap**

Enable openscap configuration in ossec.conf

*Default false*

**\$wodle\_openscap\_content**

Depending linux distribution assign profile xccdf.

**\$ossec\_conf\_template**

Path of ossec configuration agent template.

*Default wazuh/wazuh\_agent.conf.erb*

# function wazuh::addlog

---

**\$log\_name**

Configure Wazuh log name

**\$agent\_log**

Path to log file.

*Default false*

**\$logfile**

Path to log file.

**\$logtype**

The OSSEC log\_format of the file.

*Default syslog*