

# reports

## XML section name

```
<reports>
</reports>
```

Configuration options for reporting of alerts.

## Options

- [group](#)
- [category](#)
- [rule](#)
- [level](#)
- [location](#)
- [srcip](#)
- [user](#)
- [title](#)
- [email\\_to](#)
- [showlogs](#)

### group

Filter by group/category. It only accepts one group/category.

Default value	n/a
Allowed values	Any group used is allowed.

### category

Filter by group/category.

Default value	n/a
Allowed values	Any category used is allowed.

### rule

Rule ID to filter for.

Default value	n/a
Allowed values	Any Rule ID in Wazuh Rules is allowed

### level

Alert level to filter for. The report will include all levels above and including level specified.

Default value	n/a
Allowed values	Any Alert level from 1 to 16 can be used

### location

Filter by the log location or agent name.

Default value	n/a
Allowed values	Any file path, hostname or network is allowed

srcip

Filter by the source ip of the event.

Default value	n/a
Allowed values	Any hostname or network can be used.

user

Filter by the user name. This will match either the srcuser or dstuser.

Default value	n/a
Allowed values	Any username

title

Name of the report. **This is a required field.**

Default value	n/a
Allowed values	Any text

email\_to

The email address to send the completed report. **This is a required field.**

Default value	n/a
Allowed values	Any email address

showlogs

Enable or disable the inclusion of logs when creating the report.

Default value	no
Allowed values	yes, no

Example of configuration

```
<reports>
  <group>authentication_failed,</group>
  <srcip>192.168.1.10</srcip>
  <title>Auth_Report</title>
  <email_to>recipient@example.wazuh.com</email_to>
  <showlogs>yes</showlogs>
</reports>
```