

Welcome to Code Crunch!

C2 | Crunch The Code

FRI 1-2PM Weekly | Spring 2025

Attendance

Earn a Certificate of
Completion by attending
at least 70% of the
workshops



linktr.ee/CODE.CRUNCH





UMPIRE Method

U - Understand	Clarify the problem requirements. Ask questions if necessary.
M - Match:	Identify a potential solution approach by matching the problem to a known algorithm or technique.
P - Plan:	Plan your solution in pseudocode or steps before you write the code.
I - Implement:	Write the code according to your plan.
R - Review:	Review the code for mistakes or inefficiencies.
E - Evaluate:	Test your solution with different cases, including edge cases. Explain time and space complexity.



Problem 1 (HackerRank)

Given two strings, determine if they share a **common substring**.
A substring may be as small as one character.

Example:

s1 = "and"

s2 = "art"

These share the common substring "a".



Problem 2 (Leetcode #242)

Given two strings **s** and **t**, return **True** if **t** is an **anagram** of **s**, and **False** otherwise.

Example 1:

Input: s = "anagram", t = "nagaram"

Output: True

Example 2:

Input: s = "rat", t = "car"

Output: False



Problem 3 (Leetcode #169)

Given an array `nums` of size `n`, return the majority element in the array. The majority element is the element that appears more than $\lfloor n/2 \rfloor$ times. If no majority exists, return `-1`

Example 1:

Input: `nums = [3,2,3]`

Output: `3`

Example 2:

Input: `nums = [2,2,1,1,1,2,2]`

Output: `2`



Problem 4 (Leetcode #3005)

You are given an array `nums` consisting of positive integers. Return the **total frequencies** of elements in `nums` such that those elements all have the **maximum** frequency.

The **frequency** of an element is the number of occurrences of that element in the array.

Example 1:

Input: `nums = [1,2,2,3,1,4]`

Output: 4

Example 2:

Input: `nums = [1,2,3,4,5]`

Output: 5



Problem 5 (Leetcode #1207)

Given an array of integers `arr`, return `True` if the number of occurrences of each value in the array is **unique** or `False` otherwise.

Example 1:

Input: `arr = [1,2,2,1,1,3]`

Output: `True`

Example 2:

Input: `arr = [1,2]`

Output: `False`



Attendance



linktr.ee/CODE.CRUNCH



Join us for the next sessions



Crunch Convos: WED 2PM - 3PM

Crunch Code: FRI 1PM - 2PM



RSVP lu.ma/CODECRUNCH



Your feedback helps us improve. Share your thoughts!

Go to our website: go.fiu.edu/codecrunch