

Package ‘RDBqc’

October 13, 2022

Title Quality check functions for RDBFIS

Version 0.0.11

Date 2022-10-05

Maintainer Isabella Bitetto <bitetto@coispa.eu>

Description The package contains functions used to perform a priori and a posteriori quality checks on RDBFIS data.

License GPL (>= 3)

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.1

Depends R (>= 4.1.0)

Imports dplyr, ggplot2, rworldmap, sp, rworldxtra, pander, data.table, grDevices, magrittr, tictoc, tidyverse, fishmethods, tidyr, gridExtra, scales, outliers

LazyData true

Suggests rmarkdown,
knitr,
markdown

VignetteBuilder knitr

R topics documented:

ALK_tab_example	4
Catch_tab_example	4
catfau_check	5
check_EF_FDI_A	5
check_EF_FDI_G	6
check_EF_FDI_H	6
check_EF_FDI_I	7
check_EF_FDI_J	7
check_EF_taskII2	8
check_EF_taskIII	8
check_EF_taskVII2	9
check_EF_TaskVII31	9
check_EF_TaskVII32	10
check_lmat_TaskVII.3.2	10

check_lw_TaskVII.2	11
check_minmax150_TaskVII.3.1	11
check_minmax1_TaskVII.2	12
check_presence_taskII2	13
check_RD_FDI_A	13
check_RD_FDI_G	14
check_RD_FDI_H	14
check_RD_FDI_I	15
check_RD_FDI_J	15
check_RD_taskII2	16
check_RD_taskIII	16
check_RD_taskVII2	17
check_RD_taskVII31	17
check_RD_TaskVII32	18
check_species_catfau_TaskVII.3.2	18
circabc	19
combination_taskII2	19
data_ex	20
data_exampleCL	20
Discard_tab_example	21
fdi_a_catch	21
FDI_checks_spatial_HI	22
FDI_check_coord	22
FDI_coverage	23
FDI_cov_tableA	24
FDI_cov_tableG	25
FDI_cov_tableJ	26
FDI_cross_checks_AG	27
FDI_cross_checks_AH	27
FDI_cross_checks_IG	28
FDI_cross_checks_JG	28
FDI_disc_coverage	29
FDI_fishdays_cov	29
fdi_g_effort	30
fdi_h_spatial_land	30
fdi_h_spatial_landings	31
fdi_i_spatial_effort	31
fdi_j_capacity	32
FDI_landweight_cov	32
FDI_prices_cov	33
FDI_prices_not_null	33
FDI_vessel_lenth	34
FDI_vessel_numbers	35
GP_tab_example	35
Landing_tab_example	36
MA_tab_example	36
MEDBS_ALK	37
MEDBS_Catch_coverage	37
MEDBS_check_duplicates	38
MEDBS_comp_disc_YQ	39
MEDBS_comp_disc_YQ_fishery	39
MEDBS_comp_land_Q_VL	40

MEDBS_comp_land_Q_VL_fishery	41
MEDBS_comp_land_YQ	42
MEDBS_comp_land_YQ_fishery	42
MEDBS_discard_coverage	43
MEDBS_disc_mean_weight	44
MEDBS_GP_check	44
MEDBS_ks	45
MEDBS_Landing_coverage	46
MEDBS_land_mean_weight	46
MEDBS_lengthclass_0	47
MEDBS_length_ind	48
MEDBS_LW_check	49
MEDBS_MA_check	50
MEDBS_ML_check	50
MEDBS_plot_discard_ts	51
MEDBS_plot_disc_vol	52
MEDBS_plot_landing_ts	52
MEDBS_plot_land_vol	53
MEDBS_SA_check	54
MEDBS_SL_check	55
MEDBS_SOP	55
MEDBS_weight_0	56
MEDBS_weight_minus1	57
MEDBS_yr_missing_length	57
minmaxLtaskVII2	58
minmaxLtaskVII31	59
ML_tab_example	59
RCG_check_AL	60
RCG_check_CL	61
RCG_check_LFD	61
RCG_check_LFD_comm_cat	62
RCG_check_loc	63
RCG_check_lw	63
RCG_check_mat	64
RCG_check_mat_ogive	65
RCG_summarize_ind_meas	66
RCG_summarize_trips	66
SA_tab_example	67
sex_mat	67
SL_tab_example	68
task_ii2	68
task_iii	69
task_vii2	69
task_vii31	70
task_vii32	70

ALK_tab_example	<i>ALK table in MED&BS datacall format</i>
-----------------	--

Description

ALK table in MED&BS datacall format

Usage

ALK_tab_example

Format

An object of class `data.frame` with 62 rows and 114 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

Catch_tab_example	<i>Catch table in MED&BS datacall format</i>
-------------------	--

Description

Catch table in MED&BS datacall format

Usage

Catch_tab_example

Format

An object of class `data.frame` with 57 rows and 171 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

catfau_check	<i>catfau_check in GFCM datacall format</i>
--------------	---

Description

catfau_check in GFCM datacall format

Usage

catfau_check

Format

An object of class data.frame with 16 rows and 4 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

check_EF_FDI_A	<i>Check empty fields in FDI A table</i>
----------------	--

Description

The function checks the presence of not allowed empty data in the given table.

Usage

```
check_EF_FDI_A(data, verbose = TRUE)
```

Arguments

data	GFCM Task A table
verbose	boolean. If TRUE a message is printed.

Value

Two lists are returned by the function. The first list returns the number of NA for each reference column. The second list provides the index of each NA in the reference column.

Examples

```
check_EF_FDI_A(fdi_a_catch)
```

check_EF_FDI_G	<i>Check empty fields in FDI G table</i>
----------------	--

Description

The function checks the presence of not allowed empty data in the given table.

Usage

```
check_EF_FDI_G(data, verbose = TRUE)
```

Arguments

data	GFCM Task G table
verbose	boolean. If TRUE a message is printed.

Value

Two lists are returned by the function. The first list returns the number of NA for each reference column. The second list provides the index of each NA in the reference column.

Examples

```
check_EF_FDI_G(fdi_g_effort)
```

check_EF_FDI_H	<i>Check empty fields in FDI H table</i>
----------------	--

Description

The function checks the presence of not allowed empty data in the given table.

Usage

```
check_EF_FDI_H(data, verbose = TRUE)
```

Arguments

data	GFCM Task H table
verbose	boolean. If TRUE a message is printed.

Value

Two lists are returned by the function. The first list gives the number of NA for each reference column. The second list gives the index of each NA in the reference column.

Examples

```
check_EF_FDI_H(fdi_h_spatial_landings)
```

`check_EF_FDI_I`*Check empty fields in FDI I table*

Description

The function checks the presence of not allowed empty data in the given table.

Usage

```
check_EF_FDI_I(data, verbose = TRUE)
```

Arguments

<code>data</code>	GFCM Task I table
<code>verbose</code>	boolean. If TRUE a message is printed.

Value

Two lists are returned by the function. The first list gives the number of NA for each reference column. The second list gives the index of each NA in the reference column.

Examples

```
check_EF_FDI_I(fdi_i_spatial_effort)
```

`check_EF_FDI_J`*Check empty fields in FDI J table*

Description

The function checks the presence of not allowed empty data in the given table.

Usage

```
check_EF_FDI_J(data, verbose = TRUE)
```

Arguments

<code>data</code>	GFCM Task J table
<code>verbose</code>	boolean. If TRUE a message is printed.

Value

Two lists are returned by the function. The first list gives the number of NA for each reference column. The second list gives the index of each NA in the reference column.

Examples

```
check_EF_FDI_J(fdi_j_capacity)
```

check_EF_taskII2	<i>Check empty fields in GFCM Task II.2 table</i>
------------------	---

Description

The function checks the presence of not allowed empty data in the given table, according to the [GFCM, 2018. GFCM Data Collection Reference Framework \(DCRF\). Version: 20.1](#)

Usage

```
check_EF_taskII2(data, verbose = TRUE)
```

Arguments

data	GFCM Task II.2 table
verbose	boolean. If TRUE a message is printed.

Value

Two lists are returned by the function. The first list gives the number of NA for each reference column. The second list gives the index of each NA in the reference column.

Examples

```
check_EF_taskII2(task_ii2)
```

check_EF_taskIII	<i>Check empty fields in GFCM Task III table</i>
------------------	--

Description

The function checks the presence of not allowed empty data in the given table, according to the [GFCM, 2018. GFCM Data Collection Reference Framework \(DCRF\). Version: 20.1](#)

Usage

```
check_EF_taskIII(data, verbose = TRUE)
```

Arguments

data	GFCM Task III table
verbose	boolean. If TRUE a message is printed.

Value

Two lists are returned by the function. The first list gives the number of NA for each reference column. The second list gives the index of each NA in the reference column.

Examples

```
check_EF_taskIII(task_iii)
```

check_EF_taskVII2	<i>Check empty fields in GFCM Task VII.2 table</i>
-------------------	--

Description

The function checks the presence of not allowed empty data in the given table, according to the [GFCM, 2018. GFCM Data Collection Reference Framework \(DCRF\). Version: 20.1](#)

Usage

```
check_EF_taskVII2(data, verbose = TRUE)
```

Arguments

data	GFCM Task VII.2 table
verbose	boolean. If TRUE a message is printed.

Value

Two lists are returned by the function. The first list gives the number of NA for each reference column. The second list gives the index of each NA in the reference column.

Examples

```
check_EF_taskVII2(task_vii2)
```

check_EF_TaskVII31	<i>Check empty fields in GFCM Task VII.3.1 table</i>
--------------------	--

Description

The function checks the presence of not allowed empty data in the given table, according to the [GFCM, 2018. GFCM Data Collection Reference Framework \(DCRF\). Version: 20.1](#)

Usage

```
check_EF_TaskVII31(data, verbose = TRUE)
```

Arguments

data	GFCM Task VII.3.1 table
verbose	boolean. If TRUE a message is printed.

Value

Two lists are returned by the function. The first list gives the number of NA for each reference column. The second list gives the index of each NA in the reference column.

Examples

```
check_EF_TaskVII31(task_vii31)
```

check_EF_TaskVII32	<i>Check empty fields in GFCM Task VII.3.2 table</i>
--------------------	--

Description

The function checks the presence of not allowed empty data in the given table, according to the [GFCM, 2018. GFCM Data Collection Reference Framework \(DCRF\). Version: 20.1](#)

Usage

```
check_EF_TaskVII32(data, verbose = TRUE)
```

Arguments

data	GFCM Task VII.3.2 table
verbose	boolean. If TRUE a message is printed.

Value

Two lists are returned by the function. The first list gives the number of NA for each reference column. The second list gives the index of each NA in the reference column.

Examples

```
check_EF_TaskVII32(task_vii32)
```

check_lmat_TaskVII.3.2	<i>Plot of the maturity stages per length for each sex and species</i>
------------------------	--

Description

Function to plot the lengths at maturity stages by species and sex to easily identify outliers.

Usage

```
check_lmat_TaskVII.3.2(data, MS, GSA, SP)
```

Arguments

data	GFCM Task VII.3.2 table
MS	member state code
GSA	GSA code
SP	species reference code in the three alpha code format

Value

The function return a plot of the maturity stages per length and sex per species.

Examples

```
check_lmat_TaskVII.3.2(task_vii32)
```

check_lw_TaskVII.2	<i>Plot of the relationship length weight for each species</i>
--------------------	--

Description

Function to check the consistency of length-weight relationship in the GFCM Task VII.2 table per species.

Usage

```
check_lw_TaskVII.2(data, MS, GSA, SP, verbose = TRUE)
```

Arguments

data	GFCM Task VII.2 table
MS	member state code
GSA	GSA code
SP	species reference code in the three alpha code format
verbose	boolean value to obtain further explanation messages from the function

Value

The function return a plot of the length weight relationship per species.

Examples

```
check_lw_TaskVII.2(task_vii2, MS = "ITA", GSA = "18", SP = "BOG")
```

check_minmaxl50_TaskVII.3.1	<i>Comparison between min/max L50 observed for each species and sex with theoretical values</i>
-----------------------------	---

Description

Function to verify the consistency of L50 reported in the TaskVII.3.1 table with the theoretical values reported in the minmaxLtaskVII31 table. The function allows to identify the records in which the observed L50 are greater or lower than the expected ones.

Usage

```
check_minmaxl50_TaskVII.3.1(data, tab_L50, MS, GSA)
```

Arguments

data	GFCM Task VII.3.1 table
tab_L50	Theoretical values of min/max L50 for each species and sex
MS	member state code
GSA	GSA code

Value

The function returns a table with the comparison between min/max L50 observed for each species and sex with theoretical values.

Examples

```
check_minmaxl50_TaskVII.3.1(task_vii31, minmaxLtaskVII31, MS = "ITA", GSA = "19")
```

```
check_minmaxl_TaskVII.2
```

Comparison between min/max observed for each species with theoretical values

Description

Function to verify the consistency of the lengths reported in the TaskVII.2 table with the theoretical values reported in the minmaxLtaskVII2 table. The function allows to identify the records in which the observed lengths are greater or lower than the expected ones.

Usage

```
check_minmaxl_TaskVII.2(data, tab_length, MS, GSA)
```

Arguments

data	GFCM Task II.2 table
tab_length	Theoretical values of min/max length for each species
MS	member state code
GSA	GSA code

Value

The function returns a table with the comparison between min/max lengths observed for each species with theoretical values.

Examples

```
check_minmaxl_TaskVII.2(task_vii2, minmaxLtaskVII2, MS = "ITA", GSA = "18")
```

 check_presence_taskII2

Check of missing combination GSA/Fleet segment per year

Description

Function to verify the completeness of the GSA/Fleet segments in Task II.2 table, as reported in the combination_taskII2 table.

Usage

```
check_presence_taskII2(data1, data2, MS, GSA)
```

Arguments

data1	GFCM Task II.2 table
data2	List of combination of the expected GSA/Fleet segments per year for Task II.2 table
MS	member state code
GSA	GSA code

Value

The function returns a list of missing combinations GSA/Fleet segment per year.

Examples

```
check_presence_taskII2(task_ii2, combination_taskII2, MS = "ITA", GSA = "18")
```

 check_RD_FDI_A

Check duplicated records in FDI A table

Description

The function check the presence of duplicated records. In particular, it checks whether the combination of the first 19 columns generates duplicate records.

Usage

```
check_RD_FDI_A(data, verbose = TRUE)
```

Arguments

data	GFCM Task A table
verbose	boolean. If TRUE a message is printed.

Value

The function returns the indices of the duplicated rows, checking the unique combinations of the first 19 columns of the FDI A table.

Examples

```
check_RD_FDI_A(fdi_a_catch)
```

check_RD_FDI_G	<i>Check duplicated records in FDI G table</i>
----------------	--

Description

The function check the presence of duplicated records. In particular, it checks whether the combination of the first 15 columns generates duplicate records.

Usage

```
check_RD_FDI_G(data, verbose = TRUE)
```

Arguments

data	GFCM Task G table
verbose	boolean. If TRUE a message is printed.

Value

The function returns the indices of the duplicated rows, checking the unique combinations of the first 15 columns of the FDI G table.

Examples

```
check_RD_FDI_G(fdi_g_effort)
```

check_RD_FDI_H	<i>Check duplicated records in FDI H table</i>
----------------	--

Description

The function check the presence of duplicated records. In particular, it checks whether the combination of the first 15 columns generates duplicate records.

Usage

```
check_RD_FDI_H(data, verbose = TRUE)
```

Arguments

data	GFCM Task H table
verbose	boolean. If TRUE a message is printed.

Value

The function returns the indices of the duplicated rows, checking the unique combinations of the first 20 columns of the FDI G table.

Examples

```
check_RD_FDI_H(fdi_h_spatial_landings)
```

check_RD_FDI_I	<i>Check duplicated records in FDI I table</i>
----------------	--

Description

The function check the presence of duplicated records. In particular, it checks whether the combination of the first 15 columns generates duplicate records.

Usage

```
check_RD_FDI_I(data, verbose = TRUE)
```

Arguments

data	GFCM Task I table
verbose	boolean. If TRUE a message is printed.

Value

The function returns the indices of the duplicated rows, checking the unique combinations of the first 19 columns of the FDI G table.

Examples

```
check_RD_FDI_I(fdi_i_spatial_effort)
```

check_RD_FDI_J	<i>Check duplicated records in FDI J table</i>
----------------	--

Description

The function check the presence of duplicated records. In particular, it checks whether the combination of the first 15 columns generates duplicate records.

Usage

```
check_RD_FDI_J(data, verbose = TRUE)
```

Arguments

data	GFCM Task J table
verbose	boolean. If TRUE a message is printed.

Value

The function returns the indices of the duplicated rows, checking the unique combinations of the first 7 columns of the FDI G table.

Examples

```
check_RD_FDI_J(fdi_j_capacity)
```

check_RD_taskII2	<i>Check duplicated records in GFCM Task II.2 table</i>
------------------	---

Description

The function check the presence of duplicated records. In particular, it checks whether the combination of the first 5 columns generates duplicate records.

Usage

```
check_RD_taskII2(data, verbose = TRUE)
```

Arguments

data	GFCM Task II.2 table
verbose	boolean. If TRUE a message is printed.

Value

The function returns the indices of the duplicated rows, checking the unique combinations of the first 5 columns of the Task II.2 table.

Examples

```
check_RD_taskII2(task_ii2)
```

check_RD_taskIII	<i>Check duplicated records in GFCM Task III table</i>
------------------	--

Description

The function check the presence of duplicated records. In particular, it checks whether the combination of the first 10 columns generates duplicate records.

Usage

```
check_RD_taskIII(data, verbose = TRUE)
```

Arguments

data	GFCM Task III table
verbose	boolean. If TRUE a message is printed.

Value

The function returns the indices of the duplicated rows, checking the unique combinations of the first 10 columns of the Task Task III table.

Examples

```
check_RD_taskIII(task_iii)
```

check_RD_taskVII2	<i>Check duplicated records in GFCM Task VII.2 table</i>
-------------------	--

Description

The function check the presence of duplicated records. In particular, it checks whether the combination of the first 9 columns generates duplicate records.

Usage

```
check_RD_taskVII2(data, verbose = TRUE)
```

Arguments

data	GFCM Task VII.2 table
verbose	boolean. If TRUE a message is printed.

Value

The function returns the indices of the duplicated rows, checking the unique combinations of the first 9 columns of the Task Task VII.2 table.

Examples

```
check_RD_taskVII2(task_vii2)
```

check_RD_taskVII31	<i>Check duplicated records in GFCM Task VII.3.1 table</i>
--------------------	--

Description

The function check the presence of duplicated records. In particular, it checks whether the combination of the first 5 columns generates duplicate records.

Usage

```
check_RD_taskVII31(data, verbose = TRUE)
```

Arguments

data	GFCM Task VII.3.1 table
verbose	boolean. If TRUE a message is printed.

Value

The function returns the indices of the duplicated rows, checking the unique combinations of the first 5 columns of the Task Task VII.3.1 table.

Examples

```
check_RD_taskVII31(task_vii31)
```

check_RD_TaskVII32	<i>Check duplicated records in GFCM Task VII.3.2 table</i>
--------------------	--

Description

The function check the presence of duplicated records. In particular, it checks whether the combination of the first 10 columns generates duplicate records.

Usage

```
check_RD_TaskVII32(data, verbose = TRUE)
```

Arguments

data	GFCM Task VII.3.2 table
verbose	boolean. If TRUE a message is printed.

Value

The function returns the indices of the duplicated rows, checking the unique combinations of the first 10 columns of the Task Task VII.3.2 table.

Examples

```
check_RD_TaskVII32(task_vii32)
```

check_species_catfau_TaskVII.3.2	<i>Check mismatching species/Catfau and Sex per maturity stages for Task VII.3.2 table</i>
----------------------------------	--

Description

Function to check the correct codification of faunistic category according to species and sex in Task VII.3.2 table.

Usage

```
check_species_catfau_TaskVII.3.2(data, species, matsex, MS, GSA)
```

Arguments

data	GFCM Task VII.3.2 table
species	List of combination of species/faunistic category for Task VII.3.2 table
matsex	List of combination of sex/maturity stages for Task VII.3.2 table
MS	member state code
GSA	GSA code

Value

Two vectors are returned by the function. The first provides the list of mismatching combination of species/faunistic categories. The second vector provides the list of mismatching combination of sex/maturity stages.

Examples

```
check_species_catfau_TaskVII.3.2(task_vii32, catfau_check, sex_mat, MS = "ITA", GSA = "18")
```

circabc	<i>Ports coordinates according to codification CIRCABC</i>
---------	--

Description

Ports coordinates according to codification CIRCABC

Usage

```
circabc
```

Format

An object of class `data.frame` with 24335 rows and 5 columns.

Author(s)

CIRCABC <<https://circabc.europa.eu>>

combination_taskII2	<i>combination_taskII2 in GFCM datacall format</i>
---------------------	--

Description

combination_taskII2 in GFCM datacall format

Usage

```
combination_taskII2
```

Format

An object of class `data.frame` with 60 rows and 4 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

data_ex	<i>RCG CS example</i>
---------	-----------------------

Description

RCG CS example

Usage

data_ex

Format

An object of class `data.frame` with 9099 rows and 40 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

data_exampleCL	<i>RCG CL example</i>
----------------	-----------------------

Description

RCG CL example

Usage

data_exampleCL

Format

An object of class `data.frame` with 35 rows and 22 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

Discard_tab_example	<i>Discard table in MED&BS datacall format</i>
---------------------	--

Description

Discard table in MED&BS datacall format

Usage

Discard_tab_example

Format

An object of class `data.frame` with 21 rows and 114 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

fdi_a_catch	<i>fdi_a_catch in FDI DGMAREMED&BS datacall format</i>
-------------	--

Description

fdi_a_catch in FDI DGMAREMED&BS datacall format

Usage

fdi_a_catch

Format

An object of class `data.frame` with 2450 rows and 23 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

FDI_checks_spatial_HI *check NA values in spatial columns of both table H and I*

Description

The function checks the incorrect combination of NA in the spatial columns in both table H (Landings by rectangle) and table I (Effort by rectangle). The following check are included:

1. presence of NA values in 'c_square' field when 'rectangle_type', 'rectangle_lat', 'rectangle_lon' are all NA;
2. the presence any data in 'rectangle_type', 'rectangle_lat', 'rectangle_lon' when 'c_square' is reported;
3. the presence of any data in 'c-squares' when 'rectangle_type', 'rectangle_lat', 'rectangle_lon' are filled in.

Furthermore the function identifies the records without any sub-region assignment.

Usage

```
FDI_checks_spatial_HI(data, MS, verbose = FALSE)
```

Arguments

data	data frame of one between FDI table H (Landings by rectangle) and table I (Effort by rectangle)
MS	Country code
verbose	boolean. If TRUE a message is printed.

Value

The function returns a list of 2 tables. The first (NA_inconsistencies) reports the records with the inconsistencies detected in spatial of the selected table, while the second one reports the record without any sub_region assignment.

Examples

```
FDI_checks_spatial_HI(data = fdi_h_spatial_landings, MS = "PSP", verbose = TRUE)
FDI_checks_spatial_HI(data = fdi_i_spatial_effort, MS = "PSP", verbose = TRUE)
```

FDI_check_coord *Compatibility of the geographical coordinates with rectangle type*

Description

The function checks the compatibility of the geographical coordinates (latitude and longitude) with the value provided for the rectangle type.

Usage

```
FDI_check_coord(data, MS, verbose = FALSE)
```

Arguments

data	data frame of one FDI table between H (Landings by rectangle) and table I (Effort by rectangle)
MS	Country code
verbose	boolean. If TRUE a message is printed.

Value

The input data frame is filtered and is returned retaining the only records in which at least one among latitude and longitude is not compatible with the rectangle type. Two more columns ('lat.check' and 'lon.check') are added to the data frame structure to report the results of the checks respectively for latitude and longitude.

Examples

```
FDI_check_coord(data = fdi_i_spatial_effort, MS = "PSP", verbose = TRUE)
```

FDI_coverage	<i>Coverage of data by GSA and year (reporting the number of records)</i>
--------------	---

Description

Coverage of data by GSA and year (reporting the number of records)

Usage

```
FDI_coverage(data, MS, verbose = TRUE)
```

Arguments

data	data frame. One of the allowed FDI table among A, G, H, I, J
MS	Country
verbose	boolean. If TRUE a message is printed.

Value

the function returns a data frame reporting the coverage of the selected table in terms of number of records by country, GSA and year.

Examples

```
FDI_coverage(data = fdi_a_catch, MS = "PSP", verbose = FALSE)
FDI_coverage(data = fdi_h_spatial_landings, MS = "PSP", verbose = FALSE)
FDI_coverage(data = fdi_g_effort, MS = "PSP", verbose = FALSE)
```

FDI_cov_tableA	<i>Check number of record in FDI A table</i>
----------------	--

Description

The function checks and count the numbers of records data in the given table A grouped by year, GSA, MS, species, vessels length, and fishing techniques for three variables (Total live weight landed (ton), total value of landings (euro), and total discards (ton)). If SP, Vessel length, and fishing technique are not specified by the user the function combines those by default.

Usage

```
FDI_cov_tableA(
  data,
  MS,
  SP = "COMBINED",
  vessel_len = "COMBINED",
  fishtech = "COMBINED",
  GSA,
  verbose = TRUE
)
```

Arguments

data	FDI table A catch
MS	member state code
SP	species reference code in the three alpha code format ("COMBINED" values perform the analysis for all species present in data)
vessel_len	vessels length code ("COMBINED" values perform the analysis for all vessels length present in data)
fishtech	selected fishing techniques ("COMBINED" values perform the analysis for all fishing techniques present in data)
GSA	GSA code
verbose	boolean. If TRUE a message is printed.

Value

The function returns a list. The first element gives the summary table of records number. From the second to the fourth element gives 3 plots for each variables among: of total live weight landed, total value of landings (euro), and total discards (ton)).

Examples

```
FDI_cov_tableA(data = fdi_a_catch, SP = "MUT", MS = "PSP", GSA = "GSA99")
FDI_cov_tableA(
  data = fdi_a_catch, SP = "MUT", MS = "PSP",
  fishtech = unique(fdi_a_catch$fishing_tech), GSA = "GSA99"
)
FDI_cov_tableA(data = fdi_a_catch, SP = "MUT", MS = "PSP", GSA = "GSA99")
```


FDI_cov_tableG

*Check number of record in FDI G table***Description**

The function checks and count the numbers of records data in the given table grouped by year, GSA, MS, vessels length, fishing techniques, and metier for the following 8 variables: Total days at sea; Total Fishing Days; Total kW days at Sea; total GT days at sea; Total kW fishing days; totgtfishdays; Hours at Sea; kW hours at sea; according to the [Fisheries Dependent Information data call 2021 - Annex 1](#) If Vessel length, fishing technique, and metier are not specified by the user the function combines those by default.

Usage

```
FDI_cov_tableG(
  data,
  MS,
  GSA,
  vessel_len = "COMBINED",
  fishtech = "COMBINED",
  met = "COMBINED",
  verbose = TRUE
)
```

Arguments

data	FDI table G effort
MS	member state code
GSA	GSA code
vessel_len	vessels length code ("COMBINED" values perform the analysis for all vessels length present in data)
fishtech	selected fishing techniques ("COMBINED" values perform the analysis for all fishing techniques present in data)
met	selected metiers ("COMBINED" values perform the analysis for all metiers present in data)
verbose	boolean. If TRUE a message is printed.

Value

The function returns a list. The first element gives the summary table of records number. From the second to the ninth element gives 8 plots for each variables among:

- totseadays,
- totfishdays,
- totkwdaysatsea,
- totgtdaysatsea,
- totkwfishdays,
- totgtfishdays,
- hrsea,
- kwhrsea

Examples

```
FDI_cov_tableG(data = fdi_g_effort, MS = "PSP", GSA = "GSA99")
FDI_cov_tableG(fdi_g_effort, MS = "PSP", GSA = "GSA99", fishtech = "DTS", met = "OTB_MDD_>=40_0_0")
```

FDI_cov_tableJ	<i>Check number of record in FDI J table</i>
----------------	--

Description

The function checks and count the numbers of records data in the given table grouped by year, GSA, MS, vessels length, and fishing techniques for the following 4 variables: total trips; total kW; total GT; total vessels.

Usage

```
FDI_cov_tableJ(
  data,
  MS,
  GSA,
  vessel_len = "COMBINED",
  fishtech = "COMBINED",
  verbose = TRUE
)
```

Arguments

data	FDI table J capacity
MS	member state code
GSA	GSA code
vessel_len	vessels length code ("COMBINED" values perform the analysis for all vessels length present in data)
fishtech	selected fishing techniques ("COMBINED" values perform the analysis for all fishing techniques present in data)
verbose	boolean. If TRUE a message is printed.

Value

The function returns a list. The first element gives the summary table of records number. From the second to the fifth element gives 4 plots for each variables among:

- total trips;
- total kW;
- total GT;
- total vessels;

Examples

```
FDI_cov_tableJ(data = fdi_j_capacity, MS = "PSP", GSA = "GSA99")
FDI_cov_tableJ(data = fdi_j_capacity, MS = "PSP", GSA = "GSA99", fishtech = c("DTS", "PGP"))
```

FDI_cross_checks_AG	<i>Cross check between FDI tables A and G</i>
---------------------	---

Description

The function checks the possible data inconsistency between landings and effort.

Usage

```
FDI_cross_checks_AG(data1, data2, verbose = FALSE)
```

Arguments

data1	FDI table A catch
data2	FDI table G effort
verbose	boolean. If TRUE a message is printed.

Value

The function returns a table where all the miss matches between landings and effort are shown.

Examples

```
FDI_cross_checks_AG(data1 = fdi_a_catch, data2 = fdi_g_effort)
FDI_cross_checks_AG(fdi_a_catch, fdi_g_effort)
```

FDI_cross_checks_AH	<i>Cross check between FDI tables A and H</i>
---------------------	---

Description

The function checks the possible data inconsistency between landings in table A and spatial landings in table H.

Usage

```
FDI_cross_checks_AH(data1, data2, verbose = FALSE)
```

Arguments

data1	FDI catch table A
data2	FDI spatial landings table H
verbose	boolean. If TRUE a message is printed.

Value

The function returns a list with two tables. In the first table all the miss matches between landings in table A and spatial landings in table H are shown, in the second table the comparison between total landings of table A and total spatial landings in table H is shown.

Examples

```
FDI_cross_checks_AH(data1 = fdi_a_catch, data2 = fdi_h_spatial_landings)
```

FDI_cross_checks_IG	<i>Cross check between FDI tables I and G</i>
---------------------	---

Description

The function checks the possible data inconsistency between spatial effort in table I and effort in table G.

Usage

```
FDI_cross_checks_IG(data1, data2, verbose = FALSE)
```

Arguments

data1	FDI spatial effort in table I
data2	FDI effort table G
verbose	boolean. If TRUE a message is printed.

Value

The function returns a list with two tables. In the first table all the mismatches between spatial effort in table I and effort in table G are shown, in the second table the comparison between total spatial effort of table I and total effort in table G is shown.

Examples

```
FDI_cross_checks_IG(data1 = fdi_i_spatial_effort, data2 = fdi_g_effort)
```

FDI_cross_checks_JG	<i>Cross check between FDI tables J and G</i>
---------------------	---

Description

The function checks the possible data inconsistency between the amount of vessels in table J capacity and the amount of vessels in table G.

Usage

```
FDI_cross_checks_JG(data1, data2, verbose = FALSE)
```

Arguments

data1	FDI capacity in table J
data2	FDI effort table G
verbose	boolean. If TRUE a message is printed.

Value

The function returns a list with all the mismatches between number of vessels in table J and G.

Examples

```
FDI_cross_checks_JG(data1 = fdi_j_capacity, data2 = fdi_g_effort, verbose = TRUE)
FDI_cross_checks_JG(fdi_j_capacity, fdi_g_effort)
```

FDI_disc_coverage	<i>Coverage of FDI discard data</i>
-------------------	-------------------------------------

Description

The functions checks the discard coverage in table A for the selected MS by GSAs.

Usage

```
FDI_disc_coverage(data, MS, verbose = TRUE)
```

Arguments

data	data frame of the FDI table A
MS	Country
verbose	boolean. If TRUE a message is printed.

Value

The function returns a list of data frames by GSA reporting the landing volumes (with discard >0, =0 and =NK and total landing) by year

Examples

```
FDI_disc_coverage(fdi_a_catch, MS = "PSP", verbose = TRUE)
```

FDI_fishdays_cov	<i>Coverage comparison of totfishdays between FDI tables G and I</i>
------------------	--

Description

The function checks the comparison of totfishdays in FDI tables G and I

Usage

```
FDI_fishdays_cov(dataG, dataI, MS, verbose = TRUE)
```

Arguments

dataG	data frame of FDA table G
dataI	data frame of FDA table I
MS	country code
verbose	boolean. If TRUE a message is printed.

Value

The function returns a data frame of the comparison of totfishdays between FDI tables G and I

Examples

```
FDI_fishdays_cov(dataG = fdi_g_effort, dataI = fdi_i_spatial_effort, MS = "PSP", verbose = TRUE)
```

fdi_g_effort	<i>fdi_g_effort in FDI DGMAREMED&BS datacall format</i>
--------------	---

Description

fdi_g_effort in FDI DGMAREMED&BS datacall format

Usage

```
fdi_g_effort
```

Format

An object of class `data.frame` with 2450 rows and 26 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

fdi_h_spatial_land	<i>fdi_h_spatial_land in FDI DGMAREMED&BS datacall format</i>
--------------------	---

Description

fdi_h_spatial_land in FDI DGMAREMED&BS datacall format

Usage

```
fdi_h_spatial_land
```

Format

An object of class `data.frame` with 5 rows and 23 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

`fdi_h_spatial_landings`*fdi_h_spatial_landings in FDI DGMAREMED&BS datacall format*

Description

`fdi_h_spatial_landings` in FDI DGMAREMED&BS datacall format

Usage

`fdi_h_spatial_landings`

Format

An object of class `data.frame` with 2450 rows and 23 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

`fdi_i_spatial_effort` *fdi_i_spatial_effort in FDI DGMAREMED&BS datacall format*

Description

`fdi_i_spatial_effort` in FDI DGMAREMED&BS datacall format

Usage

`fdi_i_spatial_effort`

Format

An object of class `data.frame` with 2450 rows and 21 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

fdi_j_capacity	<i>fdi_j_capacity in FDI DGMAREMED&BS datacall format</i>
----------------	---

Description

fdi_j_capacity in FDI DGMAREMED&BS datacall format

Usage

```
fdi_j_capacity
```

Format

An object of class `data.frame` with 2450 rows and 14 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

FDI_landweight_cov	<i>Coverage of weight of landings in FDI table A and H</i>
--------------------	--

Description

The functions checks the coverage of weight of landings comparing data reported in table A and H.

Usage

```
FDI_landweight_cov(dataA, dataH, MS, verbose = FALSE)
```

Arguments

dataA	data frame of the FDI table A
dataH	data frame of the FDI table H
MS	Country code
verbose	boolean. If TRUE a message is printed.

Value

The function returns a data frame reporting the weight of landings by GSA and by year.

Examples

```
FDI_landweight_cov(dataA = fdi_a_catch, dataH = fdi_h_spatial_landings, MS = "PSP", verbose = TRUE)
```

FDI_prices_cov	<i>Check prices trend in FDI A table</i>
----------------	--

Description

The function checks the trend prices in the given table grouped by year, GSA, MS, and species. If SP are not specified by the user the function combines those by default.

Usage

```
FDI_prices_cov(data, MS, SP = "COMBINED", GSA = "COMBINED", verbose = TRUE)
```

Arguments

data	FDI table A catch
MS	member state code
SP	species reference code in the three alpha code format ("COMBINED" values perform the analysis for all species present in data)
GSA	GSA code ("COMBINED" values perform the analysis for all GSAs present in data).
verbose	boolean. If TRUE a message is printed.

Value

The function returns a list. The first element gives the summary table of records number. From the second to the fourth element gives 3 plots for each variables among: of total live weight landed, total value of landings (euro), and total discards (ton)).

Examples

```
FDI_prices_cov(data = fdi_a_catch, SP = c("MUT", "HKE"), MS = "PSP", GSA = "GSA99")
FDI_prices_cov(data = fdi_a_catch, SP = "MUT", MS = "PSP", GSA = "GSA99")
```

FDI_prices_not_null	<i>Check of species value</i>
---------------------	-------------------------------

Description

The function estimates from the FDI table A an average price per species and year and compares it with average price calculated per country (by species). Furthermore, the function performs comparisons between total weight landings and total value landings. In particular it identifies the cases with total landings > 0 but landings value = 0. In case SP parameter is not specified, the analysis is conducted over all the species in the provided data frame.

Usage

```
FDI_prices_not_null(data, MS, SP = NA, verbose = FALSE)
```

Arguments

data	data frame of FDA table A catch.
MS	country code
SP	vector of the species code for which the check should be performed
verbose	boolean. If TRUE a message is printed.

Value

the function returns a list of two data frames. The first one reports the prices comparison by species, while the second one reports the cases in which total landings > 0 but landings value = 0.

Examples

```
FDI_prices_not_null(
  data = fdi_a_catch, MS = "PSP",
  SP = c("ARA", "BOG", "HKE"), verbose = TRUE
)
```

FDI_vessel_lenth

Check of vessel lenght in FDI table J

Description

The function checks the average length vessels with the vessel length category (table J)

Usage

```
FDI_vessel_lenth(data, MS, verbose = TRUE)
```

Arguments

data	data frame of table J
MS	country code
verbose	boolean. If TRUE a message is printed.

Value

The function returns a list of two data frames. The first reports the records with NAs in either vessel length or vessel category or both, while the second table reports the cases in which vessel length does not match vessel length category.

Examples

```
FDI_vessel_lenth(data = fdi_j_capacity, MS = "PSP", verbose = TRUE)
```

FDI_vessel_numbers	<i>Check number of vessels in FDI table J and G</i>
--------------------	---

Description

The function cross-checks the number of vessels in table J in comparison with the number reported in table G.

Usage

```
FDI_vessel_numbers(dataJ, dataG, MS, verbose = TRUE)
```

Arguments

dataJ	data frame of FDA table J catch.
dataG	data frame of FDA table G catch.
MS	country code
verbose	boolean. If TRUE a message is printed.

Value

The function returns a list of data frames. The first element reports the number of vessel in table J in comparison with table G and the relative difference percentage, while the second one reports the vessels not present in table G.

Examples

```
FDI_vessel_numbers(dataJ = fdi_j_capacity, dataG = fdi_g_effort, MS = "PSP", verbose = TRUE)
```

GP_tab_example	<i>GP table in MED&BS datacall format</i>
----------------	---

Description

GP table in MED&BS datacall format

Usage

```
GP_tab_example
```

Format

An object of class `data.frame` with 12 rows and 22 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

Landing_tab_example	<i>Landing table in MED&BS datacall format</i>
---------------------	--

Description

Landing table in MED&BS datacall format

Usage

Landing_tab_example

Format

An object of class `data.frame` with 57 rows and 114 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

MA_tab_example	<i>MA table in MED&BS datacall format</i>
----------------	---

Description

MA table in MED&BS datacall format

Usage

MA_tab_example

Format

An object of class `data.frame` with 71 rows and 11 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

MEDBS_ALK	<i>Plot of Age-Length Keys</i>
-----------	--------------------------------

Description

The function allows to check the data in the ALK table providing plots by sex for a selected species

Usage

```
MEDBS_ALK(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	ALK table in MED&BS datacall format
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned.

Value

a list of ALK plots by sex is return.

Examples

```
MEDBS_ALK(data = ALK_tab_example, SP = "MUT", MS = "ITA", GSA = "GSA 99")
```

MEDBS_Catch_coverage	<i>Check the coverage of Catch table</i>
----------------------	--

Description

The function allows to check the coverage of Catch table by mean of summary tables summarizing both landing and discard volumes and producing relative plots for the selected species.

Usage

```
MEDBS_Catch_coverage(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	Catch table in MEDBS format
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

The function returns two summary tables: one for landing coverage and the other for discard coverage. Furthermore, plots of landings and discards by gear are also returned

Examples

```
MEDBS_Catch_coverage(Catch_tab_example, "DPS", "ITA", "GSA 9")
```

```
MEDBS_check_duplicates
```

Check for duplicated data rows in landings, discards and catch tables

Description

The function checks the presence of duplicated rows in landings, discards or catch data.

Usage

```
MEDBS_check_duplicates(data, type = "l", SP, MS, GSA, verbose = TRUE)
```

Arguments

data	data frame containing either landings, discards or catch data
type	string vector indicating the type of table to be checked. "l" for landing; "d" for discards; "c" for catch table.
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

The function returns a data frame containing the duplicated rows to be likely deleted from the data.

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Isabella Bitetto bitetto@coispa.it

Examples

```
MEDBS_check_duplicates(data = Discard_tab_example, type = "d", SP = "DPS",
MS = "ITA", GSA = "GSA 9", verbose = TRUE)
MEDBS_check_duplicates(data = Landing_tab_example, type = "l", SP = "DPS",
MS = "ITA", GSA = "GSA 9", verbose = TRUE)
MEDBS_check_duplicates(data = Catch_tab_example, type = "c", SP = "DPS",
MS = "ITA", GSA = "GSA 9", verbose = TRUE)
```

MEDBS_comp_disc_YQ	<i>Comparison between discards in weight by quarter and -1</i>
--------------------	--

Description

The function compares the discards weights aggregated by quarter and by year for a selected species at gear level.

Usage

```
MEDBS_comp_disc_YQ(data, MS, GSA, SP, verbose = FALSE)
```

Arguments

data	data frame containing discards data
MS	member state code
GSA	GSA code (Geographical sub-area)
SP	species code
verbose	boolean. If TRUE a message is printed.

Value

The function returns a data frame with the comparison of discards aggregated by quarters and by year

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Isabella Bitetto bitetto@coispa.it

Examples

```
MEDBS_comp_disc_YQ(data = Discard_tab_example, MS = "ITA", GSA = "GSA 9", SP = "DPS")
```

MEDBS_comp_disc_YQ_fishery	<i>Comparison between discards in weight by quarter, quarter -1 and by fishery</i>
----------------------------	--

Description

The function allow to estimates the discards in weight for a selected species by quarter and fishery

Usage

```
MEDBS_comp_disc_YQ_fishery(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	data frame containing discards data
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

The function returns a data frame with the comparison of discards aggregated by quarters and by year and fishery

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Isabella Bitetto bitetto@coispa.it

Examples

```
MEDBS_comp_disc_YQ_fishery(data = Discard_tab_example, SP = "DPS", MS = "ITA", GSA = "GSA 9")
```

MEDBS_comp_land_Q_VL	<i>Comparison between landings in weight by quarter accounting for vessel length</i>
----------------------	--

Description

The function allows to perform the comparison of landings of a selected species aggregated by quarters, accounting for the presence of vessel length

Usage

```
MEDBS_comp_land_Q_VL(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	data frame containing landing data
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

The function returns a data frame for the comparison of landings aggregated by quarters, accounting for the presence of vessel length information.

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Isabella Bitetto bitetto@coispa.it

Examples

```
MEDBS_comp_land_Q_VL(data = Landing_tab_example, MS = "ITA", GSA = "GSA 9", SP = "DPS")
```

```
MEDBS_comp_land_Q_VL_fishery
```

Comparison between landings in weight by quarter and fishery, accounting for vessel length

Description

The function performs the comparison of landings of a selected species aggregated by quarters and fishery, accounting for the presence of vessel length

Usage

```
MEDBS_comp_land_Q_VL_fishery(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	data frame containing landing data
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

The function returns a data frame for the comparison of landings aggregated by quarters and fishery accounting for the presence of vessel length information.

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Isabella Bitetto bitetto@coispa.it

Examples

```
MEDBS_comp_land_Q_VL_fishery(data = Landing_tab_example, SP = "DPS", MS = "ITA", GSA = "GSA 9")
```

MEDBS_comp_land_YQ	<i>Comparison between landings in weight by quarter and -1</i>
--------------------	--

Description

The function allows to perform the comparison of landings of a selected species aggregated by quarters and by year

Usage

```
MEDBS_comp_land_YQ(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	data frame containing landing data
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

The function returns a data frame for the comparison of landings aggregated by quarters and by year

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Isabella Bitetto bitetto@coispa.it

Examples

```
MEDBS_comp_land_YQ(data = Landing_tab_example, SP = "DPS", MS = "ITA", GSA = "GSA 9")
```

MEDBS_comp_land_YQ_fishery	<i>Comparison between landings in weight by quarter; quarter -1 and by fishery</i>
----------------------------	--

Description

The function allows to perform the comparison of landings of a selected species aggregated by quarters, and by year and fishery

Usage

```
MEDBS_comp_land_YQ_fishery(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	data frame containing landing data
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

The function returns a data frame for the comparison of landings aggregated by quarters, and by year and fishery

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Isabella Bitetto bitetto@coispa.it

Examples

```
MEDBS_comp_land_YQ_fishery(data = Landing_tab_example, SP = "DPS", MS = "ITA", GSA = "GSA 9")
```

```
MEDBS_discard_coverage
```

Check the coverage of discard data

Description

The function allows to check the coverage of the time series in discard table for a selected species.

Usage

```
MEDBS_discard_coverage(Discard_tab, SP, MS, GSA, verbose = TRUE)
```

Arguments

Discard_tab	Discard table in MED&BS format
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

A summary table and a plot of discard time series by year and gear are returned.

Examples

```
MEDBS_discard_coverage(Discard_tab_example, "DPS", "ITA", "GSA 9")
```

MEDBS_disc_mean_weight

Check of mean discard weight aggregations by year, gear and fishery

Description

The function allows to check consistency of mean discard of a selected species plotting the discards' weight by year, gear and fishery

Usage

```
MEDBS_disc_mean_weight(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	data frame containing discards data
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

The function returns a plot of the mean discards weight by year, gear and fishery aggregation

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Isabella Bitetto bitetto@coispa.it

Examples

```
MEDBS_disc_mean_weight(data = Discard_tab_example, SP = "DPS", MS = "ITA", GSA = "GSA 9")
```

MEDBS_GP_check

Check of growth parameters table

Description

The function checks the growth parameters by sex and year for a selected species

Usage

```
MEDBS_GP_check(data, SP, MS, GSA)
```

Arguments

data	growth parameters table in MED&BS data call format
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)

Value

A list of objects containing a summary table and different plots of the growth curves by sex and year is returned by the function.

Examples

```
MEDBS_GP_check(GP_tab_example, "MUT", "ITA", "GSA 18")
```

MEDBS_ks	<i>Kolmogorov-Smirnov test</i>
----------	--------------------------------

Description

The function allows to perform the Kolmogorov-Smirnov test on both landings and discards for a selected species providing cumulative length distribution plots by fishery and year. The function performs Kolmogorov-Smirnov tests on couples of years to assess if they belong to the same population.

Usage

```
MEDBS_ks(data, type, SP, MS, GSA, Rt = 1, verbose = TRUE)
```

Arguments

data	data frame of either landings or discards data
type	type of data frame. "l" for landing and "d" for discard
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
Rt	ratio to be applied to subsample data to reduce the risk of rejection of H0 Hypothesis
verbose	boolean. If TRUE messages are returned

Value

the function returns a list of data frames and cumulative distribution plots

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Isabella Bitetto bitetto@coispa.it

Examples

```
MEDBS_ks(data = Landing_tab_example, type = "l", SP = "DPS", MS = "ITA", GSA = "GSA 9", Rt = 1)
```

```
MEDBS_Landing_coverage
```

Check the coverage of Landing table

Description

The function allows to check the coverage in landing table providing a summary table and a plot of landing.

Usage

```
MEDBS_Landing_coverage(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	Landing table in MED&BS format
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

A list containing a summary table and coverage plot is provided.

Examples

```
MEDBS_Landing_coverage(Landing_tab_example, "DPS", "ITA", "GSA 9")
```

```
MEDBS_land_mean_weight
```

Mean weight by year, gear and fishery aggregation

Description

The function allows to check consistency of mean landing of a selected species plotting the landings' weight by year, gear and fishery

Usage

```
MEDBS_land_mean_weight(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	data frame containing landing data
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

The function returns a plot of the mean landing weight by year, gear and fishery aggregation, and returns the data frame as well.

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Isabella Bitetto bitetto@coispa.it

Examples

```
MEDBS_land_mean_weight(data = Landing_tab_example, SP = "DPS", MS = "ITA", GSA = "GSA 9")
```

MEDBS_lengthclass_0 *Checks length classes numbers with zeros in landings and discards*

Description

The function checks landings and discards for the presence of length class filled in having weight > 0.

Usage

```
MEDBS_lengthclass_0(data, type = "l", SP, MS, GSA, verbose = TRUE)
```

Arguments

data	data frame containing landing or discards data
type	string vector indicating the type of table to be checked. "l" for landing; "d" for discards.
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

The function returns a data frame with the rows with 0 values length class having weight > 0.

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Isabella Bitetto bitetto@coispa.it

Examples

```
MEDBS_lengthclass_0(data = Landing_tab_example, type = "l",
  SP = "DPS", MS = "ITA", GSA = "GSA 9", verbose = TRUE)
MEDBS_lengthclass_0(data = Discard_tab_example, type = "d", SP = "DPS",
  MS = "ITA", GSA = "GSA 9", verbose = TRUE)
```

MEDBS_length_ind	<i>Main length size indicators</i>
------------------	------------------------------------

Description

The function allows to check the consistency of length data for a selected species on both landings and discards: Main length size indicators

Usage

```
MEDBS_length_ind(
  data,
  type,
  SP,
  MS,
  GSA,
  splines = c(0.2, 0.4, 0.6, 0.8),
  Xtresholds = c(0.25, 0.5, 0.75),
  verbose = TRUE
)
```

Arguments

data	data frame of either landings or discards data
type	type of data frame. "l" for landing and "d" for discard
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
splines	spline values assignment to fit cumulative distributions
Xtresholds	threshold value
verbose	boolean. If TRUE messages are returned

Value

The function returns a plot of the Main length size indicators time series by fishery

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Isabella Bitetto bitetto@coispa.it

Examples

```
MEDBS_length_ind(Landing_tab_example,
  type = "l", SP = "DPS", MS = c("ITA"),
  GSA = c("GSA 9"), splines = c(0.2, 0.4, 0.6, 0.8),
  Xtresholds = c(0.25, 0.5, 0.75)
)
MEDBS_length_ind(Discard_tab_example,
  type = "d", SP = "DPS", MS = c("ITA"),
  GSA = c("GSA 9"), splines = c(0.2, 0.4, 0.6, 0.8),
  Xtresholds = c(0.25, 0.5, 0.75)
)
```

MEDBS_LW_check

Check LW parameters in GP table

Description

The function checks the length-weight parameters included in the GP table for a selected species.

Usage

```
MEDBS_LW_check(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	growth params table in MED&BS datacall format
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

A summary table and plots of the LW parameters are returned by the function.

Examples

```
MEDBS_LW_check(GP_tab_example, "MUT", "ITA", "GSA 18")
```

MEDBS_MA_check	<i>Check of MA_tab (maturity at age) table</i>
----------------	--

Description

The function checks the maturity at age (MA) table providing a summary table of the data coverage and plots for the selected species of the proportion of matures for age class by sex and year.

Usage

```
MEDBS_MA_check(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	maturity at AGE table in MED&BS datacall format
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

A summary table and plots are returned by the function.

Examples

```
MEDBS_MA_check(MA_tab_example, "DPS", "ITA", "GSA 99")
```

MEDBS_ML_check	<i>Check of ML_tab (maturity at length) table</i>
----------------	---

Description

The function checks the maturity at length (ML) table providing a summary table of the data coverage and plots for the selected species of the proportion of matures for age class by sex and year.

Usage

```
MEDBS_ML_check(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	maturity at length table in MED&BS datacall format
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

a summary table and plots

Examples

```
MEDBS_ML_check(ML_tab_example, "DPS", "ITA", "GSA 99")
```

MEDBS_plot_discard_ts *Plot of total discards*

Description

The function estimates the total discard time series by both year and quarters for a selected combination of member state, GSA and species.

Usage

```
MEDBS_plot_discard_ts(data, SP, MS, GSA, by = "year")
```

Arguments

data	data frame containing discard data
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
by	string defining the temporal aggregation level of discard data to be plotted. Allowed values are: "year" and "quarter"

Value

The function returns a plot of the total discard time series by year or by quarters. The plot by year also reports the landing by gear.

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Isabella Bitetto bitetto@coispa.it

Examples

```
MEDBS_plot_discard_ts(data = Discard_tab_example, SP = "DPS",
  MS = "ITA", GSA = "GSA 9", by = "quarter")
MEDBS_plot_discard_ts(data = Discard_tab_example, SP = "DPS",
  MS = "ITA", GSA = "GSA 9", by = "year")
```

MEDBS_plot_disc_vol *Plot of total discards by gear and fishery*

Description

The function allows to visual check the time series of discard volumes by fishery of a selected species

Usage

```
MEDBS_plot_disc_vol(data, SP, MS, GSA)
```

Arguments

data	data frame containing discard data
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)

Value

The function returns a plot of the total discards time series by fishery and gear

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Isabella Bitetto bitetto@coispa.it

Examples

```
MEDBS_plot_disc_vol(data = Discard_tab_example, SP = "DPS", MS = "ITA", GSA = "GSA 9")
```

MEDBS_plot_landing_ts *Plot of total landing time series*

Description

The function estimates the total landings time series by both year and quarters for a selected combination of member state, GSA and species.

Usage

```
MEDBS_plot_landing_ts(data, SP, MS, GSA, by = "year", verbose = TRUE)
```

Arguments

data	data frame containing landing data
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
by	string defining the temporal aggregation level of landing data to be plotted. Allowed values are: "year" and "quarter"
verbose	boolean. If TRUE messages are returned

Value

The function returns a plot of the total landing time series by year or by quarters. The plot by year also reports the landing by gear.

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Isabella Bitetto bitetto@coispa.it

Examples

```
MEDBS_plot_landing_ts(data = Landing_tab_example, SP = "DPS",
MS = "ITA", GSA = "GSA 9", by = "quarter")
MEDBS_plot_landing_ts(data = Landing_tab_example, SP = "DPS", MS = "ITA",
GSA = "GSA 9", by = "year")
```

MEDBS_plot_land_vol *Plot of total landing by gear and fishery*

Description

The function checks the time series of landing volumes by fishery of a selected species

Usage

```
MEDBS_plot_land_vol(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	data frame containing landing data
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

The function returns a plot of the total landing time series by fishery and gear

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Isabella Bitetto bitetto@coispa.it

Examples

```
MEDBS_plot_land_vol(data = Landing_tab_example, SP = "DPS", MS = "ITA", GSA = "GSA 9")
```

MEDBS_SA_check	<i>Check of SA_tab (sex ratio at age) table</i>
----------------	---

Description

The function allows to check the sex ratio at age (SA) table providing a summary table of the data coverage and plots for the selected species of the proportion of sex ratio for age class by year.

Usage

```
MEDBS_SA_check(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	sex ratio at age table in MED&BS datacall format
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

a summary table and plots

Examples

```
MEDBS_SA_check(SA_tab_example, "DPS", "ITA", "GSA 99")
```

MEDBS_SL_check	<i>Check of SL_tab (sex ratio at length) table</i>
----------------	--

Description

The function allows to check the sex ratio at length (SL) table providing a summary table of the data coverage and plots for the selected species of the proportion of sex ratio for length class by year.

Usage

```
MEDBS_SL_check(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	sex ratio at length table in MED&BS data call format
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

a summary table and plots

Examples

```
MEDBS_SL_check(SL_tab_example, "DPS", "ITA", "GSA 99")
```

MEDBS_SOP	<i>check of the sum of products</i>
-----------	-------------------------------------

Description

check of the sum of products

Usage

```
MEDBS_SOP(data, SP, MS, GSA, threshold = 5, verbose = TRUE)
```

Arguments

data	Catch table in MED&BS datacall format
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
threshold	threshold value in percentage to check the percentage difference between SOP and both volumes of landing and discard. Default value is 5%
verbose	boolean. If TRUE messages are returned

Value

the function returns a data frame of the record with values of percentage difference between SOP and both volumes of landing and discard greater then threshold value.

Examples

```
MEDBS_SOP(data = Catch_tab_example, SP = "DPS", MS = "ITA", GSA = "GSA 9", threshold = 5)
```

MEDBS_weight_0	<i>Check of weights 0 in landings and discards</i>
----------------	--

Description

The function checks landings or discards in weight equal to 0 having length classes filled in

Usage

```
MEDBS_weight_0(data, type = "l", SP, MS, GSA, verbose = TRUE)
```

Arguments

data	data.table object containing landing or discard data
type	type of table: "l" for landings; "d" for discards
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

The function returns a table of rows with 0 values in weights having length classes filled in.

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Isabella Bitetto bitetto@coispa.it

Examples

```
MEDBS_weight_0(data = Landing_tab_example, type = "l",
  SP = "DPS", MS = "ITA", GSA = "GSA 9", verbose = TRUE)
MEDBS_weight_0(data = Discard_tab_example, type = "d", SP = "DPS",
  MS = "ITA", GSA = "GSA 9", verbose = TRUE)
```

MEDBS_weight_minus1 *Check weights -1 in landings*

Description

The function checks landings in weight equal to -1 having length class filled in

Usage

```
MEDBS_weight_minus1(data, type = "l", SP, MS, GSA, verbose = TRUE)
```

Arguments

data	data.table object containing landing or discards data
type	type of table: "l" for landings; "d" for discards
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned.

Value

The function returns a table of rows with -1 values in landing weights having length class filled in.

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Isabella Bitetto bitetto@coispa.it

Examples

```
MEDBS_weight_minus1(data = Landing_tab_example, type = "l",
  SP = "DPS", MS = "ITA", GSA = "GSA 9", verbose = TRUE)
MEDBS_weight_minus1(data = Discard_tab_example, type = "d", SP = "DPS",
  MS = "ITA", GSA = "GSA 9", verbose = TRUE)
```

MEDBS_yr_missing_length *Years with missing length distributions*

Description

The function checks the presence of years with missing length distributions in both landings and discards for a selected species.

Usage

```
MEDBS_yr_missing_length(data, type, SP, MS, GSA)
```

Arguments

data	data frame of landings or discards data
type	type of data frame. "l" for landing and "d" for discard
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)

Value

The function returns a data frame containing the reference combination of year, gear and fishery missing length distributions.

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Isabella Bitetto bitetto@coispa.it

Examples

```
MEDBS_yr_missing_length(data = Discard_tab_example, type = "d",
  SP = "DPS", MS = "ITA", GSA = "GSA 9")
MEDBS_yr_missing_length(data = Landing_tab_example, type = "l", SP = "DPS",
  MS = "ITA", GSA = "GSA 9")
```

minmaxLtaskVII2

minmaxLtaskVII2 in GFCM datacall format

Description

minmaxLtaskVII2 in GFCM datacall format

Usage

```
minmaxLtaskVII2
```

Format

An object of class `data.frame` with 26 rows and 3 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

`minmaxLtaskVII31`*minmaxLtaskVII31 in GFCM datacall format*

Description

minmaxLtaskVII31 in GFCM datacall format

Usage

`minmaxLtaskVII31`

Format

An object of class `data.frame` with 36 rows and 4 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

`ML_tab_example`*ML table in MED&BS datacall format*

Description

ML table in MED&BS datacall format

Usage

`ML_tab_example`

Format

An object of class `data.frame` with 437 rows and 12 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

RCG_check_AL

*Check consistency of age-length relationship***Description**

The function checks the consistency of the age-length data included in the table of RCG detailed data. Furthermore, the function identifies the age data outside a reference range of values provided by the user for the species. In case the `min_age` and `max_age` parameters are not provided, the function tests the lowest and the higher values of Age as outliers by mean of the Grubbs' test (from package outliers)

Usage

```
RCG_check_AL(data, MS, GSA, SP, min_age = NA, max_age = NA, verbose = TRUE)
```

Arguments

<code>data</code>	table of detailed data in RCG format
<code>MS</code>	member state code
<code>GSA</code>	GSA code (Geographical sub-area)
<code>SP</code>	species code
<code>min_age</code>	minimum age expected
<code>max_age</code>	maximum age expected
<code>verbose</code>	boolean. If TRUE messages are returned

Value

The function returns a list of object containing a summary table, an age-length plot and a table of the outlayers, if any.

References

Grubbs, F.E. (1950). Sample Criteria for testing outlying observations. *Ann. Math. Stat.* 21, 1, 27-58

Examples

```
RCG_check_AL(data=data_ex, MS = "ITA", GSA = "GSA99",
SP = "Mullus barbatus", min_age = 0, max_age = 9)
RCG_check_AL(data=data_ex, MS = "ITA", GSA = "GSA99", SP = "Mullus barbatus")
```

RCG_check_CL	<i>Quality checks on CL RCG table</i>
--------------	---------------------------------------

Description

The function checks CL tables for temporal, spatial, species and metier coverage

Usage

```
RCG_check_CL(data, MS, GSA, SP, verbose = TRUE)
```

Arguments

data	Landing table in RCG CL format
MS	member state code
GSA	GSA code (Geographical sub-area)
SP	species code
verbose	boolean. If TRUE messages are returned

Value

The output is a list of 6 data frames:

1. Sum of Landings by year, quarter and month;
2. Sum of Landing value by year, quarter and month;
3. Sum of landings by LandCtry, VslFlgCtry, Area, Rect, SubRect, Harbour;
4. Sum of landing value by LandCtry, VslFlgCtry, Area, Rect, SubRect, Harbour;
5. Sum of landings by Year, Species, foCatEu5, foCatEu6;
6. Sum of landing value by Year, Species, foCatEu5, foCatEu6.

Examples

```
RCG_check_CL(data_exampleCL, MS = "COUNTRY1", GSA = "GSA99", SP = "Parapenaeus longirostris")
```

RCG_check_LFD	<i>Consistency check of LFDs</i>
---------------	----------------------------------

Description

The function allows to check the consistency of LFDs (length frequency distributions) by year on a given species generating a multi-frame plot. The function also returns the records in which the length classes are greater or lower than the expected ones (min_len and max_len parameters).

Usage

```
RCG_check_LFD(data, SP, MS, GSA, min_len = NA, max_len = NA, verbose = TRUE)
```

Arguments

data	RCG CS table
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
min_len	minimum length
max_len	maximum length
verbose	boolean. If TRUE messages are returned

Value

The function returns a comparison plot of LFDs among the years and a table reporting the length classes out of the expected range, according to the reference length provided.

Examples

```
RCG_check_LFD(data=data_ex, MS = "ITA", GSA = "GSA99", SP = "Mullus barbatus",
min_len = 30, max_len = 300)
RCG_check_LFD(data=data_ex, MS = "ITA", GSA = "GSA99", SP = "Mullus barbatus",
min_len = NA, max_len = NA)
```

RCG_check_LFD_comm_cat

Check consistency of LFD by year and commercial category

Description

The function allows to check the consistency of LFDs (length frequency distributions) by year and commercial size category on a given species.

Usage

```
RCG_check_LFD_comm_cat(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	RCG CS table
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

The function returns a multi-frame plot of LFDs (length frequency distributions) by year and commercial size category for the selected species. The function also returns a data frame with the length range by year and commercial size category.

Examples

```
RCG_check_LFD_comm_cat(data_ex, MS = "ITA", GSA = "GSA99", SP = "Mullus barbatus")
```

RCG_check_loc	<i>Check trip location</i>
---------------	----------------------------

Description

The function allows to check the spatial distribution of data using the initial and final coordinates, where available, and the ports position included in the data in case coordinates are not available.

Usage

```
RCG_check_loc(data, ports = circabc)
```

Arguments

data	detailed data in RCG CS format
ports	ports codification file

Value

A map of trip locations is generated.

Examples

```
RCG_check_loc(data_ex)
```

RCG_check_lw	<i>Consistency check of length-weight relationship</i>
--------------	--

Description

The function allows to check the consistency of length-weight relationship by sex and year on a given species generating a multi-frame plot. The function also returns the records in which the individual weights are greater or lower than the expected ones (Min and Max parameters). In case the Min and Max parameters are not provided, the function tests the lowest and the higher values of individual weights as outliers by mean of the Grubbs' test (from package outliers)

Usage

```
RCG_check_lw(data, SP, MS, GSA, Min = NA, Max = NA, verbose = TRUE)
```

Arguments

data	table of detailed data in RCG format
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
Min	min weight expected in the data
Max	max weight expected in the data
verbose	boolean. If it is TRUE messages are reported with the outputs

Value

Plot and error message

References

Grubbs, F.E. (1950). Sample Criteria for testing outlying observations. Ann. Math. Stat. 21, 1, 27-58

Examples

```
RCG_check_lw(data_ex, MS = "ITA", GSA = "GSA99", SP = "Mullus barbatus", Min = 0, Max = 1000)
RCG_check_lw(data_ex, MS = "ITA", GSA = "GSA99", SP = "Mullus barbatus")
```

RCG_check_mat	<i>Check consistency sex and maturity stage</i>
---------------	---

Description

The function allows to perform a visual check of the maturity stage composition by length class, sex and year.

Usage

```
RCG_check_mat(data, MS, GSA, SP, verbose = TRUE)
```

Arguments

data	table of detailed data in RCG format
MS	member state code
GSA	GSA code
SP	reference species for the analysis
verbose	boolean. If it is TRUE messages are reported with the outputs

Value

The function the returns the plot of the maturity stages by length class

Examples

```
RCG_check_mat(data_ex, MS = "ITA", GSA = "GSA99", SP = "Mullus barbatus")
```

RCG_check_mat_ogive *Maturity ogives by sex*

Description

The function allows to check the maturity stages composition estimating the maturity ogives by sex for the selected species, using a selected pool of stages to classify the immature stages in the sample.

Usage

```
RCG_check_mat_ogive(
  data,
  MS,
  GSA,
  SP,
  sex,
  immature_stages = c("0", "1", "2a"),
  verbose = TRUE
)
```

Arguments

data	table of detailed data in RCG format
MS	member state code
GSA	GSA code (Geographical sub-area)
SP	species code
sex	defines the sex of the individuals selected for the analysis ('F' for females, 'M' for males)
immature_stages	vector of maturity stages considered immature
verbose	boolean. If TRUE messages are returned

Value

Plot ogive by sex

Examples

```
RCG_check_mat_ogive(data_ex,
  MS = "ITA", GSA = "GSA99", SP = "Mullus barbatus",
  sex = "F", immature_stages = c("0", "1", "2a")
)
```

RCG_summarize_ind_meas

Number of individual by trip for which biological data have been collected (length, sex, maturity, weight and age)

Description

Number of individual by trip for which biological data have been collected (length, sex, maturity, weight and age)

Usage

```
RCG_summarize_ind_meas(data, MS, GSA, SP, verbose = TRUE)
```

Arguments

data	detailed data in RCG CS format
MS	member state code
GSA	GSA code
SP	species reference code in the three alpha code format
verbose	boolean value to obtain further explanation messages from the function

Value

a list containing a summary of measurements by trip for each biological variable

Examples

```
RCG_summarize_ind_meas(data = data_ex, MS = "ITA", GSA = "GSA99", SP = "Mullus barbatus")
```

RCG_summarize_trips	<i>summarizing the number of trips/hauls monitored by year by port, metier, sampling method;</i>
---------------------	--

Description

The function allows to summarise the number of trips/hauls monitored by year, port, metier and sampling method.

Usage

```
RCG_summarize_trips(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	RCG CS table
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

Number of trips by area, year, port, metier and sampling method

Examples

```
RCG_summarize_trips(data_ex, MS = "ITA", GSA = "GSA99", SP = "Mullus barbatus")
```

SA_tab_example	<i>SA table in MED&BS datacall format</i>
----------------	---

Description

SA table in MED&BS datacall format

Usage

```
SA_tab_example
```

Format

An object of class `data.frame` with 74 rows and 9 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

sex_mat	<i>sex_mat in GFCM datacall format</i>
---------	--

Description

sex_mat in GFCM datacall format

Usage

```
sex_mat
```

Format

An object of class `spec_tbl_df` (inherits from `tbl_df`, `tbl`, `data.frame`) with 42 rows and 5 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

`SL_tab_example`*SL table in MED&BS datacall format*

Description

SL table in MED&BS datacall format

Usage

`SL_tab_example`

Format

An object of class `data.frame` with 454 rows and 10 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

`task_ii2`*task_ii2 in GFCM DCRF datacall format*

Description

task_ii2 in GFCM DCRF datacall format

Usage

`task_ii2`

Format

An object of class `data.frame` with 5 rows and 9 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

task_iii*task_iii in GFCM DCRF datacall format*

Description

task_iii in GFCM DCRF datacall format

Usage

task_iii

Format

An object of class data.frame with 5 rows and 16 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

task_vii2*task_vii2 in GFCM DCRF datacall format*

Description

task_vii2 in GFCM DCRF datacall format

task_vii31 in GFCM DCRF datacall format

Usage

task_vii2

task_vii2

Format

An object of class data.frame with 20 rows and 13 columns.

An object of class data.frame with 20 rows and 13 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

task_vii31	<i>task_vii31 in GFCM datacall format</i>
------------	---

Description

task_vii31 in GFCM datacall format

Usage

task_vii31

Format

An object of class `data.frame` with 5 rows and 8 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

task_vii32	<i>task_vii32 in GFCM DCRF datacall format</i>
------------	--

Description

task_vii32 in GFCM DCRF datacall format

Usage

task_vii32

Format

An object of class `data.frame` with 10 rows and 15 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

Index

- * **CIRCABC**
 - circabc, [19](#)
- * **CL,**
 - data_exampleCL, [20](#)
- * **CS**
 - data_ex, [20](#)
- * **DCRF**
 - task_ii2, [68](#)
 - task_iii, [69](#)
 - task_vii2, [69](#)
 - task_vii32, [70](#)
- * **DGMAREMED&BS**
 - fdi_a_catch, [21](#)
 - fdi_g_effort, [30](#)
 - fdi_h_spatial_land, [30](#)
 - fdi_h_spatial_landings, [31](#)
 - fdi_i_spatial_effort, [31](#)
 - fdi_j_capacity, [32](#)
- * **FDI**
 - fdi_a_catch, [21](#)
 - fdi_g_effort, [30](#)
 - fdi_h_spatial_land, [30](#)
 - fdi_h_spatial_landings, [31](#)
 - fdi_i_spatial_effort, [31](#)
 - fdi_j_capacity, [32](#)
- * **GFCM**
 - catfau_check, [5](#)
 - combination_taskII2, [19](#)
 - minmaxLtaskVII2, [58](#)
 - minmaxLtaskVII31, [59](#)
 - sex_mat, [67](#)
 - task_ii2, [68](#)
 - task_iii, [69](#)
 - task_vii2, [69](#)
 - task_vii31, [70](#)
 - task_vii32, [70](#)
- * **Harbour**
 - circabc, [19](#)
- * **MED&BS**
 - ALK_tab_example, [4](#)
 - Catch_tab_example, [4](#)
 - Discard_tab_example, [21](#)
 - GP_tab_example, [35](#)
 - Landing_tab_example, [36](#)
 - MA_tab_example, [36](#)
 - ML_tab_example, [59](#)
 - SA_tab_example, [67](#)
 - SL_tab_example, [68](#)
- * **RCG,**
 - data_exampleCL, [20](#)
- * **RCG**
 - data_ex, [20](#)
- * **datacall**
 - ALK_tab_example, [4](#)
 - Catch_tab_example, [4](#)
 - catfau_check, [5](#)
 - combination_taskII2, [19](#)
 - Discard_tab_example, [21](#)
 - fdi_a_catch, [21](#)
 - fdi_g_effort, [30](#)
 - fdi_h_spatial_land, [30](#)
 - fdi_h_spatial_landings, [31](#)
 - fdi_i_spatial_effort, [31](#)
 - fdi_j_capacity, [32](#)
 - GP_tab_example, [35](#)
 - Landing_tab_example, [36](#)
 - MA_tab_example, [36](#)
 - minmaxLtaskVII2, [58](#)
 - minmaxLtaskVII31, [59](#)
 - ML_tab_example, [59](#)
 - SA_tab_example, [67](#)
 - sex_mat, [67](#)
 - SL_tab_example, [68](#)
 - task_ii2, [68](#)
 - task_iii, [69](#)
 - task_vii2, [69](#)
 - task_vii31, [70](#)
 - task_vii32, [70](#)
- * **data**
 - data_exampleCL, [20](#)
- * **landing**
 - data_exampleCL, [20](#)
- * **samplingData**
 - data_ex, [20](#)
- ALK_tab_example, [4](#)

- Catch_tab_example, 4
- catfau_check, 5
- check_EF_FDI_A, 5
- check_EF_FDI_G, 6
- check_EF_FDI_H, 6
- check_EF_FDI_I, 7
- check_EF_FDI_J, 7
- check_EF_taskII2, 8
- check_EF_taskIII, 8
- check_EF_taskVII2, 9
- check_EF_TaskVII31, 9
- check_EF_TaskVII32, 10
- check_lmat_TaskVII.3.2, 10
- check_lw_TaskVII.2, 11
- check_minmaxl50_TaskVII.3.1, 11
- check_minmaxl_TaskVII.2, 12
- check_presence_taskII2, 13
- check_RD_FDI_A, 13
- check_RD_FDI_G, 14
- check_RD_FDI_H, 14
- check_RD_FDI_I, 15
- check_RD_FDI_J, 15
- check_RD_taskII2, 16
- check_RD_taskIII, 16
- check_RD_taskVII2, 17
- check_RD_taskVII31, 17
- check_RD_TaskVII32, 18
- check_species_catfau_TaskVII.3.2, 18
- circabc, 19
- combination_taskII2, 19
- data_ex, 20
- data_exampleCL, 20
- Discard_tab_example, 21
- fdi_a_catch, 21
- FDI_check_coord, 22
- FDI_checks_spatial_HI, 22
- FDI_cov_tableA, 24
- FDI_cov_tableG, 25
- FDI_cov_tableJ, 26
- FDI_coverage, 23
- FDI_cross_checks_AG, 27
- FDI_cross_checks_AH, 27
- FDI_cross_checks_IG, 28
- FDI_cross_checks_JG, 28
- FDI_disc_coverage, 29
- FDI_fishdays_cov, 29
- fdi_g_effort, 30
- fdi_h_spatial_land, 30
- fdi_h_spatial_landings, 31
- fdi_i_spatial_effort, 31
- fdi_j_capacity, 32
- FDI_landweight_cov, 32
- FDI_prices_cov, 33
- FDI_prices_not_null, 33
- FDI_vessel_lenth, 34
- FDI_vessel_numbers, 35
- GP_tab_example, 35
- Landing_tab_example, 36
- MA_tab_example, 36
- MEDBS_ALK, 37
- MEDBS_Catch_coverage, 37
- MEDBS_check_duplicates, 38
- MEDBS_comp_disc_YQ, 39
- MEDBS_comp_disc_YQ_fishery, 39
- MEDBS_comp_land_Q_VL, 40
- MEDBS_comp_land_Q_VL_fishery, 41
- MEDBS_comp_land_YQ, 42
- MEDBS_comp_land_YQ_fishery, 42
- MEDBS_disc_mean_weight, 44
- MEDBS_discard_coverage, 43
- MEDBS_GP_check, 44
- MEDBS_ks, 45
- MEDBS_land_mean_weight, 46
- MEDBS_Landing_coverage, 46
- MEDBS_length_ind, 48
- MEDBS_lengthclass_0, 47
- MEDBS_LW_check, 49
- MEDBS_MA_check, 50
- MEDBS_ML_check, 50
- MEDBS_plot_disc_vol, 52
- MEDBS_plot_discard_ts, 51
- MEDBS_plot_land_vol, 53
- MEDBS_plot_landing_ts, 52
- MEDBS_SA_check, 54
- MEDBS_SL_check, 55
- MEDBS_SOP, 55
- MEDBS_weight_0, 56
- MEDBS_weight_minus1, 57
- MEDBS_yr_missing_length, 57
- minmaxLtaskVII2, 58
- minmaxLtaskVII31, 59
- ML_tab_example, 59
- RCG_check_AL, 60
- RCG_check_CL, 61
- RCG_check_LFD, 61
- RCG_check_LFD_comm_cat, 62
- RCG_check_loc, 63
- RCG_check_lw, 63
- RCG_check_mat, 64
- RCG_check_mat_ogive, 65

RCG_summarize_ind_meas, [66](#)

RCG_summarize_trips, [66](#)

SA_tab_example, [67](#)

sex_mat, [67](#)

SL_tab_example, [68](#)

task_ii2, [68](#)

task_iii, [69](#)

task_vii2, [69](#)

task_vii31, [70](#)

task_vii32, [70](#)