

1 APPENDIX of “Multi-Fidelity Methods for Optimization: A Survey”
2
3
4

5 **ACM Reference Format:**

6 . 2024. APPENDIX of “Multi-Fidelity Methods for Optimization: A Survey”. 1, 1 (February 2024), 34 pages.
7
8

9 **A MIND MAPS**
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50

51 Author’s address:
52 Manuscript submitted to ACM



Fig. A1. Taxonomy of research strands for multi-fidelity optimization, and the research strands and structure of this survey.




Fig. A2. Taxonomy of applications of multi-fidelity optimization across machine learning, engineering design and optimization, and scientific discovery domains.

B SUPPLEMENTARY INFORMATION OF SECTIONS 2 TO 8

B.1 Supplementary information of Section 2

Tables A1 and A2 provide the tables complementary to the statistical diagrams presented in our manuscript.

Table A1. Statistics of the number of articles published in different countries (sorted in a descending order). Note that the articles are collected in our text mining process.

COUNTRY	# OF ARTICLES	COUNTRY	# OF ARTICLES	COUNTRY	# OF ARTICLES
United States of America	372	Poland	12	Pakistan	3
China	288	Thailand	11	Norway	2
Germany	61	Iran	9	Czech Republic	2
United Kingdom	60	Turkey	9	Italy	2
Italy	41	Mexico	9	German	2
France	39	Portugal	8	Indonesia	2
Iceland	39	Sweden	6	Hungary	2
Canada	31	Ireland	6	United Arab Emirates	2
Japan	25	Greece	5	Colombia	2
India	22	Russia	4	Malaysia	2
Netherlands	22	Switzerland	4	Qatar	1
South Korea	20	Denmark	4	New Zealand	1
Australia	17	South Africa	4	Algeria	1
Spain	15	Egypt	3	Luxembourg	1
Singapore	14	Finland	3	Bangladesh	1
Belgium	12	Israel	3	NONE	23
Brazil	12	Vietnam	3		

Table A2. Statistics of the number of articles classified into different topics.

TOPIC ID	# OF ARTICLES	TOPIC KEY WORDS	TOPIC ID	# OF ARTICLES	TOPIC KEY WORDS
1	180	Surrogate model and optimization	12	34	Neural network
2	74	Turbine blade optimization	13	34	Propeller optimization
3	59	Electromagnetic optimization	14	32	Material design
4	57	Aircraft wing optimization	15	29	Manufacturing process optimization
5	57	Evolutionary optimization	16	29	Supersonic multidisciplinary design
6	48	Hyperparameter optimization	17	28	Satellite trajectory optimization
7	45	Bayesian optimization	18	28	Image reconstruction
8	43	Reservoir optimization	19	23	Control model design
9	41	Composite, buckling, optimization	20	23	Aerodynamic optimization
10	37	Simulation and ordinal transformation	21	20	Combustor design
11	35	Airfoil shape optimization	22	19	Cooling hole design
230	231	232	233	234	235
236	237	238	239	240	241
242	243	244	245	246	247
248	249	250	251	252	253
254	255	256	257	258	259
260					

261 B.2 Supplementary information of Section 3

262 Table A3 gives the number of articles categorized into different types of surrogate modeling methods. Table A4 provides
 263 a summary of the current works on multi-fidelity surrogate modeling, focusing on their native assumptions and relevant
 264 disadvantages.

265 Table A3. Statistics of the number of articles regarding the multi-fidelity surrogate modeling.
 266

269 MODELS	270 # OF ARTICLES	271 MODELS	272 # OF ARTICLES	273 MODELS	274 # OF ARTICLES
Autoregressive-based	30	Single model	8	Mapping	2
Correction-based	27	No	6	Nonlinear methods	1
MTGP	11	GP	2	Ensemble	1

275 Table A4. Summary of the current works on surrogate modeling for multi-fidelity data.
 276

279 METHODS	280 ASSUMPTIONS	281 DISADVANTAGES	282 REFERENCES
Single model	Independent	Since each fidelity is modeled independently, samples from one fidelity cannot contribute to improving the others.	RSM [30], Kriging [25, 43, 63], RBF [42, 63, 114].
Space mapping	$x_l = P(x_h)$	① It is hard to construct a good mapping model. ② It may be trapped in local minima if the LF is severely misaligned with the HF.	Linear [3, 5–7], nonlinear [4, 86]
Correction-based method	$f_h(x) = f_l(x) + \delta(x)$ $f_h(x) = \rho(x)f_l(x)$ $f_h(x) = \rho(x)f_l(x) + \delta(x)$	① Since LF and HF are modeled independently, their correlations are neglected. ② It requires evaluating samples at all fidelities, thus incurring a significant amount of sample data. ③ It cannot model the nonlinear relationship between different fidelities.	First-order [14, 33, 51] and second-order Taylor series [23, 27, 29, 73, 74], NNs [20, 37, 47, 93, 100, 101, 106, 107, 113], SVR [15, 91, 94, 122, 124], RSM [49, 95, 103, 104], Kriging [28, 29, 60, 67, 109, 123, 125–127].
AR1	$f_h(x) = \rho f_l(x) + \delta(x)$ $f_h(x), f_l(x), \delta(x)$ $\sim N(m, \sigma^2(x))$	① It can only estimate the relationship between subsequent fidelities, thereby restricting information propagation across fidelities. ② It cannot model the nonlinear relationship between different fidelities.	co-Kriging [17, 26, 35, 39, 45, 81, 117, 118, 129], hierarchical models [10, 31, 34, 35, 65, 80, 120], non-hierarchical co-Kriging [119].
MTGP	$f_h(x) = \sum_{i=1}^m a_i f_i(x)$ $f_i(x) = \sum_{i=1}^m b_i f_i(x)$	① It treats all fidelities equally, thus neglecting the relative importance of each other. ② Its computational complexity is cubic to the number of training data.	Linear relationships [77, 79, 84, 96–98], nonlinear relationships [121].
Nonlinear hierarchical method	$f_h(x) = g(f_l(x)) + \delta(x)$	① The inference is intractable. ② The number of hyperparameters is significantly larger than the other surrogate modeling methods.	GP [16, 82, 87], NNs [56, 57], others [110].
PINN	$f_h(x) = g(f_l(x)) + \delta(x)$	① It is limited to problems with PDEs. ② The number of hyperparameters is huge.	[13, 36, 64, 75, 76].

303 As discussed in Section 3.8 of our manuscript, the multi-fidelity surrogate modeling techniques can be represented
 304 as:

$$f_h(x) = \rho(x)g(f_l(x)) + \epsilon(x), \quad (1)$$

305 except the single model method. While the format of multi-task Gaussian process (MTGP) shown in Table A4 looks
 306 different from the others, we argue that it can be reformulated as equation (1). In the following paragraphs, we use
 307 the linear model of coregionalization (LMC) [1] as the representative example of MTGP to derive the corresponding
 308 Manuscript submitted to ACM

313 reformulation. Specifically, the equation of MTGP listed in Table A4 can be formulated as linear combinations of
 314 independent random functions:
 315

$$316 \quad \mathbf{f} = \begin{bmatrix} f_1(\mathbf{x}) \\ f_h(\mathbf{x}) \end{bmatrix} = \begin{bmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \end{bmatrix} \begin{bmatrix} f_1(\mathbf{x}) \\ f_2(\mathbf{x}) \end{bmatrix}, \quad (2)$$

317 where $f_1(\mathbf{x})$ and $f_2(\mathbf{x})$ are latent functions. The matrix coefficients $a_{i,j}$ are scalar coefficients, where $i, j \in \{1, 2\}$. Given
 318 a set of training data $X = \{\mathbf{x}^i\}_{i=1}^N$, we can split it into two parts $X = X_l \cup X_h$, where X_l and X_h are used for low- and
 319 high-fidelity evaluations, respectively. Accordingly, the outputs of X are denoted as $\mathbf{y} = \begin{bmatrix} \mathbf{y}_l \\ \mathbf{y}_h \end{bmatrix}$. For a testing input
 320 vector \mathbf{x}^* , the mean and variance of the target $f(\mathbf{x}^*)$ are predicted as:
 321

$$324 \quad \mu_h(\mathbf{x}^*) = (\mathbf{k}_h^f \otimes \mathbf{k}_*^x)^T \Sigma^{-1} \mathbf{y}, \Sigma = K^f \otimes K^x, \quad (3)$$

$$325 \quad \mu_l(\mathbf{x}^*) = (\mathbf{k}_l^f \otimes \mathbf{k}_*^x)^T \Sigma^{-1} \mathbf{y}, \Sigma = K^f \otimes K^x,$$

326 where \otimes is the Kronecker product, and
 327

$$328 \quad K^f = \begin{bmatrix} a_{11}^2 + a_{21}^2 & a_{11}a_{21} + a_{12}a_{21} \\ a_{11}a_{21} + a_{12}a_{21} & a_{21}^2 + a_{22}^2 \end{bmatrix}, \quad (4)$$

$$329 \quad \mathbf{k}_l^f \otimes \mathbf{k}_*^x = \begin{bmatrix} (a_{11}^2 + a_{21}^2) k(\mathbf{x}^*, X_l) \\ (a_{11}a_{21} + a_{12}a_{21}) k(\mathbf{x}^*, X_h) \end{bmatrix}, \quad (5)$$

$$330 \quad \mathbf{k}_h^f \otimes \mathbf{k}_*^x = \begin{bmatrix} (a_{11}a_{21} + a_{12}a_{21}) k(\mathbf{x}^*, X_l) \\ (a_{21}^2 + a_{22}^2) k(\mathbf{x}^*, X_h) \end{bmatrix}.$$

331 Substitute K^f , $\mathbf{k}_l^f \otimes \mathbf{k}_*^x$, and $\mathbf{k}_h^f \otimes \mathbf{k}_*^x$ into equation (3) and equation (4), we has:
 332

$$333 \quad \mu_l(\mathbf{x}^*) = \begin{bmatrix} (a_{11}^2 + a_{21}^2) k(\mathbf{x}^*, X_l) \\ (a_{11}a_{21} + a_{12}a_{21}) k(\mathbf{x}^*, X_h) \end{bmatrix}^T \Sigma^{-1} \mathbf{y}, \quad (6)$$

$$334 \quad \mu_h(\mathbf{x}^*) = \begin{bmatrix} (a_{11}a_{21} + a_{12}a_{21}) k(\mathbf{x}^*, X_l) \\ (a_{21}^2 + a_{22}^2) k(\mathbf{x}^*, X_h) \end{bmatrix}^T \Sigma^{-1} \mathbf{y},$$

$$335 \quad \mu_h(\mathbf{x}^*) = \mu_l(\mathbf{x}^*) \cdot \frac{\begin{bmatrix} (a_{11}a_{21} + a_{12}a_{21}) k(\mathbf{x}^*, X_l) \\ (a_{21}^2 + a_{22}^2) k(\mathbf{x}^*, X_h) \end{bmatrix}^T \Sigma^{-1} \mathbf{y}}{\begin{bmatrix} (a_{11}^2 + a_{21}^2) k(\mathbf{x}^*, X_l) \\ (a_{11}a_{21} + a_{12}a_{21}) k(\mathbf{x}^*, X_h) \end{bmatrix}^T \Sigma^{-1} \mathbf{y}} = \mu_l(\mathbf{x}^*) \cdot p(\mathbf{x}^*), \quad (7)$$

336 where $p(\mathbf{x}^*)$ is a composite function of \mathbf{x}^* . In this case, we can tell that equation (7) is a transformation of equation (1)
 337 with $\epsilon(\mathbf{x}) = 0$.
 338

B.3 Supplementary information of Section 5

Table A5 gives the number of articles categorized into different types of fidelity management strategies. Table A6 provides a summary of the current works on fidelity management strategies, focusing on their basic ideas and relevant disadvantages.

Table A5. Statistics of the number of articles regarding the fidelity management strategies.

METHODS	# OF ARTICLES	METHODS	# OF ARTICLES	METHODS	# OF ARTICLES
Information and cost	32	Improvement and cost	10	Correlation	2
LF first, then HF	18	Uncertainty	10	Periodic	2
Simultaneously use HF and LF	14	Only use HF	8	Curve	1

Table A6. Summary of the current works on fidelity management strategies.

METHODS	DESCRIPTION	DISADVANTAGES	REFERENCES
LF first, then HF	Allocate a fixed amount of computational budget to both LF and HF.	It is static and rigid to vibrate real-world black-box scenarios.	[22, 41, 53, 63, 66–68, 72, 92, 111, 112, 115]
Periodic strategy	Predefine the pattern used to periodically switch between different fidelities.	It is hard to determine an optimal frequency for switching fidelities.	[127]
Uncertainty	Select the fidelity level according to the uncertainty in the LF level.	① It can overly explore the LF when the LF and HF landscapes are significantly different. ② It is hard to define an appropriate uncertainty threshold.	[43]
Correlation estimation	Select the fidelity level according to the correlation between LF and HF.	It is hard to evaluate the correlation between LF and HF.	[11, 32, 61, 105]
Acquisition function	Design acquisition functions using the information gain associated with the evaluation cost as different fidelities.	It has the risk of overly exploit the fidelity with a low cost.	[38, 50, 56, 57, 69, 78, 79, 85, 96, 97, 120, 121]

417 B.4 Supplementary information of Section 8

418 Table A7 provides an overview of open-source software packages used for multi-fidelity optimization. Fig. A3 shows
 419 the temporal statistics of the packages. Further, Fig. A4 shows the proportion of the number of packages regarding
 420 different multi-fidelity optimizers and programming languages.

423 Table A7. Overview of multi-fidelity optimization software packages.
 424

425 REPOSITORY NAME	426 ALGORITHM NAME	427 YEAR	428 PROGRAMMING LANGUAGE	429 OPTIMIZER
MFB	PSO-AFAg [105]	2018	MATLAB	SAEA
TSA-BFEA	TSA-BFEA [106]	2020	MATLAB	SAEA
RoBO	Fabolas [48]	2017	Python	MFBO
dragonfly	BOCA [44]	2017	Python	MFBO
Spearmint	MTBO [96]	2012	Python	MFBO
mf-gp-ucb	MF-GP-UCB [43]	2019	MATLAB	MFBO
DNN-MFBO	DNN-MFBO [57]	2020	Python	MFBO
BMBO-DARN	BMBO-DARN [56]	2021	Python	MFBO
MF-DGP	MF-DGP [89]	2022	Python	MFBO
DyHPO	DyHPO [108]	2022	Python	MFBO
MF-MES	MF-MES [98]	2022	Python	MFBO
rmfbo	rMFBO [77]	2023	Python	MFBO
MFBoom	MFBoom [25]	2023	Python	MFBO
HpBandSter	Hyperband [54]	2017	Python	Bandit
	BOHB [24]	2018	Python	Bandit
	DEHB [2]	2021	Python	Bandit
	SMAC3 [62]	2022	Python	Bandit
darts_asha	ASHA [55]	2020	Python	Bandit
MFES-HB	MFES-HB [59]	2021	Python	Bandit
HyperTune	HyperTune [58]	2022	Python	Bandit
GPTune	GPTuneBand [128]	2022	Python	Bandit
pasha	PASHA [9]	2023	Python	Bandit
optuna	Successive Halving [40]	2019	Python	Bandit
	Hyperband [54]			

467 Continued on next page

468 Manuscript submitted to ACM

Table A7 continued from previous page

PACKAGE	REFERENCE	YEAR	PROGRAMMING LANGUAGE	OPTIMIZER		
mlr3hyperband	Successive Halving [40]	2020	R	Bandit		
	Hyperband [54]					
	Hyperband [54]					
	ASHA [55]					
	BOHB [24]					
syne-tune	DEHB [2]	2022	Python	Bandit		
	HyperTune [58]					
	DyHPO [108]					
	PASHA [9]					
	Hyperband [54]					
open-box	BOHB [24]	2023	Python	Bandit		
	MFES-HB [59]					





Fig. A3. The temporal statistics from 2017 to 2023 regarding the number of open source software packages used in multi-fidelity optimization.



(a) Proportions of multi-fidelity optimizers. (b) Proportions of programming language.

Fig. A4. Pie charts of the proportion of the number of software packages regarding (a) different multi-fidelity optimizers, and (b) programming languages considered in this survey.

B.5 Supplementary information of Section 6

Table A8 provides a comparison of key characteristics of existing benchmark test problems in multi-fidelity optimization. Table A9 provides an overview of multi-fidelity optimization benchmark software packages. Further, we provide lookup tables (Tables A10 to A18) of the mathematical definitions of the benchmark test problems examined in this survey. Additionally, we plot the 2D contours of the fitness landscapes in Figs. A5 to A20 to facilitate a visual understanding of the correlation between low- and high-fidelity levels.

Table A8. Comparison of key characteristics of existing benchmark test problems in MFO.

REFERENCES	SCALABILITY	DISCREPANCY	FIDELITY CORRELATIONS
[20, 52, 90]	✗	Linear	✗
[46, 99, 102]	✗	Linear	✓
[12, 88]	✓	Linear	✗
[105]	✓	Linear	✓
[16]	✗	Linear/Nonlinear	✗
[70]	✓	Linear/Nonlinear	✗

Table A9. Overview of multi-fidelity optimization benchmark software packages.

REPOSITORY NAME	REFERENCE	YEAR	PROGRAMMING LANGUAGE
MFB	[105]	2018	MATLAB
NAS-Bench-101	[116]	2019	Python
NAS-Bench-201	[19]	2020	Python
mf2	[102]	2020	Python
HPOBench	[21]	2021	Python
yahpo_gym	[83]	2022	Python
jahs_bench_201	[8]	2022	Python
mf-prior-bench	[71]	2023	Python
MOMF	[46]	2023	Python

Table A10. Benchmark test problems developed in [99].

PROBLEM NAME	MATHEMATICAL FORMULATION	DECISION SPACE
Branin	$f_h(x_1, x_2) = \left(x_2 - \frac{5.1}{4\pi^2} x_1^2 + \frac{5}{\pi} x_1 - 6 \right)^2 + 10 \left(1 - \frac{1}{8\pi} \right) \cos(x_1) + 10$ $f_l(x_1, x_2) = f_h(x_1, x_2) - (A_1 + 0.5) \left(x_2 - \frac{5.1}{4\pi^2} x_1^2 + \frac{5}{\pi} x_1 - 6 \right)^2, A_1 \in [0, 1]$	$x_1 \in [-5, 10], x_2 \in [0, 15]$
Paciorek	$f_h(x_1, x_2) = \sin\left(\frac{1}{x_1 x_2}\right)$ $f_l(x_1, x_2) = f_h(x_1, x_2) - 9A_2^2 \cos\left(\frac{1}{x_1 x_2}\right), A_2 \in [0, 1]$	$\{x_1, x_2\} \in [0.3, 1.0]$
Hartmann H34	$f_h(x_1, x_2, x_3, x_4) = - \sum_{i=1}^4 \alpha_i \exp\left[- \sum_{j=1}^3 \beta_{ij} (x_j - P_{ij})^2\right]$ $\alpha = \begin{bmatrix} 1 \\ 1.2 \\ 3 \\ 3.2 \end{bmatrix}, \beta = \begin{bmatrix} 3.0 & 10 & 30 \\ 0.1 & 10 & 35 \\ 3.0 & 10 & 30 \\ 0.1 & 10 & 35 \end{bmatrix}, P = \begin{bmatrix} 3689 & 1170 & 2673 \\ 4699 & 4387 & 7470 \\ 1091 & 8732 & 5547 \\ 381 & 5743 & 8828 \end{bmatrix} \times 10^{-4},$ $f_l(x_1, x_2, x_3, x_4) = - \sum_{i=1}^4 \alpha_i \exp\left[- \sum_{j=1}^3 \beta_{ij} \left(x_j - \frac{3}{4} P_{ij} (A_3 + 1) \right)^2\right], A_3 \in [0, 1]$	$\{x_1, \dots, x_4\} \in [0.3, 1.0]$
Trid	$f_h(x_1, \dots, x_{10}) = \sum_{i=1}^{10} (x_i - 1)^2 - \sum_{i=2}^{10} x_i x_{i-1}$ $f_l(x_1, \dots, x_{10}) = \sum_{i=1}^{10} (x_i - A_4)^2 - (A_4 - 0.65) \sum_{i=2}^{10} i x_i x_{i-1}, A_4 \in [0, 1]$	$\{x_1, \dots, x_{10}\} \in [-100, 100]$

Table A11. Benchmark test problems developed in [18].

PROBLEM NAME	MATHEMATICAL FORMULATION	DECISION SPACE
Six-hump camel-back	$f_h(x_1, x_2) = 4x_1^2 - 2.1x_1^4 + \frac{x_1^6}{3} + x_1x_2 - 4x_2^2 + 4x_2^4$ $f_l(x_1, x_2) = f_h(0.7x_1, 0.7x_2) + x_1x_2 - 15$	$\{x_1, x_2\} \in [-2, 2]$
Branin	$f(x_1, x_2) = 10 + \left[x_2 - 5.1 \times \frac{x_1^2}{4\pi^2} + \frac{5x_1}{\pi} - 6 \right] + 10 \cos(x_1) \left[1 - \frac{1}{8\pi} \right]$ $f_h(x_1, x_2) = f(x_1, x_2) - 22.5x_2$ $f_l(x_1, x_2) = f(0.7x_1, 0.7x_2) - 15.75x_2 + 20(0.9 + x_1)^2 - 50$	$x_1 \in [-5, 10], x_2 \in [0, 15]$
Booth	$f_h(x_1, x_2) = (x_1 + 2x_2 - 7)^2 + (2x_1 + x_2 - 5)^2$ $f_l(x_1, x_2) = f_h(0.4x_1, x_2) - 1.7x_1x_2 - x_1 + 2x_2$	$\{x_1, x_2\} \in [-10, 10]$
Bohachevsky	$f_h(x_1, x_2) = x_1^2 + 2x_2^2 - 0.3 \cos(3\pi x_1) - 0.4 \cos(4\pi x_2) + 0.7$ $f_l(x_1, x_2) = f_h(0.7x_1, x_2) + x_1x_2 - 12$	$\{x_1, x_2\} \in [-100, 100]$
Himmelblau	$f_h(x_1, x_2) = (x_1^2 + x_2 - 11)^2 + (x_2^2 + x_1 - 7)^2$ $f_l(x_1, x_2) = f_h(0.5x_1, 0.8x_2) + x_2^3 - (x_1 + 1)^2$	$\{x_1, x_2\} \in [-3, 3]$

677

678

679

680

681

682

683

684

685

686

687

688

689

690

691

692

693

694

695

696

697

698

699

700

701

702

703

704

705

706

707

708

709

710

711

712

713

714

715

716

717

718

719

720

721

722

723

724

725

726

727

728

Table A12. Benchmark test problems developed in [52].

PROBLEM NAME	MATHEMATICAL FORMULATION	DECISION SPACE
Forrester	$f_h(x) = (6x - 2)^2 \sin(12x - 4)$ $f_l(x) = 0.5f_h(x) + 10(x - 0.5) - 5$	$x \in [0, 1]$
Branin	$f(x_1, x_2) = 10 + \left[x_2 - 5.1 \times \frac{x_1^2}{4\pi^2} + \frac{5x_1}{\pi} - 6 \right] + 10 \cos(x_1) \left[1 - \frac{1}{8\pi} \right]$ $f_h(x_1, x_2) = f(x_1, x_2) - 22.5x_2$ $f_l(x_1, x_2) = f(0.7x_1, 0.7x_2) - 15.75x_2 + 20(0.9 + x_1)^2 - 50$	$x_1 \in [-5, 10],$ $x_2 \in [0, 15]$
Booth	$f_h(x_1, x_2) = (x_1 + 2x_2 - 7)^2 + (2x_1 + x_2 - 5)^2$ $f_l(x_1, x_2) = f_h(0.4x_1, x_2) - 1.7x_1x_2 - x_1 + 2x_2$	$\{x_1, x_2\} \in [-10, 10]$
Six-hump camel-back	$f_h(x_1, x_2) = 4x_1^2 - 2.1x_1^4 + \frac{x_1^6}{3} + x_1x_2 - 4x_2^2 + 4x_2^4,$ $f_l(x_1, x_2) = f_h(0.7x_1, 0.7x_2) + x_1x_2 - 15$	$\{x_1, x_2\} \in [-2, 2]$
3D Rosenbrock	$f_h(x_1, x_2, x_3) = \sum_{i=1}^2 \left[100 \left(x_i^2 - x_{i+1} \right)^2 + (x_i - 1)^2 \right]$ $f_l(x_1, x_2, x_3) = 90 \left(x_1^2 - x_2 \right)^2 + 1.1 (x_3 - 1)^2$ $+ 100 \left(x_2^2 - x_3 \right)^2 + (x_2 - 1)^2$	$\{x_1, x_2, x_3\} \in [-2.048, 2.048]$
Colville-Himmelblay	$f_h(x_1, x_2, x_3, x_4) = 100 \left(x_2 - x_1^2 \right)^2 + (1 - x_1)^2$ $+ 90 \left(x_4 - x_3^2 \right)^2 + (1 - x_3)^2$ $+ 10.1 \left((x_2 - 1)^2 + (x_4 - 1)^2 \right)$ $+ 19.8 (x_2 - 1)(x_4 - 1)$ $f_l(x_1, x_2, x_3, x_4) = f_h(x_1, x_2, x_3, x_4)$ $+ 0.1 (1 - x_1)^2 + 0.1 (1 - x_3)^2$ $- 0.1 \left((x_2 - 1)^2 + (x_4 - 1)^2 \right)$ $+ 0.2 (x_2 - 1)(x_4 - 1)$	$\{x_1, \dots, x_4\} \in [-10, 10]$
Hessen	$f_h(x_1, \dots, x_6) = 25(x_1 - 2)^2 + (x_2 - 2)^2 + (x_3 - 1)^2$ $+ (x_4 - 4)^2 + (x_5 - 1)^2 + (x_6 - 4)^2$ $f_l(x_1, \dots, x_6) = 0.6f_h(x_1, \dots, x_6) + 0.25(x_2 - 2)^2 + 0.75(x_4 - 4)^2$	$\{x_1, \dots, x_6\} \in [0, 10]$
Borehole	$f_h(x_1, \dots, x_8) = \frac{2\pi x_3 (x_4 - x_6)}{\ln(x_2/x_1) \left[1 + 2x_7x_4/\ln(x_2/x_1) x_1^2 x_8 + x_3/x_5 \right]}$ $f_l(x_1, \dots, x_8) = 0.4f_h(x_1, \dots, x_8) + 0.07x_1^2 x_8$ $+ x_1 x_7/x_3 + x_2 x_6/x_2 + x_1^2 x_4$	$x_1 \in [0.05, 0.15],$ $x_2 \in [100, 50000],$ $x_3 \in [63070, 115600],$ $x_4 \in [990, 1110],$ $x_5 \in [63.1, 116],$ $x_6 \in [700, 820],$ $x_7 \in [1120, 1680],$ $x_8 \in [9855, 12045]$

Table A13. Benchmark test problems developed in [90].

PROBLEM NAME	MATHEMATICAL FORMULATION	DECISION SPACE
SK	$f_h(x) = x^4 + 3x^3 - 10x^2 - 10x - 10$ $f_l(x) = f_h(x) + 0.5x^4 + 2x^3 + 10x^2 + 10x + 5$	$x \in [-6, 4.5]$
SSFYY2	$f_h(x) = 10 + x^2 - 10 \cos\left(\frac{x\pi}{2}\right)$ $f_l(x) = f_h(x) - (x - 4)^2$	$x \in [-16, 8]$
MLF1	$f_h(x) = (1 + x/20) \sin(x)$ $f_l(x) = f_h(x) - \left(1 + \frac{x}{20}\right) \cos(x)$	$x \in [0, 20]$
Far1	$f_h(x_1, x_2) = -2e^{\left(15(-(x_1-0.1)^2-x_2^2)\right)} - e^{\left(20(-(x_1-0.6)^2-(x_2-0.6)^2)\right)}$ $+ e^{\left(20(-(x_1+0.6)^2-(x_2-0.6)^2)\right)} + e^{\left(20(-(x_1-0.6)^2-(x_2+0.6)^2)\right)}$ $+ e^{\left(20(-(x_1+0.6)^2-(x_2+0.6)^2)\right)}$ $f_l(x_1, x_2) = f_h(x_1, x_2) - 2e^{\left(20(-(x_1+0.1)^2-(x_2-0.3)^2)\right)}$ $- e^{\left(20(-(x_1-0.4)^2-(x_2-0.6)^2)\right)} + e^{\left(20(-(x_1+0.5)^2-(x_2-0.7)^2)\right)}$ $+ e^{\left(20(-(x_1-0.5)^2-(x_2+0.7)^2)\right)} - e^{\left(20(-(x_1+0.4)^2-(x_2+0.8)^2)\right)}$	$\{x_1, x_2\} \in [-0.4, 1.2]$

Table A14. Benchmark test problems developed in [88].

PROBLEM NAME	MATHEMATICAL FORMULATION	DECISION SPACE
Rosenbrock	$f_h(\mathbf{x}) = \sum_{i=1}^{D-1} (1 - x_i)^2 + 100 (x_{i+1} - x_i^2)^2$ $f_l(\mathbf{x}) = \frac{f_h(\mathbf{x}) - 4.0 - \sum_{i=1}^D 0.5x_i}{10.0 + \sum_{i=1}^D 0.25x_i}$	$\mathbf{x} \in [-2, 2]$
exponential-sine	$f_h(\mathbf{x}) = \frac{1}{D} \sum_{i=1}^D \exp(-0.1x_i) \sin\left(\frac{\pi}{2}x_i\right)$ $f_l(\mathbf{x}) = \frac{1}{D} \sum_{i=1}^D \sin\left(\frac{\pi}{2}x_i\right)$	$\mathbf{x} \in [-2, 2]$
Heterogeneous-1	$f_h(x) = \sin[30(x - 0.9)^4] \cos[2(x - 0.9)] + (x - 0.9)/2$ $f_l(x) = \frac{f_h(x) - 1.0 + x}{1.0 + 0.25x}$	$x \in [0, 1]$
Heterogeneous-2	$f_h(x_1, x_2) = \sin[21(x_1 - 0.9)^4] \cos[2(x_1 - 0.9)] + (x_1 - 0.7)/2 + 2x_2^2 \sin(x_1 x_2)$ $f_l(x_1, x_2) = \frac{f_h(x_1, x_2) - 2.0 + x_1 + x_2}{5.0 + 0.25x_1 + 0.5x_2}$	$\{x_1, x_2\} \in [0, 1]$
Heterogeneous-3	$f_h(x_1, x_2, x_3) = \sin[21(x_1 - 0.9)^4] \cos[2(x_1 - 0.9)] + (x_1 - 0.7)/2 + 2x_2^2 \sin(x_1 x_2) + 3x_3^3 \sin(x_1 x_2 x_3)$ $f_l(x_1, x_2, x_3) = \frac{f_h(x_1, x_2, x_3) - 2.0 + x_1 + x_2 + x_3}{5.0 + 0.25x_1 + 0.5x_2 - 0.75x_3}$	$\{x_1, x_2, x_3\} \in [0, 1]$

Table A15. Benchmark test problems developed in [12].

PROBLEM NAME	MATHEMATICAL FORMULATION	DECISION SPACE
Rosenbrock	$f_h(x_1, x_2) = (1 - x_1)^2 + 100 (x_2 - x_1^2)^2$ $f_l(\mathbf{x}) = \frac{f_h(\mathbf{x}) - 4.0 - \sum_{i=1}^2 0.5x_i}{3.0 + \sum_{i=1}^2 0.25x_i}$	$\{x_1, x_2\} \in [-2, 2]$
Runge	$f_h(x_1, x_2, x_3) = \frac{1}{1 + x_1^2 + x_2^2 + x_3^2}$ $f_l(\mathbf{x}) = \frac{f_h(\mathbf{x}) - 4.0 - \sum_{i=1}^3 0.5x_i}{3.0 + \sum_{i=1}^3 0.25x_i}$	$\{x_1, x_2, x_3\} \in [-2, 2]$

Table A16. Benchmark test problems developed in [102].

PROBLEM NAME	MATHEMATICAL FORMULATION	DECISION SPACE
PARK-1	$f_h(\mathbf{x}) = \frac{x_1}{2} \left[\sqrt{1 + (x_2 + x_3^2) \frac{x_4}{x_1^2}} - 1 \right] + (x_1 + 3x_4) \exp [1 + \sin (x_3)]$ $f_l(\mathbf{x}) = \left[1 + \frac{\sin (x_1)}{10} \right] f_h(\mathbf{x}) - 2x_1 + x_2^2 + x_3^2 + 0.5$	$\{x_1, x_2, x_3, x_4\} \in [0, 1]$
PARK-2	$f_h(\mathbf{x}) = \frac{2}{3} \exp (x_1 + x_2) - x_4 \sin (x_3) + x_3$ $f_l(\mathbf{x}) = 1.2f_h(\mathbf{x}) - 1$	$\{x_1, x_2, x_3\} \in [-2, 2]$
Paciorek with noise	$f_h(\mathbf{x}) = \sin \left(\prod_{i=1}^D x_i \right)^{-1} + N(0, \alpha_1)$ $f_l(\mathbf{x}) = f_h(\mathbf{x}) - 9A^2 \cos \left(\prod_{i=1}^D x_i \right)^{-1} + N(0, \alpha_2), A \in [0, 1]$	$\mathbf{x} \in [0.3, 1.0]^D$

885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936

Table A17. Benchmark test problems developed in [70].

PROBLEM NAME	MATHEMATICAL FORMULATION	DECISION SPACE
Forrester	$f_h(x) = (6x - 2)^2 \sin(12x - 4)$ $f_l(x) = (5.5x - 2.5)^2 \sin(12x - 4)$ $f_l(x) = 0.75f_h(x) + 5(x - 0.5) - 2$ $f_l(x) = 0.5f_h(x) + 10(x - 0.5) - 5$	$x \in [0, 1]$
discontinuous Forrester	$f_h(x) = \begin{cases} (6x - 2)^2 \sin(12x - 4), & 0 \leq x \leq 0.5 \\ (6x - 2)^2 \sin(12x - 4) + 10, & 0.5 < x \leq 1 \end{cases}$ $f_l(x) = \begin{cases} 0.5f_h(x) + 10(x - 0.5) - 5, & 0 \leq x \leq 0.5 \\ 0.5f_h(x) + 10(x - 0.5) - 2, & 0.5 < x \leq 1 \end{cases}$	$x \in [0, 1]$
Rosenbrock	$f_h(\mathbf{x}) = \sum_{i=1}^{D-1} 100 (x_{i+1} - x_i^2)^2 + (1 - x_i)^2$ $f_l(\mathbf{x}) = \sum_{i=1}^{D-1} 50 (x_{i+1} - x_i^2)^2 + (-2 - x_i)^2 - \sum_{i=1}^D 0.5x_i$ $f_t(\mathbf{x}) = \frac{f_h(\mathbf{x}) - 4 - \sum_{i=1}^D 0.5x_i}{10 + \sum_{i=1}^D 0.25x_1}$	$\mathbf{x} \in [-2, 2]$
Shifted-rotated Rastrigin	$f_h(\mathbf{z}) = \sum_{i=1}^D (z_i^2 + 1 - \cos(10\pi z_i))$ $\mathbf{z} = R(\theta)(\mathbf{x} - \mathbf{x}^\star), R(\theta) = \begin{bmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{bmatrix},$ $f_l(\mathbf{z}) = f_l(\mathbf{z}, \phi_i) = f_h(\mathbf{z}) + e_r(\mathbf{z}, \phi_i), i = 1, 2, 3$ $e_r(\mathbf{z}, \phi) = \sum_{i=1}^D a(\phi) \cos^2(w(\phi)z_i + b(\phi) + \pi)$ $a(\phi) = \Theta(\phi), w(\phi) = 10\pi\Theta(\phi),$ $b(\phi) = 0.5\pi\Theta(\phi), \Theta(\phi) = 1 - 0.0001\phi$ $\phi_1 = 10000, \phi_2 = 5000, \phi_3 = 2500$	$\mathbf{x} \in [-0.1, 0.2]$


Table A18. Benchmark test problems developed in [16].

NAME	PROBLEM	PARAMETER DOMAINS
Linear-A	$f_h(x) = (6x - 2)^2 \sin(12x - 4)$ $f_l(x) = \frac{1}{2}f_h(x) + 10\left(x - \frac{1}{2}\right) + 5$	$x \in [0, 1]$
Linear-B	$f_h(x) = 5x^2 \sin(12x)$ $f_l(x) = 2f_h(x) + \left(x^3 - \frac{1}{2}\right) \sin\left(3x - \frac{1}{2}\right) + 4 \cos(2x)$	$x \in [0, 1]$
NonLinear-A	$f_h(x) = (x - \sqrt{2})(f_h(x))^2$ $f_l(x) = \sin(8\pi x)$	$x \in [0, 1]$
NonLinear-B	$f_h(x) = xe^{f_l(2x-.2)} - 1$ $f_l(x) = \cos(15x)$	$x \in [0, 1]$

989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040

1041 B.6 Visualization benchmarks in Section 6

- 1042 Fig. A5 to Fig. A8 show the four multi-fidelity problems in [99].
- 1043 Fig. A9 to Fig. A13 show the five two-dimensional multi-fidelity problems in [18].
- 1044 Fig. A14 shows the two-dimensional multi-fidelity problem in [90].
- 1045 Fig. A15 to Fig. A17 show the three two-dimensional multi-fidelity problems in [88].
- 1046 Fig. A18 shows the two-dimensional multi-fidelity problem in [12].
- 1047 Fig. A19 shows the two-dimensional multi-fidelity problem in [70].
- 1048 Fig. A20 shows the one-dimensional multi-fidelity problems in [16, 52, 88, 90].



1079 Fig. A5. With Branin representing the HF problem, the following are presented: (a) and (b) show the fitness landscape of HF and LF
 1080 problems, respectively, with $A = 0.25$ for the LF problem; (c) and (d) show the Spearman correlation and RMSE between HF and LF
 1081 problems, respectively.




Fig. A6. With Paciorek representing the HF problem, the following are presented: (a) and (b) show the fitness landscape of HF and LF problems, respectively, with $A = 0.25$ for the LF problem; (c) and (d) show the Spearman correlation and RMSE between HF and LF problems, respectively.




Fig. A7. With Hartmann3 representing the HF problem, the following are presented: (a) and (b) show the Spearman correlation and RMSE between HF and LF problems, respectively.




Fig. A8. With Trid representing the HF problem, the following are presented: (a) and (b) show the Spearman correlation and RMSE between HF and LF problems, respectively.






Fig. A9. With Six hump camel-back representing the HF problem, the following are presented: (a) and (b) show the fitness landscape of HF and LF problems, respectively.






Fig. A12. With Bohachevsky representing the HF problem, the following are presented: (a) and (b) show the fitness landscape of HF and LF problems, respectively.








Fig. A13. With Himmelblau representing the HF problem, the following are presented: (a) and (b) show the fitness landscape of HF and LF problems, respectively.





1368 Fig. A16. With exponential-sine representing the HF problem, the following are presented: (a) and (b) show the fitness landscape of
1369 HF and LF problems, respectively.



1386 Fig. A17. With Heterogeneous-2 representing the HF problem, the following are presented: (a) and (b) show the fitness landscape of
1387 HF and LF problems, respectively.




Fig. A18. With Rosenbrock representing the HF problem, the following are presented: (a) and (b) show the fitness landscape of HF and LF problems, respectively.




Fig. A19. With Rosenbrock representing the HF problem, the following are presented: (a), (b), and (c) show the fitness landscape of HF and two LF problems, respectively.




Fig. A20. This figure shows the HF and LF functions for one-dimensional benchmarks.

1509 REFERENCES

- 1510 [1] Mauricio A. Álvarez, Lorenzo Rosasco, and Neil D. Lawrence. 2012. Kernels for Vector-Valued Functions: A Review. *Found. Trends Mach. Learn.* 4, 3
 1511 (2012), 195–266.
- 1512 [2] Noor H. Awad, Neeratyoy Mallik, and Frank Hutter. 2021. DEHB: Evolutionary Hyperband for Scalable, Robust and Efficient Hyperparameter
 1513 Optimization. In *IJCAI'21: Proc. of the Thirtieth International Joint Conference on Artificial Intelligence*. ijcai.org, 2147–2153.
- 1514 [3] Mohamed H Bakr, John W Bandler, Natalia Georgieva, and Kaj Madsen. 1999. A hybrid aggressive space-mapping algorithm for EM optimization.
 1515 *IEEE Trans. Microw. Theory Tech.* 47, 12 (1999), 2440–2449.
- 1516 [4] Mohamed H. Bakr, John W. Bandler, Mostafa A. Ismail, José Ernesto Rayas-Sánchez, and Q. j. Zhang. 2000. Neural space mapping EM optimization
 1517 of microwave structures. *2000 IEEE MTT-S International Microwave Symposium Digest* 2 (2000), 879–882 vol.2.
- 1518 [5] John W Bandler, Radoslaw M Biernacki, Shao Hua Chen, Piotr A Grobelny, and Ronald H Hemmers. 1994. Space mapping technique for
 1519 electromagnetic optimization. *IEEE Trans. Microw. Theory Tech.* 42, 12 (1994), 2536–2544.
- 1520 [6] John W Bandler, Radoslaw M Biernacki, Shao Hua Chen, Piotr A Grobelny, Ronald H Hemmers, and Kaj Madsen. 1995. Electromagnetic optimization
 1521 exploiting aggressive space mapping. *IEEE Trans. Microw. Theory Tech.* 43, 12 (1995), 2874–2882.
- 1522 [7] John W Bandler, Radoslaw M Biernacki, Shao Hua Chen, Piotr A Grobelny, Ronald H Hemmers, and Kaj Madsen. 1998. A trust region aggressive
 1523 space mapping algorithm for EM optimization. *IEEE Trans. Microw. Theory Tech.* 46, 12 (1998), 2412–2425.
- 1524 [8] Archit Bansal, Danny Stoll, Maciej Janowski, Arber Zela, and Frank Hutter. 2022. JAHS-Bench-201: A Foundation For Research On Joint Architecture
 1525 And Hyperparameter Search. In *NeurIPS'22: Proc. of 35th Annual Conference on Neural Information Processing Systems 2022*.
- 1526 [9] Ondrej Bohdal, Lukas Balles, Martin Wistuba, Beyza Ermis, Cédric Archambeau, and Giovanni Zappella. 2023. PASHA: Efficient HPO and NAS
 1527 with Progressive Resource Allocation. In *ICLR'23: Proc. of The Eleventh International Conference on Learning Representations*. OpenReview.net.
- 1528 [10] L Bonfiglio, P Perdikaris, S Brizzolara, and GE Karniadakis. 2018. Multi-fidelity optimization of super-cavitating hydrofoils. *Comput. Methods Appl.
 1529 Mech. Eng.* 332 (2018), 63–85.
- 1530 [11] Jürgen Branke, Md. Asafuddoula, Kalyan Shankar Bhattacharjee, and Tapabrata Ray. 2017. Efficient Use of Partially Converged Simulations in
 1531 Evolutionary Optimization. *IEEE Trans. Evol. Comput.* 21, 1 (2017), 52–64.
- 1532 [12] Dean E. Bryson and Markus P. Rumpfkeil. 2016. Variable-fidelity surrogate modeling of lambda wing transonic aerodynamic performance. In *Proc.
 1533 of the 54th AIAA Aerospace Sciences Meeting*. AIAA, 0294.
- 1534 [13] Souvik Chakraborty. 2021. Transfer learning based multi-fidelity physics informed deep neural network. *J. Comput. Phys.* 426 (2021), 109942.
- 1535 [14] Kwan J. Chang, Raphael T. Haftka, Gary L. Giles, and Pi-Jen Kao. 1993. Sensitivity-based scaling for approximating structural response. *J. Aircr.* 30,
 1536 2 (1993), 283–288.
- 1537 [15] Stella M. Clarke, Jan H. Griebsch, and Timothy W. Simpson. 2003. Analysis of Support Vector Regression for Approximation of Complex Engineering
 1538 Analyses. In *IDETC-CIE'23: International Design Engineering Technical Conferences and Computers and Information in Engineering Conference*, Vol. 37009. 535–543.
- 1539 [16] Kurt Cutajar, Mark Pullin, Andreas C. Damianou, Neil D. Lawrence, and Javier González. 2019. Deep Gaussian Processes for Multi-fidelity Modeling.
 1540 *CoRR* abs/1903.07320 (2019). arXiv:1903.07320
- 1541 [17] Fei Ding and Ahsan Kareem. 2018. A multi-fidelity shape optimization via surrogate modeling for civil structures. *J. Wind Eng. Ind. Aerodyn.* 178
 1542 (2018), 49–56.
- 1543 [18] Huachao Dong, Baowei Song, Peng Wang, and Shuai Huang. 2015. Multi-fidelity information fusion based on prediction of kriging. *Struct.
 1544 Multidisc. Optim.* 51 (2015), 1267–1280.
- 1545 [19] Xuanyi Dong and Yi Yang. 2020. NAS-Bench-201: Extending the Scope of Reproducible Neural Architecture Search. In *ICLR'20: Proc. of the 8th
 1546 International Conference on Learning Representations*. OpenReview.net.
- 1547 [20] Cédric Durantin, Justin Rouxel, Jean-Antoine Désidéri, and Alain Glière. 2017. Multifidelity surrogate modeling based on radial basis functions.
 1548 *Struct. Multidiscip. Optim.* 56, 5 (2017), 1061–1075.
- 1549 [21] Katharina Eggensperger, Philipp Müller, Neeratyoy Mallik, Matthias Feurer, René Sass, Aaron Klein, Noor H. Awad, Marius Lindauer, and Frank
 1550 Hutter. 2021. HPOBench: A Collection of Reproducible Multi-Fidelity Benchmark Problems for HPO. In *NeurIPS'21: Proc. of the Annual Conference
 1551 on Neural Information Processing Systems 2021*.
- 1552 [22] Mohammed A. El-Beltagy and Andy J. Keane. 1999. A Comparison of Various Optimization Algorithms on a Multilevel Problem. *Eng. Appl. Artif.
 1553 Intell.* 12, 5 (1999), 639–654.
- 1554 [23] Michael Eldred, Anthony Giunta, and S. Collis. 2004. Second-order corrections for surrogate-based optimization with model hierarchies. In *Proc. of
 1555 the 10th AIAA/ISSMO Multidisciplinary Analysis and Optimization Conference*. 4457.
- 1556 [24] Stefan Falkner, Aaron Klein, and Frank Hutter. 2018. BOHB: Robust and Efficient Hyperparameter Optimization at Scale. In *ICML'18: Proc. of the
 1557 35th International Conference on Machine Learning (Proceedings of Machine Learning Research, Vol. 80)*. PMLR, 1436–1445.
- 1558 [25] Jose Pablo Folch, Robert M. Lee, Behrang Shafei, David Walz, Calvin Tsay, Mark van der Wilk, and Ruth Misener. 2023. Combining multi-fidelity
 1559 modelling and asynchronous batch Bayesian Optimization. *Comput. Chem. Eng.* 172 (2023), 108194.
- 1560 [26] Alexander I. J. Forrester, András Sóbester, and Andy J. Keane. 2007. Multi-fidelity optimization via surrogate modelling. *Proc. Math. Phys. Eng. Sci.
 1561 ROY SOC A-MATH PHY* 463, 2088 (2007), 3251–3269.

- 1561 [27] Shawn Gano, Victor Perez, John Renaud, Stephen Batill, and Brian Sanders. 2004. Multilevel variable fidelity optimization of a morphing unmanned
1562 aerial vehicle. In *Proc. of the 45th AIAA/ASCE/ASCE/AHS/ASC Structures, Structural Dynamics & Materials Conference*. 1763.
- 1563 [28] Shawn E. Gano, John E. Renaud, Jay D. Martin, and Timothy W. Simpson. 2006. Update strategies for Kriging models used in variable fidelity
1564 optimization. *Struct. Multidiscip. Optim.* 32, 4 (2006), 287–298.
- 1565 [29] Shawn E. Gano, John E. Renaud, and Brian Sanders. 2005. Hybrid variable fidelity optimization by using a Kriging-based scaling function. *AIAA J.*
1566 43, 11 (2005), 2422–2433.
- 1567 [30] Anthony A Giunta, Vladimir Balabanov, Matthew Kaufman, Susan Burgee, Bernard Grossman, Raphael T Haftka, William H Mason, and Layne T
1568 Watson. 1997. Variable-complexity response surface design of an HSCT configuration. *Multidisciplinary Design Optimization, Alexandrov NM and*
1569 *Hussaini MY eds* (1997), 53–69.
- 1570 [31] Loic Le Gratiet. 2014. Recursive co-Kriging model for design of computer experiments with multiple levels of fidelity. *Int. J. Uncertain. Quantif.* 4, 5
1571 (2014).
- 1572 [32] Ahsanal Habib, Hemant K Singh, and Tapabrata Ray. 2019. A multiple surrogate assisted multi/many-objective multi-fidelity evolutionary
1573 algorithm. *Inf. Sci.* 502 (2019), 537–557.
- 1574 [33] Raphael T. Haftka. 1991. Combining global and local approximations. *AIAA J.* 29, 9 (1991), 1523–1525.
- 1575 [34] Zhonghua Han, Chenzhou Xu, Zhang Liang, Zhang Yu, Keshi Zhang, and Wenping Song. 2020. Efficient aerodynamic shape optimization using
1576 variable-fidelity surrogate models and multilevel computational grids. *Chinese J. Aeronaut.* 33, 1 (2020), 31–47.
- 1577 [35] Zhong-Hua Han, Ralf Zimmermann, and Stefan Görtz. 2012. Alternative co-Kriging method for variable-fidelity surrogate modeling. *AIAA J.* 50, 5
1578 (2012), 1205–1210.
- 1579 [36] Kohei Harada, Dushhyanth Rajaram, and Dimitri N. Mavris. 2022. Application of Multi-Fidelity Physics-Informed Neural Network on Transonic
1580 Airfoil using Wind Tunnel Measurements. *AIAA SCITECH 2022 Forum* (2022).
- 1581 [37] Kurt Hornik, Maxwell B. Stinchcombe, and Halbert White. 1989. Multilayer feedforward networks are universal approximators. *Neural Netw.* 2, 5
1582 (1989), 359–366.
- 1583 [38] Deng Huang, Theodore T. Allen, William I. Notz, and R. Allen Miller. 2006. Sequential kriging optimization using multiple-fidelity evaluations.
1584 *Struct. Multidiscip. Optim.* 32 (2006), 369–382.
- 1585 [39] Likeng Huang, Zhenghong Gao, and Dehu Zhang. 2013. Research on multi-fidelity aerodynamic optimization methods. *Chinese J. Aeronaut.* 26, 2
1586 (2013), 279–286.
- 1587 [40] Kevin G. Jamieson and Ameet Talwalkar. 2016. Non-stochastic Best Arm Identification and Hyperparameter Optimization. In *AISTATS’16: Proc. of*
1588 *the 19th International Conference on Artificial Intelligence and Statistics*, Vol. 51. 240–248.
- 1589 [41] Puyu Jiang, Qi Zhou, Jun Liu, and Yuansheng Cheng. 2019. A Three-Stage Surrogate Model Assisted Multi-Objective Genetic Algorithm for
1590 Computationally Expensive Problems. In *IEEE Congress on Evolutionary Computation, CEC 2019, Wellington, New Zealand, June 10–13, 2019*. IEEE,
1591 1680–1687.
- 1592 [42] Ioannis C. Kampolis, A. S. Zymaris, V. G. Asouti, and Kyriakos C. Giannakoglou. 2007. Multilevel optimization strategies based on metamodel-
1593 assisted evolutionary algorithms, for computationally expensive problems. In *CEC’07: Proc. of the IEEE Congress on Evolutionary Computation*.
1594 IEEE, 4116–4123.
- 1595 [43] Kirthevasan Kandasamy, Gautam Dasarathy, Junier B. Oliva, Jeff G. Schneider, and Barnabás Póczos. 2019. Multi-Fidelity Gaussian Process Bandit
1596 Optimisation. *J. Artif. Intell. Res.* 66 (2019), 151–196.
- 1597 [44] Kirthevasan Kandasamy, Gautam Dasarathy, Jeff G. Schneider, and Barnabás Póczos. 2017. Multi-fidelity Bayesian Optimisation with Continuous
1598 Approximations. In *ICML’17: Proc. of the 34th International Conference on Machine Learning*, Vol. 70. PMLR, 1799–1808.
- 1599 [45] MC Kennedy and A O’Hagan. 2000. Predicting the Output from a Complex Computer Code When Fast Approximations are Available. *Biometrika*
1600 87, 1 (2000), 1–13.
- 1601 [46] Angus Kenny, Tapabrata Ray, Hemant Kumar Singh, and Xiaodong Li. 2023. A Test Suite for Multi-objective Multi-fidelity Optimization. In
1602 *EMO’23: Proc. of the 12th International Conference on Evolutionary Multi-Criterion Optimization*. Springer, 361–373.
- 1603 [47] Hong Seok Kim, Muammer Koc, and Jun Ni. 2007. A hybrid multi-fidelity approach to the optimal design of warm forming processes using a
1604 knowledge-based artificial neural network. *Int. J. Mach. Tools Manuf.* 47, 2 (2007), 211–222.
- 1605 [48] Aaron Klein, Stefan Falkner, Simon Bartels, Philipp Hennig, and Frank Hutter. 2017. Fast Bayesian Optimization of Machine Learning Hyperpa-
1606 rameters on Large Datasets. In *AISTATS’17: Proc. of the 20th International Conference on Artificial Intelligence and Statistics (Proceedings of Machine*
1607 *Learning Research*, Vol. 54). PMLR, 528–536.
- 1608 [49] Duane L Knill, Anthony A Giunta, Chuck A Baker, Bernard Grossman, William H Mason, Raphael T Haftka, and Layne T Watson. 1999. Response
1609 surface models combining linear and Euler aerodynamics for supersonic transport design. *J. Aircr.* 36, 1 (1999), 75–86.
- 1610 [50] Eric Hans Lee, Valerio Perrone, Cédric Archambeau, and Matthias W. Seeger. 2020. Cost-aware Bayesian Optimization. *CoRR* abs/2003.10870
1611 (2020). arXiv:2003.10870
- 1612 [51] Robert Lewis and Stephen Nash. 2000. A multigrid approach to the optimization of systems governed by differential equations. In *Proc. of the 8th*
1613 *Symposium on Multidisciplinary Analysis and Optimization*. 4890.
- 1614 [52] Chengshan Li, Peng Wang, and Huachao Dong. 2018. Kriging-based multi-fidelity optimization via information fusion with uncertainty. *J. Mech.*
1615 *Sci. Technol.* 32, 1 (2018), 245–259.

- [53] Hui Li, Zhiguo Huang, Xiao Liu, Chenbo Zeng, and Peng Zou. 2020. Multi-fidelity meta-optimization for nature inspired optimization algorithms. *Appl. Soft Comput.* 96 (2020), 106619.
- [54] Lisha Li, Kevin G. Jamieson, Giulia DeSalvo, Afshin Rostamizadeh, and Ameet Talwalkar. 2017. Hyperband: A Novel Bandit-Based Approach to Hyperparameter Optimization. *J. Mach. Learn. Res.* 18 (2017), 185:1–185:52.
- [55] Liam Li, Kevin G. Jamieson, Afshin Rostamizadeh, Ekaterina Gonina, Jonathan Ben-tzur, Moritz Hardt, Benjamin Recht, and Ameet Talwalkar. 2020. A System for Massively Parallel Hyperparameter Tuning. In *MLSys'20: Proc. of Machine Learning and Systems 2020*. mlsys.org.
- [56] Shibo Li, Robert M. Kirby, and Shandian Zhe. 2021. Batch Multi-Fidelity Bayesian Optimization with Deep Auto-Regressive Networks. In *NeurIPS'21: Proc. of the Annual Conference on Neural Information Processing Systems 2021*. 25463–25475.
- [57] Shibo Li, Wei Xing, Robert M. Kirby, and Shandian Zhe. 2020. Multi-Fidelity Bayesian Optimization via Deep Neural Networks. In *NeurIPS'20: Proc. of the Annual Conference on Neural Information Processing Systems 2020*.
- [58] Yang Li, Yu Shen, Huajun Jiang, Wentao Zhang, Jixiang Li, Ji Liu, Ce Zhang, and Bin Cui. 2022. Hyper-Tune: Towards Efficient Hyper-parameter Tuning at Scale. *Proc. VLDB Endow.* 15, 6 (2022), 1256–1265.
- [59] Yang Li, Yu Shen, Jiawei Jiang, Jinyang Gao, Ce Zhang, and Bin Cui. 2021. MFES-HB: Efficient Hyperband with Multi-Fidelity Quality Measurements. In *AAAI'21: Proc. of the AAAI Conference on Artificial Intelligence*. AAAI Press, 8491–8500.
- [60] Zengcong Li, Kuo Tian, Hongqing Li, Yunfeng Shi, and Bo Wang. 2021. A Competitive Variable-Fidelity Surrogate-Assisted CMA-ES Algorithm Using Data Mining Techniques. *Aerosp. Sci. Technol.* 119 (2021), 107084.
- [61] Dudy Lim, Yew-Soon Ong, Yaochu Jin, and Bernhard Sendhoff. 2008. Evolutionary Optimization with Dynamic Fidelity Computational Models. In *ICIC'08: Proc. of the 4th International Conference on Intelligent Computing (Lecture Notes in Computer Science, Vol. 5227)*. Springer, 235–242.
- [62] Marius Lindauer, Katharina Eggensperger, Matthias Feurer, André Biedenkapp, Difan Deng, Carolin Benjamins, Tim Ruhkopf, René Sass, and Frank Hutter. 2022. SMAC3: A Versatile Bayesian Optimization Package for Hyperparameter Optimization. *J. Mach. Learn. Res.* 23 (2022), 54:1–54:9. <http://jmlr.org/papers/v23/21-0888.html>
- [63] Bo Liu, Slawomir Koziel, and Qingfu Zhang. 2016. A Multi-fidelity Surrogate-Model-Assisted Evolutionary Algorithm for Computationally Expensive Optimization Problems. *J. Comput. Sci.* 12 (2016), 28–37.
- [64] Dehao Liu and Yan Wang. 2019. Multi-fidelity physics-constrained neural network and its application in materials modeling. *J. Mech. Des.* 141, 12 (2019), 121403.
- [65] Fei Liu, Zhong-Hua Han, Yang Zhang, Ke Song, Wen-Ping Song, Feng Gui, and Ji-Bin Tang. 2019. Surrogate-based aerodynamic shape optimization of hypersonic flows considering transonic performance. *Aerosp. Sci. Technol.* 93 (2019), 105345.
- [66] Shulei Liu, Handing Wang, and Wen Yao. 2022. A surrogate-assisted evolutionary algorithm with hypervolume triggered fidelity adjustment for noisy multiobjective integer programming. *Appl. Soft Comput.* 126 (2022), 109263.
- [67] Yan Liu and Matthew Collette. 2014. Improving surrogate-assisted variable fidelity multi-objective optimization using a clustering algorithm. *Appl. Soft Comput.* 24 (2014), 482–493.
- [68] Zhao Liu, Hongyi Xu, and Ping Zhu. 2020. An adaptive multi-fidelity approach for design optimization of mesostructure-structure systems. *Struct. Multidiscipl. Optim.* 62 (2020), 375–386.
- [69] Phuc Luong, Dang Nguyen, Sunil Gupta, Santu Rana, and Svetha Venkatesh. 2021. Adaptive cost-aware Bayesian optimization. *Knowl. Based Syst.* 232 (2021), 107481.
- [70] Laura Mainini, Andrea Serani, Markus P. Rumpfkeil, Edmondo A. Minisci, Domenico Quagliarella, H. Pehlivan, S. Yıldız, S. Ficini, Riccardo Pellegrini, F. Di Fiore, Dean E. Bryson, M. Nikbay, M. Diez, and Phil Beran. 2022. Analytical Benchmark Problems for Multifidelity Optimization Methods. In *Research Workshop AVT-354 on Multi-fidelity Methods for Military Vehicle Design*.
- [71] Neeratyoy Mallik, Edward Bergman, Carl Hvarfner, Danny Stoll, Maciej Janowski, Marius Lindauer, Luigi Nardi, and Frank Hutter. 2023. PriorBand: Practical Hyperparameter Optimization in the Age of Deep Learning. *Corr abs/2306.12370* (2023). arXiv:[2306.12370](https://arxiv.org/abs/2306.12370)
- [72] Mohammad Mohiuddin Mamun, Hemant Kumar Singh, and Tapabrata Ray. 2022. A Multifidelity Approach for Bilevel Optimization With Limited Computing Budget. *IEEE Trans. Evol. Comput.* 26, 2 (2022), 392–399.
- [73] Xavier Marduel, Christophe Tribes, and Jean-Yves Trépanier. 2002. Optimization using variable fidelity solvers: exploration of an approximation management framework for aerodynamic shape optimization. In *Proc. of the 9th AIAA/ISSMO symposium on multidisciplinary analysis and optimization*. 5595.
- [74] Xavier Marduel, Christophe Tribes, and Jean-Yves Trépanier. 2006. Variable-fidelity optimization: efficiency and robustness. *Optim. Eng.* 7, 4 (2006), 479–500.
- [75] Xuhui Meng and George Em Karniadakis. 2020. A composite neural network that learns from multi-fidelity data: Application to function approximation and inverse PDE problems. *J. Comput. Phys.* 401 (2020).
- [76] Xuhui Meng, Zhicheng Wang, Dixia Fan, Michael S. Triantafyllou, and George Em Karniadakis. 2021. A fast multi-fidelity method with uncertainty quantification for complex data correlations: Application to vortex-induced vibrations of marine risers. *Comput. Methods Appl. Mech. Eng.* 386 (2021), 114212.
- [77] Petrus Mikkola, Julien Martinelli, Louis Filstroff, and Samuel Kaski. 2023. Multi-Fidelity Bayesian Optimization with Unreliable Information Sources. In *AISTATS'23: Proc. of the 2023 International Conference on Artificial Intelligence and Statistics*, Vol. 206. PMLR, 7425–7454.
- [78] Henry B. Moss, David S. Leslie, Javier Gonzalez, and Paul Rayson. 2021. GIBBON: General-purpose Information-Based Bayesian Optimisation. *J. Mach. Learn. Res.* 22 (2021), 235:1–235:49.

- [79] Henry B. Moss, David S. Leslie, and Paul Rayson. 2020. MUMBO: Multi-task Max-Value Bayesian Optimization. In *ECML/PKDD’20: Proc. of the 2020 European Conference on Machine Learning and Knowledge Discovery in Databases (Lecture Notes in Computer Science, Vol. 12459)*. Springer, 447–462.
- [80] Pramudita S Palar and Koji Shimoyama. 2017. Multi-fidelity uncertainty analysis in CFD using hierarchical Kriging. In *Proc. of the 35th AIAA Applied Aerodynamics Conference*. 3261.
- [81] Chanyoung Park, Raphael T. Haftka, and Nam H. Kim. 2017. Remarks on multi-fidelity surrogates. *Struct. Multidiscipl. Optim.* 55, 3 (2017), 1029–1050.
- [82] Paris Perdikaris, Maziar Raissi, Andreas Damianou, Neil D Lawrence, and George Em Karniadakis. 2017. Nonlinear Information Fusion Algorithms for Data-Efficient Multi-fidelity Modelling. *Proc. R. Soc. A: Math. Phys. Eng. Sci.* 473, 2198 (2017), 20160751.
- [83] Florian Pfisterer, Lennart Schneider, Julia Moosbauer, Martin Binder, and Bernd Bischof. 2022. YAHPO Gym - An Efficient Multi-Objective Multi-Fidelity Benchmark for Hyperparameter Optimization. In *AutoML’22: Proc. of 2022 International Conference on Automated Machine Learning (Proceedings of Machine Learning Research, Vol. 188)*. PMLR, 3/1–39.
- [84] Matthias Poloczek, Jialei Wang, and Peter I. Frazier. 2017. Multi-Information Source Optimization. In *NeurIPS’17: Annual Conference on Neural Information Processing Systems 2017*. 4288–4298.
- [85] Patrick H. Reisenthel and Theodore T. Allen. 2014. Application of multifidelity expected improvement algorithms to aeroelastic design optimization. In *AIAA’14: Proc. of the 10th AIAA Multidisciplinary Design Optimization Conference*. 1490.
- [86] J. Ren, Leifur P. Leifsson, Slawomir Koziel, and Yonatan Aefwark Tesfahunegn. 2016. Multi-fidelity aerodynamic shape optimization using manifold mapping. In *Proc. of the 57th AIAA/ASCE/AHS/ASC Structures, Structural Dynamics, and Materials Conference*. 0419.
- [87] James Requeima, William Tebbutt, Wessel Bruinsma, and Richard E. Turner. 2019. The Gaussian Process Autoregressive Regression Model (GPAR). In *AISTAS’19: Proc. of the 22nd International Conference on Artificial Intelligence and Statistics*, Vol. 89. 1860–1869.
- [88] Markus P. Rumpfkeil and Philip S. Beran. 2020. Multi-Fidelity, Gradient-enhanced, and Locally Optimized Sparse Polynomial Chaos and Kriging Surrogate Models Applied to Benchmark Problems. In *AIAA Scitech 2020 Forum*. 0677.
- [89] Tom Savage, Nausheen Basha, Omar K. Matar, and Ehecatl Antonio del Rio-Chanona. 2022. Deep Gaussian Process-based Multi-fidelity Bayesian Optimization for Simulated Chemical Reactors. *CoRR* abs/2210.17213 (2022). arXiv:2210.17213
- [90] A Serani, R Pellegrini, J Wackers, C-E Jeanson, P Queutey, Michel Visonneau, and M Diez. 2019. Adaptive multi-fidelity sampling for CFD-based optimisation via radial basis function metamodels. *Int. J. Comut. Fluid Dyn.* 33, 6–7 (2019), 237–255.
- [91] Maolin Shi, Liye Lv, Wei Sun, and Xueguan Song. 2020. A multi-fidelity surrogate model based on support vector regression. *Struct. Multidiscip. Optim.* 61, 6 (2020), 2363–2375.
- [92] Leshi Shu, Ping Jiang, Qi Zhou, Xinyu Shao, Jiexiang Hu, and Xiangzheng Meng. 2018. An on-line variable fidelity metamodel assisted Multi-objective Genetic Algorithm for engineering design optimization. *Appl. Soft Comput.* 66 (2018), 438–448.
- [93] Xueguan Song, Liye Lv, Wei Sun, and Jie Zhang. 2019. A radial basis function-based multi-fidelity surrogate model: exploring correlation between high-fidelity and low-fidelity models. *Struct. Multidiscipl. Optim.* 60, 3 (2019), 965–981.
- [94] Guangyong Sun, Guangyao Li, and Qing Li. 2012. Variable fidelity design based surrogate and artificial bee colony algorithm for sheet metal forming process. *Finite Elem. Anal. Des.* 59 (2012), 76–90.
- [95] Guangyong Sun, Guangyao Li, Shiwei Zhou, Wei Xu, Xujing Yang, and Qing Li. 2011. Multi-fidelity optimization for sheet metal forming process. *Struct. Multidiscipl. Optim.* 44, 1 (2011), 111–124.
- [96] Kevin Swersky, Jasper Snoek, and Ryan Prescott Adams. 2013. Multi-Task Bayesian Optimization. In *NIPS’13: Proc. of the Annual Conference on Neural Information Processing Systems 2013*. 2004–2012.
- [97] Shion Takeo, Hitoshi Fukuoka, Yuhki Tsukada, Toshiyuki Koyama, Motoki Shiga, Ichiro Takeuchi, and Masayuki Karasuyama. 2020. Multi-fidelity Bayesian Optimization with Max-value Entropy Search and its Parallelization. In *ICML’20: Proc. of the 37th International Conference on Machine Learning (Proceedings of Machine Learning Research, Vol. 119)*. PMLR, 9334–9345.
- [98] Shion Takeo, Hitoshi Fukuoka, Yuhki Tsukada, Toshiyuki Koyama, Motoki Shiga, Ichiro Takeuchi, and Masayuki Karasuyama. 2022. A Generalized Framework of Multifidelity Max-Value Entropy Search Through Joint Entropy. *Neural Comput.* 34, 10 (2022), 2145–2203.
- [99] David JJ Toal. 2015. Some considerations regarding the use of multi-fidelity Kriging in the construction of surrogate models. *Struct. Multidiscipl. Optim.* 51, 6 (2015), 1223–1245.
- [100] Maxim Tyan, Nhu Van Nguyen, and Jae-Woo Lee. 2015. Improving variable-fidelity modelling by exploring global design space and radial basis function networks for aerofoil design. *Eng. Optim.* 47, 7 (2015), 885–908.
- [101] Nhu Van Nguyen and Maxim Tyan and Jae-Woo Lee. 2015. A modified variable complexity modeling for efficient multidisciplinary aircraft conceptual design. *Optim. Eng.* 16, 2 (2015), 483–505.
- [102] Sander van Rijn and Sebastian Schmitt. 2020. MF2: A Collection of Multi-Fidelity Benchmark Functions in Python. *J. Open Source Softw.* 5, 52 (2020), 2049.
- [103] Roberto Vitali, Raphael Haftka, and Bhavani Sankar. 1998. Correction response surface approximations for stress intensity factors of a composite stiffened plate. In *Proc. of the 39th AIAA/ASME/ASCE/AHS/ASC Structures, Structural Dynamics, and Materials Conference and Exhibit*. 2047.
- [104] Roberto Vitali, Raphael T. Haftka, and B. V. Sankar. 2002. Multi-fidelity design of stiffened composite panel with a crack. *Struct. Multidiscip. Optim.* 23 (2002), 347–356.
- [105] Handing Wang, Yaochu Jin, and John Doherty. 2018. A Generic Test Suite for Evolutionary Multifidelity Optimization. *IEEE Trans. Evol. Comput.* 22, 6 (2018), 836–850.

- [106] Handing Wang, Yaochu Jin, Cuie Yang, and Licheng Jiao. 2020. Transfer Stacking from Low-to High-Fidelity: A Surrogate-Assisted Bi-Fidelity Evolutionary Algorithm. *Appl. Soft Comput.* 92 (2020), 106276.
- [107] Brad Warner and Manavendra Misra. 1996. Understanding neural networks as statistical tools. *Am. Stat.* 50, 4 (1996), 284–293.
- [108] Martin Wistuba, Arlind Kadra, and Josif Grabocka. 2022. Supervising the Multi-Fidelity Race of Hyperparameter Configurations. In *NeurIPS'22: Proc. of the Annual Conference on Neural Information Processing Systems 2022*.
- [109] Ying Xiong, Wei Chen, and Kwok-Leung Tsui. 2008. A New Variable-Fidelity Optimization Framework Based on Model Fusion and Objective-Oriented Sequential Sampling. *J. Mech. Des.* 130, 11 (2008), 1114011–1114019.
- [110] Yueqi Xu, Xueguan Song, and Chao Zhang. 2021. Hierarchical regression framework for multi-fidelity modeling. *Knowl. Based Syst.* 212 (2021), 106587.
- [111] Haizhou Yang, Seong Hyeong Hong, and Yi Wang. 2022. A sequential multi-fidelity surrogate-based optimization methodology based on expected improvement reduction. *Struct. Multidiscipl. Optim.* 65, 5 (2022), 153.
- [112] Haizhou Yang and Yi Wang. 2023. A sparse multi-fidelity surrogate-based optimization method with computational awareness. *Eng. Comput.* 39, 5 (2023), 3473–3489.
- [113] Jin Yi, Liang Gao, Xinyu Li, Christine A. Shoemaker, and Chao Lu. 2019. An on-line variable-fidelity surrogate-assisted harmony search algorithm with multi-level screening strategy for expensive engineering design optimization. *Knowl. Based Syst.* 170 (2019), 1–19.
- [114] Jin Yi, Yichi Shen, and Christine A. Shoemaker. 2020. A multi-fidelity RBF surrogate-based optimization framework for computationally expensive multi-modal problems with application to capacity planning of manufacturing systems. *Struct. Multidiscipl. Optim.* 62, 4 (2020), 1787–1807.
- [115] Jin Yi, Yichi Shen, and Christine A. Shoemaker. 2020. A multi-fidelity RBF Surrogate-Based Optimization Framework for Computationally Expensive Multi-Modal Problems with Application to Capacity Planning of Manufacturing Systems. *Struct. Multidiscipl. Optim.* 62, 4 (2020), 1787–1807.
- [116] Chris Ying, Aaron Klein, Eric Christiansen, Esteban Real, Kevin Murphy, and Frank Hutter. 2019. NAS-Bench-101: Towards Reproducible Neural Architecture Search. In *ICML'19: Proc. of the 36th International Conference on Machine Learning*, Vol. 97. PMLR, 7105–7114.
- [117] Hau Kit Yong, Lieran Wang, David JJ. Toal, Andy J. Keane, and Felix Stanley. 2019. Multi-fidelity Kriging-assisted structural optimization of whole engine models employing medial meshes. *Struct. Multidiscipl. Optim.* 60, 3 (2019), 1209–1226.
- [118] Hao Zhang, Yifei Li, Ziyu Chen, Xinrong Su, and Xin Yuan. 2019. Multi-fidelity model based optimization of shaped film cooling hole and experimental validation. *Int. J. Heat Mass Transf.* 132 (2019), 118–129.
- [119] Lili Zhang, Yuda Wu, Ping Jiang, Seung-Kyum Choi, and Qi Zhou. 2022. A multi-fidelity surrogate modeling approach for incorporating multiple non-hierarchical low-fidelity data. *Adv. Eng. Informatics* 51 (2022), 101430.
- [120] Yu Zhang, Zhong-Hua Han, and Ke-Shi Zhang. 2018. Variable-fidelity expected improvement method for efficient global optimization of expensive functions. *Struct. Multidiscipl. Optim.* 58, 4 (2018), 1431–1451.
- [121] Yehong Zhang, Trong Nghia Hoang, Bryan Kian Hsiang Low, and Mohan Kankanhalli. 2017. Information-based multi-fidelity Bayesian optimization. In *NIPS Workshop on Bayesian Optimization*.
- [122] Jun Zheng, Xinyu Shao, Liang Gao, Ping Jiang, and Haobo Qiu. 2015. Difference mapping method using least square support vector regression for variable-fidelity metamodeling. *Eng. Optim.* 47, 6 (2015), 719–736.
- [123] Qi Zhou, Xinyu Shao, Ping Jiang, Zhongmei Gao, Chao-Chao Wang, and Leshi Shu. 2016. An active learning metamodeling approach by sequentially exploiting difference information from variable-fidelity models. *Adv. Eng. Informatics* 30, 3 (2016), 283–297.
- [124] Qi Zhou, Xinyu Shao, Ping Jiang, Hui Zhou, and Leshi Shu. 2015. An adaptive global variable fidelity metamodeling strategy using a support vector regression based scaling function. *Simul. Model. Pract. Theory* 59 (2015), 18–35.
- [125] Qi Zhou, Yan Wang, Seung-Kyun Choi, Ping Jiang, Xinyu Shao, and Jiexiang Hu. 2017. A sequential multi-fidelity metamodeling approach for data regression. *Knowl. Based Syst.* 134 (2017), 199–212.
- [126] Qi Zhou, Jinhong Wu, Tao Xue, and Peng Jin. 2021. A Two-Stage Adaptive Multi-Fidelity Surrogate Model-Assisted Multi-Objective Genetic Algorithm for Computationally Expensive Problems. *Eng. Comput.* 37, 1 (2021), 623–639.
- [127] Jiandao Zhu, Yi-Jen Wang, and Matthew Collette. 2014. A Multi-Objective Variable-Fidelity Optimization Method for Genetic Algorithms. *Eng. Optim.* 46, 4 (2014), 521–542.
- [128] Xinran Zhu, Yang Liu, Pieter Ghysels, David Bindel, and Xiaoye S. Li. 2022. GPTuneBand: Multi-task and Multi-fidelity Autotuning for Large-scale High Performance Computing Applications. In *PPSC'22: Proc. of the 2022 SIAM Conference on Parallel Processing for Scientific Computing*. 1–13.
- [129] Ralf Zimmermann and Zhong-Hua Han. 2010. Simplified cross-correlation estimation for multi-fidelity surrogate co-Kriging models. *Adv. Appl. Math. Sci.* 7, 2 (2010), 181–202.