Bitwise Operations

- Bitwise operations in high-level languages are applied to integers
- Java has three primary sizes for signed integers
- Two types of Bitwise Operations
 - Boolean based operations
 - Shift-based operations
- Boolean-based Operations:
 - And: s1 = t1 & t2;
 - s1 = t1 | t2;Or: $s1 = t1 ^ t2;$
 - Xor:

- short (16 bit chunks)
- int (32 bit chunks)
- long (64 bit chunks)

```
Complement: s1 = ~t1; nor $s1, $t1, $zero # s1 = ~(t1 | 0)
                               and $s1, $t1, $t2
                              or $s1, $t1, $t2
                               xor $s1, $t1, $t2
```

Shift-based Operations:

```
Un/Signed Left Shift
Unsigned Right Shift
                     s1 = t1 >>> 2;
Signed Right Shift
Unsigned Left Shift
                     s1 = t1 <<< t2:
```

```
s1 = t1 << 2; sll $s1, $t1, 2 # Shift Left Logical
             srl $s1, $t1, 2
                               # Shift Right Logical
```

s1 = t1 >> 2; sra \$s1, \$t1, 2 # Shift Right Arithmetic

Boolean-based Bitwise Operations

Let's assume 4-bit chunks:

s1 = t1 & t2 and \$s1, \$t1, \$t2 And:


o Xor:

Complement: s1 = ~t1 nor \$s1, \$t1, \$zero

Or: $s1 = t1 \mid t2$ or \$s1, \$t1, \$t2

s1 = t1 ^ t2 xor \$s1, \$t1, \$t2

А	В	nor	&	I	٨
0	0	1	0	0	0
0	1	0	0	1	1
1	0	0	0	1	1
1	1	0	1	1	0



Shift-based Operations

Foreshadow:


- Integers are encoded in 2's complement
- In such numbers, the MSB is represents the sign
- 1 -> a negative number

- Java and MIPS supported:
 - Shift Left Logical
 - Shift Right Logical
 - Shift Right Arithmetic


- s1 = t1 << 2 sll \$s1, \$t1, 2
 - srl \$s1, \$t1, 2
 - sra \$s1, \$t1, 2

Let's Assume 4-bits and a shift of "1"


shift left logical



shift right logical



shift right arithmetic




Additional Shift-based Operations

- Rotates or Circular Shifts
 - Rotate Left Logical
 - Rotate Right Logical ror \$s1, \$t1, 2
- rol \$s1, \$t1, 2
- Typically, not supported in high-level languages
- Let's Assume 4-bits and a shift of "1"


sll \$s1, \$t1, 2 srl \$at, \$t1, 30 or \$s1, \$s1, \$at

srl \$s1, \$t1, 2 sll \$at, \$t1, 30 or \$s1, \$s1, \$at





rotate right



Repositioning Fields within a Register

- Consider a register (16 bits) containing information
- Consider extracting a subrange of bits

