

Base Conversion

Between Powers of 2: 2, 8, 16

Examples: [Rechunk](#)

1. Convert each digit to binary: [Lookup Table](#) or from memory!
2. Merge then rechunk the bits
3. Convert each chunk to the appropriate digit

Base N to 10

- Use Expanded Notation, or
- For each digit: multiply by N , and then add the value of the digit

Base 10 to Base N

- Successively divide the number by N
- The concatenation of the remainders produce the final value
- Consider the examples via the spreadsheet: [Base Conversion](#)

Base N to Base 10




Algorithm: multiply, add, and shift

16# 5a2

- set $v = 0$
- For each digit (from left to right)
 - $v = v * \text{base}$; # Multiple by the base
 - $v = v + \text{digit}_{10}$; # Add the next digit
- print v

v:	5	=	0	* 16 +	5	5
v:	90	=	5	* 16 +	10	a
v:	1442	=	90	* 16 +	2	2

Consider: 16# 5a2 == 1442



Base N to Base 10




Algorithm: multiply, add, and shift

2# 10110101

- set $v = 0$
- For each digit (from left to right)
 - $v = v * \text{base}$; # Multiple by the base
 - $v = v + \text{digit}_{10}$; # Add the next digit
- print v

Consider: 2# 10110101 == 181




v:	1	=	0	* 2 +	1	1
v:	2	=	1	* 2 +	0	0
v:	5	=	2	* 2 +	1	1
	11	=	5	* 2 +	1	1
	22	=	11	* 2 +	0	0
	45	=	22	* 2 +	1	1
	90	=	45	* 2 +	0	0
	181	=	90	* 2 +	1	1

--

?8# 453

- set $v = 0$
- For each digit (from left to right)
 - $v = v * \text{base}$; # Multiple by the base
 - $v = v + \text{digit}_{10}$; # Add the next digit
- print v

Consider: $8\# == ?$



v:	4	=	0	* 8 +	4	4
v:	37	=	4	* 8 +	5	5
v:	299	=	37	* 8 +	3	3

Base Conversion of Real Numbers

Base 10 to Base N

- The whole portion is divided by the new base, repeatedly
 - $\text{Dividend} / \text{Divisor} = (\text{Quotient}, \text{Remainder})$
 - The concatenation of the Remainders provide you with the final digits
- The fraction portion is multiplied by the new base, repeatedly
 - $\text{Multiplier} * \text{Multiplicand} = (\text{Overflow}, \text{Product})$
 - The concatenation of the Overflows provide you with the final digits
- Consider the examples via the spreadsheet: [Base Conversion](#)

Decimal Real to Binary Real

1. Split the number at the radix point: *whole . fractional*

2. With the whole part,


```
number = whole
while (number != 0 ){
    number = number / 2
    push ( number % 2 )
}
pop_all();
```

3. With the fractional part

```
max = 10 ** stringlength(fractional)
number = fractional
while (number != 0 ) {
    number = number * 2
    if ( number > max ) {
        emit 1
        number = number - max
    } else {
        emit 0
    }
}
```

4. Put the two pieces together

Real: Decimal to Binary



Example: - 39.234

Whole Part

1. Split the number at the radix point: - 39 . *fractional*

2. With the whole part,

```
number = whole
while (number != 0 ){
    number = number / 2
    push ( number % 2 )
}
pop_all();
```

number: 39

```
number = 39 / 2
→ 19
push ( 39 % 2 )
→ 1


number = 19 / 2
→ 9
push( 19 % 2)      → 1

number = 9 / 2
→ 4
push( 9 % 2)        → 1

number = 4 / 2
→ 2
push( 4 % 2)        → 0

number = 2 / 2
→ 1
push ( 2 % 2 )      → 0

number = 1 / 2
→ 0
push ( 1 % 2 )      → 1
```



4. Put the two pieces together



Example: - 39.234

Fractional Part

1. Split the number at the radix point: *whole . 234*

`max = 10 ** |234| == 1,000`

`number = 234`

`number = 234 * 2 = 0,468`

`number = 468 * 2 = 0,936`

`number = 936 * 2 = 1,872 - 1000 =`

872

`number = 872 * 2 = 1,744 - 1000 =`

744

`number = 744 * 2 = 1,488 - 1000 =`

488

4. Put the two pieces together

`number = 488 * 2 = 0,976`

`number = 976 * 2 = 1,952 - 1000 =`

952

3. With the fractional part

`max = 10 ** stringlength(fractional)`

`number = fractional`

`while (number != 0) {`

`number = number * 2`

`if (number > max) {`

`emit 1`

`number = number - max`

`} else {`

`emit 0`

`}`

`}`

1000 =	
.	0011101

Example: - 39.234

Both Parts

1. Split the number at the radix point: *whole . fractional*

2. With the whole part,

```
number = whole
while (number != 0 ){
    number = number / 2
    push ( number % 2 )
}
pop_all();
```

3. With the fractional part

```
max = 10 ** stringlength(fractional)
number = fractional
while (number != 0 ) {
    number = number * 2
    if ( number > max ) {
        emit 1
        number = number - max
    } else {
        emit 0
    }
}
```

4. Put the two pieces together

-	100111	.	0011101
---	--------	---	---------

Example: 45.45

Whole Part

1. Split the number at the radix point: *whole . fractional*

2. With the whole part,

```
number = whole
while (number != 0 ){
    number = number / 2
    push ( number % 2 )
}
pop_all();
```

4. Put the two pieces together

101101	.
--------	---

number: 45

```
number = 45 / 2 → 22
push ( 45 % 2 )
→ 1
number = 22 / 2 → 11
push ( 22 % 2 )
→ 0
number = 11 / 2
→ 5
push ( 11 % 2 )
→ 1
number = 5 / 2
→ 2
push ( 5 % 2 )
→ 1
number = 2 / 2
→ 1
push ( 2 % 2 )
→ 0
number = 1 / 2
```

1
0
1
1
0
1

Example: 45.45

Fractional Part

1. Split the number at the radix point: *whole . 45*

```
max = 10 ** |45| == 100
number = 45
  number = number * 2 = 90
  number = number * 2 = 180 - 100 = 80
  number = 80 * 2 = 160 - 100 = 60
  number = 60 * 2 = 120 - 100 = 20
  number = 20 * 2 = 40
  number = 40 * 2 = 80
  number = 80 * 2 = 160 - 100 = 60
```

3. With the fractional part

```
max = 10 ** strlen(fractional)
number = fractional
while (number != 0) {
  number = number * 2
  if ( number > max ) {
    emit 1
    number = number - max
  } else {
    emit 0
  }
}
```

4. Put the two pieces together

.	0111001
---	---------

Example: 45.45

1. Split the number at the radix point: *whole . fractional*

2. With the whole part,

```
number = whole
while (number != 0 ){
    number = number / 2
    push ( number % 2 )
}
pop_all();
```

3. With the fractional part

```
max = 10 ** ( | fractional | )
fractional = number
while (number != 0 ) {
    number = number * 2
    if ( number > max ) {
        emit 1
        number = number - max
    } else {
        emit 0
    }
}
```

4. Put the two pieces together

101101	.	0111001
--------	---	---------

Example:

Whole Part

1. Split the number at the radix point: ? . *fractional*


2. With the whole part,

```
number = whole
while (number != 0 ){
    number = number / 2
    push ( number % 2 )
}
pop_all();
```

number:

```
number = / 2 →
push ( % 2 )
→ 1
```

4. Put the two pieces together



Example:

Fractional Part

1. Split the number at the radix point: *whole . ?*

```
max = 10 ** |?| ==  
number = ?  
    number = number * 2 =
```

3. With the fractional part

```
max = 10 ** stringlength(fractional)  
number = fractional  
while (number != 0 ) {  
    number = number * 2  
    if ( number > max ) {  
        emit 1  
        number = number - max  
    } else {  
        emit 0  
    }  
}
```

4. Put the two pieces together

	.	
--	---	--

Example:

1. Split the number at the radix point: *whole . fractional*

2. With the whole part,

```
number = whole
while (number != 0 ){
    number = number / 2
    push ( number % 2 )
}
pop_all();
```

3. With the fractional part

```
max = 10 ** ( | fractional | )
fractional = number
while (number != 0 ) {
    number = number * 2
    if ( number > max ) {
        emit 1
        number = number - max
    } else {
        emit 0
    }
}
```

4. Put the two pieces together

	.	
--	---	--