# COMP 3721

Tutorial 2

• DFA

1) Prove that  $\mathbb{N} \times \mathbb{N}$  is countable.

#### Hints:

It is equinumerous with  $\mathbb{N}$ .

Find a way to enumerate every element in it within finite steps.

Using conclusions from the lecture.

- Prove that  $\mathbb{N} \times \mathbb{N}$  is countable.
- Proof 1(a little bit complicated):
  - Find a bijection between  $\mathbb{N} \times \mathbb{N}$  and  $\mathbb{N}$  .
  - The following function is such a bijection:
  - f(a, b) = (a + b 1)\*(a + b 2)/2 + a
  - Prove that it is a bijection....


• Prove that  $\mathbb{N} \times \mathbb{N}$  is countable.

- Proof 2:
  - A way to enumerate all elements:
    - enumerate tuple (a, b) where:
    - a + b = 0
    - a + b = 1
    - a + b = 2
    - ...
  - Every (a, b) will be reached in finite step..

(0,0)	(0,1)	(0,2)	(0,3)	
(1,0)	(1,1)	(1,2)	(1,3)	
(2,0)	(2,1)	(2,2)	(2,3)	
(3,0)	(3,1)	(3,2)	(3,3)	


• Prove that  $\mathbb{N} \times \mathbb{N}$  is countable.

- Proof 3:
  - Use that:
  - the Cartesian product of two countable sets is countable...




- 1) Construct a DFA for accepting the language with regular expression  $b^*a(a \cup b)^*$ .
- 2) Construct a DFA for accepting each of the following languages:
  - a)  $\{w \in \{a, b\}^* : w \text{ contains the string } abbab\}.$
  - b)  $\{w \in \{a, b\}^*: w \text{ don't have } abb \text{ as a substring}\}.$
  - c)  $\{w \in \{a, b\}^*: w \text{ has a number of } a'\text{s divisible by 3}\}.$
  - d)  $\{w \in \{a, b\}^*: w \text{ has an odd number of } a'\text{s and an even number of } b'\text{s}\}.$


1) Construct a DFA for accepting the language with regular expression  $b^*a(a\cup b)^*$  .



- 2) Construct a DFA for accepting each of the following languages:
  - a)  $\{w \in \{a, b\}^* : w \text{ contains the string } abbab\}.$




- 2) Construct a DFA for accepting each of the following languages:
  - a)  $\{w \in \{a, b\}^* : w \text{ contains the string } abbab\}.$
  - b)  $\{w \in \{a, b\}^*: w \text{ don't have } abb \text{ as a substring}\}.$



#### 2) Construct a DFA for accepting each of the following languages:

- a)  $\{w \in \{a, b\}^* : w \text{ contains the string } abbab\}.$
- b)  $\{w \in \{a, b\}^*: w \text{ don't have } abb \text{ as a substring}\}.$
- c)  $\{w \in \{a, b\}^*: w \text{ has a number of } a'\text{s divisible by 3}\}.$



#### 2) Construct a DFA for accepting each of the following languages:

- a)  $\{w \in \{a, b\}^* : w \text{ contains the string } abbab\}.$
- b)  $\{w \in \{a, b\}^*: w \text{ don't have } abb \text{ as a substring}\}.$
- c)  $\{w \in \{a, b\}^*: w \text{ has a number of } a'\text{s divisible by 3}\}.$
- d)  $\{w \in \{a, b\}^*: w \text{ has an odd number of } a'\text{s and an even number of } b'\text{s}\}.$

