

Program Page API

ATTENTION!!!

After the user successfully logs in, the system will automatically issue a JWT token. For every subsequent request, this token needs to be included in the request header sent to the server. The header name should be `token`, and its value should be the JWT token issued at login. If the system detects that the user is not logged in, it will return the following fixed error message:

```
1 {"code":0, "msg":"NOT_LOGIN"}
```

1. Query all Programs

1.1 Basic Information

Request Path: `/progs`

Request Method: `GET`

API Description: This API is used to query all programs.

1.2 Request Parameters

Format: `queryString`

Request Parameter Example:

```
1 /progs
```

or

```
1 /progs?name=xxx
```

Note: The `name` parameter is optional. If the `name` parameter is set, a fuzzy search will be performed in the database to find related data.

1.3 Response Data

Format: `application/json`

Response Parameter Example:

```
1 {
2   "code": 1,
3   "msg": "success",
4   "data": [
5     {
6       "progId": 1,
7       "name": "update failed",
8       "maxCap": 99,
9       "techReq": "abcd",
10      "costPerson": 123.00,
11      "duration": "aaa",
12      "status": 1,
13      "description": null,
14      "category": null,
15      "feeType": null,
```

```
16     "monday": null,
17     "tuesday": null,
18     "wednesday": null,
19     "thursday": null,
20     "friday": null
21 },
22 {
23     "progId": 2,
24     "name": "22222",
25     "maxCap": 99,
26     "techReq": "abcd",
27     "costPerson": 123.00,
28     "duration": "aaa",
29     "status": 2,
30     "description": null,
31     "category": null,
32     "feeType": null,
33     "monday": null,
34     "tuesday": null,
35     "wednesday": null,
36     "thursday": null,
37     "friday": null
38 }
39 ]
40 }
```

2. Delete Program by ID

2.1 Basic Information

Request Path: /progs/{id}

Request Method: DELETE

API Description: This API is used to delete a program by its id.

2.2 Request Parameters

Format: Path variable

Request Parameter Example:

```
1 /progs/1
```

2.3 Response Data

Format: application/json

Response Parameter Example:

```
1 {
2     "code": 1,
3     "msg": "success",
4     "data": null
5 }
```

3. Add new Program

3.1 Basic Information

Request Path: `/progs`

Request Method: `POST`

API Description: This API is used to add a new program.

3.2 Request Parameters

Format: `application/json`

Request Parameter Example:

```
1 {
2   "name": "test",
3   "maxCap": 99,
4   "techReq": "abcd",
5   "costPerson": 123.00,
6   "duration": "aaa",
7   "status": 1,
8   "description": null,
9   "thursday": null,
10  "wednesday": null,
11  "friday": null,
12  "tuesday": null,
13  "monday": null,
14  "category": "tuesday",
15  "feeType": "free"
16 }
```

3.3 Response Data

Format: `application/json`

Response Parameter Example:

```
1 {
2   "code": 1,
3   "msg": "success",
4   "data": null
5 }
```

4. Query Program by id

4.1 Basic Information

Request Path: `/progs/{id}`

Request Method: `GET`

API Description: This API is used to query a program by its id.

4.2 Request Parameters

Format: Path Variable

Request Parameter Example:

```
1 /progs/2
```

4.3 Response Data

Format: application/json

Response Parameter Example:

```
1 {
2   "code": 1,
3   "msg": "success",
4   "data": {
5     "progId": 2,
6     "name": "22222",
7     "maxCap": 99,
8     "techReq": "abcd",
9     "costPerson": 123.00,
10    "duration": "aaa",
11    "status": 2,
12    "description": null,
13    "category": null,
14    "feeType": null,
15    "monday": null,
16    "tuesday": null,
17    "wednesday": null,
18    "thursday": null,
19    "friday": null
20  }
21 }
```

5. Update Program

5.1 Basic Information

Request Path: /progs

Request Method: PUT

API Description: This API is used to update program.

5.2 Request Parameters

Format: application/json

Request Parameter Example:

```
1 {
2   "progId": "9",
3   "name": "test1",
4   "maxCap": 99,
5   "techReq": "abcd",
6   "costPerson": 123.00,
7   "duration": "aaa",
8   "status": 1,
9   "description": null,
10  "thursday": null,
```

```
11     "wednesday": null,  
12     "friday": null,  
13     "tuesday": null,  
14     "monday": null,  
15     "category": "monday",  
16     "feeType": "paid"  
17 }
```

5.3 Response Data

Format: application/json

Response Parameter Example:

```
1 {  
2     "code": 1,  
3     "msg": "success",  
4     "data": null  
5 }
```