

# Dionex\_COMPASS\_August2022

Stephanie J. Wilson

2023-01-23

## Daily Set up

Read in and Format the raw data - change wd & file names

```
# SULFATE DATA:
```

```
## Read in raw data file from Dionex - copied and saved as a txt
```

```
Sdat <- read.table("Raw Data/COMPASS_Synoptic_CB_MonMon_202208_S04a.txt", sep='\t' , header=T, skip=3)  
head(Sdat)
```

```
##      X      X.1      X.2 IC.S04 IC.S04.1 IC.S04.2 IC.S04.3 IC.S04.4  
## 1 1 Lab Blank Unknown 4.453  0.0337    5.56   0.0343    0.09  
## 2 2 Lab Blank Unknown 4.100  0.0238    3.82   0.0242    0.07  
## 3 3 Lab Blank Unknown  n.a.    n.a.    n.a.    n.a.    n.a.  
## 4 4 Lab Blank Unknown 4.450  0.0349    5.48   0.0356    0.09  
## 5 5 Lab Blank Unknown  n.a.    n.a.    n.a.    n.a.    n.a.  
## 6 6 Lab Blank Unknown 4.450  0.0117    2.36   0.0119    0.04
```

```
## Only keep the columns that we need
```

```
Sdat <- Sdat[ ,c(2,5)] # dont need this here  
head(Sdat)
```

```
##      X.1 IC.S04.1  
## 1 Lab Blank  0.0337  
## 2 Lab Blank  0.0238  
## 3 Lab Blank   n.a.  
## 4 Lab Blank  0.0349  
## 5 Lab Blank   n.a.  
## 6 Lab Blank  0.0117
```

```
## Name the columns correctly
```

```
colnames(Sdat) <- c( "Sample_ID", "S04_ppm")  
Sdat$Sample_ID <- as.factor(Sdat$Sample_ID)  
Sdat$S04_ppm <- as.numeric(Sdat$S04_ppm)
```

```
## Warning: NAs introduced by coercion
```

```
Sdat <- as.data.frame(Sdat)
head(Sdat)
```

```
##   Sample_ID S04_ppm
## 1 Lab Blank  0.0337
## 2 Lab Blank  0.0238
## 3 Lab Blank      NA
## 4 Lab Blank  0.0349
## 5 Lab Blank      NA
## 6 Lab Blank  0.0117
```

```
#Chloride data
```

```
## Read in raw data file from Dionex - copied and saved as a txt
```

```
Cldat <- read.table("Raw Data/COMPASS_Synoptic_CB_MonMon_202208_Cla.txt",sep='\t' , header=T, skip=3)
head(Cldat)
```

```
##   X      X.1      X.2 IC.Cl IC.Cl.1 IC.Cl.2 IC.Cl.3 IC.Cl.4
## 1 1 Lab Blank Unknown 3.287 0.0017    0.37 0.0023    0.03
## 2 2 Lab Blank Unknown 3.287 0.0068    1.46 0.0092    0.09
## 3 3 Lab Blank Unknown 3.290 0.3186  100.00 0.4348    3.14
## 4 4 Lab Blank Unknown 3.287 0.0814   17.08 0.1111    0.37
## 5 5 Lab Blank Unknown 3.290 0.3173  100.00 0.4331    3.13
## 6 6 Lab Blank Unknown 3.287 0.0079    2.14 0.0108    0.11
```

```
## Only keep the columns that we need
```

```
Cldat <- Cldat[,c(2,5)]
head(Cldat)
```

```
##           X.1 IC.Cl.1
## 1 Lab Blank 0.0017
## 2 Lab Blank 0.0068
## 3 Lab Blank 0.3186
## 4 Lab Blank 0.0814
## 5 Lab Blank 0.3173
## 6 Lab Blank 0.0079
```

```
## Name the columns correctly
```

```
colnames(Cldat) <- c( "Sample_ID", "Cl_ppm")
Cldat$Sample_ID <- as.factor(Cldat$Sample_ID)
Cldat$Cl_ppm <- as.numeric(Cldat$Cl_ppm)
```

```
## Warning: NAs introduced by coercion
```

```
Cldat <- as.data.frame(Cldat)
head(Cldat)
```

```
##   Sample_ID Cl_ppm
## 1 Lab Blank 0.0017
## 2 Lab Blank 0.0068
## 3 Lab Blank 0.3186
## 4 Lab Blank 0.0814
## 5 Lab Blank 0.3173
## 6 Lab Blank 0.0079
```

```
## Bring the data back together:
all_dat <- merge(Sdat, Cldat, by="Sample_ID")
head(all_dat)
```

```
##      Sample_ID   S04_ppm   Cl_ppm
## 1          1036.0978 7696.6153
## 2          1036.0978 2087.0619
## 3          1036.0978   0.0017
## 4          1036.0978 2460.2340
## 5          1036.0978      NA
## 6          226.5618 7696.6153
```

```
## Remove empty lines
all_dat <- all_dat[!(is.na(all_dat$Sample_ID) | all_dat$Sample_ID==""), ]
head(all_dat)
```

```
##              Sample_ID   S04_ppm   Cl_ppm
## 26  1_MSM_202208_UP_LysA_20cm 157.5194 1860.322
## 27 10_MSM_202208_TR_LysA_20cm 406.2132 2697.053
## 28 11_MSM_202208_TR_LysA_45cm 469.2068 3444.071
## 29 12_MSM_202208_TR_LysB_10cm 378.0426 2925.598
## 30 13_MSM_202208_TR_LysB_20cm 169.5410 2694.274
## 31 14_MSM_202208_TR_LysB_45cm 285.5842 3085.438
```

```
all_dat <- droplevels(all_dat[!all_dat$Sample_ID == 'Lab Blank',])
head(all_dat)
```

```
##              Sample_ID   S04_ppm   Cl_ppm
## 26  1_MSM_202208_UP_LysA_20cm 157.5194 1860.322
## 27 10_MSM_202208_TR_LysA_20cm 406.2132 2697.053
## 28 11_MSM_202208_TR_LysA_45cm 469.2068 3444.071
## 29 12_MSM_202208_TR_LysB_10cm 378.0426 2925.598
## 30 13_MSM_202208_TR_LysB_20cm 169.5410 2694.274
## 31 14_MSM_202208_TR_LysB_45cm 285.5842 3085.438
```

Pull out standards - could do some checks here if we want

```
stds <- all_dat[grepl("Standard", all_dat$Sample_ID),]
head(stds)
```

```
##      Sample_ID S04_ppm Cl_ppm
## 520 Standard 1  0.5088 5.0017
## 521 Standard 1  0.5088 5.0358
## 522 Standard 1  0.5088 5.2399
## 523 Standard 1  0.5088 5.1696
## 524 Standard 1  0.5106 5.0017
## 525 Standard 1  0.5106 5.0358
```

```
stds_chk_S <- stds %>%
  group_by(Sample_ID) %>%
  summarise(mean = mean(SO4_ppm), sd = sd(SO4_ppm))
stds_chk_S$cv <- (stds_chk_S$sd/stds_chk_S$mean)*100
stds_chk_S$flag <- ifelse(stds_chk_S$cv < 2, 'YES', 'NO, rerun')
head(stds_chk_S)
```

```
## # A tibble: 5 x 5
##   Sample_ID    mean      sd      cv flag
##   <fct>      <dbl>   <dbl> <dbl> <chr>
## 1 Standard 1  0.522 0.0132  2.53 NO, rerun
## 2 Standard 2  0.987 0.00391 0.396 YES
## 3 Standard 3  2.05  0.00517 0.252 YES
## 4 Standard 4  9.87  0.00692 0.0702 YES
## 5 Standard 5 20.1  0.0311  0.155 YES
```

```
stds_chk_Cl <- stds %>%
  group_by(Sample_ID) %>%
  summarise(mean = mean(Cl_ppm), sd = sd(Cl_ppm))
stds_chk_Cl$cv <- (stds_chk_Cl$sd/stds_chk_Cl$mean)*100
stds_chk_Cl$flag <- ifelse(stds_chk_Cl$cv < 2, 'YES', 'NO, rerun')
head(stds_chk_Cl)
```

```
## # A tibble: 5 x 5
##   Sample_ID    mean      sd      cv flag
##   <fct>      <dbl>   <dbl> <dbl> <chr>
## 1 Standard 1   5.11 0.100  1.96 YES
## 2 Standard 2  10.3 0.0303 0.294 YES
## 3 Standard 3  20.7 0.0363 0.175 YES
## 4 Standard 4  98.4 0.173  0.176 YES
## 5 Standard 5 201.  0.241  0.120 YES
```

## Calculate mmol/L concentrations

```
#remove standards from sample dataframe
sampledat <- all_dat[!grepl("Standard", all_dat$Sample_ID),]
head(sampledat)
```

```
##           Sample_ID  SO4_ppm  Cl_ppm
## 26 1_MSM_202208_UP_LysA_20cm 157.5194 1860.322
## 27 10_MSM_202208_TR_LysA_20cm 406.2132 2697.053
## 28 11_MSM_202208_TR_LysA_45cm 469.2068 3444.071
## 29 12_MSM_202208_TR_LysB_10cm 378.0426 2925.598
## 30 13_MSM_202208_TR_LysB_20cm 169.5410 2694.274
## 31 14_MSM_202208_TR_LysB_45cm 285.5842 3085.438
```

```
# Constants needed for calculations:
clmw <- 35.45      #molecular weight of Chloride: 35.45
smw <- 32.06       #molecular weight of sulfur: 32.06
```

```

# Convert ppm to mmol/L
sampledat$SO4_mM <- (sampledat$SO4_ppm / smw)
sampledat$Cl_mM <- (sampledat$Cl_ppm / clmw)

# Calculate Salinity
# calculated using the Knudsen equation
# Salinity = 0.03 + 1.8050 * Chlorinity
# Ref: A Practical Handbook of Seawater Analysis by Strickland & Parsons (P. 11)
# =((1.807*Cl_ppm)+0.026)/1000
sampledat$salinity <- ((1.8070 * sampledat$Cl_ppm) + 0.026) / 1000

head(sampledat)

```

```

##           Sample_ID  SO4_ppm  Cl_ppm  SO4_mM  Cl_mM  salinity
## 26  1_MSM_202208_UP_LysA_20cm 157.5194 1860.322  4.913269 52.47736 3.361629
## 27 10_MSM_202208_TR_LysA_20cm 406.2132 2697.053 12.670405 76.08049 4.873601
## 28 11_MSM_202208_TR_LysA_45cm 469.2068 3444.071 14.635271 97.15292 6.223462
## 29 12_MSM_202208_TR_LysB_10cm 378.0426 2925.598 11.791722 82.52745 5.286582
## 30 13_MSM_202208_TR_LysB_20cm 169.5410 2694.274  5.288241 76.00210 4.868580
## 31 14_MSM_202208_TR_LysB_45cm 285.5842 3085.438  8.907804 87.03632 5.575412

```

Pull out dups and check with percent difference

```

#Show me the data that we have from the calculations
head(sampledat)

```

```

##           Sample_ID  SO4_ppm  Cl_ppm  SO4_mM  Cl_mM  salinity
## 26  1_MSM_202208_UP_LysA_20cm 157.5194 1860.322  4.913269 52.47736 3.361629
## 27 10_MSM_202208_TR_LysA_20cm 406.2132 2697.053 12.670405 76.08049 4.873601
## 28 11_MSM_202208_TR_LysA_45cm 469.2068 3444.071 14.635271 97.15292 6.223462
## 29 12_MSM_202208_TR_LysB_10cm 378.0426 2925.598 11.791722 82.52745 5.286582
## 30 13_MSM_202208_TR_LysB_20cm 169.5410 2694.274  5.288241 76.00210 4.868580
## 31 14_MSM_202208_TR_LysB_45cm 285.5842 3085.438  8.907804 87.03632 5.575412

```

```

#pull out any rows that have "dup" in the SampleID column
dups <- sampledat %>%
  filter(str_detect(Sample_ID, "dup")) #have to change this to match data
head(dups)

```

```

##           Sample_ID  SO4_ppm  Cl_ppm  SO4_mM  Cl_mM
## 1 26_MSM_202208_WC_SipC_45cm_dup 52.7837 6322.2044  1.646404 1.783414e+02
## 2 37_MSM_202208_RHZ_UP_SF_8_dup  61.1325 1659.3508  1.906815 4.680820e+01
## 3 45_MSM_202208_RHZ_TR_SF_8_dup 534.3976 4088.4286 16.668671 1.153294e+02
## 4  8_MSM_202208_UP_LysC_45cm_dup  44.5578   0.3469  1.389825 9.785614e-03
##           salinity
## 1 1.142425e+01
## 2 2.998473e+00
## 3 7.387816e+00
## 4 6.528483e-04

```

```
#remove these from sample dataframe in a new dataframe
sampledat2 <- sampledat %>%
  filter(!str_detect(Sample_ID, "dup")) %>%
  filter(!str_detect(Sample_ID, "spk"))
head(sampledat2)
```

```
##           Sample_ID  S04_ppm  Cl_ppm  S04_mM  Cl_mM salinity
## 1 1_MSM_202208_UP_LysA_20cm 157.5194 1860.322  4.913269 52.47736 3.361629
## 2 10_MSM_202208_TR_LysA_20cm 406.2132 2697.053 12.670405 76.08049 4.873601
## 3 11_MSM_202208_TR_LysA_45cm 469.2068 3444.071 14.635271 97.15292 6.223462
## 4 12_MSM_202208_TR_LysB_10cm 378.0426 2925.598 11.791722 82.52745 5.286582
## 5 13_MSM_202208_TR_LysB_20cm 169.5410 2694.274  5.288241 76.00210 4.868580
## 6 14_MSM_202208_TR_LysB_45cm 285.5842 3085.438  8.907804 87.03632 5.575412
```

```
#remove the dup from these IDs so we will have duplicate sample names
dups$Sample_ID<-gsub("_dup", "", as.character(dups$Sample_ID))
dups <- dups[ , -c(2,3)]
colnames(dups) <- c('Sample_ID', 'S04_mM_dup', 'Cl_mM_dup', 'salinity_dup')
head(dups)
```

```
##           Sample_ID S04_mM_dup  Cl_mM_dup salinity_dup
## 1 26_MSM_202208_WC_SipC_45cm  1.646404 1.783414e+02 1.142425e+01
## 2 37_MSM_202208_RHZ_UP_SF_8   1.906815 4.680820e+01 2.998473e+00
## 3 45_MSM_202208_RHZ_TR_SF_8  16.668671 1.153294e+02 7.387816e+00
## 4 8_MSM_202208_UP_LysC_45cm   1.389825 9.785614e-03 6.528483e-04
```

```
#put it back together with the old data set and look for duplicates
QAdups <- merge(sampledat2, dups)
head(QAdups)
```

```
##           Sample_ID  S04_ppm  Cl_ppm  S04_mM  Cl_mM
## 1 26_MSM_202208_WC_SipC_45cm 52.4325 6240.8845  1.6354492 176.04751763
## 2 37_MSM_202208_RHZ_UP_SF_8  60.4674 1640.4626  1.8860699  46.27539069
## 3 45_MSM_202208_RHZ_TR_SF_8 520.7936 3992.5401 16.2443419 112.62454443
## 4 8_MSM_202208_UP_LysC_45cm  9.8873  2.0883  0.3083999  0.05890832
##           salinity S04_mM_dup  Cl_mM_dup salinity_dup
## 1 11.277304292  1.646404 1.783414e+02 1.142425e+01
## 2 2.964341918  1.906815 4.680820e+01 2.998473e+00
## 3 7.214545961 16.668671 1.153294e+02 7.387816e+00
## 4 0.003799558  1.389825 9.785614e-03 6.528483e-04
```

```
QAdups$S04_dups_chk <- ((abs(QAdups$S04_mM-QAdups$S04_mM_dup))/((QAdups$S04_mM+QAdups$S04_mM_dup)/2))*100
QAdups$S04_dups_flag <- ifelse(QAdups$S04_dups_chk <10, 'YES', 'NO, rerun')

QAdups$Cl_dups_chk <- ((abs(QAdups$Cl_mM-QAdups$Cl_mM_dup))/((QAdups$Cl_mM+QAdups$Cl_mM_dup)/2))*100
QAdups$Cl_dups_flag <- ifelse(QAdups$Cl_dups_chk <10, 'YES', 'NO, rerun')

head(QAdups)
```

```
##           Sample_ID  S04_ppm  Cl_ppm  S04_mM  Cl_mM
## 1 26_MSM_202208_WC_SipC_45cm 52.4325 6240.8845  1.6354492 176.04751763
```

```
## 2 37_MSM_202208_RHZ_UP_SF_8 60.4674 1640.4626 1.8860699 46.27539069
## 3 45_MSM_202208_RHZ_TR_SF_8 520.7936 3992.5401 16.2443419 112.62454443
## 4 8_MSM_202208_UP_LysC_45cm 9.8873 2.0883 0.3083999 0.05890832
##      salinity S04_mM_dup Cl_mM_dup salinity_dup S04_dups_chk S04_dups_flag
## 1 11.277304292 1.646404 1.783414e+02 1.142425e+01 0.6675778 YES
## 2 2.964341918 1.906815 4.680820e+01 2.998473e+00 1.0939154 YES
## 3 7.214545961 16.668671 1.153294e+02 7.387816e+00 2.5784900 YES
## 4 0.003799558 1.389825 9.785614e-03 6.528483e-04 127.3594869 NO, rerun
## Cl_dups_chk Cl_dups_flag
## 1 1.294584 YES
## 2 1.144804 YES
## 3 2.373193 YES
## 4 143.019054 NO, rerun
```

```
#plot dups output as a bar graph to easily check - want any over 10% to be red need to work on this
Sdupsbar <- ggplot(data = QAdups, aes(x = Sample_ID, y = S04_dups_chk, fill=S04_dups_chk)) +
  geom_bar(stat = 'identity') +
  scale_fill_gradient2(low='darkgreen', mid='darkgreen', high='darkgrey', space='Lab') +
  theme_classic() + labs(x= "Sample ID", y="Difference Between S04 Duplicates (%)") +
  theme(legend.position="none") + geom_hline(yintercept=10, linetype="dashed",
  color = "black", size=1)
```

```
## Warning: Using 'size' aesthetic for lines was deprecated in ggplot2 3.4.0.
## i Please use 'linewidth' instead.
## This warning is displayed once every 8 hours.
## Call 'lifecycle::last_lifecycle_warnings()' to see where this warning was
## generated.
```

```
Cldupsbar <- ggplot(data = QAdups, aes(x = Sample_ID, y = Cl_dups_chk, fill=Cl_dups_chk)) +
  geom_bar(stat = 'identity') +
  scale_fill_gradient2(low='darkgreen', mid='darkgreen', high='darkgrey', space='Lab') +
  theme_classic() + labs(x= "Sample ID", y="Difference Between Cl Duplicates (%)") +
  theme(legend.position="none") + geom_hline(yintercept=10, linetype="dashed",
  color = "black", size=1)

ggarrange(Sdupsbar, Cldupsbar, ncol=2, nrow=1)
```



```

#the cv
# calculate the sd bewteen the two duplicates then divide by the mean and multiply by 100

df2 <- as.data.frame(QAdups$S04_mM)
df2$dups <- QAdups$S04_mM_dup

df2$sds <- apply(df2,1,sd)

QAdups$S04_dups_cv <- (df2$sds)/((QAdups$S04_mM+QAdups$S04_mM_dup)/2) * 100
QAdups$S04_dups_cv_flag <- ifelse(QAdups$S04_dups_cv <11, 'YES', 'NO, rerun')

head(QAdups)

```

```

##           Sample_ID  S04_ppm    Cl_ppm    S04_mM    Cl_mM
## 1 26_MSM_202208_WC_SipC_45cm 52.4325 6240.8845 1.6354492 176.04751763
## 2 37_MSM_202208_RHZ_UP_SF_8 60.4674 1640.4626 1.8860699 46.27539069
## 3 45_MSM_202208_RHZ_TR_SF_8 520.7936 3992.5401 16.2443419 112.62454443
## 4 8_MSM_202208_UP_LysC_45cm 9.8873 2.0883 0.3083999 0.05890832
##           salinity S04_mM_dup    Cl_mM_dup salinity_dup S04_dups_chk S04_dups_flag
## 1 11.277304292 1.646404 1.783414e+02 1.142425e+01 0.6675778 YES
## 2 2.964341918 1.906815 4.680820e+01 2.998473e+00 1.0939154 YES
## 3 7.214545961 16.668671 1.153294e+02 7.387816e+00 2.5784900 YES
## 4 0.003799558 1.389825 9.785614e-03 6.528483e-04 127.3594869 NO, rerun
##           Cl_dups_chk Cl_dups_flag S04_dups_cv S04_dups_cv_flag
## 1 1.294584 YES 0.4720488 YES
## 2 1.144804 YES 0.7735150 YES
## 3 2.373193 YES 1.8232678 YES
## 4 143.019054 NO, rerun 90.0567568 NO, rerun

```

```

#plot dups output as a bar graph to easily check - want any over 10% to be red need to work on this
Sdupsbar <- ggplot(data = QAdups, aes(x = Sample_ID, y = S04_dups_cv, fill=S04_dups_chk)) +
  geom_bar(stat = 'identity') +
  scale_fill_gradient2(low='darkgreen', mid='darkgreen', high='darkgrey', space='Lab') +
  theme_classic() + labs(x= "Sample ID", y="CV Between S04 Duplicates (%)") +
  theme(legend.position="none") + geom_hline(yintercept=10, linetype="dashed",
  color = "black", size=1)

Cldupsbar <- ggplot(data = QAdups, aes(x = Sample_ID, y = Cl_dups_chk, fill=Cl_dups_chk)) +
  geom_bar(stat = 'identity') +
  scale_fill_gradient2(low='darkgreen', mid='darkgreen', high='darkgrey', space='Lab') +
  theme_classic() + labs(x= "Sample ID", y="CV Between Cl Duplicates (%)") +
  theme(legend.position="none") + geom_hline(yintercept=10, linetype="dashed",
  color = "black", size=1)

ggarrange(Sdupsbar, Cldupsbar,ncol=2, nrow=1)

```



```
#Show me the data that we have from the calculations
head(sampledat)
```

```
##           Sample_ID S04_ppm Cl_ppm S04_mM Cl_mM salinity
## 26 1_MSM_202208_UP_LysA_20cm 157.5194 1860.322 4.913269 52.47736 3.361629
## 27 10_MSM_202208_TR_LysA_20cm 406.2132 2697.053 12.670405 76.08049 4.873601
## 28 11_MSM_202208_TR_LysA_45cm 469.2068 3444.071 14.635271 97.15292 6.223462
## 29 12_MSM_202208_TR_LysB_10cm 378.0426 2925.598 11.791722 82.52745 5.286582
## 30 13_MSM_202208_TR_LysB_20cm 169.5410 2694.274 5.288241 76.00210 4.868580
## 31 14_MSM_202208_TR_LysB_45cm 285.5842 3085.438 8.907804 87.03632 5.575412
```

```
#pull out any rows that have "spk" in the SampleID column
spks <- sampledat %>%
  filter(str_detect(Sample_ID, "spk")) #have to change this to match data
head(spks)
```

```
##           Sample_ID S04_ppm Cl_ppm S04_mM Cl_mM
## 1 26_MSM_202208_WC_SipC_45cm_spk 290.4766 6810.1389 9.060405 1.921055e+02
## 2 37_MSM_202208_RHZ_UP_SF_8_spk 178.5871 1666.1291 5.570402 4.699941e+01
## 3 45_MSM_202208_RHZ_TR_SF_8_spk 649.8361 4082.0336 20.269373 1.151490e+02
## 4 8_MSM_202208_UP_LysC_45cm_spk 156.6900 0.0336 4.887399 9.478138e-04
##           salinity
## 1 1.230595e+01
## 2 3.010721e+00
## 3 7.376261e+00
## 4 8.671520e-05
```

```
#remove the dup from these IDs so we will have duplicate sample names
spks$Sample_ID<-gsub("_spk","",as.character(spks$Sample_ID))
spks <- spks[ ,-c(2,3, 5,6)]
colnames(spks) <- c('Sample_ID', 'S04_mM_spk')
head(spks)
```

```
##           Sample_ID S04_mM_spk
## 1 26_MSM_202208_WC_SipC_45cm 9.060405
## 2 37_MSM_202208_RHZ_UP_SF_8 5.570402
## 3 45_MSM_202208_RHZ_TR_SF_8 20.269373
## 4 8_MSM_202208_UP_LysC_45cm 4.887399
```

```
#put it back together with the old data set and look for duplicates
QAspks <- merge(sampledat, spks)
head(QAspks)
```

```
##           Sample_ID S04_ppm Cl_ppm S04_mM Cl_mM
## 1 26_MSM_202208_WC_SipC_45cm 52.4325 6240.8845 1.6354492 176.04751763
## 2 37_MSM_202208_RHZ_UP_SF_8 60.4674 1640.4626 1.8860699 46.27539069
## 3 45_MSM_202208_RHZ_TR_SF_8 520.7936 3992.5401 16.2443419 112.62454443
## 4 8_MSM_202208_UP_LysC_45cm 9.8873 2.0883 0.3083999 0.05890832
##           salinity S04_mM_spk
## 1 11.277304292 9.060405
```

```
## 2 2.964341918 5.570402
## 3 7.214545961 20.269373
## 4 0.003799558 4.887399
```

```
#now we need to calculate the spike concentration and calculate the spike recovery
spkconc <- (250/smw)      # in mM
spkvol <- 10              # in uL
spkvol <- spkvol/1000000
#spike for these samples was 10uL of the 250mM standard
QAspks$SO4_spk_Conc <- (spkconc)*spkvol      # mmoles of SO4
head(QAspks)
```

```
##           Sample_ID  SO4_ppm  Cl_ppm  SO4_mM  Cl_mM
## 1 26_MSM_202208_WC_SipC_45cm 52.4325 6240.8845 1.6354492 176.04751763
## 2 37_MSM_202208_RHZ_UP_SF_8 60.4674 1640.4626 1.8860699 46.27539069
## 3 45_MSM_202208_RHZ_TR_SF_8 520.7936 3992.5401 16.2443419 112.62454443
## 4 8_MSM_202208_UP_LysC_45cm 9.8873 2.0883 0.3083999 0.05890832
##      salinity SO4_mM_spk SO4_spk_Conc
## 1 11.277304292 9.060405 7.797879e-05
## 2 2.964341918 5.570402 7.797879e-05
## 3 7.214545961 20.269373 7.797879e-05
## 4 0.003799558 4.887399 7.797879e-05
```

```
#need to determine dilution factors and initial amount of sample added
#if your samples are all the same dilution just use the first line
#for Steph / COMPASS this depends on the site so...
QAspks$Dilution <- 1
QAspks$Dilution <- ifelse(str_detect(QAspks$Sample_ID, "MSM_UP"), 50, QAspks$Dilution)
QAspks$Dilution <- ifelse(str_detect(QAspks$Sample_ID, "MSM_TR"), 50, QAspks$Dilution)
QAspks$Dilution <- ifelse(str_detect(QAspks$Sample_ID, "MSM_WC"), 100, QAspks$Dilution)
QAspks$Dilution <- ifelse(str_detect(QAspks$Sample_ID, "GCrew_UP"), 50, QAspks$Dilution)
QAspks$Dilution <- ifelse(str_detect(QAspks$Sample_ID, "GCrew_TR"), 50, QAspks$Dilution)
QAspks$Dilution <- ifelse(str_detect(QAspks$Sample_ID, "GCrew_WC"), 100, QAspks$Dilution)
QAspks$Dilution <- ifelse(str_detect(QAspks$Sample_ID, "GWI_UP"), 100, QAspks$Dilution)
QAspks$Dilution <- ifelse(str_detect(QAspks$Sample_ID, "GWI_TR"), 100, QAspks$Dilution)
QAspks$Dilution <- ifelse(str_detect(QAspks$Sample_ID, "GWI_WC"), 200, QAspks$Dilution)
#QAspks$Dilution <- ifelse(str_detect(QAspks$Sample_ID, "SWH_UP"), 100, QAspks$Dilution)
#QAspks$Dilution <- ifelse(str_detect(QAspks$Sample_ID, "SWH_TR"), 100, QAspks$Dilution)
#QAspks$Dilution <- ifelse(str_detect(QAspks$Sample_ID, "SWH_WC"), 100, QAspks$Dilution)

#Set Sample volumes in uL
QAspks$SampleVol <- 1
QAspks$SampleVol <- ifelse(str_detect(QAspks$Sample_ID, "MSM_UP"), 1501, QAspks$SampleVol)
QAspks$SampleVol <- ifelse(str_detect(QAspks$Sample_ID, "MSM_TR"), 1501, QAspks$SampleVol)
QAspks$SampleVol <- ifelse(str_detect(QAspks$Sample_ID, "MSM_WC"), 1475, QAspks$SampleVol)
QAspks$SampleVol <- ifelse(str_detect(QAspks$Sample_ID, "GCrew_UP"), 1501, QAspks$SampleVol)
QAspks$SampleVol <- ifelse(str_detect(QAspks$Sample_ID, "GCrew_TR"), 1501, QAspks$SampleVol)
QAspks$SampleVol <- ifelse(str_detect(QAspks$Sample_ID, "GCrew_WC"), 1475, QAspks$SampleVol)
QAspks$SampleVol <- ifelse(str_detect(QAspks$Sample_ID, "GWI_UP"), 1475, QAspks$SampleVol)
QAspks$SampleVol <- ifelse(str_detect(QAspks$Sample_ID, "GWI_TR"), 1475, QAspks$SampleVol)
QAspks$SampleVol <- ifelse(str_detect(QAspks$Sample_ID, "GWI_WC"), 1462, QAspks$SampleVol)
#QAspks$SampleVol <- ifelse(str_detect(QAspks$Sample_ID, "SWH_UP"), 100, QAspks$SampleVol)
#QAspks$SampleVol <- ifelse(str_detect(QAspks$Sample_ID, "SWH_TR"), 100, QAspks$SampleVol)
```

```
#QAspks$SampleVol <- ifelse(str_detect(QAspks$Sample_ID, "SWH_WC"), 100, QAspks$SampleVol)

#change sample volume to L
QAspks$SampleVol <- QAspks$SampleVol/1000000
head(QAspks)
```

```
##           Sample_ID  S04_ppm  Cl_ppm  S04_mM  Cl_mM
## 1 26_MSM_202208_WC_SipC_45cm 52.4325 6240.8845 1.6354492 176.04751763
## 2 37_MSM_202208_RHZ_UP_SF_8 60.4674 1640.4626 1.8860699 46.27539069
## 3 45_MSM_202208_RHZ_TR_SF_8 520.7936 3992.5401 16.2443419 112.62454443
## 4 8_MSM_202208_UP_LysC_45cm 9.8873 2.0883 0.3083999 0.05890832
##           salinity S04_mM_spk S04_spk_Conc Dilution SampleVol
## 1 11.277304292 9.060405 7.797879e-05 1 1e-06
## 2 2.964341918 5.570402 7.797879e-05 1 1e-06
## 3 7.214545961 20.269373 7.797879e-05 1 1e-06
## 4 0.003799558 4.887399 7.797879e-05 1 1e-06
```

```
#gives us the total S04 in the sample in mmoles
QAspks$S04_Total_unspkd <- (QAspks$S04_mM/QAspks$Dilution)*(QAspks$SampleVol)

##total S04 in spiked sample in mmoles
QAspks$S04_Total_spkd <- (QAspks$S04_mM_spk/QAspks$Dilution)*(QAspks$SampleVol+spkvol)

QAspks$S04_expctd_spkd <- (QAspks$S04_Total_unspkd + QAspks$S04_spk_Conc)
QAspks$spk_recovery <- (QAspks$S04_Total_spkd/QAspks$S04_expctd_spkd)*100
QAspks$S04_spks_flag <- ifelse(QAspks$spk_recovery <=120 & QAspks$spk_recovery >=80 , 'YES', 'NO, rerun')


head(QAspks)
```

```
##           Sample_ID  S04_ppm  Cl_ppm  S04_mM  Cl_mM
## 1 26_MSM_202208_WC_SipC_45cm 52.4325 6240.8845 1.6354492 176.04751763
## 2 37_MSM_202208_RHZ_UP_SF_8 60.4674 1640.4626 1.8860699 46.27539069
## 3 45_MSM_202208_RHZ_TR_SF_8 520.7936 3992.5401 16.2443419 112.62454443
## 4 8_MSM_202208_UP_LysC_45cm 9.8873 2.0883 0.3083999 0.05890832
##           salinity S04_mM_spk S04_spk_Conc Dilution SampleVol S04_Total_unspkd
## 1 11.277304292 9.060405 7.797879e-05 1 1e-06 1.635449e-06
## 2 2.964341918 5.570402 7.797879e-05 1 1e-06 1.886070e-06
## 3 7.214545961 20.269373 7.797879e-05 1 1e-06 1.624434e-05
## 4 0.003799558 4.887399 7.797879e-05 1 1e-06 3.083999e-07
## S04_Total_spkd S04_expctd_spkd spk_recovery S04_spks_flag
## 1 9.966446e-05 7.961424e-05 125.18422 NO, rerun
## 2 6.127443e-05 7.986486e-05 76.72264 NO, rerun
## 3 2.229631e-04 9.422313e-05 236.63309 NO, rerun
## 4 5.376138e-05 7.828719e-05 68.67201 NO, rerun
```

```
#plot spk recoveries output as a bar graph to easily check - want any over 10% to be red need to work on
spksbar <- ggplot(data = QAspks, aes(x = Sample_ID, y = spk_recovery)) +
  geom_bar(stat = 'identity') +
  scale_fill_manual(values=c("lightblue4")) +
  theme_classic() + labs(x= "Sample ID", y="Spike Recovery (%)") +
  theme(legend.position="none") +
  geom_hline(yintercept=80, linetype="dashed", color = "black", size=1) +
```

```
geom_hline(yintercept=120, linetype="dashed", color = "black", size=1)
```

spksbar



```
#check for percent of no, reruns to see if it would warrant reruns
Perc_spks <- QAspks %>%
  group_by(S04_spks_flag) %>%
  summarise(no_rows = length(S04_spks_flag))
Perc_spks$Total <- length(QAspks$S04_spks_flag)
Perc_spks$Percent <- (Perc_spks$no_rows / Perc_spks$Total)*100
head(Perc_spks)
```

```
## # A tibble: 1 x 4
##   S04_spks_flag no_rows Total Percent
##   <chr>         <int> <int>   <dbl>
## 1 NO, rerun      4      4     100
```

Make final dataframe with IDs

```
#for steph <- pull out identifiers of the sample names
#pull the sample ID and separate it by the underscores
IDs <- data.frame(do.call('rbind', strsplit(as.character(sampledat2$Sample_ID), '_ ', fixed=TRUE)))
```

```
## Warning in rbind(c("1", "MSM", "202208", "UP", "LysA", "20cm"), c("10", :
## number of columns of result is not a multiple of vector length (arg 1)
```

```
colnames(IDs) <- c("Analysis_No" , "Date","Site", "Zone", "Replicate", "Depth", "Tree")
head(IDs)
```

```
##   Analysis_No Date   Site Zone Replicate Depth Tree
## 1           1  MSM 202208  UP      LysA  20cm   1
## 2          10  MSM 202208  TR      LysA  20cm  10
## 3          11  MSM 202208  TR      LysA  45cm  11
## 4          12  MSM 202208  TR      LysB  10cm  12
## 5          13  MSM 202208  TR      LysB  20cm  13
## 6          14  MSM 202208  TR      LysB  45cm  14
```

```
#rejoin them to the dataframe
alldat <- cbind(IDs, sampled2)
head(alldat)
```

```
##   Analysis_No Date   Site Zone Replicate Depth Tree           Sample_ID
## 1           1  MSM 202208  UP      LysA  20cm   1 1_MSM_202208_UP_LysA_20cm
## 2          10  MSM 202208  TR      LysA  20cm  10 10_MSM_202208_TR_LysA_20cm
## 3          11  MSM 202208  TR      LysA  45cm  11 11_MSM_202208_TR_LysA_45cm
## 4          12  MSM 202208  TR      LysB  10cm  12 12_MSM_202208_TR_LysB_10cm
## 5          13  MSM 202208  TR      LysB  20cm  13 13_MSM_202208_TR_LysB_20cm
## 6          14  MSM 202208  TR      LysB  45cm  14 14_MSM_202208_TR_LysB_45cm
##   S04_ppm  Cl_ppm   S04_mM   Cl_mM salinity
## 1 157.5194 1860.322  4.913269 52.47736 3.361629
## 2 406.2132 2697.053 12.670405 76.08049 4.873601
## 3 469.2068 3444.071 14.635271 97.15292 6.223462
## 4 378.0426 2925.598 11.791722 82.52745 5.286582
## 5 169.5410 2694.274  5.288241 76.00210 4.868580
## 6 285.5842 3085.438  8.907804 87.03632 5.575412
```

## Make final dataframe with IDs

```
write.csv(alldat, file="Processed Data/COMPASS_SynopticCB_PW_Processed_Cl_S04_202208a.csv") #Change fi
```

END