


Balanced Trees



Categories of Data Structures

Linear Ordered

Lists

Stacks


Queues



Non-linear Ordered

Trees


Graphs



Not Ordered

Sets

Tables/Maps




Recap

- **Binary Search Trees**

- **Operations**
- **Traversals**

Non-linear Ordered


Trees




Agenda

- **Trees**
 - **More Properties Related to Height**
- **Binary Search Tree Performance**
- **Rotations**
- **Balanced Trees: AVL Trees**
 - **Properties**
 - **Insertion/Deletion**
 - **Performance**

How do we fix the Worst Case?




- Never add new leaves at the bottom: **Increase size of node**
- **Transform** the “Spindly” Tree to “Bushy Tree” using Tools and Algorithms



Rotations

Rotations

Tools to Rearrange the Tree Without affecting its **Semantics**




BST Insertion: Inventing the Tool


$n!$ different ways to insert n elements,

Catalan (n) different BSTs


1, 2, 3




1, 3, 2





3, 1, 2



3, 2, 1




2, 3, 1 or 2, 1, 3




Goal


1, 2, 3




1, 3, 2




3, 1, 2




3, 2, 1



2, 3, 1 or 2, 1, 3



Left Rotation: Right Right Case




Left Rotation: Right Right Case



Single Rotation



Left Rotation: Right Right Case

```
rotateLeft (node)
{
    grandchild = node->right->left;
    newParent = node->right;
    newParent->left = node;
    node->right = grandchild;
    return newParent;
}
```



Left Rotation: Right Right Case



```
rotateLeft (node)
{
    grandchild = node->right->left;
    newParent = node->right;
    newParent->left = node;
    node->right = grandchild;
    return newParent;
}
```




Left Rotation: Right Right Case

```
rotateLeft (node)
{
    grandchild = node->right->left;
    newParent = node->right;
    newParent->left = node;
    node->right = grandchild;
    return newParent;
}
```


Take Constant Time, $O(1)$



Right Rotation: Left Left Case




Right Rotation: Left Left Case




Single Rotation

Right Left Rotation: Right Left Case




Right Left Rotation: Right Left Case




Double Rotation

Left Right Rotation: Left Right Case




Left Right Rotation: Left Right Case




Double Rotation

Take Constant Time, $O(1)$


Tool Issue: Can Get Messy on a Prebuilt Tree



Fix for Messiness




AVL Trees




Adelson-Velsky and Landis Trees

- **Height Balanced Binary Search Trees**
- **Invariants:**
 - **Maintains BST invariants**
 - Every node has 0, 1, or 2 children
 - Every element on the left is smaller and every element on the right is greater than a node.
 - **For every node x , Balance Factor = 0, -1 or 1**




AVL Tree


Balance Factor of x = Height (left subtree of x) - Height (right subtree of x)




Left Rotation: Right Right Case




Right Rotation: Left Left Case



Right Left Rotation: Right Left Case



Left Right Rotation: Left Right Case



AVL Tree Rotations


Balance Factor of x = Height (left subtree of x) - Height (right subtree of x)

Case (Alignment)	Balance Factor		Rotation
	Parent	Child	
Left Left	+2	+1	Right
Right Right	-2	-1	Left
Left Right	+2	-1	Left Right
Right Left	-2	+1	Right Left

If Balance Factor of x = Height (right subtree of x) - Height (left subtree of x),
Reverse all signs in the table!

AVL Tree


Height of an AVL Tree with n Nodes = $1.44 \log_2 (n+2)$



AVL Insert, Delete and Search


Worst Case ~ Height = $\log n$

And Common Operations will be $O(\log n)$



AVL Trees: Insertion/Deletion

- Same as **Binary Search Trees**
- Identify **deepest node that breaks the Balance Factor rule**;
Start rotating and move further **up** the search path
- After Insertion/Deletion **height of all nodes in Search Path**
may change



AVL Tree : C++ Insert

```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);

    else if (key < root->val)
        root->left = insert(root->left, key);

    else
        root->right = insert(root->right, key);
    // hint: find height
    return root;
}
```


```
IF tree is right heavy
{
    IF tree's right subtree is left heavy
        Perform Right Left rotation
    ELSE
        Perform Left rotation
}
ELSE IF tree is left heavy
{
    IF tree's left subtree is right heavy
        Perform Left Right rotation
    ELSE
        Perform Right rotation
}
```

AVL Tree : Insert

Insert 25

```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```




AVL Tree : Insert

25

Insert 25

```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```




AVL Tree : Insert

25

Insert 22


```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```




AVL Tree : Insert

Insert 22




```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```




AVL Tree : Insert

Insert 4




```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```




AVL Tree : Insert



```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```



AVL Tree : Insert



```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```

AVL Tree : Insert




```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```



AVL Tree : Insert




```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);


    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```

```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```



AVL Tree : Insert



```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```




```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```



AVL Tree : Insert



```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```




```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);


    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```

```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```



AVL Tree : Insert



```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```




```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);


    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```

```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```



AVL Tree : Insert



```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```

```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);


    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```

```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```



AVL Tree : Insert




```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```

```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```


AVL Tree : Insert




```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```

```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```

AVL Tree : Insert




```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```

```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```

AVL Tree : Insert



```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);


    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```

```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```




AVL Tree : Insert




```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```



AVL Tree : Insert




```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```




AVL Tree : Insert



```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```


AVL Tree : Insert



```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```


AVL Tree : Insert



```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```



AVL Tree : Insert



```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);


    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```

AVL Tree : Insert




AVL Tree : Insert

Insert 1




```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```



AVL Tree : Insert

Insert 1




```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```


AVL Tree : Insert

Insert 2




```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```



AVL Tree : Insert

Insert 2




```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);
    else if (key < root->val)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);

    IF tree is right heavy
        IF tree's right subtree is left heavy
            Perform Right Left rotation
        ELSE
            Perform Left rotation
    ELSE IF tree is left heavy
        IF tree's left subtree is right heavy
            Perform Left Right rotation
        ELSE
            Perform Right rotation
    }
    return root;
}
```


AVL Tree : Insert

Insert 2



AVL Tree : C++ Node Class

```
01 class TreeNode {
02     public:
03         int val;
04         int height; // Or Balance Factor
05         TreeNode *left;
06         TreeNode *right;
07         TreeNode(int x) : val(x), left(nullptr), right(nullptr) {}
08 };
```



AVL Tree : C++ Insert

```
TreeNode* insert(TreeNode* root, int key)
{
    if (root == nullptr)
        return new TreeNode(key);

    else if (key < root->val)
        root->left = insert(root->left, key);

    else
        root->right = insert(root->right, key);

    return root;
}
```

```
IF tree is right heavy
{
    IF tree's right subtree is left heavy
        Perform Right Left rotation
    ELSE
        Perform Left rotation
}
ELSE IF tree is left heavy
{
    IF tree's left subtree is right heavy
        Perform Left Right rotation
    ELSE
        Perform Right rotation
}
```

Questions


Agenda

- **B Trees**


- **Properties**
- **Insertion**
- **Use Cases**
- **B Trees vs B+ Trees**

- **Splay Trees**

- **Properties**




How do we fix the Worst Case in a BST?




- Transform the “Spindly” Tree to “Bushy Tree” using Tools and Algorithms (Transformation)
- Never add new leaves at the bottom: Increase size of node (Alter the Structure by Design)

Insertion in Non-Random Order

Insert 100, 101, 111,
115, 120, 135




Insertion in Non-Random Order




Insertion in Non-Random Order

- Can lead to overstuffing
- Overstuffed trees have better balanced height
- Consistent BST



Insertion in Non-Random Order

- Can lead to overstuffing
- Overstuffed trees have better balanced height
- Consistent BST





Fixes the height imbalance problem

Doesn't fix Non-random insertion


Insertion in Non-Random Order

- Can lead to overstuffing
- Overstuffed trees have better balanced height
- Consistent BST

Fix: Set a limit, **L** on the node filling





B Trees



Property #1




Each Node is a Block Containing Multiple “Keys”, Keys at most 1

5	7	25	44
---	---	----	----




Property #1

Each Node is a Block Containing Multiple “Keys”, Keys at most 1




Property #2

B Trees are n-ary Trees, each node has up to n children. They follow BST property



Property #2

B Trees are n-ary Trees, each node has up to n children. They follow BST property




n Children, here n = 3

Not a Binary Tree!


Property #3

Tree Building is Bottom-up




Property #4

Order “n” tree has at most n children (n=2, l=1 is a BST)



Property #5


Leaves are at same depth



Property #6

Keys


- Non-leaf nodes store up to $n-1$ keys. Thus, l is at most $n-1$ for internal nodes.
- All keys are in Sorted Order
- Leaf nodes have $[\text{ceil}(l/2), l]$ keys except when tree has less than $l/2$ elements (Not strictly enforced)



Property #7


Children

- Root is a leaf or has $[2, n]$ children
- Non-leaf nodes have $[\text{ceil}(n/2), n]$ children




Properties Summary

- **Each Node is a Block Containing Multiple “Keys”**
- **B Trees are n-ary Trees or have an order “n”**
- **Children**
 - **Root is a leaf or has $[2, n]$ children**
 - **Non-leaf nodes have $[\text{ceil}(n/2), n]$ children**
 - **Maximum children is at most n for all nodes**
- **Keys**
 - **All keys are in Sorted Order**
 - **Non-leaf nodes store up to n-1 keys**
 - **Leaf nodes have $[\text{ceil}(l/2), l]$ keys except when tree has less than $l/2$ elements (Not strictly enforced)**
- **All leaves are at same depth, so the tree is always balanced**
- **Data items are stored in leaves and non-leaf nodes in a B Tree. In a B+ Tree, data is stored in only leaves**
- **When a node is full Splitting occurs**




Examples

- **B-trees of order $n=4$, $l=3$ are also called a 2-3-4 tree or a 2-4 tree.**
 - “2-3-4” refers to the number of children that a node can have, e.g. a 2-3-4 tree node may have 2, 3, or 4 children.
- **B-trees of order $n=3$, $l=2$ are also called a 2-3 tree.**
- **l can be very large in case of file systems**



2-3-4 a.k.a. 2-4 Tree:
Max 3 items per node.
Max 4 non-null children per node.
 $n=4$, $l=3$



2-3 Tree ($l=2$):
Max 2 items per node.
Max 3 non-null children per node.
 $n=3$, $l=2$


B Tree Insertion

2-3 Tree (L=2):

Max 2 items per node.

Max 3 non-null children per node.

Insert 1




B Tree

2-3 Tree (L=2):

Max 2 items per node.

Max 3 non-null children per node.

Insert 1






B Tree

2-3 Tree (L=2):

Max 2 items per node.

Max 3 non-null children per node.

Insert 1







B Tree


2-3 Tree (L=2):

Max 2 items per node.


Max 3 non-null children per node.



Height is still perfectly balanced!




B+ Tree



B Tree + All data is stored in the leaves +
The leaves have pointers to the other leaves forming a linked list for faster traversal


https://en.wikipedia.org/wiki/B%2B_tree

B+ Tree



B+ Tree Insertion


N = 4 (at most 4 children and 3 keys in a non-leaf node),
L = 5 (at most 5 keys in a leaf node)



B+ Tree Insertion


N = 4 (at most 4 children and 3 keys in a non-leaf node),
L = 5 (at most 5 keys in a leaf node)

Add 40




B+ Tree Insertion

N = 4 (at most 4 children and 3 keys in a non-leaf node),
L = 5 (at most 5 keys in a leaf node)




B+ Tree Insertion

N = 4 (at most 4 children and 3 keys in a non-leaf node),
L = 5 (at most 5 keys in a leaf node)




B+ Tree Insertion

N = 4 (at most 4 children and 3 keys in a non-leaf node),
L = 5 (at most 5 keys in a leaf node)




B+ Tree Insertion

N = 4 (at most 4 children and 3 keys in a non-leaf node),
L = 5 (at most 5 keys in a leaf node)




B+ Tree Insertion

N = 4 (at most 4 children and 3 keys in a non-leaf node),
L = 5 (at most 5 keys in a leaf node)




B+ Tree Insertion

N = 4 (at most 4 children and 3 keys in a non-leaf node),
L = 5 (at most 5 keys in a leaf node)



B+ Tree

A completely full B+ Tree with $N=3$ and $L=3$ and height = 2 (has level 0, 1, 2) has how many unique values?



B+ Tree

A completely full B+ Tree with $N=3$ and $L=3$ and height = 2 (has level 0, 1, 2) has how many unique values?


Level 0 - 2 values

Level 1 - 3 nodes, each with 2 values = 6 values

Level 2 - $3*3 = 9$ nodes, each with 3 values = 27 values - 6 - 2 = 19

$$2+6+19=27$$

Or, root has 3 children, each child has 3 children. So 9 leaves. Each leaf has 3 values. So 27 values.




Use Case

- **Hard Drives, Databases, Filesystems**
- **Indexing Example**
 - **Tracks, Sectors and Blocks**

Performance

- **Height: Between $\sim \log_{l+1}(n)$ and $\sim \log_2(n)$**
- **Largest possible height is all non-leaf nodes have $l/2$ items**
- **Smallest possible height is all nodes have l items**
- **Overall height is therefore $O(\log n)$**
- **Search Time: $O(hl) \sim O(l \log(n))$, where**
 - **h is height of tree**
 - **n is maximum number of children**
 - **l is maximum number of keys**
- **Search Time: $O(\log(n))$, as l is a constant**




Mentimeter


menti.com
5253 8085



Splay Tree




Searching for Random Inputs



$O(n)$ or $O(\log n)$ in BST or AVL Tree


Searching for Non-Random Inputs



$O(n)$ or $O(\log n)$ in BST or AVL Tree

What if the Input is non-Random?

Enter Splay Tree




If we are searching 91 again and again, bring it closer to root!

Simple Rotation won't work!

Special rotations involving grandparent, parent and child.

Enter Splay Tree




A splay tree is a self-balancing binary search tree with the additional property that recently accessed elements are quick to access again.

Splay Tree


- A binary search tree with the additional property that **recently accessed elements are quick to access again**
- For many sequences of non-random operations, splay trees perform better than other search trees
- The splay tree was invented by Daniel Sleator and Robert Tarjan
- All normal operations on a binary search tree are combined with one basic operation, called **splaying**. Splaying the tree for a certain element rearranges the tree so that the element is placed at the root of the tree.

https://en.wikipedia.org/wiki/Splay_tree




Splay Tree: Zig Rotation

Search x
 $\text{Splay}(x)$




Zig = Right Rotation ($\text{Splay}(x)$, x is left of parent and has no grandparent)




Splay Tree: Zig Rotation

Search x
Splay(x)




Zig = Right Rotation (Splay(x), x is left of parent and has no grandparent)




Splay Tree: Zag Rotation (Zig)

Search x
Splay(x)




Zag = Left Rotation (Splay(x), x is right of parent and has no grandparent)




Splay Tree: Zag Rotation (Zig)

Search x
Splay(x)




Zag




Zag = Left Rotation (Splay(x), x is right of parent and has no grandparent)

Splay Tree: Zig Zig Rotation




Splay Tree: Zig Zig Rotation




Splay Tree: Zig Zag Rotation


Search y
Splay(y)



Zig-Zag



Splay Tree: Basic Idea



The basic idea of a splay tree is that after a node is accessed, it is pushed to the root via a series of rotations. And it does manage to shorten the tree.


Start at bottom and move up! `Splay(N)` till `N.Parent == null`

Splay Tree: Insert/Search

- Same as BST followed by a Splay Operation on the searched node or newly inserted node
- **Splay(N)**
 - ❖ Determine proper case for rotation and apply
 - **Zig Zig**
 - **Zig Zag**
 - **Zig**
 - ❖ If N.Parent != null:
 - **Splay(N)**


Splay Tree: Performance

- A splay tree is a data structure that guarantees that m tree operations will take $O(m \log n)$ time, where n is number of nodes
- On average, a tree operation is $O(\log n)$
- In the worst case, an operation is $O(n)$, but subsequent operations are fast
- Implemented in Cache and Garbage Collection




Mentimeter

What will be the value of root node if we insert 4 into this Splay Tree?



Mentimeter


What will be the value of root node if we insert 4 into this Splay Tree?



Resources

- B+ Tree Visualization: <https://www.cs.usfca.edu/~galles/visualization/BPlusTree.html>
- Splay Tree Visualization: <https://www.cs.usfca.edu/~galles/visualization/SplayTree.html>
- Original Paper, Splay Tree: <https://www.cs.cmu.edu/~sleator/papers/self-adjusting.pdf>
- <https://stackoverflow.com/questions/7467079/difference-between-avl-trees-and-splay-trees>


Red Black Tree



Red Black Tree Properties


A red-black tree maintains the following invariants:

1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black



Red Black Tree General Idea

- Color is stored as a Boolean in the **TreeNode** class
- Fixing the tree invariants by **rotation** or through **color flips**




Red Black Tree Insertion

- Insert the item into the binary search tree as usual
- Color it red
- If the tree is empty, color it black and make it a root, we are done


Red Black Tree Insertion

- Insert the item into the binary search tree as usual
- Color it red
- If the tree is empty, color it black and make it a root, we are done




Red Black Tree Insertion

- Insert the item into the binary search tree as usual
- Color it red
- If the parent is black, we are done





Red Black Tree Insertion

- Insert the item into the binary search tree as usual
- Color it red
- If the parent is red, look at the aunt/uncle or parent's sibling



Red Black Tree Insertion


- If the uncle is red, **flip colors**
- If the uncle is black, **rotate**
- **After Rotation** **After Color Flip (P, GP)**




Example

Insert 3

- If the uncle is red, flip colors
- If the uncle is black, rotate
- After Rotation



After Color Flip (P, GP)



A red-black tree maintains the following invariants:


1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 3



- If the uncle is red, flip colors
- If the uncle is black, rotate
- After Rotation



After Color Flip (P, GP)




A red-black tree maintains the following invariants:

1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 3




- If the uncle is red, flip colors

- If the uncle is black, rotate

- After Rotation



- After Color Flip (P, GP)



A red-black tree maintains the following invariants:


1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 1



- If the uncle is red, flip colors
- If the uncle is black, rotate
- After Rotation



After Color Flip (P, GP)




A red-black tree maintains the following invariants:


1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 1



- If the uncle is red, flip colors
- If the uncle is black, rotate
- After Rotation



After Color Flip (P, GP)




A red-black tree maintains the following invariants:

1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 5




- If the uncle is red, flip colors

- If the uncle is black, rotate

- After Rotation



- After Color Flip (P, GP)




A red-black tree maintains the following invariants:

1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 5




- If the uncle is red, flip colors

- If the uncle is black, rotate

- After Rotation



- After Color Flip (P, GP)




A red-black tree maintains the following invariants:


1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 7



- If the uncle is red, flip colors
- If the uncle is black, rotate
- After Rotation



After Color Flip (P, GP)




A red-black tree maintains the following invariants:


1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 7



- If the uncle is red, flip colors
- If the uncle is black, rotate
- After Rotation



After Color Flip (P, GP)




A red-black tree maintains the following invariants:


1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 7



- If the uncle is red, flip colors
- If the uncle is black, rotate
- After Rotation



After Color Flip (P, GP)




A red-black tree maintains the following invariants:


1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 7



- If the uncle is red, flip colors
- If the uncle is black, rotate
- After Rotation



After Color Flip (P, GP)




A red-black tree maintains the following invariants:


1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 7



- If the uncle is red, flip colors
- If the uncle is black, rotate
- After Rotation



After Color Flip (P, GP)




A red-black tree maintains the following invariants:

1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 6




- If the uncle is red, flip colors

- If the uncle is black, rotate

- After Rotation



- After Color Flip (P, GP)




A red-black tree maintains the following invariants:

1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 6




- If the uncle is red, flip colors

- If the uncle is black, rotate

- After Rotation



- After Color Flip (P, GP)




A red-black tree maintains the following invariants:

1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 6




- If the uncle is red, flip colors

- If the uncle is black, rotate

After Rotation



After Color Flip (P, GP)




A red-black tree maintains the following invariants:

1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black


Example

Insert 6




- If the uncle is red, flip colors
- If the uncle is black, rotate

After Rotation



After Color Flip (P, GP)




A red-black tree maintains the following invariants:

1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 6




- If the uncle is red, flip colors

- If the uncle is black, rotate

After Rotation



After Color Flip (P, GP)




A red-black tree maintains the following invariants:

1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 6




- If the uncle is red, flip colors

- If the uncle is black, rotate

- After Rotation



- After Color Flip (P, GP)





A red-black tree maintains the following invariants:

1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 6




- If the uncle is red, flip colors

- If the uncle is black, rotate

After Rotation



After Color Flip (P, GP)




A red-black tree maintains the following invariants:

1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 8




- If the uncle is red, flip colors

- If the uncle is black, rotate

- After Rotation



- After Color Flip (P, GP)




A red-black tree maintains the following invariants:

1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 8




- If the uncle is red, flip colors

- If the uncle is black, rotate

- After Rotation



- After Color Flip (P, GP)




A red-black tree maintains the following invariants:


1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 8



- If the uncle is red, flip colors
- If the uncle is black, rotate
- After Rotation



After Color Flip (P, GP)




A red-black tree maintains the following invariants:


1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 8



- If the uncle is red, flip colors
- If the uncle is black, rotate
- After Rotation



After Color Flip (P, GP)




A red-black tree maintains the following invariants:


1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 8



- If the uncle is red, flip colors
- If the uncle is black, rotate
- After Rotation



After Color Flip (P, GP)




A red-black tree maintains the following invariants:

1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 9




- If the uncle is red, flip colors

- If the uncle is black, rotate

- After Rotation



- After Color Flip (P, GP)




A red-black tree maintains the following invariants:

1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 9




- If the uncle is red, flip colors

- If the uncle is black, rotate

- After Rotation



- After Color Flip (P, GP)




A red-black tree maintains the following invariants:

1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 9




- If the uncle is red, flip colors

- If the uncle is black, rotate

- After Rotation



- After Color Flip (P, GP)




A red-black tree maintains the following invariants:

1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 9




- If the uncle is red, flip colors

- If the uncle is black, rotate

After Rotation



After Color Flip (P, GP)




A red-black tree maintains the following invariants:

1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 9




- If the uncle is red, flip colors

- If the uncle is black, rotate

After Rotation



After Color Flip (P, GP)




A red-black tree maintains the following invariants:

1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 9




- If the uncle is red, flip colors

- If the uncle is black, rotate

After Rotation



After Color Flip (P, GP)




A red-black tree maintains the following invariants:

1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 9




- If the uncle is red, flip colors

- If the uncle is black, rotate

- After Rotation



- After Color Flip (P, GP)




A red-black tree maintains the following invariants:

1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 10




- If the uncle is red, flip colors

- If the uncle is black, rotate

- After Rotation



- After Color Flip (P, GP)




A red-black tree maintains the following invariants:

1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 10




- If the uncle is red, flip colors

- If the uncle is black, rotate

- After Rotation



- After Color Flip (P, GP)




A red-black tree maintains the following invariants:


1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 10



- If the uncle is red, flip colors
- If the uncle is black, rotate
- After Rotation



After Color Flip (P, GP)




A red-black tree maintains the following invariants:


1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 10



- If the uncle is red, flip colors
- If the uncle is black, rotate
- After Rotation



After Color Flip (P, GP)




A red-black tree maintains the following invariants:


1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 10



- If the uncle is red, flip colors
- If the uncle is black, rotate
- After Rotation



After Color Flip (P, GP)




A red-black tree maintains the following invariants:


1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 10



- If the uncle is red, flip colors
- If the uncle is black, rotate
- After Rotation



After Color Flip (P, GP)




A red-black tree maintains the following invariants:

1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 10




- If the uncle is red, flip colors

- If the uncle is black, rotate

After Rotation



After Color Flip (P, GP)




A red-black tree maintains the following invariants:

1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 10




- If the uncle is red, flip colors

- If the uncle is black, rotate

- After Rotation



- After Color Flip (P, GP)




A red-black tree maintains the following invariants:

1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 10




- If the uncle is red, flip colors

- If the uncle is black, rotate

After Rotation



After Color Flip (P, GP)




A red-black tree maintains the following invariants:

1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Example


Insert 10




- If the uncle is red, flip colors

- If the uncle is black, rotate

After Rotation



After Color Flip (P, GP)




A red-black tree maintains the following invariants:

1. A node is either red or black
2. The root is always black
3. A red node always has black children (a null reference is considered to refer to a black node) Or No two consecutive Red nodes
4. The number of black nodes in any path from the root to a leaf is the same
5. Null nodes are attached to the leaves and are black

Red Black Tree Insertion

```
RBTreeBalance(tree, node)
{
    if (node->parent == null)
    {
        node->color = black
        return
    }
    if (node->parent->color == black)
        return
    parent = node->parent
    grandparent = RBTreeGetGrandparent(node)
    uncle = RBTreeGetUncle(node)
    if (uncle != null && uncle->color == red)
    {
        parent->color = uncle->color = black
        grandparent->color = red
        RBTreeBalance(tree, grandparent)
        return
    }
    if (node == parent->right && parent == grandparent->left)
    {
        RBTreeRotateLeft(tree, parent)
        node = parent
        parent = node->parent
    }
    else if (node == parent->left && parent == grandparent->right)
    {
        RBTreeRotateRight(tree, parent)
        node = parent
        parent = node->parent
    }
    parent->color = black
    grandparent->color = red
    if (node == parent->left)
        RBTreeRotateRight(tree, grandparent)
    else
        RBTreeRotateLeft(tree, grandparent) }
```




Red Black Tree Insertion

1. Search (top-down) and insert the new item u as in a Binary Search Tree.
2. Return (bottom-up) and
 - 2.1 If u is root, make it black and the algorithm ends or
 - 2.2 if its parent t is black, the algorithm ends
 - 2.3 If both u and its parent t are red, do one of the following:
 - 2.3.1. [change colors] If t and its sibling v are red:
Color t and v black and their parent p red.
Continue the algorithm with p if necessary.
 - 2.3.2. [rotations] If t is red and v black, perform a rotation.
After the rotation, p and its new parent exchange their colors.
There are no longer two consecutive red nodes in the tree.

ROTATION:

- 1 While the recursion returns, keep track of
node p ,
 p 's child t and
 p 's grandchild u within the path from inserted node to p .
- 2 If rotation is needed in p , do one of the following rotations:
 - if $(p.\text{left} == t)$ and $(p.\text{left}.\text{left} == u)$, single rotation right in p ;
 - if $(p.\text{right} == t)$ and $(p.\text{right}.\text{right} == u)$, single rotation left in p ;
 - if $(p.\text{left} == t)$ and $(p.\text{left}.\text{right} == u)$, LR-double rotation in p ; or
 - if $(p.\text{right} == t)$ and $(p.\text{right}.\text{left} == u)$, RL-double rotation in p .

<https://opensa-server.cs.vt.edu/ODSA/Books/Everything/html/RedBlack.html>




Use Case

- **Tree Set, Tree Map, Hash Maps are backed up by a Red Black Tree**
- **C++ STL**

Performance

	Average	Worst case
▪ Space	$O(n)$	$O(n)$
▪ Search	$O(\log n)$	$O(\log n)$
▪ Insert	$O(\log n)$	$O(\log n)$
▪ Delete	$O(\log n)$	$O(\log n)$

Balanced Trees



1. Is this an AVL Tree?

2. If it is not AVL Tree, how we should rotate the tree to make it balance?

Questions

Questions