

CoppeTeX quick reference

Class `coppe`, v4.1 — every option, command and environment

This is the short companion to `coppe.pdf`, the full manual, which is written in Portuguese. A COPPE thesis may be written in Portuguese, English or Spanish (CEPG Resolution 302/2024, art. 57); this sheet is for whoever writes it in English.

The **Where** column says where a command may appear: PRE means the preamble, before `\begin{document}`; DOC means after `\begin{document}`, and, for everything that feeds the cover, *before* `\maketitle`.

Three things that surprise people. The document data goes *inside* `document`, not in the preamble. The bibliography is `biblatex` with `biber`, not `BibTeX`. And `\frontmatter`/`\mainmatter` are what switch folio numbering on, so leaving them out gives the wrong page numbers.

Command	Example	Where	What it does
CLASS OPTIONS — work type, one is required			
<code>msc</code>	<code>\documentclass[msc]{coppe}</code>	PRE	M.Sc. dissertation.
<code>dsc</code>	<code>\documentclass[dsc]{coppe}</code>	PRE	D.Sc. thesis.
<code>mscexam</code>	<code>\documentclass[mscexam]{coppe}</code>	PRE	M.Sc. qualifying exam. No CAPES sheet, no catalogue card, no reference above the abstract.
<code>dscexam</code>	<code>\documentclass[dscexam]{coppe}</code>	PRE	D.Sc. qualifying exam. Same.
<code>mscsem</code>	<code>\documentclass[mscsem]{coppe}</code>	PRE	M.Sc. seminar, a requirement of some Programas and <i>not</i> a qualifying exam. Same three omissions: it is not deposited.
CLASS OPTIONS — writing language			
<code>brazilian</code>	<code>[brazilian,dsc]</code>	PRE	Portuguese. The default; needs no writing.
<code>english</code>	<code>[english,dsc]</code>	PRE	English. The foreign abstract switches to Portuguese.
<code>spanish</code>	<code>[spanish,dsc]</code>	PRE	Spanish. Needs <code>coppe-lang-spanish.def</code> and <code>spanish-coppe.lbx</code> . Three abstracts.
<code>french</code>	<code>[french,dsc]</code>	PRE	French. Not a permitted thesis language; ships as a demonstration.
<code>italian</code>	<code>[italian,dsc]</code>	PRE	Italian. Same.
CLASS OPTIONS — the rest			
<code>numbers</code>	<code>[dsc,numbers]</code>	PRE	Numeric citations [1] instead of author-date; list in citation order.
<code>pdfa</code>	<code>[dsc,pdfa]</code>	PRE	PDF/A-2b output, required for deposit (2.2d): the deposit is digital only, and PDF/A (ISO 19005) keeps the file self-contained — embedded fonts, sRGB colour, XMP metadata, nothing external. Off by default; <code>max-exemplo.tex</code> turns it on, and turning it on early is recommended. Check with veraPDF.
<code>comserifa</code>	<code>[dsc,comserifa]</code>	PRE	Serif family. Sans is the default since v4.1.

Command	Example	Where	What it does
<code>semserifa</code>	--	PRE	Accepted, does nothing. What it asked for became the default.
<code>semlinks</code>	<code>[dsc,semlinks]</code>	PRE	Accepted; confirms the default (links with no colour and no frame, still clickable). Wins over the two below.
<code>linkscommoldura</code>	<code>[dsc,linkscommoldura]</code>	PRE	Framed links, on screen only (the frame is not printed).
<code>setavermelha</code>	<code>[dsc,setavermelha]</code>	PRE	Red curved arrow at the start of a wrapped listing line. Black by default.
<code>linkscoloridos</code>	<code>[dsc,linkscoloridos]</code>	PRE	Coloured link text. Against 2.1(b) of the UFRJ manual (black text): for on-screen reading copies, not for deposit.
<code>doublespacing</code>	<code>[dsc,doublespacing]</code>	PRE	Double spacing instead of one-and-a-half (2.2c).
<code>twoside</code>	<code>[dsc,twoside]</code>	PRE	Mirrored margins, for printing and binding.
<code>oneside</code>	<code>[dsc,oneside]</code>	PRE	One-sided, 3 cm left margin on every sheet. The default.
<code>semorientadornabanca</code>	<code>[dsc,semorientadornabanca]</code>	PRE	Approval sheet with the examiners only. By default the advisors head the board, as 3.1.2.1.3(e) requires.
<code>orientadorexamina</code>	<code>[dsc,orientadorexamina]</code>	PRE	Accepted, no effect: the advisors are on the board by default.
<code>coorientador</code>	<code>[dsc,coorientador]</code>	PRE	List coadvisors on the abstract pages too.
<code>rascunhoficha</code>	<code>[dsc,rascunhoficha]</code>	PRE	Draft catalogue card while writing. Never valid for deposit.
<code>resumosemreferencia</code>	<code>[dsc,resumosemreferencia]</code>	PRE	Drop the work's own reference from the top of the three abstracts. It is printed by default (3.1.2.1.4, Annexes E and F).
<code>listasnosumario</code>	<code>[dsc,listasnosumario]</code>	PRE	Put the pre-textual lists in the table of contents. Against NBR 6027 and the UFRJ manual (3.1.2.1.6): use only if your Programa requires it.
<code>simbolosalfabeticos</code>	<code>[dsc,simbolosalfabeticos]</code>	PRE	List of symbols in alphabetical order instead of order of appearance.
<code>assinaturas</code>	--	PRE	Accepted, does nothing. Signature rules are gone: deposit is digital.
<code>numeraisromanos</code>	<code>[dsc,numeraisromanos]</code>	PRE	Roman numerals on pre-textual sheets. Against 2.7; legacy only.
<code>morewrites</code>	<code>[dsc,morewrites]</code>	PRE	A missing <code>morewrites</code> package becomes an error, not a warning.
<code>semmakeindex</code>	<code>[dsc,semmakeindex]</code>	PRE	Do not run <code>makeindex</code> from the class. By default the class runs it at the end of each compilation (restricted shell escape is enough), so the lists and the index appear in any editor.

Command	Example	Where	What it does
<code>semmorewrites</code>	<code>[dsc,semmorewrites]</code>	PRE	Do not load <code>morewrites</code> . Saves about half a second per <code>pdflatex</code> pass (Overleaf free plan). Safe only without an index, several indexes, a glossary or nomenclature: the class stops with a clear error if the 16 streams run out.
PREAMBLE			
<code>\addbibresource</code>	<code>\addbibresource{thesis.bib}</code>	PRE	Declare the bibliography database. With the <code>.bib</code> extension.
<code>\makelosymbols</code>	<code>\makelosymbols</code>	PRE	Turn on collection of the list of symbols. Without it, <code>\syml</code> records nothing.
<code>\makeloabbreviations</code>	<code>\makeloabbreviations</code>	PRE	Same for the list of abbreviations.
<code>\makelosiglas</code>	<code>\makelosiglas</code>	PRE	Separate list of acronyms (recommended by 3.1.2.2.6). Without it, acronyms go to the list of abbreviations.
<code>\newcoppefloat</code>	<code>\newcoppefloat{map}{Map}{List of Maps}</code>	PRE	Declare your own float: caption on top, <code>\source</code> below, own list.
<code>\newsigla</code>	<code>\newsigla{ufrj}{UFRJ}{Universidade Federal...}</code>	PRE	Declare an acronym for <code>\sigla</code> .
<code>\usecoppelanguage</code>	<code>\usecoppelanguage{french}</code>	PRE	Load one more language pack, for quotations in a third language.
<code>\graphicspath</code>	<code>\graphicspath{{figures/}}</code>	PRE	Where your figures live. Standard L ^A T _E X.
<code>\freeconfig</code>	<code>\freeconfig{Dr.}{...}{...}{...}{...}{...}</code>	PRE	Override the work type entirely. Escape hatch; do not use for a normal thesis.
IDENTIFICATION — after <code>\begin{document}</code>, before <code>\maketitle</code>			
<code>\title</code>	<code>\title{Título da tese}</code>	DOC	The Portuguese title.
<code>\foreigntitle</code>	<code>\foreigntitle{Thesis title}</code>	DOC	The English title.
<code>\titlein</code>	<code>\titlein{spanish}{Título}</code>	DOC	The title in any other language.
<code>\subtitle</code>	<code>\subtitle{Um subtítulo}</code>	DOC	Optional subtitle, Portuguese. Printed after a colon, in ordinary case.
<code>\foreignsubtitle</code>	<code>\foreignsubtitle{A subtitle}</code>	DOC	The same, English.
<code>\subtitlein</code>	<code>\subtitlein{spanish}{...}</code>	DOC	The same, any language.
<code>\author</code>	<code>\author{All given names}{Surname}</code>	DOC	Two arguments: the catalogue card has to invert the name.
<code>\advisor</code>	<code>\advisor{Ana}{Lima}{D.Sc.}{UFRJ}</code>	DOC	Name, surname, degree, institution. Repeat per advisor. Optional first argument is the treatment.
<code>\coadvisor</code>	<code>\coadvisor{Bia}{Sousa}{Ph.D.}{UFF}</code>	DOC	Same four arguments.
<code>\examiner</code>	<code>\examiner{Carlos Dias}{D.Sc.}{USP}</code>	DOC	Name and surname in one argument, then degree and institution.
<code>\department</code>	<code>\department{PESC}</code>	DOC	The Programa’s acronym. The class knows all thirteen.
<code>\date</code>	<code>\date{09}{2026}</code>	DOC	Month and year of deposit, as numbers. Not the defence date.
<code>\dataaprovacao</code>	<code>\dataaprovacao{15 de setembro de 2026}</code>	DOC	Defence date, in words. Without it the sheet reads “a ser determinada”.

Command	Example	Where	What it does
<code>\keyword</code>	<code>\keyword{Formal methods}</code>	DOC	One call per keyword, main language.
<code>\foreignkeyword</code>	<code>\foreignkeyword{Métodos formais}</code>	DOC	One call per keyword, foreign language.
<code>\braziliankeyword</code>	<code>\braziliankeyword{Métodos formais}</code>	DOC	Portuguese keywords when the work is not in Portuguese.
<code>\volumes</code>	<code>\volumes{3}</code>	DOC	How many volumes. Nothing is printed when there is one.
<code>\volume</code>	<code>\volume{1}</code>	DOC	Which volume this is.
TITLE PAGE AND CAPES SHEET			
<code>\areaconcentracao</code>	<code>\areaconcentracao{Engenharia de Sistemas}</code>	DOC	Area of concentration. On three sheets.
<code>\linhapesquisa</code>	<code>\linhapesquisa{Engenharia de Dados}</code>	DOC	Research line, on the title page. Label follows the main language. Empty is fine.
<code>\tipoproducao</code>	<code>\tipoproducao{bibliografica}</code>	DOC	One of <code>bibliografica</code> , <code>artistica</code> , <code>tecnologica</code> , <code>tecnica</code> .
<code>\projetovinculado</code>	<code>\projetovinculado{sim}</code>	DOC	<code>sim</code> or <code>nao</code> : is there a linked research project?
<code>\nomeprojeto</code>	<code>\nomeprojeto{Nome do projeto}</code>	DOC	Its name, if there is one.
<code>\agenciafomento</code>	<code>\agenciafomento{Conselho...}{CNPq}</code>	DOC	Funding agency, full name and acronym. One call each.
<code>\fichacatalografica</code>	<code>\fichacatalografica{ficha.pdf}</code>	DOC	The official catalogue card, as a PDF from the SiBI generator.
STRUCTURE			
<code>\maketitle</code>	<code>\maketitle</code>	DOC	Typesets cover, title page and CAPES sheet. After all the data.
<code>\frontmatter</code>	<code>\frontmatter</code>	DOC	Opens the pre-textual part and typesets the approval sheet.
<code>\mainmatter</code>	<code>\mainmatter</code>	DOC	Opens the textual part. This is what starts printing the folio.
<code>\backmatter</code>	<code>\backmatter</code>	DOC	Opens the post-textual part.
<code>\dedication</code>	<code>\dedication{To those who waited.}</code>	DOC	Dedication, on a sheet of its own.
<code>\epigrafe</code>	<code>\epigrafe{quotation}{author}</code>	DOC	Epigraph (3.1.2.2.3), on a sheet of its own, after the acknowledgements.
<code>abstract</code>	<code>\begin{abstract} ...</code>	DOC	Abstract in the main language. One sheet, one paragraph, 250 words.
<code>foreignabstract</code>	<code>\begin{foreignabstract} ...</code>	DOC	Abstract in the foreign language.
<code>brazilianabstract</code>	<code>\begin{brazilianabstract} ...</code>	DOC	Third abstract, Portuguese, for a Spanish- or French-main work.
<code>\configuraresumos</code>	<code>\configuraresumos{true}{true}{true}{true}</code>	PRE	Turns the four optional elements of every abstract sheet on or off, in every language: page identification, title and author, advising, reference. All on by default; only the abstract text itself cannot be turned off.
<code>\appendix</code>	<code>\appendix</code>	DOC	Opens the appendices: text <i>you</i> wrote.
<code>\annex</code>	<code>\annex</code>	DOC	Opens the annexes: documents you did <i>not</i> write.
<code>\printbibliography</code>	<code>\printbibliography</code>	DOC	The reference list, titled “Referências” (3.1.4.1).

Command	Example	Where	What it does
<code>\coppetexfinalpage</code>	<code>\coppetexfinalpage</code>	DOC	Optional colophon, every item measured at compile time: class version, engine and its version, TeX system, L ^A T _E X format, font family and encoding, biblatex version, date, hour, operating system and machine.
Only the table of contents is mandatory (3.1.2.1.6). Every list is optional (3.1.2.2); the COPPE norm (§10) adds the lists of <i>quadros</i> , programs and algorithms whenever the work has one of them.			
PRE-TEXTUAL LISTS — lists first, table of contents last (3.1.2.1.6)			
<code>\listoffigures</code>	<code>\listoffigures</code>	DOC	List of figures.
<code>\listoftables</code>	<code>\listoftables</code>	DOC	List of tables.
<code>\listofquadros</code>	<code>\listofquadros</code>	DOC	List of <i>quadros</i> (framed on all sides, unlike a table).
<code>\listofprogramas</code>	<code>\listofprogramas</code>	DOC	List of code listings.
<code>\listofalgorithms</code>	<code>\listofalgorithms</code>	DOC	List of algorithms.
<code>\printloabbreviations</code>	<code>\printloabbreviations</code>	DOC	List of abbreviations and acronyms. No page numbers (4.1.1).
<code>\printlosiglas</code>	<code>\printlosiglas</code>	DOC	List of acronyms, when <code>\makelosiglas</code> is on.
<code>\printlosymbols</code>	<code>\printlosymbols</code>	DOC	List of symbols, in order of first appearance (3.1.2.2.7).
<code>\makeglossarylist</code>	<code>\makeglossarylist</code>	PRE	The automatic glossary (3.1.4.2). Without it, write <code>\theglossary</code> by hand.
<code>\glossaryterm</code>	<code>\glossaryterm[key]{term}{definition}</code>	DOC	Registers a glossary term where it appears; prints nothing. Alphabetical, accents included.
<code>\printglossarylist</code>	<code>\printglossarylist</code>	DOC	The glossary, right after <code>\printbibliography</code> .
<code>\index</code>	<code>\index{term!sub see{other}}</code>	DOC	Index entry (with <code>makeidx</code>). Accented entries get an unaccented sort key; <code>key@term</code> wins.
<code>\acron</code>	<code>\acron[key]{UFRJ}{meaning}</code>	DOC	Registers an acronym; <code>\sigla</code> uses it.
<code>\tableofcontents</code>	<code>\tableofcontents</code>	DOC	The table of contents. Comes last of all the lists.
ILLUSTRATIONS — caption on top, source below (2.10)			
<code>\source</code>	<code>\source{Prepared by the author.}</code>	DOC	The source line, below the float. Mandatory by the norm.
<code>\fonte</code>	<code>\fonte{Elaboração própria.}</code>	DOC	The same command, Portuguese name.
<code>\cpsource</code>	<code>\cpsource{...}</code>	DOC	Clash-safe alias, always available.
<code>\cpfonte</code>	<code>\cpfonte{...}</code>	DOC	Likewise.
<code>quadro</code>	<code>\begin{quadro}[ht] ...</code>	DOC	A float framed on all sides. Behaves like <code>figure</code> .
<code>python</code>	<code>\begin{python}[caption={...}]</code>	DOC	Python listing, syntax-highlighted, caption on top.
<code>java, xml, html, prolog</code>	<code>\begin{java}[...] ...</code>	DOC	The same, for those languages.
<code>\pythoninline</code>	<code>\pythoninline{f(x)}</code>	DOC	Code inside a paragraph.
<code>\javainline</code>	<code>\javainline{new X()}</code>	DOC	Likewise.
<code>\pythonexternal</code>	<code>\pythonexternal{code.py}</code>	DOC	Listing read from a file.
<code>\javaexternal</code>	<code>\javaexternal{Code.java}</code>	DOC	Likewise.

Command	Example	Where	What it does
<code>\pythonstyle</code>	<code>\pythonstyle</code>	DOC	Apply a language's style without opening the environment. Also <code>\javastyle</code> , <code>\xmlstyle</code> , <code>\htmlstyle</code> , <code>\prologstyle</code> .
QUOTATIONS, ACRONYMS, SYMBOLS			
<code>\citacao</code>	<code>\citacao{up to three lines}</code>	DOC	Short quotation, inside the paragraph, in quotation marks.
<code>longquote</code>	<code>\begin{longquote} ...</code>	DOC	Quotation over three lines: indented 4 cm past the margin, smaller, single spaced, no quotation marks (2.2b).
<code>\abbrev</code>	<code>\abbrev[IoT]{IoT}{Internet of Things}</code>	DOC	Register an acronym. Optional first argument is the sort key.
<code>\syml</code>	<code>\syml{α}{Learning rate}</code>	DOC	Register a symbol. Same optional sort key.
<code>\sigla</code>	<code>\sigla{ufrj}</code>	DOC	Full form on first use, acronym afterwards (2.8). <code>\sigla*</code> forces the full form.
CITATIONS — biblatex, with the natbib layer on			
<code>\cite</code>	<code>\cite{key}</code>	DOC	(SURNAME, 2026), or [1] with numbers.
<code>\citet</code>	<code>\citet{key}</code>	DOC	SURNAME (2026).
<code>\citep</code>	<code>\citep{key}</code>	DOC	(SURNAME, 2026).
<code>\textcite</code>	<code>\textcite{key}</code>	DOC	Same as <code>\citet</code> , biblatex spelling.
<code>\parencite</code>	<code>\parencite{key}</code>	DOC	Same as <code>\citep</code> .
<code>\citeauthor</code>	<code>\citeauthor{key}</code>	DOC	The author alone.
<code>\citeyear</code>	<code>\citeyear{key}</code>	DOC	The year alone.
<code>\citetitle</code>	<code>\citetitle{key}</code>	DOC	The title alone.
<code>\cite[p. 45]</code>	<code>\cite[p. 45, our translation]{key}</code>	DOC	Page, and any note, in the optional argument.
<code>\citepapud</code>	<code>\citepapud[45]{Original}{1953}{key-read}</code>	DOC	Citation of a citation (4.1.2.2.1). Three mandatory arguments: the original author and year, which are printed as text, and the key of the work you actually read, which is the only one that enters the list. Also <code>\citetaud</code> .
<code>\nocite</code>	<code>\nocite{key}</code>	DOC	Into the list without citing in the text.

Full manual: `coppe.pdf`, in Portuguese. Worked examples: `min-exemplo.tex` (only what is mandatory) and `max-exemplo.tex` (everything). Problems: <https://github.com/COPPE-UFRJ/CoppeTeX/issues>