

UFRJ
UNIVERSIDADE FEDERAL
DO RIO DE JANEIRO



COPPE
Instituto Alberto Luiz Coimbra de
Pós-Graduação e Pesquisa de Engenharia
UFRJ

UNIVERSIDADE FEDERAL DO RIO DE JANEIRO

INSTITUTO ALBERTO LUIZ COIMBRA DE
PÓS-GRADUAÇÃO E PESQUISA DE ENGENHARIA

PROGRAMA DE ENGENHARIA DE SISTEMAS E COMPUTAÇÃO

AUTHOR'S NAME

TITLE OF THE WORK: an example of use of CoppeTeX in English

RIO DE JANEIRO
2026

Author's Name

TITLE OF THE WORK: an example of use of CoppeTeX in English

Tese de Doutorado apresentada ao Programa de Pós-Graduação em Engenharia de Sistemas e Computação, Instituto Alberto Luiz Coimbra de Pós-Graduação e Pesquisa de Engenharia, Universidade Federal do Rio de Janeiro, como requisito parcial à obtenção do título de Doutor em Engenharia de Sistemas e Computação.

Orientador: First Advisor

Rio de Janeiro
2026

Espaço reservado à ficha catalográfica.

Gere-a em `fichacatalografica.sibi.ufrj.br` e inclua o arquivo com `\fichacatalografica{arquivo.pdf}`, ou solicite-a à biblioteca da sua unidade.

Author's Name

Title of the Work: an example of use of CoppeTeX in English

Tese de Doutorado apresentada ao Programa de Pós-Graduação em Engenharia de Sistemas e Computação, Instituto Alberto Luiz Coimbra de Pós-Graduação e Pesquisa de Engenharia, Universidade Federal do Rio de Janeiro, como requisito parcial à obtenção do título de Doutor em Engenharia de Sistemas e Computação.

Aprovada em: to be determined

Aprovada por:

First Examiner, D.Sc., UFRJ

Second Examiner, D.Sc., UFRJ

RESUMO

NAME, Author's. **Title of the Work**: an example of use of CoppeTeX in English. Rio de Janeiro, 2026. Tese (Doutorado em Engenharia de Sistemas e Computação) — Instituto Alberto Luiz Coimbra de Pós-Graduação e Pesquisa de Engenharia, Universidade Federal do Rio de Janeiro, Rio de Janeiro, 2026.

Este é o resumo em português, a língua vernácula, que vem antes do abstract qualquer que seja o idioma do trabalho (Manual 3.1.2). Num trabalho em inglês, quem o produz é o ambiente `foreignabstract`.

Palavras-chave: multilíngue; demonstração.

ABSTRACT

NAME, Author's. **Title of the Work**: an example of use of CoppeTeX in English. Rio de Janeiro, 2026. Tese (Doutorado em Engenharia de Sistemas e Computação) — Instituto Alberto Luiz Coimbra de Pós-Graduação e Pesquisa de Engenharia, Universidade Federal do Rio de Janeiro, Rio de Janeiro, 2026.

This is the abstract in English, the main language of this work, used when the class is loaded with the `english` option. It comes after the abstract in Portuguese. Lorem ipsum dolor sit amet, consectetur adipiscing elit.

Keywords: Multilingual; Demonstration.

CONTENTS

1 INTRODUCTION 6
1.1 THE DEPOSIT FILE: PDF/A 6
1.2 WRITE STREAMS 6

1 INTRODUCTION

This chapter shows that the body is composed in English while the cover and folha-de-rosto remain in Portuguese (the UFRJ institutional template).

1.1 THE DEPOSIT FILE: PDF/A

Deposit at UFRJ has been digital only since CEPG Resolution 246/2023, and the UFRJ Manual (2.2d) requires the final file in **PDF/A**, the long-term archiving format. PDF/A is PDF restricted by ISO 19005 for preservation: every font is embedded, colours declare a profile (sRGB) that makes them device independent, metadata go in an XMP packet that repositories read, and nothing depends on the outside — no external content, JavaScript or encryption. The file then opens the same way decades from now, on any computer.

The class uses **PDF/A-2b**: part 2 allows transparency, which part 1 forbids and which coloured boxes and graphics often produce, and level *b* guarantees faithful visual reproduction. The `pdfa` option in `\documentclass[english,dsc,pdfa]{ufrj}` is all it takes: the class loads `pdfx`, builds the metadata from the title, author and keywords, and embeds the colour profile. Turn it on early, as `coppe-max-exemplo.tex` does: a non-conforming PDF or image shows up the day it is added, not the day before the deposit. To check, use the veraPDF validator, PDF/A-2b profile.

1.2 WRITE STREAMS

pdfLaTeX keeps at most sixteen files open for writing, and each list, index or glossary takes one. That is why the class loads `morewrites`. The `semmorewrites` option turns it off and saves about half a second per pass, but only suits a work with no index, no multiple indexes and no glossary.