



ZAP Scanning Report

Site: <http://host.docker.internal:3001>

Generated on Tue, 29 Sept 2026 18:09:43

ZAP Version: 2.17.0

ZAP by [Checkmarx](#)

Summary of Alerts

Risk Level	Number of Alerts
High	0
Medium	3
Low	7
Informational	6
False Positives:	0

Insights

Level	Reason	Site	Description	Statistic
Low	Warning		ZAP warnings logged - see the zap.log file for details	1
Info	Informational	http://host.docker.internal:3001	Percentage of responses with status code 2xx	93 %
Info	Informational	http://host.docker.internal:3001	Percentage of responses with status code 3xx	6 %
Info	Informational	http://host.docker.internal:3001	Percentage of endpoints with content type application/javascript	78 %
Info	Informational	http://host.docker.internal:3001	Percentage of endpoints with content type font/woff2	2 %
Info	Informational	http://host.docker.internal:3001	Percentage of endpoints with content type image/x-icon	2 %
Info	Informational	http://host.docker.internal:3001	Percentage of endpoints with content type text/css	2 %
Info	Informational	http://host.docker.internal:3001	Percentage of endpoints with content type text/html	9 %
Info	Informational	http://host.docker.internal:3001	Percentage of endpoints with method GET	100 %
Info	Informational	http://host.docker.internal:3001	Count of total endpoints	41

Info	Informational	http://host.docker.internal:3001	Percentage of slow responses	6 %
------	---------------	----------------------------------	------------------------------	-----

Summary of Sequences

For each step: result (Pass/Fail) - risk (of highest alert(s) for the step, if any).

Alerts

Name	Risk Level	Number of Instances
CSP: Failure to Define Directive with No Fallback	Medium	4
CSP: Wildcard Directive	Medium	4
CSP: style-src unsafe-inline	Medium	4
Cross-Origin-Embedder-Policy Header Missing or Invalid	Low	3
Cross-Origin-Opener-Policy Header Missing or Invalid	Low	3
Cross-Origin-Resource-Policy Header Missing or Invalid	Low	Systemic
Dangerous JS Functions	Low	2
Permissions Policy Header Not Set	Low	Systemic
Server Leaks Information via "X-Powered-By" HTTP Response Header Field(s)	Low	5
Timestamp Disclosure - Unix	Low	3
Content-Type Header Missing	Informational	2
Information Disclosure - Suspicious Comments	Informational	35
Modern Web Application	Informational	2
Non-Storable Content	Informational	3
Storable and Cacheable Content	Informational	1
Storable but Non-Cacheable Content	Informational	Systemic

Alert Detail

Medium	CSP: Failure to Define Directive with No Fallback
Description	The Content Security Policy fails to define one of the directives that has no fallback. Missing/excluding them is the same as allowing anything.
URL	http://host.docker.internal:3001
Node Name	http://host.docker.internal:3001
Method	GET
Parameter	content-security-policy
Attack	
Evidence	default-src 'self'; script-src 'self' 'nonce-YWVvKjQyNzEtMGY0Ni00YTEwLWE5ZWQtZGYzYzIzYzA4Zjhh' 'strict-dynamic' 'wasm-unsafe-eval'; style-src 'self' 'unsafe-inline'; img-src 'self' data: blob: https; font-src 'self' data;; connect-

	src 'self' https: wss: http://localhost:* ws://localhost.*; object-src 'none'; base-uri 'self'; frame-ancestors 'none'
Other Info	The directive(s): form-action is/are among the directives that do not fallback to default-src.
URL	http://host.docker.internal:3001/dashboard
Node Name	http://host.docker.internal:3001/dashboard
Method	GET
Parameter	content-security-policy
Attack	
Evidence	default-src 'self'; script-src 'self' 'nonce-N2RIMzI1NWUtNzBjYy00YTE1LThjOTktNTM0NzI1Nzc4ZTNi' 'strict-dynamic' 'wasm-unsafe-eval'; style-src 'self' 'unsafe-inline'; img-src 'self' data: blob: https:; font-src 'self' data:; connect-src 'self' https: wss: http://localhost:* ws://localhost.*; object-src 'none'; base-uri 'self'; frame-ancestors 'none'
Other Info	The directive(s): form-action is/are among the directives that do not fallback to default-src.
URL	http://host.docker.internal:3001/login?next=%2Frobots.txt
Node Name	http://host.docker.internal:3001/login (next)
Method	GET
Parameter	content-security-policy
Attack	
Evidence	default-src 'self'; script-src 'self' 'nonce-MzlxNWMxMDctMmU4OS00ZTc2LWExYWUtMmY0NGRmYmM5OTk1' 'strict-dynamic' 'wasm-unsafe-eval'; style-src 'self' 'unsafe-inline'; img-src 'self' data: blob: https:; font-src 'self' data:; connect-src 'self' https: wss: http://localhost:* ws://localhost.*; object-src 'none'; base-uri 'self'; frame-ancestors 'none'
Other Info	The directive(s): form-action is/are among the directives that do not fallback to default-src.
URL	http://host.docker.internal:3001/login?next=%2Fsitemap.xml
Node Name	http://host.docker.internal:3001/login (next)
Method	GET
Parameter	content-security-policy
Attack	
Evidence	default-src 'self'; script-src 'self' 'nonce-NDZjODgzYTltZjJmZi00MzdjLTk5OWltMzA0Y2JINDMwMjc5' 'strict-dynamic' 'wasm-unsafe-eval'; style-src 'self' 'unsafe-inline'; img-src 'self' data: blob: https:; font-src 'self' data:; connect-src 'self' https: wss: http://localhost:* ws://localhost.*; object-src 'none'; base-uri 'self'; frame-ancestors 'none'
Other Info	The directive(s): form-action is/are among the directives that do not fallback to default-src.
Instances	4
Solution	Ensure that your web server, application server, load balancer, etc. is properly configured to set the Content-Security-Policy header.
Reference	https://www.w3.org/TR/CSP/ https://caniuse.com/#search=content+security+policy https://content-security-policy.com/ https://github.com/HtmlUnit/htmlunit-csp https://web.dev/articles/csp#resource-options
CWE Id	693

WASC Id	15
Plugin Id	10055

Medium	CSP: Wildcard Directive
Description	Content Security Policy (CSP) is an added layer of security that helps to detect and mitigate certain types of attacks. Including (but not limited to) Cross Site Scripting (XSS), and data injection attacks. These attacks are used for everything from data theft to site defacement or distribution of malware. CSP provides a set of standard HTTP headers that allow website owners to declare approved sources of content that browsers should be allowed to load on that page — covered types are JavaScript, CSS, HTML frames, fonts, images and embeddable objects such as Java applets, ActiveX, audio and video files.
URL	http://host.docker.internal:3001
Node Name	http://host.docker.internal:3001
Method	GET
Parameter	content-security-policy
Attack	
Evidence	default-src 'self'; script-src 'self' 'nonce-YWVkJNjQyNzEtMGY0Ni00YTEwLWE5ZWQtZGYzYzIzYzA4Zjhh' 'strict-dynamic' 'wasm-unsafe-eval'; style-src 'self' 'unsafe-inline'; img-src 'self' data: blob: https:; font-src 'self' data:; connect-src 'self' https: wss: http://localhost:* ws://localhost:*; object-src 'none'; base-uri 'self'; frame-ancestors 'none'
Other Info	The following directives either allow wildcard sources (or ancestors), are not defined, or are overly broadly defined: img-src, connect-src
URL	http://host.docker.internal:3001/dashboard
Node Name	http://host.docker.internal:3001/dashboard
Method	GET
Parameter	content-security-policy
Attack	
Evidence	default-src 'self'; script-src 'self' 'nonce-N2RIMZl1NWUtNzBjYy00YTE1LTljOTktNTM0NzI1Nzc4ZTNi' 'strict-dynamic' 'wasm-unsafe-eval'; style-src 'self' 'unsafe-inline'; img-src 'self' data: blob: https:; font-src 'self' data:; connect-src 'self' https: wss: http://localhost:* ws://localhost:*; object-src 'none'; base-uri 'self'; frame-ancestors 'none'
Other Info	The following directives either allow wildcard sources (or ancestors), are not defined, or are overly broadly defined: img-src, connect-src
URL	http://host.docker.internal:3001/login?next=%2Frobots.txt
Node Name	http://host.docker.internal:3001/login (next)
Method	GET
Parameter	content-security-policy
Attack	
Evidence	default-src 'self'; script-src 'self' 'nonce-MzIxNWMyMDctMmU4OS00ZTc2LWExYWUtMmY0NGRmYmM5OTk1' 'strict-dynamic' 'wasm-unsafe-eval'; style-src 'self' 'unsafe-inline'; img-src 'self' data: blob: https:; font-src 'self' data:;

	connect-src 'self' https: wss: http://localhost:* ws://localhost:*; object-src 'none'; base-uri 'self'; frame-ancestors 'none'
Other Info	The following directives either allow wildcard sources (or ancestors), are not defined, or are overly broadly defined: img-src, connect-src
URL	http://host.docker.internal:3001/login?next=%2Fsitemap.xml
Node Name	http://host.docker.internal:3001/login (next)
Method	GET
Parameter	content-security-policy
Attack	
Evidence	default-src 'self'; script-src 'self' 'nonce-NDZjODgzYTltZjMzA0Y2JINDMwMjc5' 'strict-dynamic' 'wasm-unsafe-eval'; style-src 'self' 'unsafe-inline'; img-src 'self' data: blob: https:; font-src 'self' data:; connect-src 'self' https: wss: http://localhost:* ws://localhost:*; object-src 'none'; base-uri 'self'; frame-ancestors 'none'
Other Info	The following directives either allow wildcard sources (or ancestors), are not defined, or are overly broadly defined: img-src, connect-src
Instances	4
Solution	Ensure that your web server, application server, load balancer, etc. is properly configured to set the Content-Security-Policy header.
Reference	https://www.w3.org/TR/CSP/ https://caniuse.com/#search=content+security+policy https://content-security-policy.com/ https://github.com/HtmlUnit/htmlunit-csp https://web.dev/articles/csp#resource-options
CWE Id	693
WASC Id	15
Plugin Id	10055

Medium	CSP: style-src unsafe-inline
Description	Content Security Policy (CSP) is an added layer of security that helps to detect and mitigate certain types of attacks. Including (but not limited to) Cross Site Scripting (XSS), and data injection attacks. These attacks are used for everything from data theft to site defacement or distribution of malware. CSP provides a set of standard HTTP headers that allow website owners to declare approved sources of content that browsers should be allowed to load on that page — covered types are JavaScript, CSS, HTML frames, fonts, images and embeddable objects such as Java applets, ActiveX, audio and video files.
URL	http://host.docker.internal:3001
Node Name	http://host.docker.internal:3001
Method	GET
Parameter	content-security-policy
Attack	
Evidence	default-src 'self'; script-src 'self' 'nonce-YWVkJNjQyNzEtMGY0Ni00YTEwLWE5ZWQtZGYzYzIzYzA4Zjhh' 'strict-dynamic' 'wasm-unsafe-eval'; style-src 'self' 'unsafe-inline'; img-src 'self' data: blob: https:; font-src 'self' data:; connect-

	src 'self' https: wss: http://localhost:* ws://localhost.*; object-src 'none'; base-uri 'self'; frame-ancestors 'none'
Other Info	style-src includes unsafe-inline.
URL	http://host.docker.internal:3001/dashboard
Node Name	http://host.docker.internal:3001/dashboard
Method	GET
Parameter	content-security-policy
Attack	
Evidence	default-src 'self'; script-src 'self' 'nonce-N2RIMzI1NWUtNzBjYy00YTE1LThjOTktNTM0NzI1Nzc4ZTNi' 'strict-dynamic' 'wasm-unsafe-eval'; style-src 'self' 'unsafe-inline'; img-src 'self' data: blob: https:; font-src 'self' data:; connect-src 'self' https: wss: http://localhost:* ws://localhost.*; object-src 'none'; base-uri 'self'; frame-ancestors 'none'
Other Info	style-src includes unsafe-inline.
URL	http://host.docker.internal:3001/login?next=%2Frobots.txt
Node Name	http://host.docker.internal:3001/login (next)
Method	GET
Parameter	content-security-policy
Attack	
Evidence	default-src 'self'; script-src 'self' 'nonce-MzlxNWMxMDctMmU4OS00ZTc2LWExYWUtMmY0NGRmYmM5OTk1' 'strict-dynamic' 'wasm-unsafe-eval'; style-src 'self' 'unsafe-inline'; img-src 'self' data: blob: https:; font-src 'self' data:; connect-src 'self' https: wss: http://localhost:* ws://localhost.*; object-src 'none'; base-uri 'self'; frame-ancestors 'none'
Other Info	style-src includes unsafe-inline.
URL	http://host.docker.internal:3001/login?next=%2Fsitemap.xml
Node Name	http://host.docker.internal:3001/login (next)
Method	GET
Parameter	content-security-policy
Attack	
Evidence	default-src 'self'; script-src 'self' 'nonce-NDZjODgzYTltZjJmZi00MzdjLTk5OWltMzA0Y2JINDMwMjc5' 'strict-dynamic' 'wasm-unsafe-eval'; style-src 'self' 'unsafe-inline'; img-src 'self' data: blob: https:; font-src 'self' data:; connect-src 'self' https: wss: http://localhost:* ws://localhost.*; object-src 'none'; base-uri 'self'; frame-ancestors 'none'
Other Info	style-src includes unsafe-inline.
Instances	4
Solution	Ensure that your web server, application server, load balancer, etc. is properly configured to set the Content-Security-Policy header.
Reference	https://www.w3.org/TR/CSP/ https://caniuse.com/#search=content+security+policy https://content-security-policy.com/ https://github.com/HtmlUnit/htmlunit-csp https://web.dev/articles/csp#resource-options
CWE Id	693

WASC Id	15
Plugin Id	10055

Low	Cross-Origin-Embedder-Policy Header Missing or Invalid
Description	Cross-Origin-Embedder-Policy header is a response header that prevents a document from loading any cross-origin resources that don't explicitly grant the document permission (using CORP or CORS).
URL	http://host.docker.internal:3001
Node Name	http://host.docker.internal:3001
Method	GET
Parameter	Cross-Origin-Embedder-Policy
Attack	
Evidence	
Other Info	
URL	http://host.docker.internal:3001/dashboard
Node Name	http://host.docker.internal:3001/dashboard
Method	GET
Parameter	Cross-Origin-Embedder-Policy
Attack	
Evidence	
Other Info	
URL	http://host.docker.internal:3001/login?next=%2Fsitemap.xml
Node Name	http://host.docker.internal:3001/login (next)
Method	GET
Parameter	Cross-Origin-Embedder-Policy
Attack	
Evidence	
Other Info	
Instances	3
Solution	Ensure that the application/web server sets the Cross-Origin-Embedder-Policy header appropriately, and that it sets the Cross-Origin-Embedder-Policy header to 'require-corp' for documents. If possible, ensure that the end user uses a standards-compliant and modern web browser that supports the Cross-Origin-Embedder-Policy header (https://caniuse.com/mdn-http_headers_cross-origin-embedder-policy).
Reference	https://developer.mozilla.org/en-US/docs/Web/HTTP/Reference/Headers/Cross-Origin-Embedder-Policy
CWE Id	693
WASC Id	14
Plugin Id	90004

Low	Cross-Origin-Opener-Policy Header Missing or Invalid
Description	Cross-Origin-Opener-Policy header is a response header that allows a site to control if others included documents share the same browsing context. Sharing the same browsing context with untrusted documents might lead to data leak.
URL	http://host.docker.internal:3001
Node Name	http://host.docker.internal:3001
Method	GET
Parameter	Cross-Origin-Opener-Policy
Attack	
Evidence	
Other Info	
URL	http://host.docker.internal:3001/dashboard
Node Name	http://host.docker.internal:3001/dashboard
Method	GET
Parameter	Cross-Origin-Opener-Policy
Attack	
Evidence	
Other Info	
URL	http://host.docker.internal:3001/login?next=%2Fsitemap.xml
Node Name	http://host.docker.internal:3001/login (next)
Method	GET
Parameter	Cross-Origin-Opener-Policy
Attack	
Evidence	
Other Info	
Instances	3
Solution	Ensure that the application/web server sets the Cross-Origin-Opener-Policy header appropriately, and that it sets the Cross-Origin-Opener-Policy header to 'same-origin' for documents. 'same-origin-allow-popups' is considered as less secured and should be avoided. If possible, ensure that the end user uses a standards-compliant and modern web browser that supports the Cross-Origin-Opener-Policy header (https://caniuse.com/mdn-http_headers_cross-origin-opener-policy).
Reference	https://developer.mozilla.org/en-US/docs/Web/HTTP/Reference/Headers/Cross-Origin-Opener-Policy
CWE Id	693
WASC Id	14
Plugin Id	90004
Low	Cross-Origin-Resource-Policy Header Missing or Invalid

Description	Cross-Origin-Resource-Policy header is an opt-in header designed to counter side-channels attacks like Spectre. Resource should be specifically set as shareable amongst different origins.
URL	http://host.docker.internal:3001
Node Name	http://host.docker.internal:3001
Method	GET
Parameter	Cross-Origin-Resource-Policy
Attack	
Evidence	
Other Info	
URL	http://host.docker.internal:3001/_next/static/chunks/0zix_%40swc_helpers_cjs_0hi-e47._.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/0zix_@swc_helpers_cjs_0hi-e47._.js
Method	GET
Parameter	Cross-Origin-Resource-Policy
Attack	
Evidence	
Other Info	
URL	http://host.docker.internal:3001/_next/static/chunks/%5Broot-of-the-server%5D_06sa18r._.css
Node Name	http://host.docker.internal:3001/_next/static/chunks/[root-of-the-server]__06sa18r._.css
Method	GET
Parameter	Cross-Origin-Resource-Policy
Attack	
Evidence	
Other Info	
URL	http://host.docker.internal:3001/_next/static/chunks/apps_frontend_1anvha4._.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/apps_frontend_1anvha4._.js
Method	GET
Parameter	Cross-Origin-Resource-Policy
Attack	
Evidence	
Other Info	
URL	http://host.docker.internal:3001/favicon.ico?favicon.34t707dgcc5_r.ico
Node Name	http://host.docker.internal:3001/favicon.ico (favicon.34t707dgcc5_r.ico)
Method	GET
Parameter	Cross-Origin-Resource-Policy
Attack	
Evidence	

Other Info	
Instances	Systemic
Solution	Ensure that the application/web server sets the Cross-Origin-Resource-Policy header appropriately, and that it sets the Cross-Origin-Resource-Policy header to 'same-origin' for all web pages. 'same-site' is considered as less secured and should be avoided. If resources must be shared, set the header to 'cross-origin'. If possible, ensure that the end user uses a standards-compliant and modern web browser that supports the Cross-Origin-Resource-Policy header (https://caniuse.com/mdn-http_headers_cross-origin-resource-policy).
Reference	https://developer.mozilla.org/en-US/docs/Web/HTTP/Reference/Headers/Cross-Origin-Embedder-Policy
CWE Id	693
WASC Id	14
Plugin Id	90004

Low	Dangerous JS Functions
Description	A dangerous JS function seems to be in use that would leave the site vulnerable.
URL	http://host.docker.internal:3001/_next/static/chunks/03gi_next_dist_compiled_react-server-dom-turbopack_0cnc0mo._.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/03gi_next_dist_compiled_react-server-dom-turbopack_0cnc0mo._.js
Method	GET
Parameter	
Attack	
Evidence	eval(
Other Info	
URL	http://host.docker.internal:3001/_next/static/chunks/turbopack-apps_frontend_1vgo3ux._.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/turbopack-apps_frontend_1vgo3ux._.js
Method	GET
Parameter	
Attack	
Evidence	eval(
Other Info	
Instances	2
Solution	See the references for security advice on the use of these functions.
Reference	https://v17.angular.io/guide/security
CWE Id	749
WASC Id	
Plugin Id	10110

Low	Permissions Policy Header Not Set
------------	--

Description	Permissions Policy Header is an added layer of security that helps to restrict from unauthorized access or usage of browser/client features by web resources. This policy ensures the user privacy by limiting or specifying the features of the browsers can be used by the web resources. Permissions Policy provides a set of standard HTTP headers that allow website owners to limit which features of browsers can be used by the page such as camera, microphone, location, full screen etc.
URL	http://host.docker.internal:3001
Node Name	http://host.docker.internal:3001
Method	GET
Parameter	
Attack	
Evidence	
Other Info	
URL	http://host.docker.internal:3001/_next/static/chunks/0zix_%40swc_helpers_cjs_0hi-e47._.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/0zix_@swc_helpers_cjs_0hi-e47._.js
Method	GET
Parameter	
Attack	
Evidence	
Other Info	
URL	http://host.docker.internal:3001/_next/static/chunks/apps_frontend_1anvha4._.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/apps_frontend_1anvha4._.js
Method	GET
Parameter	
Attack	
Evidence	
Other Info	
URL	http://host.docker.internal:3001/dashboard
Node Name	http://host.docker.internal:3001/dashboard
Method	GET
Parameter	
Attack	
Evidence	
Other Info	
URL	http://host.docker.internal:3001/login?next=%2Fsitemap.xml
Node Name	http://host.docker.internal:3001/login (next)
Method	GET
Parameter	

Attack	
Evidence	
Other Info	
Instances	Systemic
Solution	Ensure that your web server, application server, load balancer, etc. is configured to set the Permissions-Policy header.
Reference	https://developer.mozilla.org/en-US/docs/Web/HTTP/Reference/Headers/Permissions-Policy https://developer.chrome.com/blog/feature-policy/ https://scotthelme.co.uk/a-new-security-header-feature-policy/ https://w3c.github.io/webappsec-feature-policy/ https://www.smashingmagazine.com/2018/12/feature-policy/
CWE Id	693
WASC Id	15
Plugin Id	10063

Low	Server Leaks Information via "X-Powered-By" HTTP Response Header Field(s)
Description	The web/application server is leaking information via one or more "X-Powered-By" HTTP response headers. Access to such information may facilitate attackers identifying other frameworks/components your web application is reliant upon and the vulnerabilities such components may be subject to.
URL	http://host.docker.internal:3001
Node Name	http://host.docker.internal:3001
Method	GET
Parameter	
Attack	
Evidence	X-Powered-By: Next.js
Other Info	
URL	http://host.docker.internal:3001/dashboard
Node Name	http://host.docker.internal:3001/dashboard
Method	GET
Parameter	
Attack	
Evidence	X-Powered-By: Next.js
Other Info	
URL	http://host.docker.internal:3001/forgot-password
Node Name	http://host.docker.internal:3001/forgot-password
Method	GET
Parameter	
Attack	
Evidence	X-Powered-By: Next.js
Other Info	

URL	http://host.docker.internal:3001/login?next=%2Fsitemap.xml
Node Name	http://host.docker.internal:3001/login (next)
Method	GET
Parameter	
Attack	
Evidence	X-Powered-By: Next.js
Other Info	
URL	http://host.docker.internal:3001/register?next=%2Frobots.txt
Node Name	http://host.docker.internal:3001/register (next)
Method	GET
Parameter	
Attack	
Evidence	X-Powered-By: Next.js
Other Info	
Instances	5
Solution	Ensure that your web server, application server, load balancer, etc. is configured to suppress "X-Powered-By" headers.
Reference	https://owasp.org/www-project-web-security-testing-guide/v42/4-Web_Application_Security_Testing/01-Information_Gathering/08-Fingerprint_Web_Application_Framework https://www.troyhunt.com/shhh-dont-let-your-response-headers/
CWE Id	497
WASC Id	13
Plugin Id	10037

Low	Timestamp Disclosure - Unix
Description	A timestamp was disclosed by the application/web server. - Unix
URL	http://host.docker.internal:3001/_next/static/chunks/0135_%40vis_gl_react-google-maps_dist_index_modern_mjs_14thg6o._.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/0135_@vis_gl_react-google-maps_dist_index_modern_mjs_14thg6o._.js
Method	GET
Parameter	
Attack	
Evidence	2040873379
Other Info	2040873379, which evaluates to: 2034-09-03 05:16:19.
URL	http://host.docker.internal:3001/_next/static/chunks/03gi_next_dist_compiled_react-dom_03jsizz._.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/03gi_next_dist_compiled_react-dom_03jsizz._.js
Method	GET
Parameter	

Attack	
Evidence	2080374784
Other Info	2080374784, which evaluates to: 2035-12-04 09:53:04.
URL	http://host.docker.internal:3001/_next/static/chunks/node_modules__pnpm_1somse8._.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/node_modules__pnpm_1somse8._.js
Method	GET
Parameter	
Attack	
Evidence	1719601643
Other Info	1719601643, which evaluates to: 2024-06-28 19:07:23.
Instances	3
Solution	Manually confirm that the timestamp data is not sensitive, and that the data cannot be aggregated to disclose exploitable patterns.
Reference	https://cwe.mitre.org/data/definitions/200.html
CWE Id	497
WASC Id	13
Plugin Id	10096

Informational	Content-Type Header Missing
Description	The Content-Type header was either missing or empty.
URL	http://host.docker.internal:3001
Node Name	http://host.docker.internal:3001
Method	GET
Parameter	content-type
Attack	
Evidence	
Other Info	
URL	http://host.docker.internal:3001/robots.txt
Node Name	http://host.docker.internal:3001/robots.txt
Method	GET
Parameter	content-type
Attack	
Evidence	
Other Info	
Instances	2
Solution	Ensure each page is setting the specific and appropriate content-type value for the content being delivered.
Reference	https://learn.microsoft.com/en-us/previous-versions/windows/internet-explorer/ie-developer/compatibility/gg622941(v=vs.85)

CWE Id	345
WASC Id	12
Plugin Id	10019

Informational	Information Disclosure - Suspicious Comments
---------------	--

Description	The response appears to contain suspicious comments which may help an attacker.
URL	http://host.docker.internal:3001/_next/static/chunks/03gi_next_0d5psxk_.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/03gi_next_0d5psxk_.js
Method	GET
Parameter	
Attack	
Evidence	is skipped, try to select the next sibling an
Other Info	The following pattern was used: \bSELECT\b and was detected 2 times, the first in likely comment: "// If the element is skipped, try to select the next sibling and try again.", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/03gi_next_0d5psxk_.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/03gi_next_0d5psxk_.js
Method	GET
Parameter	
Attack	
Evidence	/** * Check where the top corner of t
Other Info	The following pattern was used: \bWHERE\b and was detected 2 times, the first in likely comment: "/* * Check where the top corner of the HTML element is relative to the usable * viewport. * * Scroll padding is resolved laz", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/03gi_next_0d5psxk_.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/03gi_next_0d5psxk_.js
Method	GET
Parameter	
Attack	
Evidence	// TODO: Once we start trac
Other Info	The following pattern was used: \bTODO\b and was detected 8 times, the first in likely comment: "// TODO: Once we start tracking back/forward history at each route level,", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/03gi_next_0d5psxk_.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/03gi_next_0d5psxk_.js

Method	GET
Parameter	
Attack	
Evidence	e rewritten ones in from a Server Component.
Other Info	The following pattern was used: \bFROM\b and was detected 8 times, the first in likely comment: "// the rewritten ones in from a Server Component.", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/03gi_next_0d5psxk._js
Node Name	http://host.docker.internal:3001/_next/static/chunks/03gi_next_0d5psxk._js
Method	GET
Parameter	
Attack	
Evidence	ion component if no user-defined boundary is
Other Info	The following pattern was used: \bUSER\b and was detected 6 times, the first in likely comment: "// wrap in an extra function component if no user-defined boundary is", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/03gi_next_0d5psxk._js
Node Name	http://host.docker.internal:3001/_next/static/chunks/03gi_next_0d5psxk._js
Method	GET
Parameter	
Attack	
Evidence	is already caused a bug where the first chi
Other Info	The following pattern was used: \bBUG\b and was detected 2 times, the first in likely comment: "// This already caused a bug where the first child was a <link/> in head.", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/03gi_next_0d5psxk._js
Node Name	http://host.docker.internal:3001/_next/static/chunks/03gi_next_0d5psxk._js
Method	GET
Parameter	
Attack	
Evidence	ly warnings emitted later
Other Info	The following pattern was used: \bLATER\b and was detected in likely comment: "// Capture the Owner Stack during render so dev-only warnings emitted later", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/03gi_next_dist_1tby8ai._js
Node Name	http://host.docker.internal:3001/_next/static/chunks/03gi_next_dist_1tby8ai._js
Method	GET
Parameter	
Attack	
Evidence	find the pathname, query and hash and return

Other Info	The following pattern was used: \bQUERY\b and was detected in likely comment: "/* * Given a path this function will find the pathname, query and hash and return * them. This is useful to parse full paths ", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/03gi_next_dist_1tby8ai_.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/03gi_next_dist_1tby8ai_.js
Method	GET
Parameter	
Attack	
Evidence	with null captured later.
Other Info	The following pattern was used: \bLATER\b and was detected 2 times, the first in likely comment: "// (e.g., in onRecoverableError) with null captured later.", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/03gi_next_dist_1tby8ai_.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/03gi_next_dist_1tby8ai_.js
Method	GET
Parameter	
Attack	
Evidence	// TODO(veil): Include orig
Other Info	The following pattern was used: \bTODO\b and was detected 10 times, the first in likely comment: "// TODO(veil): Include original Owner Stack (NDX-905)", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/03gi_next_dist_1tby8ai_.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/03gi_next_dist_1tby8ai_.js
Method	GET
Parameter	
Attack	
Evidence	ed to * either the user's instrumentation m
Other Info	The following pattern was used: \bUSER\b and was detected 3 times, the first in likely comment: "/* * This module imports the configured client instrumentation modules. * * The `private-next-instrumentation-client` module", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/03gi_next_dist_1tby8ai_.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/03gi_next_dist_1tby8ai_.js
Method	GET
Parameter	
Attack	

Evidence	s the name inferred from the namespace objec
Other Info	The following pattern was used: \bFROM\b and was detected 17 times, the first in likely comment: "// so it retains the name inferred from the namespace object", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/03gi_next_dist_1tby8ai_.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/03gi_next_dist_1tby8ai_.js
Method	GET
Parameter	
Attack	
Evidence	tter error for case where `throw undefined`
Other Info	The following pattern was used: \bWHERE\b and was detected 3 times, the first in likely comment: "// provide better error for case where `throw undefined`", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/03gi_next_dist_compiled_0o3iz22_.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/03gi_next_dist_compiled_0o3iz22_.js
Method	GET
Parameter	
Attack	
Evidence	OTHERWISE, ARISING FROM, * OUT OF OR IN CO
Other Info	The following pattern was used: \bFROM\b and was detected 4 times, the first in likely comment: "/* * MIT License * * Copyright (c) Facebook, Inc. and its affiliates. * * Permission is hereby granted, free of charge, to", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/03gi_next_dist_compiled_0o3iz22_.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/03gi_next_dist_compiled_0o3iz22_.js
Method	GET
Parameter	
Attack	
Evidence	// TODO: remove this key fr
Other Info	The following pattern was used: \bTODO\b and was detected 3 times, the first in likely comment: "// TODO: remove this key from page config instead of allow listing it", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/0t07_%40tanstack_query-core_build_modern_0ngzlox_.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/0t07_@tanstack_query-core_build_modern_0ngzlox_.js

Method	GET
Parameter	
Attack	
Evidence	lbacks or functions where reading the latest
Other Info	The following pattern was used: \bWHERE\b and was detected in likely comment: "/* * Imperative (non-reactive) way to retrieve data for a QueryKey. * Should only be used in callbacks or functions where rea", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/0t07_%40tanstack_query-core_build_modern_Ongzlox._.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/0t07_@tanstack_query-core_build_modern_Ongzlox._.js
Method	GET
Parameter	
Attack	
Evidence	on used by TanStack Query internals. */
Other Info	The following pattern was used: \bQUERY\b and was detected 9 times, the first in likely comment: "/* * Manages environment detection used by TanStack Query internals. */", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/0yf6_react-joyride_dist_index_mjs_1hjn-f._.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/0yf6_react-joyride_dist_index_mjs_1hjn-f._.js
Method	GET
Parameter	
Attack	
Evidence	/** * Select properties from an
Other Info	The following pattern was used: \bSELECT\b and was detected in likely comment: "/* * Select properties from an object */", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/0yf6_react-joyride_dist_index_mjs_1hjn-f._.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/0yf6_react-joyride_dist_index_mjs_1hjn-f._.js
Method	GET
Parameter	
Attack	
Evidence	Log method calls if debug is enabled */
Other Info	The following pattern was used: \bDEBUG\b and was detected in likely comment: "/* * Log method calls if debug is enabled

	*/", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/0yf6_react-joyride_dist_index_mjs_1hjn-f._js
Node Name	http://host.docker.internal:3001/_next/static/chunks/0yf6_react-joyride_dist_index_mjs_1hjn-f._js
Method	GET
Parameter	
Attack	
Evidence	ith undefined value from an object */
Other Info	The following pattern was used: \bFROM\b and was detected 3 times, the first in likely comment: "/* * Remove properties with undefined value from an object */", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/1hn7_tailwind-merge_dist_bundle-mjs_mjs_04a_myf._js
Node Name	http://host.docker.internal:3001/_next/static/chunks/1hn7_tailwind-merge_dist_bundle-mjs_mjs_04a_myf._js
Method	GET
Parameter	
Attack	
Evidence	/** * User Select * @se
Other Info	The following pattern was used: \bUSER\b and was detected in likely comment: "/* * User Select * @see https://tailwindcss.com/docs/user-select */", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/1hn7_tailwind-merge_dist_bundle-mjs_mjs_04a_myf._js
Node Name	http://host.docker.internal:3001/_next/static/chunks/1hn7_tailwind-merge_dist_bundle-mjs_mjs_04a_myf._js
Method	GET
Parameter	
Attack	
Evidence	iciently by joining from startIndex onwards
Other Info	The following pattern was used: \bFROM\b and was detected 4 times, the first in likely comment: "// Build classRest string efficiently by joining from startIndex onwards", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/1hn7_tailwind-merge_dist_bundle-mjs_mjs_04a_myf._js
Node Name	http://host.docker.internal:3001/_next/static/chunks/1hn7_tailwind-merge_dist_bundle-mjs_mjs_04a_myf._js
Method	GET
Parameter	
Attack	

Evidence	m baseConfig Config where other config will b
Other Info	The following pattern was used: \bWHERE\b and was detected in likely comment: "/* * @param baseConfig Config where other config will be merged into. This object will be mutated. * @param configExtension P", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/1hn7_tailwind-merge_dist_bundle-mjs_mjs_04a_myf_.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/1hn7_tailwind-merge_dist_bundle-mjs_mjs_04a_myf_.js
Method	GET
Parameter	
Attack	
Evidence	ttom-left * @todo class group will be
Other Info	The following pattern was used: \bTODO\b and was detected 2 times, the first in likely comment: "/* * Inset Inline Start * @see https://tailwindcss.com/docs/top-right-bottom-left * @todo class group will", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/1o1f_%40radix-ui_react-select_dist_index_mjs_15pwp7m_.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/1o1f_@radix-ui_react-select_dist_index_mjs_15pwp7m_.js
Method	GET
Parameter	
Attack	
Evidence	/ controlled by the user since they may want
Other Info	The following pattern was used: \bUSER\b and was detected in likely comment: "// controlled by the user since they may want to manage overflow in a", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/1o1f_%40radix-ui_react-select_dist_index_mjs_15pwp7m_.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/1o1f_@radix-ui_react-select_dist_index_mjs_15pwp7m_.js
Method	GET
Parameter	
Attack	
Evidence	// src/select.tsx
Other Info	The following pattern was used: \bSELECT\b and was detected 2 times, the first in likely comment: "// src/select.tsx", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/1o1f_%40radix-ui_react-select_dist_index_mjs_15pwp7m_.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/1o1f_@radix-ui_react-select_dist_index_mjs_15pwp7m_.js
Method	GET

Parameter	
Attack	
Evidence	revents the content from going off the start
Other Info	The following pattern was used: \bFROM\b and was detected in likely comment: "// Prevents the content from going off the starting edge of the", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/apps_frontend_1538uwk_.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/apps_frontend_1538uwk_.js
Method	GET
Parameter	
Attack	
Evidence	this is to manage a user
Other Info	The following pattern was used: \bUSER\b and was detected in likely comment: "// this is to manage a user", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/turbopack-apps_frontend_1vgo3ux_.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/turbopack-apps_frontend_1vgo3ux_.js
Method	GET
Parameter	
Attack	
Evidence	a Refresh Boundary later.
Other Info	The following pattern was used: \bLATER\b and was detected in likely comment: "// still a Refresh Boundary later.", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/turbopack-apps_frontend_1vgo3ux_.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/turbopack-apps_frontend_1vgo3ux_.js
Method	GET
Parameter	
Attack	
Evidence	/ same URL: https://bugs.webkit.org/show_bug
Other Info	The following pattern was used: \bBUGS\b and was detected in likely comment: "// same URL: https://bugs.webkit.org/show_bug.cgi?id=187726", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/turbopack-apps_frontend_1vgo3ux_.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/turbopack-apps_frontend_1vgo3ux_.js
Method	GET
Parameter	
Attack	
Evidence	// TODO(alexkirsch) This is
Other Info	The following pattern was used: \bTODO\b and was detected 4 times, the first in likely comment: "// TODO(alexkirsch) This is not defined in the HMR API. It was used to", see evidence field for the suspicious comment/snippet.

URL	http://host.docker.internal:3001/_next/static/chunks/turbopack-apps_frontend_1vgo3ux._.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/turbopack-apps_frontend_1vgo3ux._.js
Method	GET
Parameter	
Attack	
Evidence	ative to the origin where a chunk can be fetc
Other Info	The following pattern was used: \bWHERE\b and was detected 3 times, the first in likely comment: "/* * Returns the URL relative to the origin where a chunk can be fetched from. */", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/turbopack-apps_frontend_1vgo3ux._.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/turbopack-apps_frontend_1vgo3ux._.js
Method	GET
Parameter	
Attack	
Evidence	ead of accessing it from the module object t
Other Info	The following pattern was used: \bFROM\b and was detected 38 times, the first in likely comment: "// We need to store this here instead of accessing it from the module object to:", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/turbopack-apps_frontend_1vgo3ux._.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/turbopack-apps_frontend_1vgo3ux._.js
Method	GET
Parameter	
Attack	
Evidence	emove fragments and query parameters since th
Other Info	The following pattern was used: \bQUERY\b and was detected 7 times, the first in likely comment: "/* * Remove fragments and query parameters since they are never part of the context map keys * * This matches how we parse p", see evidence field for the suspicious comment/snippet.
URL	http://host.docker.internal:3001/_next/static/chunks/turbopack-apps_frontend_1vgo3ux._.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/turbopack-apps_frontend_1vgo3ux._.js
Method	GET
Parameter	
Attack	
Evidence	es the HMR API that user code calls (module.
Other Info	The following pattern was used: \bUSER\b and was detected 2 times, the first in likely comment: "/*

	* Creates the module.hot API object and its internal state. * This provides the HMR API that user code calls (module.hot.a", see evidence field for the suspicious comment/snippet.
Instances	35
Solution	Remove all comments that return information that may help an attacker and fix any underlying problems they refer to.
Reference	
CWE Id	615
WASC Id	13
Plugin Id	10027

Informational	Modern Web Application
Description	The application appears to be a modern web application. If you need to explore it automatically then the Client Spider may well be more effective than the standard one.
URL	http://host.docker.internal:3001
Node Name	http://host.docker.internal:3001
Method	GET
Parameter	
Attack	
Evidence	<script src="/_next/static/chunks/03gi_next_dist_compiled_next-devtools_index_0bx615q.js" async="" nonce="YWVkJyQyNzEtMGY0Ni00YTEwLWE5ZWQtZGYzYzIzYzA4Zjhh"></script>
Other Info	No links have been found while there are scripts, which is an indication that this is a modern web application.
URL	http://host.docker.internal:3001/dashboard
Node Name	http://host.docker.internal:3001/dashboard
Method	GET
Parameter	
Attack	
Evidence	<script src="/_next/static/chunks/03gi_next_dist_compiled_next-devtools_index_0bx615q.js" async="" nonce="N2RIMzI1NWUtNzBjYy00YTE1LTljOTktNTM0NzI1Nzc4ZTNi"></script>
Other Info	No links have been found while there are scripts, which is an indication that this is a modern web application.
Instances	2
Solution	This is an informational alert and so no changes are required.
Reference	
CWE Id	
WASC Id	
Plugin Id	10109

Informational	Non-Storable Content
Description	The response contents are not storable by caching components such as proxy servers. If the response does not contain sensitive, personal or user-specific information, it may benefit from being stored and cached, to improve performance.

URL	http://host.docker.internal:3001
Node Name	http://host.docker.internal:3001
Method	GET
Parameter	
Attack	
Evidence	307
Other Info	
URL	http://host.docker.internal:3001/robots.txt
Node Name	http://host.docker.internal:3001/robots.txt
Method	GET
Parameter	
Attack	
Evidence	307
Other Info	
URL	http://host.docker.internal:3001/sitemap.xml
Node Name	http://host.docker.internal:3001/sitemap.xml
Method	GET
Parameter	
Attack	
Evidence	307
Other Info	
Instances	3
Solution	The content may be marked as storable by ensuring that the following conditions are satisfied: The request method must be understood by the cache and defined as being cacheable ("GET", "HEAD", and "POST" are currently defined as cacheable) The response status code must be understood by the cache (one of the 1XX, 2XX, 3XX, 4XX, or 5XX response classes are generally understood) The "no-store" cache directive must not appear in the request or response header fields For caching by "shared" caches such as "proxy" caches, the "private" response directive must not appear in the response For caching by "shared" caches such as "proxy" caches, the "Authorization" header field must not appear in the request, unless the response explicitly allows it (using one of the "must-revalidate", "public", or "s-maxage" Cache-Control response directives) In addition to the conditions above, at least one of the following conditions must also be satisfied by the response: It must contain an "Expires" header field It must contain a "max-age" response directive For "shared" caches such as "proxy" caches, it must contain a "s-maxage" response directive

	It must contain a "Cache Control Extension" that allows it to be cached It must have a status code that is defined as cacheable by default (200, 203, 204, 206, 300, 301, 404, 405, 410, 414, 501).
Reference	https://datatracker.ietf.org/doc/html/rfc7234 https://datatracker.ietf.org/doc/html/rfc7231 https://www.w3.org/Protocols/rfc2616/rfc2616-sec13.html
CWE Id	524
WASC Id	13
Plugin Id	10049

Informational	Storable and Cacheable Content
----------------------	---------------------------------------

Description	The response contents are storable by caching components such as proxy servers, and may be retrieved directly from the cache, rather than from the origin server by the caching servers, in response to similar requests from other users. If the response data is sensitive, personal or user-specific, this may result in sensitive information being leaked. In some cases, this may even result in a user gaining complete control of the session of another user, depending on the configuration of the caching components in use in their environment. This is primarily an issue where "shared" caching servers such as "proxy" caches are configured on the local network. This configuration is typically found in corporate or educational environments, for instance.
URL	http://host.docker.internal:3001/_next/static/media/5c285b27cdda1fe8-s.p.2_mbdogr7ni8i.woff2
Node Name	http://host.docker.internal:3001/_next/static/media/5c285b27cdda1fe8-s.p.2_mbdogr7ni8i.woff2
Method	GET
Parameter	
Attack	
Evidence	max-age=31536000
Other Info	
Instances	1
Solution	Validate that the response does not contain sensitive, personal or user-specific information. If it does, consider the use of the following HTTP response headers, to limit, or prevent the content being stored and retrieved from the cache by another user: Cache-Control: no-cache, no-store, must-revalidate, private Pragma: no-cache Expires: 0 This configuration directs both HTTP 1.0 and HTTP 1.1 compliant caching servers to not store the response, and to not retrieve the response (without validation) from the cache, in response to a similar request.
Reference	https://datatracker.ietf.org/doc/html/rfc7234 https://datatracker.ietf.org/doc/html/rfc7231 https://www.w3.org/Protocols/rfc2616/rfc2616-sec13.html
CWE Id	524
WASC Id	13
Plugin Id	10049

Informational	Storable but Non-Cacheable Content
----------------------	---

Description	The response contents are storable by caching components such as proxy servers, but will not be retrieved directly from the cache, without validating the request upstream, in response to similar requests from other users.
URL	http://host.docker.internal:3001/_next/static/chunks/0zix_%40swc_helpers_cjs_0hi-e47._.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/0zix_@swc_helpers_cjs_0hi-e47._.js
Method	GET
Parameter	
Attack	
Evidence	no-cache
Other Info	
URL	http://host.docker.internal:3001/_next/static/chunks/%5Broot-of-the-server%5D_06sa18r._.css
Node Name	http://host.docker.internal:3001/_next/static/chunks/[root-of-the-server]__06sa18r._.css
Method	GET
Parameter	
Attack	
Evidence	no-cache
Other Info	
URL	http://host.docker.internal:3001/_next/static/chunks/apps_frontend_1anvha4._.js
Node Name	http://host.docker.internal:3001/_next/static/chunks/apps_frontend_1anvha4._.js
Method	GET
Parameter	
Attack	
Evidence	no-cache
Other Info	
URL	http://host.docker.internal:3001/dashboard
Node Name	http://host.docker.internal:3001/dashboard
Method	GET
Parameter	
Attack	
Evidence	no-cache
Other Info	
URL	http://host.docker.internal:3001/favicon.ico?favicon.34t707dgcc5_r.ico
Node Name	http://host.docker.internal:3001/favicon.ico (favicon.34t707dgcc5_r.ico)
Method	GET
Parameter	
Attack	

Evidence	no-cache
Other Info	
Instances	Systemic
Solution	
Reference	https://datatracker.ietf.org/doc/html/rfc7234 https://datatracker.ietf.org/doc/html/rfc7231 https://www.w3.org/Protocols/rfc2616/rfc2616-sec13.html
CWE Id	524
WASC Id	13
Plugin Id	10049

Sequence Details

With the associated active scan results.