

#Codefromexercise2

```
import pandas as pd
import numpy as np
df= pd.read_csv('penguins_size.csv')
df=df.dropna()
df['species'].replace({'Adelie': 1, 'Chinstrap': 2, 'Gentoo': 3}, inplace=True)
df['island'].replace({'Torgersen': 1, 'Biscoe': 2, 'Dream': 3}, inplace=True)
df['sex'].replace({'MALE': 1, 'FEMALE': 2}, inplace=True)
df.info()
print(df)
df.info()
df['sex'] = pd.to_numeric(df['sex'], errors='coerce')
df=df.dropna()
df.isnull().values.any()
df.head(5)
df.describe()
#Convertcategoricaltoindicatorvalues
df= pd.get_dummies(df)
#Convertdatatoarray
y = np.array(df['body_mass_g'])
#Listfeatures
f_list = list(df.columns)
#Convertdatatoarray
df= np.array(df)
#Trainmodel
from sklearn.model_selection import train_test_split
train_x, test_x, train_y, test_y = train_test_split(df, y, test_size = 0.2, random_state = 42)
#RFC
rfc = RandomForestClassifier(n_estimators=100)
rfc.fit(train_x, train_y)
y_pred = rfc.predict(test_x)
from sklearn import metrics
print(metrics.accuracy_score(test_y,y_pred))
```

#Random Forest

```
from sklearn.ensemble import RandomForestRegressor
```

```

rf = RandomForestRegressor(n_estimators = 1000, random_state = 42)
rf.fit(train_x, train_y);
predictions = rf.predict(test_x)
errors = abs(predictions - test_y)
#Meanabsoluteerror
print( round(np.mean(errors), 2), 'mm.')
MAPE = 100 * (errors / test_y)
accuracy = 100 - np.mean(MAPE)
print(round(accuracy, 2), '%.')

```

#Build Random Hyperparameter Grid

```

from sklearn.model_selection import RandomizedSearchCV
n_estimators = [int(x) for x in np.linspace(start = 200, stop = 2000, num = 10)]

```

#Random Search Training

```

rf_random = RandomizedSearchCV(estimator = rf, param_distributions = random_grid,
n_iter = 100, cv = 3, verbose=2, random_state=42, n_jobs = -1)
rf_random.fit(train_x, train_y)
rf_random.get_params

```

#Evaluate random search

```

def evaluate(model, test_x, test_y):
    predictions = model.predict(test_x)
    errors = abs(predictions - test_y)
    mape = 100 * np.mean(errors / test_y)
    accuracy = 100 - mape
    print('Model Performance')
    print('Average Error: {:.4f} degrees.'.format(np.mean(errors)))
    print('Accuracy = {:.2f}%'.format(accuracy))

    return accuracy

base_model = RandomForestRegressor(n_estimators = 10, random_state = 42)
base_model.fit(train_x, train_y)
base_accuracy = evaluate(base_model, test_x, test_y)

param_grid = {
    'bootstrap': [True],
    'max_depth': [10, 20, 30, 40],

```

```

    'max_features': [2,3],
    'min_samples_leaf': [1, 2, 3],
    'min_samples_split': [8, 10, 12],
    'n_estimators': [1000, 1500, 2000, 2500]
}
from sklearn.model_selection import GridSearchCV
rf = RandomForestRegressor()
grid_search = GridSearchCV(estimator = rf, param_grid = param_grid,
                           cv = 3, n_jobs = -1, verbose = 2)
grid_search.fit(train_x, train_y)

```

```

grid_search.best_params_
best_grid = grid_search.best_estimator_
grid_accuracy = evaluate(best_grid, test_x, test_y)
print('Improvement of {:.2f}%'.format( 100 * (grid_accuracy - base_accuracy) /
base_accuracy))

```

```

param_grid = {
    'bootstrap': [True],
    'max_depth': [20, 30, 40, 50],
    'max_features': [3,4],
    'min_samples_leaf': [2, 3, 4],
    'min_samples_split': [10, 12, 14],
    'n_estimators': [1500, 2000, 2500, 3000]
}
from sklearn.model_selection import GridSearchCV
rf = RandomForestRegressor()
grid_search = GridSearchCV(estimator = rf, param_grid = param_grid,
                           cv = 3, n_jobs = -1, verbose = 2)
grid_search.fit(train_x, train_y)

```

```

grid_search.best_params_
best_grid = grid_search.best_estimator_
Import evaluate
grid_accuracy = evaluate(best_grid, test_x, test_y)
print('Improvement of {:.2f}%'.format( 100 * (grid_accuracy - base_accuracy) /
base_accuracy))

```

#Improvement of 0.67%

#Check for overfitting

```
from sklearn.svm import SVC
svclassifier = SVC(kernel='rbf', C=1)
svclassifier.fit(train_x, train_y)
print(svclassifier.score(train_x, train_y))
print(svclassifier.score(test_x, test_y))
```

#SVM

```
from sklearn.model_selection import train_test_split
features = pd.read_csv('penguins_size.csv')
features = pd.get_dummies(features)
features = features.dropna()
from sklearn.svm import SVC
train_set, test_set = train_test_split(features, test_size=0.2)
```

#Classify

```
x_train = train_set.iloc[:,2].values
y_train = train_set.iloc[:,2].values
x_test = test_set.iloc[:,0:2].values
y_test = test_set.iloc[:,2].values
```

#Time to do the thing

```
m = SVC()
m.fit(x_train, y_train)
print(100*m.score(x_test, y_test), '%')
from sklearn.metrics import classification_report, confusion_matrix
p = m.predict(x_test)
print(classification_report(y_test, p))
```

#Gridsearch

```
from sklearn.model_selection import GridSearchCV
param_grid = {'C': [0.1, 1, 10, 100, 1000],
              'gamma': [1, 0.1, 0.01, 0.001, 0.0001],
              'kernel': ['rbf']}
```

```
g = GridSearchCV(SVC(), param_grid, refit = True, verbose = 3)
```

```
g.fit(x_train, y_train)
g_predictions = g.predict(x_test)

print(classification_report(y_test, g_predictions))
#Check For Overfitting
m.score(x_train,y_train)
m.score(x_test,y_test)
```

#LinearRegression

```
x=features.drop('body_mass_g', axis=1)
y=features.body_mass_g
x_train,x_test,y_train, y_test= train_test_split(x,y, test_size=0.2, random_state=42)
from sklearn.linear_model import LinearRegression
reg = LinearRegression().fit(x,y)
reg.score(x,y)
reg.get_params()
```

```
reg.set_params(**{
    'copy_X': True,
    'fit_intercept': True,
    'n_jobs':0,
    'positive': False})
```

```
reg.score(x,y)
```

```
reg.set_params(**{
    'copy_X': False,
    'fit_intercept': True,
    'n_jobs':0,
    'positive': False})
```

```
reg.score(x,y)
```

```
reg.set_params(**{
    'copy_X': False,
    'fit_intercept': False,
    'n_jobs':0,
    'positive': False})
```

```
reg.score(x,y)
```

```
reg.set_params(**{  
    'copy_X': False,  
    'fit_intercept': False,  
    'n_jobs': 100000,  
    'positive': False})
```

```
reg.score(x,y)
```

```
reg.set_params(**{  
    'copy_X': False,  
    'fit_intercept': False,  
    'n_jobs': 1000000,  
    'positive': True})
```

```
reg.score(x,y)
```

```
reg.score(x_train,y_train)
```

```
reg.score(x_test,y_test)
```

#Codefromexercise2

```
import pandas as pd
import numpy as np
df= pd.read_csv('penguins_size.csv')
df=df.dropna()
df['species'].replace({'Adelie': 1, 'Chinstrap': 2, 'Gentoo': 3}, inplace=True)
df['island'].replace({'Torgersen': 1, 'Biscoe': 2, 'Dream': 3}, inplace=True)
df['sex'].replace({'MALE': 1, 'FEMALE': 2}, inplace=True)
df.info()
print(df)
df.info()
df['sex'] = pd.to_numeric(df['sex'], errors='coerce')
df=df.dropna()
df.isnull().values.any()
df.head(5)
df.describe()
#Convertcategoricaltoindicatorvalues
df= pd.get_dummies(df)
#Convertdatatoarray
y = np.array(df['body_mass_g'])
#Listfeatures
f_list = list(df.columns)
#Convertdatatoarray
df= np.array(df)
```

```
import pandas as pd
from sklearn.ensemble import RandomForestRegressor
from sklearn.model_selection import cross_val_score, train_test_split
from bayes_opt import BayesianOptimization
```

#Load data

```
wn = pd.read_csv('winequality2.csv')
wn.isnull().values.any()
x=wn.drop('quality', axis=1)
y=wn.quality
from sklearn.model_selection import train_test_split
x_train,x_test,y_train, y_test= train_test_split(x,y, test_size=0.2, random_state=42)
from sklearn.ensemble import RandomForestClassifier

rfc = RandomForestClassifier(n_estimators=100)

rfc.fit(x_train,y_train)

y_pred = rfc.predict(x_test)

from sklearn import metrics

print('Accuracy: ', metrics.accuracy_score(y_test,y_pred))
```

#Accuracy is 0.64