

Pipeline Optimization

Bimal Pandey

Introduction: This report introduces pipeline optimization of different ML models to predict wine quality. The method includes the classification task to predict the wine quality. Random Forest and Support vector Machine classifiers are used for the task of classification.

Dataset Description: The Red Wine dataset consists of 1599 observations and 12 characteristics, out of which 11 are input variables and the remaining one is output variable. Here, the data have only float and integer values (only for the target variable) and there are no null/missing values.

Input Variables:

- Fixed Acidity
- Volatile acidity
- Citric acid
- Residual sugar
- Chlorides
- Free sulfur dioxide
- total sulfur dioxide
- density
- Ph
- Sulphates
- Alcohol

Output variable:

- Quality

Experimental Setup: First of all, I imported different libraries needed for implementing and running the program.

```
import pandas as pd

from sklearn.ensemble import RandomForestClassifier

from sklearn.pipeline import Pipeline

from sklearn.ensemble import GradientBoostingClassifier

from sklearn.impute import SimpleImputer

from sklearn.compose import ColumnTransformer

from sklearn.preprocessing import StandardScaler, MinMaxScaler, OneHotEncoder

from sklearn.pipeline import Pipeline

from sklearn.model_selection import train_test_split, GridSearchCV

from sklearn.metrics import accuracy_score
```

```

from sklearn.svm import SVC
from sklearn.compose import ColumnTransformer
import numpy as np
import matplotlib.pyplot as plt
from sklearn.model_selection import KFold
!pip install optuna
import optuna

```

Then, dataset are split into training and test sets. After that, pipeline preprocessing is carried out.

```
numerical_features= X.select_dtypes(include=['int64', 'float64']).columns
```

```
categorical_features= X.select_dtypes(include=['object']).columns
```

The first part of pipeline uses imputer as a tool for the imputation of missing values if any and replaces the missing values with mean of data. The simple imputer is used in this process. Similarly, categorical features are encoded if there exists any. The data are standardized by the Standard Scaler. The Column Transformer is used for combining numerical and categorical preprocessing. The pipeline includes either RandomForestClassifier or SVM classifier in the optimization process. The hyperparameters of these classifiers are systematically tuned using Grid Search method and Bayesian Optimization using optuna.

For the RandomForestClassifier, the default hyperparameters used are

```
n_estimators = trial.suggest_int('n_estimators', 100, 200, step=100)
```

```
max_depth = trial.suggest_int('max_depth', 2, 25, log= True)
```

The grid search is used for the tuning of hyperparameters for both classifier at first stage and best parameters are obtained which are used for training the classifier to get best optimized accuracy. At, the next stage Bayesian optimization using optuna is used for tuning the hyperparameters of both classifier.

Results:

Grid Search Method

RandomForestClassifier

Accuracy before optimization: 0.65

Accuracy after optimization: 0.67

Support Vector Machine

Accuracy before: 0.64

Accuracy after optimization: 0.68

Using Optuna

Random Forest Classifier

Best accuracy: 0.67



