# Introduction to Swirles

and Intel GPUs in general

#### What is Swirles?

- Swirles is our new HPC cluster and the successor to Fawcett.
- There are several partitions (use sinfo to check):
  - The Intel components are named Cosmos XI
    - pvc: 3 nodes of Intel Data Center GPU Max 1550 (PVCs), Sapphire Rapids host with 1TB mem.
    - spr: 4 nodes of Sapphire Rapids HBMs
  - ampere: 3 nodes of Nvidia A100, host has 2TB mem
  - lovelace: 1 node of Nvidia L40
  - genoa: 6 nodes of AMD EPYC 9654, 1.5 TB mem
- Intel parts funded by ExCALIBUR as a GPU testbed (open to all UK researchers)
- For now, we haven't worked out a fair usage policy, expect this to change in the future



### Access to Swirles

• First generate a SSH key-pair using: ssh-keygen -t ed25519 -f <name of ssh key>

replacing <name\_of\_ssh\_key> with something memorable. It will prompt you for a password to access the key pair, please do not leave it blank. The key pair needs to go in your ~/.ssh directory and the public key needs to be sent to <a href="mailto:help@maths.cam.ac.uk">help@maths.cam.ac.uk</a> Early access GR users can send theirs to James Parke.

- Two ways to log in:
  - 1. ssh username@ssh.maths.cam.ac.uk and then ssh swirles.
  - 2. In your .ssh/config file, define a new entry: Host <a href="mailto:swirles.maths.cam.ac.uk">swirles.maths.cam.ac.uk</a>

User <username>

ProxyJump username@ssh.maths.cam.ac.uk
IdentityFile ~/.ssh/<name\_of\_ssh\_key>

Then you can directly log into Swirles using ssh username@swirles.maths.cam.ac.uk

- Your username is your CRSid, the password is your usual Maths password for logging into your desktop or Fawcett
- How to check if you have a login (and how long your account is valid for):

https://useradmin.maths.cam.ac.uk/selfservice/record

• If you don't have a login, you need to contact Maths IT with a support request: <a href="https://exam.ac.uk">help@maths.cam.ac.uk</a> Please also mention which group you belong to so that your usage can be charged correctly and so that you can be assigned the appropriate storage space.

#### Slurm on Swirles

#### How to submit jobs

- You can use mpirun directly from the node (for now...) or you can use Slurm to queue a job (recommended)
- Example Slurm script (also on the GitHub repo):

```
#!/bin/bash
#SBATCH --partition <name>
                                  #<name> can be either pvc, ampere, genoa, spr
#SBATCH --nodes=<#nodes>
                                  #how many nodes
#SBATCH --ntasks=<#tasks>
                                  #how many tasks (MPI ranks) in total
#SBATCH --cpus-per-task=<#cpus>
                                  #set to > 1 to use OpenMP threads
#SBATCH --time=<hh:mm:ss>
#SBATCH --gres=gpu:<#gpus>
                                  #necessary for GPU resources, choose from 1 - 4
export OMP_NUM_THREADS=$SLURM_CPUS_PER_TASK
cd ${MY_WORK_DIR}
source my_modules.sh
mpirun -np $SLURM_NTASKS ./my_exec
```

### Slurm on Swirles

#### How to submit jobs

- Can also use 'srun' or 'salloc'
- For example:
  - srun -p pvc --nodes=1 --mpi=pmi2 --cpus-per-task=28 --gres=gpu:1 -time=00:30:00 <my program>
    - Run my\_program on a compute node with 28 MPI ranks for 30 min but output to my current terminal
  - salloc -p pvc --nodes=1 --cpus-per-task=28 --time=00:30:00
    - Run an interactive job with 28 MPI ranks for 30 mins (need to ssh into the compute node yourself)
    - If using mpirun directly on PVCs, use the option --bootstrap=fork (this will expose the tiles as separate devices). Also unset ZE\_AFFINITY\_MASK.

### The Swirles environment

- Swirles uses a module system, like on Fawcett.
- No modules are loaded by default (try doing a module list)
- To gain access to the modules compiled for Swirles type:
  - module use /cephfs/software/spack/spack-modules/maths-2024.1/linux-ubuntu22.04-x86\_64\_v4
  - Some essential modules:
    - module load cmake
    - module load miniforge3/4.8.3-4-Linux-x86\_64/gcc/s2ikv54u
    - module load python/3.11.7/gcc/swa4n3ak
      - Then use a virtual env to install the python packages that you need.
- The OS is Ubuntu 22.04
- Editors are vi or nano But I have an emacs installation which you are welcome to use:

```
/alt/applic/user-maint/jk945/emacs
```

Just make an alias or add it to your PATH in .bashrc

## Compilers on Swirles

- For an Intel oneAPI environment:
  - module load intel/compiler-intel-llvm/2024.2.0
  - module load intel/mpi/2021.13
  - module load intel/mkl/2024.2
  - The MPI compiler is then mpiicc/mpiicpx/mpiifx
- For a GNU environment:
  - module load gcc
  - module load openmpi
  - The MPI compiler is then mpicc/mpicxx/mpif90
- For CUDA:
  - module load cuda/12.6.3/gcc/bxp4amlg
  - The compiler is nvcc
  - There is no CUDA enabled MPI library yet
- NB: You can type 'which mpirun' to check your version of MPI

## Example environment setup

On the sw-pvc0X nodes, type: source /local/scratch/public/swirles-env.sh to set up the following environment

```
#!/bin/bash
module load intel/compiler-intel-llvm/2024.2.0
module load intel/mpi/2021.13
module load intel/mkl/2024.2
export I_MPI_PMI_LIBRARY=/usr/lib/x86_64-linux-gnu/libpmi2.so #this points Slurm to the API (PMI-2) for launching MPI jobs
                                                               #this allows GPU to GPU direct communication via MPI (GPU aware MPI)
export I_MPI_0FFL0AD=1
unset ZE_AFFINITY_MASK
                                                               #if this is set, then GPU pinning is automatically disabled
export ZE FLAT DEVICE HIERARCHY=FLAT
                                                               #exposes tiles as separate devices
export I_MPI_OFFLOAD_TOPOLIB=level_zero
                                                               #set interface for GPU topology recognition to level zero
                                                               #enable GPU pinning (somewhat degenerate with I_MPI_OFFLOAD)
export I_MPI_OFFLOAD_PIN=1
export I_MPI_DEBUG=3
                                                               #this prints pinning information
alias my_sysmon='watch -n 1 /alt/applic/user-maint/jk945/pti-gpu/tools/sysmon/install/bin/sysmon'
```

This contains all the environment variables you need to run a SYCL program or use MPI enabled GPU communications or use Slurm with multiple GPUs per job

More info at Miren's guide to running GRTeclyn on Dawn: <a href="https://github.com/GRTLCollaboration/GRTeclyn/issues/67">https://github.com/GRTLCollaboration/GRTeclyn/issues/67</a>

## Storage on Swirles

#### Where do I put my stuff?

- /home/<username> should be the same as on Fawcett/local desktop
- You should have space for outputs on /cephfs/store/<group-name> the amount of space each group has depends on their level of contribution towards the purchase of the system.
- There is an additional 5 GB for user wide installations of software at /alt/applic/user-maint/<username>

#### Hands-on demos

- There are some simple MPI, SYCL, Pytorch scripts in the GitHub repo
  - Load your preferred modules (this must be the Intel oneAPI libraries if using SYCL)
  - Compile: mpicpx -c test\_sycl.cxx
  - Link: mpicpx -o test\_sycl.out -fsycl test\_sycl.o
- Try out your own codes:
  - Pluto: OK
  - Athena++: OK
  - Idefix: Limited functionality, Serial host + CUDA: OK, MPI + OpenMP: OK, MPI + CUDA: Not currently possible, MPI+SYCL: Not currently possible