go2market

Communication Platform

Bi-Directional Audio Streaming

Complete WebSocket Integration Guide

Version	2.0 — Enhanced
Date	April 2026
Audience	Partners & Developers
Classification	Confidential

Confidential — Internal & Partner Use Only

© 2026 go2market India Pvt Ltd

Introduction

This document is the complete technical and operational reference for integrating with go2market's Bi-Directional Audio Streaming framework. It covers everything from the WebSocket event specification to sample code, real-world use cases, troubleshooting, and a deployment checklist.

The go2market audio streaming system enables continuous, low-latency transfer of voice audio and metadata between the platform and your external endpoint. Once connected, go2market forwards live caller audio every 100 ms; your server processes it (using AI, IVR logic, or any pipeline) and returns synthesized audio that go2market plays back to the caller in real time.

1. Overview

Two categories of events power the exchange:

Direction	Who Sends	Events
Outbound	go2market → Your Endpoint	connected, start, media, stop, dtmf, mark
Inbound	Your Endpoint → go2market	media, mark, clear

Audio Format (fixed throughout integration)

Encoding: mulaw / G.711 μ-law (audio/x-mulaw)

Sample Rate: 8,000 Hz | Bit Depth: 8-bit | Bit Rate: 64 kbps

Chunk alignment (inbound): 160 bytes or a clean multiple (320, 480 … 4000)

© 2026 go2market India Pvt Ltd

2. Getting Started — 5 Steps to Go Live

Follow these five steps in order to integrate with go2market audio streaming.

1

Set Up Your WebSocket Server

Spin up a WebSocket server that accepts persistent connections. It must handle concurrent streams and process JSON messages. Node.js (ws library), Python (websockets / FastAPI), or any language works.

2

Share Your WSS URL with go2market

Provide your endpoint URL in the format wss://your-domain.com/stream. Ensure TLS is configured (wss:// is mandatory). go2market will call this URL each time a new call is initiated.

3

Receive the 'start' Event

The first meaningful event after connection. It carries streamSid, callSid, accountSid, caller/callee numbers, audio format, and any customParameters your team configured. Parse this to initialize your session state.

4

Handle Incoming 'media' Events

go2market sends one media event every 100 ms. Each carries a Base64-encoded mulaw audio chunk. Decode → buffer → send to your AI/speech pipeline. Track sequenceNumber to detect dropped frames.

5

Send Back a 'media' Response

Return your synthesized or processed audio by sending a media event with Base64-encoded mulaw payload, aligned to 160-byte boundaries. Optionally follow with a mark event to receive a playback-complete callback.

© 2026 go2market India Pvt Ltd

3. Authentication & Security

Securing your WebSocket endpoint is critical. go2market supports the following authentication patterns:

Method	How to Implement	Recommended For
Bearer Token (Header)	Pass Authorization: Bearer <token> in the HTTP upgrade request headers	Most integrations
Query Parameter Token	Append ?token=<secret> to the wss:// URL	Quick prototypes
mTLS (Client Certificates)	Configure mutual TLS on your server; go2market sends a client cert	Enterprise / high-security
IP Allowlisting	Restrict ingress to go2market's published IP ranges	Additional layer

Security Best Practices

- Always use wss:// (TLS). Plain ws:// will be rejected.
- Rotate tokens periodically and store them in environment variables — never hardcode.
- Validate the streamSid on every event to prevent stream-injection attacks.
- Implement rate limiting on your WebSocket endpoint.

© 2026 go2market India Pvt Ltd

4. Outbound Events (go2market → Your Endpoint)

4.1 connected — Session Handshake

Sent immediately upon WebSocket connection. Confirms the channel is open.

Property	Type	Description
event	string	Always "connected"

```
{
  "event": "connected"
}
```

4.2 start — Stream Initialization

Sent once, right after connected. Contains all session metadata your server needs.

Property	Type	Description
event	string	Always "start"
sequenceNumber	string	Starts at "1"; monotonically increasing
start.streamSid	string	Unique ID for this stream session (MZ…)
start.accountSid	string	Your go2market account identifier (AC…)
start.callSid	string	Unique call identifier (CA…)
start.from	string	Caller's phone number
start.to	string	Callee's phone number
start.direction	string	"inbound" or "outbound"
start.mediaFormat.encoding	string	Always "audio/x-mulaw"
start.mediaFormat.sampleRate	number	Always 8000 Hz
start.mediaFormat.bitRate	number	Always 64 kbps
start.mediaFormat.bitDepth	number	Always 8 bits
start.customParameters	object	Optional key-value pairs set by your team
streamSid	string	Top-level mirror of start.streamSid

```
{
  "event": "start",
  "sequenceNumber": "1",
  "start": {
    "accountSid": "ACXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX",
    "streamSid":  "MZXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX",
    "callSid":    "CAXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX",
    "from": "+911234567890",
    "to":   "+919876543210",
    "direction": "inbound",
    "mediaFormat": {
      "encoding":   "audio/x-mulaw",
      "sampleRate": 8000,
      "bitRate":    64,
```

© 2026 go2market India Pvt Ltd

```
      "bitDepth":   8
    },
    "customParameters": {
      "FirstName": "Jane",
      "LastName":  "Doe",
      "CRM_ID":    "CRM-00421"
    }
  },
  "streamSid": "MZXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX"
}
```

4.3 media — Live Audio Frames

One event every 100 ms throughout the call. Carries raw mulaw audio as Base64.

Property	Type	Description
event	string	Always "media"
sequenceNumber	string	Increments per event; use to detect dropped frames
media.chunk	string	Chunk index starting at "1"
media.timestamp	string	Elapsed ms from stream start
media.payload	string	Base64-encoded mulaw/8000 PCM audio
streamSid	string	Matches the value from the start event

```
{
  "event": "media",
  "sequenceNumber": "3",
  "media": {
    "chunk":     "1",
    "timestamp": "100",
    "payload":   "no+JhoaJjpz..."
  },
  "streamSid": "MZXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX"
}
```

4.4 stop — Stream Termination

Sent when the call ends or stream is explicitly closed. No further media events follow.

Property	Type	Description
event	string	Always "stop"
sequenceNumber	string	Continues the session counter
stop.accountSid	string	Account that owned the stream
stop.callSid	string	Call that has ended
stop.reason	string	Human-readable termination reason
streamSid	string	Stream that has been closed

```
{
```

© 2026 go2market India Pvt Ltd

```
  "event": "stop",
  "sequenceNumber": "5",
  "stop": {
    "accountSid": "ACXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX",
    "callSid":    "CAXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX",
    "reason":     "Caller disconnected"
  },
  "streamSid": "MZXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX"
}
```

4.5 dtmf — Keypad Input

Fired when a caller presses a key. Use for menu navigation or PIN entry.

```
{
  "event": "dtmf",
  "streamSid":      "MZXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX",
  "sequenceNumber": "5",
  "dtmf": { "digit": "1" }
}
```

4.6 mark — Playback Completion Signal

go2market echoes this back (with the same label) once all queued audio before the mark has finished playing.

```
{
  "event": "mark",
  "sequenceNumber": "4",
  "streamSid": "MZXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX",
  "mark": { "name": "segment-end-label" }
}
```

© 2026 go2market India Pvt Ltd

5. Inbound Events (Your Endpoint → go2market)

5.1 media — Return Audio

Inject synthesized audio into the call. Payload must be Base64-encoded mulaw/8000 PCM, **aligned to 160-byte boundaries**. Non-conforming payloads cause audible artifacts.

```
{
  "event": "media",
  "streamSid": "MZXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX",
  "media": {
    "payload": "a3242sa...",
    "chunk": 1
  }
}
```

5.2 mark — Playback Checkpoint

Send after one or more media events. go2market echoes it back once that audio finishes playing, letting you sequence segments precisely.

```
{
  "event": "mark",
  "streamSid": "MZXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX",
  "mark": { "name": "response-block-1" }
}
```

5.3 clear — Buffer Flush

Immediately discards all buffered audio on go2market's side. Use for barge-in: when the caller interrupts the AI's response.

```
{
  "event": "clear",
  "streamSid": "MZXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX"
}
```

© 2026 go2market India Pvt Ltd

6. Sample Code

The following examples demonstrate a minimal but production-ready integration pattern in Node.js.

6.1 WebSocket Server — Receive Audio

```
// install: npm install ws
const WebSocket = require('ws');
const wss = new WebSocket.Server({ port: 8080 });

wss.on('connection', (ws) => {
  console.log('New stream connection');
  let sessionMeta = null;

  ws.on('message', (rawMsg) => {
    const msg = JSON.parse(rawMsg);

    switch (msg.event) {
      case 'connected':
        console.log('Handshake received — channel open');
        break;

      case 'start':
        sessionMeta = msg.start;
        console.log('Stream started:', sessionMeta.streamSid);
        console.log('Caller:', sessionMeta.from, '->', sessionMeta.to);
        break;

      case 'media':
        const audioBuffer = Buffer.from(msg.media.payload, 'base64');
        // → Send audioBuffer to your AI / ASR pipeline
        handleAudio(ws, msg.streamSid, audioBuffer);
        break;

      case 'dtmf':
        console.log('Key pressed:', msg.dtmf.digit);
        break;

      case 'stop':
        console.log('Stream ended:', msg.stop.reason);
        cleanupSession(msg.streamSid);
        break;
    }
  });
});
```

6.2 Send Dummy Audio Response

```
// Generate 160 bytes of silence (mulaw silence = 0xFF)
function silencePayload(bytes = 160) {
  return Buffer.alloc(bytes, 0xFF).toString('base64');
}

function handleAudio(ws, streamSid, audioBuffer) {
  // Replace silencePayload() with your real TTS / AI output
  const responsePayload = silencePayload(160);
```

© 2026 go2market India Pvt Ltd

```
  // Send audio back to go2market
  ws.send(JSON.stringify({
    event: 'media',
    streamSid,
    media: { payload: responsePayload, chunk: 1 }
  }));

  // Optional: request playback-complete callback
  ws.send(JSON.stringify({
    event: 'mark',
    streamSid,
    mark: { name: 'response-sent-' + Date.now() }
  }));
}

function cleanupSession(streamSid) {
  // Release AI context, close DB connections, etc.
  console.log('Cleaning up session:', streamSid);
}
```

6.3 Python Alternative (websockets library)

```
# install: pip install websockets
import asyncio, json, base64, websockets

async def handler(websocket):
    async for raw in websocket:
        msg = json.loads(raw)
        event = msg.get('event')

        if event == 'connected':
            print('Connected')

        elif event == 'start':
            stream_sid = msg['start']['streamSid']
            print(f'Stream started: {stream_sid}')

        elif event == 'media':
            audio = base64.b64decode(msg['media']['payload'])
            # → Process audio (ASR / AI)
            response = base64.b64encode(b'\xff' * 160).decode()
            await websocket.send(json.dumps({
                'event': 'media',
                'streamSid': msg['streamSid'],
                'media': {'payload': response, 'chunk': 1}
            }))

        elif event == 'stop':
            print('Stream stopped:', msg['stop']['reason'])

async def main():
    async with websockets.serve(handler, '0.0.0.0', 8080):
        await asyncio.Future()

asyncio.run(main())
```

© 2026 go2market India Pvt Ltd

7. Real-World Use Case — AI Voice Agent

A customer calls into your IVR. go2market streams their voice to your AI server. The AI transcribes speech, generates a reply, converts it to audio, and plays it back — all in near real time.

7.1 End-to-End Flow

Step	Who	Action	go2market Event
1	go2market	Customer call arrives; WebSocket connection opened	connected
2	go2market	Session metadata sent (numbers, codec, CRM params)	start
3	go2market	Customer audio streamed at 100 ms intervals	media (outbound)
4	Your Server	Audio decoded → sent to ASR (e.g., Deepgram, OpenAI Whisper)	—
5	Your Server	Transcript → LLM → response text generated	—
6	Your Server	Response text → TTS → mulaw audio generated	—
7	Your Server	mulaw audio sent back in 160-byte chunks	media (inbound)
8	Your Server	Mark sent to detect playback completion	mark (inbound)
9	go2market	Audio played to caller; mark echoed back when done	mark (outbound)
10	go2market	Caller hangs up; stream terminated	stop

7.2 Barge-In (Interruption) Pattern

When the customer speaks while the AI is talking — a "barge-in" — your server must:

1. Detect the customer voice in the incoming media stream (VAD — Voice Activity Detection)
2. Send a clear event immediately to flush go2market's playback buffer
3. Stop generating the previous TTS response
4. Process the new customer utterance and generate a fresh response
5. Send the new audio via media events

© 2026 go2market India Pvt Ltd

8. Stream Lifecycle

Phase	Event(s)	Your Action
Connection	connected	Confirm socket open; allocate session state
Initialization	start	Store streamSid, callSid, caller info; init AI context
Bidirectional Audio	media (both directions)	Decode → process → respond with audio
Synchronization	mark (both directions)	Use to gate next audio segment on confirmed playback
Interruption	clear (inbound)	Flush outgoing buffer; restart AI response pipeline
DTMF Input	dtmf	Handle keypress: navigate menu, capture PIN, etc.
Termination	stop	Flush pending work; release resources; close AI session

© 2026 go2market India Pvt Ltd

9. Error Handling & Troubleshooting

Symptom	Likely Cause	Fix
Audio sounds choppy / robotic	Inbound payload not aligned to 160 bytes	Pad payload to next 160-byte multiple
Stream stops unexpectedly	Server not responding within timeout	Implement WebSocket ping/pong heartbeat
Missing audio segments	Dropped frames (gap in sequenceNumber)	Validate sequenceNumber; request retransmit or interpolate
go2market doesn't connect	WSS URL invalid or cert untrusted	Verify TLS cert chain and wss:// URL format
Authentication failure	Token missing or expired	Check Authorization header; rotate and redeploy token
mark event not received	clear was sent before mark could echo	Only send clear when intentionally interrupting
High latency in AI response	Full ASR+LLM+TTS pipeline too slow	Use streaming ASR + streaming TTS; pre-generate silence

9.1 Heartbeat Implementation

```
// Keep the WebSocket alive — go2market drops idle connections
const HEARTBEAT_INTERVAL = 25000; // 25 seconds

wss.on('connection', (ws) => {
  const ping = setInterval(() => {
    if (ws.readyState === WebSocket.OPEN) ws.ping();
  }, HEARTBEAT_INTERVAL);

  ws.on('pong', () => console.log('Heartbeat pong received'));
  ws.on('close', () => clearInterval(ping));
});
```

© 2026 go2market India Pvt Ltd

10. Implementation Notes

- **streamSid uniqueness:** Every event in a session shares the same streamSid. Mismatches cause routing failures — always validate.
- **Base64 encoding:** All audio payloads (both directions) must be Base64-encoded mulaw/8000 PCM.
- **Chunk alignment:** Inbound audio must align to 160-byte boundaries. Deviations cause audible artifacts.
- **mark for synchronization:** The primary mechanism for sequencing audio segments. Use it before sending the next segment.
- **Post-stop discipline:** After receiving stop, never send further media or mark events for that streamSid.
- **Sequence validation:** go2market guarantees delivery order, but still validate sequenceNumber to detect dropped frames.
- **Concurrency:** Your server must handle multiple simultaneous WebSocket connections — one per active call.

© 2026 go2market India Pvt Ltd

11. Pre-Launch Customer Checklist

Complete all items below before going live. This checklist covers infrastructure, integration logic, audio quality, and operational readiness.

11.1 Infrastructure & Connectivity

	Category	Requirement	Notes / Status
☐	**WebSocket URL**	WSS endpoint is reachable from the internet	wss://your-domain.com/stream
☐	**TLS Certificate**	Valid cert installed; chain is trusted	Check with: curl -I https://your-domain.com
☐	**DNS**	Domain resolves correctly and is stable	Avoid dynamic IPs
☐	**Port**	Inbound port open in firewall (443 or 8080)	Verify with nmap or telnet
☐	**Load Balancing**	Sticky sessions configured for WebSocket	Needed if using multiple nodes
☐	**Auto-scaling**	Server scales under concurrent call load	Test with 50+ simultaneous connections

11.2 Authentication

	Category	Requirement	Notes / Status
☐	**Auth Method**	Bearer token, query param, or mTLS configured	Agree method with go2market team
☐	**Token Rotation**	Process in place to rotate secrets	Minimum every 90 days
☐	**IP Allowlist**	go2market IPs added to your ingress rules	Request IP list from go2market support
☐	**StreamSid Validation**	Each event's streamSid validated server-side	Prevents injection attacks

11.3 Audio Processing

	Category	Requirement	Notes / Status
☐	**Decoding**	Base64 → mulaw decoded correctly	Test with a known audio file
☐	**Chunk Alignment**	Outbound payload = 160 bytes or multiple	Log payload sizes in dev mode
☐	**Encoding**	Response audio re-encoded to mulaw/8000	Use ffmpeg or libmulaw
☐	**Silence Padding**	Gaps filled with 0xFF silence bytes	Prevents buffer underruns
☐	**Latency Target**	End-to-end AI response < 500 ms	Measure ASR + LLM + TTS separately

11.4 Integration Logic

© 2026 go2market India Pvt Ltd

	Category	Requirement	Notes / Status
☐	**Event Handling**	All 6 events handled: connected, start, media, stop, dtmf, mark	No unhandled events
☐	**Session State**	streamSid, callSid stored per connection	Use Map<streamSid, sessionObj>
☐	**Sequence Tracking**	sequenceNumber validated per stream	Log gaps; alert on > 3 missed
☐	**Barge-In / clear**	clear event sent on detected interruption	Test with VAD enabled
☐	**mark Usage**	mark sent after each audio segment	Confirm echo received before next segment
☐	**stop Cleanup**	Resources freed on stop event	No memory leaks after call ends

11.5 Operational Readiness

	Category	Requirement	Notes / Status
☐	**Logging**	All events logged with streamSid + timestamp	Use structured JSON logs
☐	**Monitoring**	Alerts on connection errors and latency spikes	Integrate with Datadog / Grafana
☐	**Error Recovery**	Graceful handling of WebSocket disconnects	Implement reconnect with backoff
☐	**Load Testing**	Tested at 2× expected peak concurrency	Use k6 or Locust
☐	**Runbook**	On-call runbook documented for incidents	Include escalation path
☐	**go2market Contact**	Support contact confirmed for go-live day	Slack channel or email thread ready

© 2026 go2market India Pvt Ltd

12. Glossary

Term	Definition
streamSid	Unique identifier (MZ…) for a single streaming session
callSid	Unique identifier (CA…) for the phone call
accountSid	go2market account identifier (AC…)
mulaw / G.711 μ-law	Audio compression codec; 8-bit samples at 8000 Hz; used for telephony
Base64	Encoding scheme that converts binary data to ASCII text for JSON transport
DTMF	Dual-Tone Multi-Frequency; tones generated when pressing telephone keys
VAD	Voice Activity Detection; detects presence of speech in an audio stream
ASR	Automatic Speech Recognition; converts speech audio to text
TTS	Text-to-Speech; converts text to synthesized speech audio
Barge-in	Customer interrupts AI playback; requires clear + fresh response
mark	Checkpoint mechanism: echoed back by go2market on playback completion
clear	Inbound event to flush go2market's audio playback buffer immediately
WSS	WebSocket Secure; WebSocket over TLS (mandatory for this integration)

© 2026 go2market India Pvt Ltd

13. OBD Campaign API

The Create OBD Campaign API allows you to launch an Outbound Dialer (OBD) voice campaign programmatically. Use this during demos to place test calls and validate your audio streaming integration end-to-end.

What is OBD?

Outbound Dialer (OBD) lets go2market automatically dial a list of phone numbers and play a pre-recorded or AI-generated voice message. Combined with the WebSocket audio streaming integration, your AI responses can be delivered live to each called party.

13.1 API Details

Field	Value
Method	POST
URL	https://obd.voicensms.in/obd/OBDAPI/webresources/CreateOBDCampaignPost
Content-Type	application/json
Authentication	ukey parameter (unique per user account)

13.2 Request Body — Full Example

```
{
  "sourcetype":    "1",
  "sendnow":       "0",
  "schddate":      "2018-02-15 12:57:00",
  "campaigntype":  "4",
  "filetype":      "2",
  "ukey":          "u0cwLIzeZVp9FKHvQ4-jXG7sriBTt_mYgg==",
  "serviceno":     "073/ 086/ 079/ 0140",
  "ivrtemplateid": "163",
  "retryatmpt":    "0",
  "retryduration": "15",
  "msisdnlist": [
    {
      "phoneno": "93XXXXXXXX",
      "WSS":     "XXXXXXXXX"
    }
  ]
}
```

13.3 Parameter Reference

Parameter	Type	Required	Description / Allowed Values
sourcetype	string	Yes	"1" — fetch phone numbers from msisdnlist array
sendnow	string	Yes	"0" = Send immediately | "1" = Schedule for schddate
schddate	string	Conditional	Scheduled datetime: "YYYY-MM-DD HH:MM:SS" (only used when sendnow = "1")
campaigntype	string	Yes	"3" = Promotional | "4" = Transactional

© 2026 go2market India Pvt Ltd

Parameter	Type	Required	Description / Allowed Values
filetype	string	Yes	"2" — fixed value, do not change
ukey	string	Yes	Your unique authentication key — available in your go2market user profile
serviceno	string	Yes	Caller service number (e.g., 073 / 086 / 079 / 0140)
ivrtemplateid	string	Yes	"26" = Simple | "37" = DTMF | "39" = Latching | Custom ID (shared by go2market)
retryatmpt	string	No	Number of retry attempts on failed/unanswered calls (e.g., "0", "1", "2")
retryduration	string	No	Wait between retries: "0" = immediate | "15" = 15 min | "30" = 30 min | "60" = 1 hour
voice_file	string	No	Name of the pre-recorded voice file to play
dtmf_input	string	No	Valid DTMF digit(s) expected from the caller
wait_duration	string	No	Max wait for DTMF input — maximum value is 8 seconds
noinput_prompt	string	No	Audio prompt played when no DTMF input is received
invalid_file	string	No	Audio file played on invalid DTMF input
thankyou_file	string	No	Audio file played at end of successful interaction
retry_attempt	string	No	Number of retries allowed within a DTMF session
retry_digit	string	No	DTMF digit that triggers a retry within the session
msisdnlist	array	Yes	Array of objects: [{"phoneno": "93XXXXXXXX", "WSS": "XXXXXXXXX"}]
msisdnlist.phoneno	string	Yes	Destination phone number to be dialled
msisdnlist.WSS	string	Yes	WebSocket Stream Session ID — links this call to your WS stream

13.4 ivrtemplateid Quick Reference

Template ID	Type	Use Case	DTMF Support
26	Simple	Play a single voice message; no interaction required	No
37	DTMF	Caller presses keys to navigate IVR menu	Yes
39	Latching	Extended session; maintains call connection for multi-step flows	Yes
Custom	Custom (WSS)	Unique template built by go2market; uses WebSocket Streaming (WSS) to deliver live AI audio to the called party in real time	Yes — WSS

13.5 Campaign Type Comparison

campaigntype	Label	Use For	Regulatory Note
3	Promotional	Marketing, offers, announcements to opted-in lists	DND compliance required
4	Transactional	OTPs, alerts, order updates, service notifications	Exempt from DND restrictions

© 2026 go2market India Pvt Ltd

13.6 sendnow & Scheduling

sendnow Value	Behaviour	schddate Required?
"0"	Campaign launches immediately after API call	No — ignored even if provided
"1"	Campaign is scheduled; starts at the time set in schddate	Yes — format: YYYY-MM-DD HH:MM:SS

✅ Demo Testing Tips

1. Set sendnow to "0" to fire the campaign instantly during a demo.
2. Use campaigntype "4" (Transactional) to bypass DND filters on test numbers.
3. Set retryatmpt to "0" during demos to avoid repeated calls to the same number.
4. Use ivrtemplateid "26" (Simple) for the quickest demo — no DTMF handling needed.
5. Your ukey is available under Profile → API Settings in the go2market dashboard.

13.7 cURL Demo Command

```
curl -X POST \
  https://obd.voicensms.in/obd/OBDAPI/webresources/CreateOBDCampaignPost \
  -H 'Content-Type: application/json' \
  -d '{
    "sourcetype":    "1",
    "sendnow":       "0",
    "campaigntype":  "4",
    "filetype":      "2",
    "ukey":          "YOUR_UKEY_HERE",
    "serviceno":     "073",
    "ivrtemplateid": "26",
    "retryatmpt":    "0",
    "retryduration": "15",
    "msisdnlist":    [{"phoneno": "93XXXXXXXXXX", "WSS": "YOUR_WSS_ID"}]
  }'
```

13.8 Retry Logic

Total Calls = 1 (original) + retryatmpt (retries)

go2market currently supports retryatmpt values: 0, 1, or 2 (max 2 retries = 3 total calls)

retryatmpt value	Total Calls	retryduration options	Call Timeline
0	1 call	N/A (no retry)	Call 1 at T+0 min. No further attempts regardless of outcome.
1	2 calls	0 / 15 / 30 / 60	• duration=0: Call 1 at T+0 min → immediate retry → Call 2 at T+0 min

© 2026 go2market India Pvt Ltd

			• duration=15: Call 1 at T+0 min → retry → Call 2 at T+15 min • duration=30: Call 1 at T+0 min → retry → Call 2 at T+30 min • duration=60: Call 1 at T+0 min → retry → Call 2 at T+60 min
2 ★ MAX	3 calls	0 / 15 / 30 / 60	**Example (duration=15): Call 1 at T+0 → Call 2 at T+15 min → Call 3 at T+30 min** Example (duration=30): Call 1 at T+0 → Call 2 at T+30 min → Call 3 at T+60 min Example (duration=60): Call 1 at T+0 → Call 2 at T+60 min → Call 3 at T+120 min *★ Recommended for TQ-6.3 compliance. Retries stop immediately on first ANSWERED call.*

⚠ Important Notes
- go2market currently supports a maximum of retryatmpt="2" (i.e., 2 retries = 3 total calls).
- A separate CDR callback is delivered to your webhook for EVERY call attempt (including retries). Each CDR carries a retryAttempt field (0, 1, 2) so you can track which attempt this represents.
- If any attempt is ANSWERED, all remaining scheduled retries are automatically cancelled.
- retryduration applies uniformly between each pair of attempts (the same gap is used for all retries in a campaign).

13.9 Pacing Control

go2market's Outbound Dialer (OBD) supports configurable call pacing to control the rate at which bulk outbound notifications are dispatched. Pacing is controlled through campaign scheduling, retry intervals, and batch sizing parameters in the OBD API.

Pacing Control	API Parameter	Details & Allowed Values
Dispatch Mode	sendnow	• "0" — Immediate dispatch (all numbers dialled as fast as possible) • "1" — Scheduled start; set exact launch time via schddate (YYYY-MM-DD HH:MM:SS). Use to stagger large batches across specific time windows (e.g., 9 AM–6 PM only).
Retry Gap (Inter-attempt Pacing)	retryduration	Controls the wait time between each call attempt for a given number: • "0" — Immediate retry (no gap) • "15" — 15-min gap • "30" — 30-min gap • "60" — 60-min gap *Applies uniformly to all retry pairs in the campaign. Primary pacing lever for avoiding call congestion per number.*
Campaign Type (Regulatory Pacing)	campaigntype	• "3" Promotional — DND-filtered, limits reach to opted-in numbers only (natural throughput cap) • "4" Transactional — Full list dialled, no DND filter, maximum throughput
Batch Wave Pacing	msisdnlist + schddate	Split a large list into smaller batches across multiple API calls. Each call = one campaign wave. Schedule waves at desired intervals using schddate.

© 2026 go2market India Pvt Ltd

		Example: 1,00,000 numbers → 10 batches of 1,0000 each → 1 wave per hour = spread over 10 hours.

Common Pacing Scenarios

Use Case	sendnow	retryatmpt	retryduration	Effective Call Timeline
Flash OTP / urgent alert (no retry)	0 (immediate)	0	N/A	Max speed, 1 attempt per number
Appointment reminder (2 retries, 30-min apart)	0 (immediate)	2	30	Call 1 at T+0 → Call 2 at T+30 min → Call 3 at T+60 min
Bulk notification 10K numbers, 10 hourly waves	1 (scheduled per wave)	0 or 2	0 / 60	1,000/hr wave pacing across 10 hours
Loan recovery follow-up (max retry, 1-hr gaps)	0 (immediate)	2	60	Call 1 at T+0 → Call 2 at T+60 min → Call 3 at T+120 min

13.10 Add to Glossary

Term	Definition
OBD	Outbound Dialer — automated system that places calls and plays audio to recipients
ukey	User authentication key unique to each go2market account; found in user profile
ivrtemplateid	Template ID that defines the call interaction type (Simple, DTMF, Latching, Custom)
msisdnlist	JSON array of destination phone numbers and their associated WSS stream IDs
Promotional (type 3)	Campaign for marketing/offers; subject to DND filter compliance
Transactional (type 4)	Campaign for service notifications/alerts; exempt from DND restrictions
schddate	Scheduled launch datetime for a campaign (YYYY-MM-DD HH:MM:SS format)
retryatmpt	Number of re-dial attempts if the called party does not answer
retryduration	Wait time between retry attempts: 0 = immediate, 15/30/60 = minutes

14. CDR Callback API — Disposition Webhook

go2market automatically pushes Call Detail Records (CDR) to the customer's registered webhook endpoint on every call completion. No polling required — disposition data is delivered in real time as a JSON POST to your system, enabling CRM updates, analytics pipelines, and billing reconciliation without any additional API calls.

14.1 How It Works

© 2026 go2market India Pvt Ltd

Step	Actor	Action
1	Customer (one-time setup)	Register your HTTPS webhook URL with go2market (via dashboard or support ticket). URL must accept HTTP POST with Content-Type: application/json.
2	go2market Platform	Call is initiated (inbound or OBD outbound). go2market handles the full call lifecycle.
3	go2market Platform	Call ends (caller disconnects, timeout, or error). go2market compiles the full CDR record.
4	go2market → Customer Webhook	HTTP POST sent to customer's registered webhook URL with full CDR JSON payload within ~2 seconds of call termination.
5	Customer System	Receive CDR, respond HTTP 200 OK to acknowledge. go2market retries up to 3 times on non-2xx responses (15 min interval).

14.2 CDR Payload Fields

Every CDR callback POST contains the following fields. All timestamps are in ISO 8601 format (UTC) with millisecond precision.

Field	Type	Description
`event`	string	Always "cdr" — identifies this as a CDR callback event
`callSid`	string	Unique call identifier (CA…). Use to correlate with WebSocket stream events.
`streamSid`	string	WebSocket stream session ID (MZ…). Links CDR to the audio stream.
`accountSid`	string	go2market account identifier (AC…). Useful for multi-tenant setups.
`from`	string	Caller CLI (phone number in E.164 format, e.g., +911234567890). Masked in logs per TQ-4.7.
`to`	string	Dialled number / destination CLI (E.164 format).
`direction`	string	"inbound" or "outbound" — call direction relative to go2market platform.
`disposition`	string	Call outcome: ANSWERED | NO_ANSWER | BUSY | FAILED | CANCELLED
`disconnectReason`	string	Human-readable reason: e.g., "Caller disconnected", "No answer after 30s", "Network error"
`callStartTime`	string	ISO 8601 UTC timestamp when call was initiated (ms precision). e.g., 2026-06-01T10:23:45.123Z
`callAnswerTime`	string | null	Timestamp when call was answered. null if unanswered (NO_ANSWER / BUSY).
`callEndTime`	string	ISO 8601 UTC timestamp when call terminated.
`durationSeconds`	integer	Total call duration in seconds (from answer to end). 0 for unanswered calls.
`channelId`	string	Service channel / DID number used for the call (maps to TQ-5.2 channel identifier).
`campaignId`	string | null	OBD campaign ID if call was outbound. null for inbound calls.
`retryAttempt`	integer	Which retry this CDR represents. 0 = original attempt, 1 = first retry, etc.
`customParameters`	object	Key-value pairs passed in the original OBD request (e.g., CRM_ID, FirstName). Echoed back in CDR for easy record matching.

© 2026 go2market India Pvt Ltd

webhookTimestamp	string	ISO 8601 UTC timestamp when this webhook POST was dispatched by go2market.

14.3 Sample CDR Payload — ANSWERED Call

HTTP POST to https://your-domain.com/webhook/cdr with Content-Type: application/json

```
{
  "event":            "cdr",
  "callSid":          "CAXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX",
  "streamSid":        "MZXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX",
  "accountSid":       "ACXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX",
  "from":             "+911234567890",
  "to":               "+919876543210",
  "direction":        "outbound",
  "disposition":      "ANSWERED",
  "disconnectReason": "Caller disconnected",
  "callStartTime":    "2026-06-01T10:23:45.123Z",
  "callAnswerTime":   "2026-06-01T10:23:47.456Z",
  "callEndTime":      "2026-06-01T10:25:12.789Z",
  "durationSeconds":  85,
  "channelId":        "073-DID-001",
  "campaignId":       "CAMP-20260601-0042",
  "retryAttempt":     0,
  "customParameters": {
    "FirstName": "Jane",
    "LastName":  "Doe",
    "CRM_ID":    "CRM-00421"
  },
  "webhookTimestamp": "2026-06-01T10:25:13.002Z"
}
```

14.4 Sample CDR Payload — NO_ANSWER (with Retry)

```
{
  "event":            "cdr",
  "callSid":          "CAXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXY",
  "from":             "+910000000073",
  "to":               "+919876543211",
  "direction":        "outbound",
  "disposition":      "NO_ANSWER",
  "disconnectReason": "No answer after 30s",
  "callStartTime":    "2026-06-01T10:30:00.000Z",
  "callAnswerTime":   null,
  "callEndTime":      "2026-06-01T10:30:30.000Z",
  "durationSeconds":  0,
  "channelId":        "073-DID-001",
  "campaignId":       "CAMP-20260601-0042",
  "retryAttempt":     1,
  "customParameters": { "CRM_ID": "CRM-00421" },
  "webhookTimestamp": "2026-06-01T10:30:30.512Z"
}
```

— End of Document —

© 2026 go2market India Pvt Ltd