



NUI MAYNOOTH
Ollscoil na hÉireann Má Nuad

OLLSCOIL NA hÉIREANN MÁ NUAD
THE NATIONAL UNIVERSITY OF IRELAND MAYNOOTH

AUTUMN 2015 EXAMINATION

CS424

**Programming Language Design & Language
Semantics**

Dr. D. Charles, Dr. A. Winstanley, Prof. B. Pearlmutter

Time allowed: 2 hours

Answer **four** questions

All questions carry equal marks

- 1 (a) Define a Scheme function `reverse-with-count` which takes two lists, the second of which is a list of non-negative integers the same length as the first list, and returns a list of elements from the first list, in reverse order, each repeated a number of times as specified by the corresponding element of the second list. **[25 marks]**
[25 marks]
- Examples:
- ```
(reverse-with-count '(a b c) '(1 2 3)) => (c c c b b a)
(reverse-with-count '(d c b a) '(3 0 0 1)) => (a d d d)
```
- 2 (a) Define a Haskell function `revCount` which takes two lists, the second of which is a list of non-negative Ints the same length as the first list, and returns a list of elements from the first list, in reverse order, each repeated a number of times as specified by the corresponding element of the second list. **[25 marks]**  
[25 marks]
- Examples:
- ```
revCount ['a','b','c'] [1,2,3] => ['c','c','c','b','b','a']
revCount ['d','c','b','a'] [3,0,0,1] => ['a','d','d','d']
```
- 3 (a) Define a Prolog predicate `noah/3` which is true of three lists when corresponding elements of the first two lists, which are of the same length are lined up two-by-two on the third list. **[25 marks]**
[25 marks]
- Examples:
- ```
noah([],[],[]).
noah([a,b,c,d],[aye,bee,sea,dee],[a,aya,b,bee,c,sea,d,dee]).
```
- 4 (a) Can the expression `lambda v:T . v v` be well-types in the simply-timed lambda calculus by giving an appropriate type for `T`? If so, give such a type. If not, explain why not. **[25 marks]**  
[25 marks]
- 5 (a) Assuming you brushed up on both languages, which would it be easier for you to write a Prolog interpreter in: Scheme or Haskell? Explain. **[25 marks]**  
[25 marks]