



CPFFLOORS
FLOORING DISTRIBUTORS

www.cpffloors.com



Guide: **Cleaning** and Maintenance

For products we recommend the following:

- 1) Use Rejuvenate Product diluted in water
- 2) Mineral Spirits for sticky stains.



Cleaning and Maintenance

First, all dirt and dust from the flooring must be removed with a brush or vacuum cleaner. Then cleaned with water and a neutral appropriate cleaning agent always diluted in water, at least twice and until the water stays clean. We strongly recommend using vinyl Planks cleaning products. Any other cleaning product may contain agents that damage resilient floor surfaces. The coating of the top layer makes a specific treatment after installation unnecessary. We recommend avoiding cleaning with wax or wax-based products. All cleaning products used must contain a neutral Ph. level.



How to Protect the Floor During & After Installation (During Construction)

1

After each section of the floor has been installed and thoroughly cleaned, cover it with a breathable construction paper. Do not apply the tape directly to the floor surface. This could damage the finish.

2

During construction, cover the floor to keep it free of dirt and construction debris. Never use a beater brush.

3

If dry repairs or any type of sanding is necessary, cover the floor thoroughly. This type of dust and grit can damage the floor finish and is very difficult to remove if it gets into the joints. Do not wet scrub this type of dust. If necessary, always use a brushless vacuum cleaner to remove construction dust.

4

Before placing furniture on the new floor, place 3/16" thick felt pads under the legs of all furniture.

5

Furniture with metal or casters ARE NOT APPROVED for use on rigid core vinyl flooring.

6

Never roll or pull anything heavy on new flooring. It will cause nicks or scratches in the surface. Always use a soft wheeled dolly when moving objects or an upturned piece of carpeting or a pneumatic sled.

Maintenance And Care Tips:

Preventative Maintenance:



Use non-staining floor protectors on the legs of chairs, appliances, and all heavy furniture to prevent indentations and scratches. Floor protectors should be at least 1" in diameter.



Periodically clean protectors to remove embedded grit that may cause scratching.



Place walk-off mats at entrances. Ensure the mats have a non-rubberized backing and are marked as non-staining.



To protect your floor from office chairs with casters, we recommend using a hard surface (non-studded), non-rubber chair mat. For light, rolling furniture, use broad-surface, non-staining casters that are at least 1" wide and 2" in diameter. Scratch, indentation. Warranty will be void if you don't protect your flooring with a chair mat when using chairs with casters.

Cleaning and Maintenance:

Use non-staining floor protectors on the legs of chairs, appliances, and all heavy furniture to prevent indentations and scratches. Floor protectors should be at least 1" in diameter.



Regularly sweep the floor with a soft bristle broom to remove loose dirt.



For everyday cleaning, a mop moistened with water.



Wash the floor with a non-abrasive, neutral pH floor cleaner approved for vinyl floors.

**Do Not Use the Following products on
Coreproof Rigid Core Vinyl**



Abrasive cleaning product as Ammonia.



Acetone.



Wax or oil based products.



Vacuum cleaner with a rotating beater bar engaged.



scan me

Let's Click Together

 www.cpffloors.com

 sales@cpffloors.com

 6700 NW 77 CT, Suite 100, Miami, FL, 33166