

Bayesian Optimization in Machine Learning

José Jiménez

Master's Thesis
Master's degree in Statistics and Operations Research

supervised by Josep Ginebra¹

¹ Department of Statistics and Operations Research. ETSEIB.



UNIVERSITAT POLITÈCNICA
DE CATALUNYA
BARCELONATECH



UNIVERSITAT DE
BARCELONA

Goals of this thesis

This Master's thesis has different and complimentary aims:

- Provide an introduction to both Gaussian Process regression and Bayesian optimization.
- Show that the Bayesian Optimization framework works in several real-world machine learning tasks.
- Write a complete software package (pyGPGO) for users to apply Bayesian Optimization in their research.

Organization of the work

Organized in 4 self-contained chapters.

- **Chapter 2** focuses on an introduction to regression problems using Gaussian Processes. These are surrogate models we will use for Bayesian Optimization.
- **Chapter 3** covers the main topic in this work, Bayesian Optimization.
- **Chapter 4** presents experiments using the Bayesian Optimization framework. Mostly mid-sized supervised-learning problems.
- **Chapter 5** provides technical explanations for pyGPGO, the software developed alongside this manual.

A brief introduction: setting the problem

Overall, Bayesian Optimization focuses on:

$$\max_{\mathbf{x} \in \mathcal{A}} f(\mathbf{x}) \quad (1)$$

We make almost no assumptions about f :

- f may not have a closed-form expression.
- Evaluations of f may be noisy.
- No gradient information needed.

An example arises when optimizing the *loss* function of a machine-learning model w.r.t. hyperparameters (e.g. log-loss):

$$\mathcal{L}(\mathbf{y}, \hat{\mathbf{y}}) = -\frac{1}{n} \sum_i (y_i \log(\hat{y}_i) + (1 - y_i) \log(1 - \hat{y}_i)) \quad (2)$$

We are interested in cases where f is **expensive** to evaluate.

A brief introduction: the big picture

Main idea

- We are going to use a **Gaussian Process** to model f .
- Our model will suggest new points to evaluate according to a GP dependant **acquisition function** α .
- Then iteratively update the model with new information.

Part I: Gaussian Process Regression

Gaussian Process Regression: basic definitions

Definition 1.

A Gaussian Process is a collection of random variables, any finite number of which have a joint Gaussian distribution. This process is defined by two functions. Its *mean function*:

$$m(\mathbf{x}) = \mathbb{E} [f(\mathbf{x})] \quad (3)$$

and its *covariance function*:

$$k(\mathbf{x}, \mathbf{x}') = \mathbb{E} [(f(\mathbf{x}) - m(\mathbf{x})) (f(\mathbf{x}') - m(\mathbf{x}'))] \quad (4)$$

We say that f is a Gaussian Process with mean $m(\mathbf{x})$ and covariance function $k(\mathbf{x}, \mathbf{x}')$ and write:

$$f(\mathbf{x}) \sim \mathcal{GP}(m(\mathbf{x}), k(\mathbf{x}, \mathbf{x}')) \quad (5)$$

Gaussian Process Regression: basic definitions

Define then a covariance function, such as the *squared exponential* kernel:

$$k(\mathbf{x}, \mathbf{x}') = \exp\left(-\frac{1}{2}|\mathbf{x} - \mathbf{x}'|^2\right) \quad (6)$$

where $|\cdot|$ denotes the standard L_2 norm. Drawing samples from a Gaussian Process, assuming zero mean, for given finite inputs X_* simplifies to sampling from:

$$\mathbf{f}_* \sim \mathcal{N}(\mathbf{0}, K(X_*, X_*)) \quad (7)$$

Gaussian Process Regression: prediction

Assume training data $\mathcal{D} = \{(\mathbf{x}_i, y_i) \mid i = 1, \dots, n\}$

Prediction using GP prior

Let \mathbf{y} and \mathbf{f}_* be jointly Gaussian:

$$\begin{bmatrix} \mathbf{y} \\ \mathbf{f}_* \end{bmatrix} \sim \mathcal{N} \left(\mathbf{0}, \begin{bmatrix} K(X, X) + \sigma_n^2 I & K(X, X_*) \\ K(X_*, X) & K(X_*, X_*) \end{bmatrix} \right) \quad (8)$$


We want to condition \mathbf{f}_* over \mathbf{y} .

$$\mathbf{f}_* | \mathbf{y} \sim \mathcal{N}(\bar{\mathbf{f}}_*, \text{Cov}(\mathbf{f}_*)) \quad (9)$$

where:

$$\begin{aligned} \bar{\mathbf{f}}_* &= K(X_*, X) (K(X, X) + \sigma_n^2 I)^{-1} \mathbf{y} \\ \text{Cov}(\mathbf{f}_*) &= K(X_*, X_*) - K(X_*, X) (K(X, X) + \sigma_n^2 I)^{-1} K(X, X_*) \end{aligned} \quad (10)$$

Gaussian Process Regression: an example



Gaussian Process Regression: on covariance functions

Some common covariance function choices

$$\begin{aligned}
 k_{SE}(r) &= \exp\left(-\frac{r^2}{2l^2}\right) & k_{\text{Matérn}}(r) &= \frac{2^{1-\nu}}{\Gamma(\nu)} \left(\frac{\sqrt{2\nu}r}{l}\right)^\nu K_\nu\left(\frac{\sqrt{2\nu}r}{l}\right) \\
 k_{GE}(r) &= \exp\left(-\left(\frac{r}{l}\right)^\gamma\right) & k_{RQ}(r) &= \left(1 + \frac{r^2}{2\alpha l^2}\right)^{-\alpha}
 \end{aligned}
 \tag{11}$$

where $r = \|\mathbf{x} - \mathbf{x}'\|$. Observations can be **noisy**:

$$k^y(\mathbf{x}_p, \mathbf{x}_q) = \sigma_f^2 k(\mathbf{x}_p, \mathbf{x}_q) + \sigma_n^2 \delta_{pq} \tag{12}$$

- There are different approaches towards hyperparameter treatment.

Gaussian Process Regression: Type II Maximum-Likelihood

An empirical Bayes approach to choosing hyperparameters. Noticing that $\mathbf{y} \sim \mathcal{N}(\mathbf{0}, K + \sigma_n^2 I)$

Marginal log-likelihood

$$\log p(\mathbf{y}|X) = -\frac{1}{2}\mathbf{y}^T (K + \sigma_n^2 I)^{-1} \mathbf{y} - \frac{1}{2} \log |K + \sigma_n^2 I| - \frac{n}{2} \log 2\pi \quad (13)$$

Derivative w.r.t hyperparameters

$$\frac{\partial}{\partial \theta_j} \log p(\mathbf{y}|X, \theta) = \frac{1}{2} \mathbf{y}^T K^{-1} \frac{\partial K}{\partial \theta_j} K^{-1} \mathbf{y} - \frac{1}{2} \text{tr} \left(K^{-1} \frac{\partial K}{\partial \theta_j} \right) \quad (14)$$

Gaussian Process Regression: incorporating diff. priors

We have assumed $m(\mathbf{x}) = 0$ for simplicity. We can incorporate prior knowledge:

Different prior mean

$$f(\mathbf{x}) \sim \mathcal{GP}(m(\mathbf{x}), k(\mathbf{x}, \mathbf{x}^*)) \quad (15)$$

Posterior mean becomes:

$$\mathbf{f}_* = \mathbf{m}(X_*) + k(X_*, X)K^{-1}(\mathbf{y} - \mathbf{m}(X)) \quad (16)$$

Posterior variance remains unchanged.

Gaussian Process Regression: marginalizing over hyperparameters

The full Bayesian approach does not optimize the marginal likelihood, but integrates the uncertainty of hyperparameters θ into the model, either using MCMC or Variational Inference techniques.

Full Bayesian approach

$$\theta \sim p_h(\theta) \quad (17)$$

$$\mathbf{f} \sim \mathcal{N}(0, \Sigma_\theta) \quad (18)$$

$$\mathcal{L}(\mathbf{f}) = p(\text{data}|\mathbf{f}) = p(\mathbf{y}|\mathbf{f}) \quad (19)$$

We wish to sample from the joint posterior under unknowns:

$$p(\mathbf{f}, \theta | \text{data}) \propto \mathcal{L}(\mathbf{f})p(\mathbf{f})p_h(\theta) \quad (20)$$

Several strategies for sampling from latent Gaussian models proposed in main text.

Part II: Bayesian Optimization

Bayesian Optimization: introduction

Again, assume:

$$\max_{\mathbf{x} \in \mathcal{A}} f(\mathbf{x}) \quad (21)$$

Assume that we have sampled our function f to optimize a small number of times n . Providing us with training data:

$$\mathcal{D}_n = \{\mathbf{x}_i, y_i, i = 1, \dots, n\}. \quad (22)$$

Our steps here are:


- 1 Fit a **Gaussian Process** regression model on \mathcal{D}_n .
- 2 Choose the next point to sample, according to an *acquisition function*, depending on GP.
- 3 Evaluate said point. Augment training data. Repeat.

Bayesian optimization: algorithm


Algorithm 1 Bayesian optimization framework

- 1: Sample a small number of points $\mathbf{x} \in \mathcal{A}$. Evaluate $f(\mathbf{x})$ to get \mathcal{D}_n
 - 2: **for** $n = 1, 2, \dots$ **do**
 - 3: Fit a GP regression model on \mathcal{D}_n
 - 4: $\mathbf{x}_{n+1} \leftarrow \arg \max_{\mathbf{x}} \alpha(\mathbf{x}, \mathcal{D}_n)$
 - 5: Evaluate $f(\mathbf{x}_{n+1}) = y_{n+1}$
 - 6: Augment data $\mathcal{D}_{n+1} = \{\mathcal{D}_n, (\mathbf{x}_{n+1}, y_{n+1})\}$
 - 7: **end for**
-


Bayesian optimization: example




Bayesian optimization: example




Bayesian optimization: example




Bayesian optimization: example



Bayesian optimization: example



Bayesian optimization: example



Bayesian optimization: on acquisition functions

Three popular categories: improvement-based, optimistic, and information-based policies.

Improvement-based

Denote τ our best evaluation so far.

Probability of Improvement:

$$\alpha_{\text{PI}}(\mathbf{x}, \mathcal{D}_n) = P(\nu > \tau) = \Phi\left(\frac{\mu_n(\mathbf{x}) - \tau}{\sigma_n(\mathbf{x})}\right) \quad (23)$$

Expected Improvement:

$$\alpha_{\text{EI}}(\mathbf{x}, \mathcal{D}_n) = (\mu_n(\mathbf{x}) - \tau) \Phi\left(\frac{\mu_n(\mathbf{x}) - \tau}{\sigma_n(\mathbf{x})}\right) + \sigma_n(\mathbf{x}) \phi\left(\frac{\mu_n(\mathbf{x}) - \tau}{\sigma_n(\mathbf{x})}\right) \quad (24)$$

Bayesian optimization: on acquisition functions

Optimistic acquisitions

Upper Confidence Bound:

$$\alpha_{\text{UCB}}(\mathbf{x}, \mathcal{D}_n) = \mu_n(\mathbf{x}) + \beta_n \sigma_n(\mathbf{x}) \quad (25)$$

Information-based


Entropy-based:

$$\alpha_{\text{ES}}(\mathbf{x}|\mathcal{D}_n) = H(\mathbf{x}^*|\mathcal{D}_n) - \mathbb{E}_{y|\mathcal{D}_n, \mathbf{x}} [H(\mathbf{x}^*|\mathcal{D}_n \cup \{(\mathbf{x}, y)\})] \quad (26)$$


Predictive Entropy Search:

$$\alpha_{\text{PES}}(\mathbf{x}, \mathcal{D}_n) = H(y|\mathcal{D}_n, \mathbf{x}) - \mathbb{E}_{\mathbf{x}^*|\mathcal{D}_n} [H(y|\mathcal{D}_n, \mathbf{x}, \mathbf{x}^*)] \quad (27)$$

Bayesian optimization: acquisition function behaviour



Bayesian optimization: why does it work?



Bayesian optimization: role of hyperparameters

Gaussian Process hyperparameters θ cause uncertainty in the optimization procedure:

$$\alpha(\mathbf{x}) = \mathbb{E}_{\theta|\mathcal{D}_n} [\alpha(\mathbf{x}, \theta)] = \int_{\Theta} \alpha(\mathbf{x}|\theta) p(\theta|\mathcal{D}_n) d\theta. \quad (28)$$

Approach 1. MAP estimate $\hat{\theta}_{\text{MAP}}$


$$\hat{\alpha}(\mathbf{x}) = \alpha(\mathbf{x}, \hat{\theta}) \quad (29)$$

Approach 2. Sample posterior $p(\theta|\mathcal{D}_n)$. Integrated acquisition functions

$$\mathbb{E}_{\theta|\mathcal{D}_n} [\alpha(\mathbf{x}, \theta)] \approx \frac{1}{M} \sum_{i=1}^M \alpha(\mathbf{x}, \theta_n^{(i)}) \quad (30)$$

Bayesian optimization: Integrated acquisition example

Figure: Means of 200 posterior predictive distributions, taken from sampled posterior $p(\theta|\mathcal{D}_n)$



Bayesian optimization: optimizing acquisitions

We have assumed that the **acquisition function** is easily optimized. This is not necessarily the case:

- It is often multimodal.
- Or non-convex.
- Furthermore theoretical convergence is guaranteed when finding global maximum \mathbf{x}^* .

One may be thinking that we have switched optimization problems! (f by α). However, α is usually very cheap to compute.

- In practice α is optimized using multi-start quasi-Newton methods (e.g. L-BFGS-B) or evolutionary approaches (e.g. CMA-ES).

Bayesian optimization: Other surrogates

The Bayesian Optimization framework is not limited to a **Gaussian Process** surrogate:

- Random Forests: empirical estimate of variance provided by predictions of trees.
- Gradient Boosting Machines: using quantile regression for variance estimate.
- Sparse pseudo-input GPs
- Student-t Processes
- ...

Student-t Process example

$$\mathbf{f}^* | \mathbf{f} \sim \mathcal{T} \left(\nu + n, \phi_2, \frac{\nu + \beta_1 - 2}{\nu + n - 2} \tilde{\mathbf{K}}_{**} \right) \quad (31)$$

Part III: Experiments and benchmarking

Experiments

The aim is to demonstrate that Bayesian Optimization works in real hyperparameter optimization problems.

- Mid-sized supervised learning problems. Both regression and classification considered.
- Two examples explained in detail: datasets related to relevant computational chemistry problems.
- Other examples drawn from other areas, such as medicine. Available from other sources (UCI ML repository).

Experiments: benchmarking rules

Loss functions used:

Binary classification

Logarithmic loss:

$$\mathcal{L}(\mathbf{y}, \hat{\mathbf{y}}) = -\frac{1}{n} \sum_i (y_i \log(\hat{y}_i) + (1 - y_i) \log(1 - \hat{y}_i)) \quad (32)$$

Regression

Mean Squared Error (MSE)

$$\mathcal{L}(\mathbf{y}, \hat{\mathbf{y}}) = \frac{1}{n} \sum_i (y_i - \hat{y}_i)^2 \quad (33)$$

Experiments: benchmarking rules

- Shuffled $k = 5$ fold cross-validation scheme for loss evaluation.
- Features scaled: zero mean, unit variance.
- $n = 50$ (+3 to account GP fitting) total function evaluations.
- Gaussian Process surrogate, with squared exponential covariance function.

Experiments: benchmarking rules

- Type II ML estimation of all hyperparameters at each stage (l , σ_n^2 , σ_f^2).
- Expected Improvement and GP-UCB ($\beta = 0.5$, $\beta = 1.5$) acquisitions.
- **Random search** is considered as baseline for all experiments.
- Machine-learning models used:
 - Support Vector Machines
 - K-Nearest-Neighbours
 - Gradient Boosting Machines
 - One-Hidden Layer Neural Networks

Experiments: benchmarking rules

Table: SVM parameters.

Parameter	Type	Bounds
C	\mathbb{R}^+	$[10^{-5}, 10^5]$ (log-scaled)
γ	\mathbb{R}^+	$[10^{-5}, 10^5]$ (log-scaled)

Table: KNN parameters.

Parameter	Type	Bounds
k	Integer	$\{10, \dots, 50\}$

Experiments: benchmarking rules

Table: GBM parameters.

Parameter	Type	Bounds
learning_rate	\mathbb{R}^+	$[10^{-5}, 10^{-2}]$
n_estimators	Integer	$\{10, \dots, 100\}$
max_depth	Integer	$\{2, \dots, 100\}$
min_samples_split	Integer	$\{2, \dots, 100\}$

Table: MLP parameters.

Parameter	Type	Bounds
hidden_layer_size	Integer	$[5, 50]$
alpha	\mathbb{R}^+	$[0, 0.9]$

Experiment I: Binding affinity prediction dataset

- Problem is to predict some binding/inhibition constant between a protein and a ligand (K_d , K_i). Target variable is defined as $y = -\log_{10} K$




Figure: Illustration of the protein-ligand binding scenario.

Experiment I: Binding affinity prediction dataset

Set of features used

Pair of atom-type counts from protein and ligand in the binding site.

$$\{P_j\}_{j=1}^9 = \{C, N, O, F, P, S, Cl, Br, I\}$$

$$\{L_i\}_{i=1}^9 = \{C, N, O, F, P, S, Cl, Br, I\}$$

$$\mathbf{x}(Z(P_j), Z(L_i)) = \sum_{k=1}^{P_j} \sum_{l=1}^{L_i} \Theta(d_{\text{cutoff}} - d_{kl}) \quad (34)$$


Data

- PDBbind v.2015 database of affinity and kinetic biological data.
- A refined set of $n = 3623$ of protein-ligand pairs for training, and another $m = 195$ structurally diverse for testing.


Experiment I: Binding affinity prediction dataset

Figure: Benchmarking results for the binding affinity dataset (1/2).

(a) SVM




(b) KNN




Experiment I: Binding affinity prediction dataset

Figure: Benchmarking results for the binding affinity dataset (2/2).

(a) MLP



(b) GBM



Experiment II: Protein-protein interface prediction

- Predict whether a particular residue is in contact with a chain of another protein.
- Interfaces are **not** considered target-specific.




Figure: An interface between two chains of a dimer. Residues considered interfacial are marked in blue.

Experiment II: Protein-protein interface prediction

Features used

Descriptors resemble those detailed in (Jiménez *et al.* 2017). Average pharmacophoric-like features computed in a particular neighbourhood (20\AA^3) of a residue.


Data

PIFACE database of clustered protein interface. Over 22k structurally unique interfaces extracted from the Protein Data Bank.


Experiment II: Protein-protein interface prediction

Figure: Benchmarking results for the protein-protein interface dataset (1/2).

(a) SVM




(b) KNN




Experiment II: Protein-protein interface prediction

Figure: Benchmarking results for the protein-protein interface dataset (2/2).

(a) MLP




(b) GBM




Experiments: other datasets (1/3)

Figure: Benchmarking results for the LSVT Voice Rehabilitation dataset.

(a) SVM




(b) KNN




Experiments: other datasets (1/3)

Figure: Benchmarking results for the LSVT Voice Rehabilitation dataset.

(a) MLP




(b) GBM



Experiments: other datasets (2/3)

Figure: Benchmarking results for the Parkinson's dataset.


(a) SVM




Experiments: other datasets (2/3)

Figure: Benchmarking results for the Parkinson's dataset.

(a) MLP




(b) GBM




Experiments: other datasets (3/3)

Figure: Benchmarking results for the Breast cancer dataset.

(a) SVM




(b) KNN




Experiments: other datasets (3/3)

Figure: Benchmarking results for the Breast cancer dataset.

(a) MLP



(b) GBM



Part IV: Software development

pyGPGO: Bayesian Optimization for Python

There are many possible choices in the Bayesian Optimization framework:

- Choice of surrogate model.
- Covariance function to use
- Acquisition behaviour
- Hyperparameter treatment

They naturally motivate a modular design. Most of the available software focuses on a particular implementation of the Bayesian optimization algorithm.

pyGPGO is a package I wrote to cover as many of these scenarios as possible.

pyGPGO: features

pyGPGO features:

- A completely modular and customizable design. Easy to setup and minimal dependencies.
- A wide range of surrogate models: Gaussian Processes, Student-t Processes, Random Forests, Extra Random Forests and Gradient Boosting Machines.
- Most of the usual covariance functions, as well as its derivatives: squared exponential, Matérn, γ -exponential, rational quadratic, exponential sine, and dot product.
- Many acquisition function behaviours: probability of improvement, expected improvement, upper confidence bound and entropy-based, as well as their integrated versions.
- Type II Maximum-Likelihood of covariance function hyperparameters.
- MCMC sampling for full-Bayesian treatment of hyperparameters (via pyMC3).

pyGPGO: a simple example

```
1 import numpy as np
2 from pyGPGO.covfunc import matern32
3 from pyGPGO.acquisition import Acquisition
4 from pyGPGO.surrogates.GaussianProcess import GaussianProcess
5 from pyGPGO.GPGO import GPGO
6
7
8 def f(x, y):
9     # Franke's function (https://www.mathworks.com/help/curvefit/franke.html)
10    one = 0.75 * np.exp(-(9 * x - 2) ** 2 / 4 - (9 * y - 2) ** 2 / 4)
11    two = 0.75 * np.exp(-(9 * x + 1) ** 2 / 49 - (9 * y + 1) / 10)
12    three = 0.5 * np.exp(-(9 * x - 7) ** 2 / 4 - (9 * y - 3) ** 2 / 4)
13    four = 0.25 * np.exp(-(9 * x - 4) ** 2 - (9 * y - 7) ** 2)
14    return one + two + three - four
```

pyGPGO: a simple example

```
1 cov = matern32()
2 gp = GaussianProcess(cov)
3 acq = Acquisition(mode='ExpectedImprovement')
4 param = {'x': ('cont', [0, 1]),
5          'y': ('cont', [0, 1])}
6
7 np.random.seed(1337)
8 gpgo = GPGO(gp, acq, f, param)
9 gpgo.run(max_iter=10)
10 gpgo.getResult()
```

pyGPGO: optimizing SVM hyperparameters

```
1 import numpy as np
2 from sklearn.datasets import make_moons
3 from sklearn.svm import SVC
4 from sklearn.model_selection import cross_val_score
5
6
7 from pyGPGO.GPGO import GPGO
8 from pyGPGO.surrogates.GaussianProcess import GaussianProcess
9 from pyGPGO.acquisition import Acquisition
10 from pyGPGO.covfunc import squaredExponential
11
12
13 def evaluateModel(C, gamma):
14     clf = SVC(C=10**C, gamma=10**gamma)
15     return np.average(cross_val_score(clf, X, y))
```

pyGPGO: optimizing SVM hyperparameters

```
1 X, y = make_moons(n_samples = 200, noise = 0.3)
2
3 sexp = squaredExponential()
4 gp = GaussianProcess(sexp, optimize = True, usegrads = True)
5 acq = Acquisition(mode = 'UCB', beta = 1.5)
6
7 params = {'C':      ('cont', (-4, 5)),
8           'gamma':  ('cont', (-4, 5))}
9
10 gpgo = GPGO(gp, acq, evaluateModel, params)
11 gpgo.run(max_iter = 50)
12 gpgo.getResult()
```

pyGPGO: Bayesian Optimization for Python



- The software is MIT licensed and can be downloaded from its GitHub repository @ <https://github.com/hawk31/pyGPGO>
- Extensive documentation can be found in ReadTheDocs.
pygpgo.readthedocs.io/en/latest
- Anyone can contribute to the project!
(Implement new features, report bugs, improve docs...)
- All benchmarking, examples and thesis code is also available.



&



pyGPGO in numbers



pyGPGO: Future work

Like any other piece of software, there is always stuff to do!

- Constrained optimization. $P(\mathcal{C}(\mathbf{x})) \geq 1 - \delta$
- Better support for non-stationary covariance functions.
- GPU support for non-MCMC samplers (BBVI).
- A parallel interface for experiment running.
- More acquisitions, surrogates...

Thank you

Q&A time!

Acknowledgements to :

- Josep Ginebra
- Víctor Peña

My lab co-workers @ **UPF** for letting me spend time on this project!

- Gianni de Fabritiis
- Stefan Doerr
- Gerard Martínez
- Miha Škalič
- Pablo Herrera
- João Damas
- Adrià Pérez