

Installation Zabbix Server

Preparation:

```
# Update and upgrade system
sudo apt update && sudo apt upgrade -y

# Installation of Apache2 and PHP with required elements
sudo apt-get install apache2 php8.3-mysqli php8.3-bcmath php8.3-mbstring
php8.3-sockets php8.3-gd php8.3-xml php8.3-xmlwriter php8.3-xmlreader
php8.3-ctype -y

# Installation and start of MySQL server
sudo apt-get install mysql-server -y
sudo systemctl enable mysql
sudo systemctl enable apache2
sudo service mysql start
sudo service apache2 start

# MySQL secure installation
sudo mysql_secure_installation
y
1 # Or pick a level
y
y
y
y
# Set MySQL root password with native authentication
sudo mysql -u root
ALTER USER 'root'@'localhost' IDENTIFIED WITH mysql_native_password BY
'password';
FLUSH PRIVILEGES;
EXIT;

# To be able to run these from zabbix web page
sudo apt install nmap -y
sudo apt install traceroute -y
```

Firewall configuration:

```
sudo ufw reset
sudo ufw allow from 192.168.175.0/24 to any port 10050 proto tcp
sudo ufw allow from 192.168.175.0/24 to any port 10051 proto tcp
sudo ufw allow from 192.168.175.0/24 to any port 80 proto tcp
sudo ufw allow from 192.168.175.0/24 to any port 22 proto tcp
```

```
sudo ufw reload
sudo ufw enable
sudo ufw status verbose
```

Zabbix installation:

```
# Zabbix installation
wget https://repo.zabbix.com/zabbix/7.2/release/ubuntu/pool/main/z/zabbix-
release/zabbix-release_latest_7.2+ubuntu24.04_all.deb

sudo dpkg -i zabbix-release_latest_7.2+ubuntu24.04_all.deb

sudo apt update

sudo apt install zabbix-server-mysql zabbix-frontend-php zabbix-apache-conf
zabbix-sql-scripts zabbix-agent -y

mysql -u root -p
# password
create database zabbix character set utf8mb4 collate utf8mb4_bin;
create user zabbix@localhost identified by 'password';
grant all privileges on zabbix.* to zabbix@localhost;

# This command will cause a warning since it's deprecated and will be
removed in a future release
# To verify : SHOW WARNINGS
set global log_bin_trust_function_creators = 1;
quit;

# This will take a while
zcat /usr/share/zabbix/sql-scripts/mysql/server.sql.gz | mysql --default-
character-set=utf8mb4 -uzabbix -p zabbix
# password

mysql -u root -p
# password

# This command will cause a warning too
set global log_bin_trust_function_creators = 0;
quit;
```

Configuration:

Server

```
sudo nano /etc/zabbix/zabbix_server.conf
# DBPassword=password
```

```
# ListenPort=10051
# StatsAllowedUP=192.168.175.0/24
```

Agent

```
sudo nano /etc/zabbix/zabbix_agentd.conf
# Server=192.168.175.100
# ListenPort=10050
# Hostname=zabbix-srv
# RefreshActiveChecks=5
# HeartbeatFrequency=60
# AllowRoot=0
```

Restart and enable Zabbix (server and agent) and Apache2

```
sudo systemctl restart zabbix-server zabbix-agent apache2
sudo systemctl enable zabbix-server zabbix-agent apache2
```