

MySQL server installation and configuration

Preparation

Switch to root and upgrade system

```
su -s  
apt update  
apt upgrade -y
```

Install gnupg (necessary for MySQL installation)

```
apt install gnupg -y
```

Install MySQL server

```
wget https://dev.mysql.com/get/mysql-apt-config_0.8.30-1_all.deb  
dpkg -i mysql-apt-config_0.8.30-1_all.deb  
apt update  
apt install mysql-server -y
```

After mysql install SSH fails (IP changes from static to DHCP)

```
systemctl restart networking
```

Enable and start MySQL

```
systemctl enable mysql  
systemctl start mysql
```

Check MySQL version (optional)

```
mysql --version
```

Installation and configuration Zabbix agent2

```
wget https://repo.zabbix.com/zabbix/7.2/release/debian/pool/main/z/zabbix-  
release/zabbix-release_latest_7.2+debian12_all.deb
```

```
dpkg -i zabbix-release_latest_7.2+debian12_all.deb
apt update
apt install zabbix-agent2

systemctl restart zabbix-agent2
systemctl enable zabbix-agent2
```

Configure ip, hostname and stuff

```
nano /etc/zabbix/zabbix_agent2.conf
```

```
# Server=192.168.175.100
# ListenPort=10050
# Hostname=zabbix-srv
# RefreshActiveChecks=5
# HeartbeatFrequency=60
# AllowRoot=0
```

```
systemctl restart zabbix-agent2
```

Check with which user Zabbix Agent2 runs

```
ps aux | grep zabbix_agentd2
```

Zabbix agent service file

```
nano /lib/systemd/system/zabbix-agent2.service
```

Configure MySQL monitoring

```
mysql -u root -p
# Enter password
mysql> CREATE USER 'zbx_monitor'@ '%' IDENTIFIED BY 'Pa$$w0rd';
mysql> GRANT REPLICATION CLIENT,PROCESS,SHOW DATABASES,SHOW VIEW ON *.* TO
'zbx_monitor'@ '%';
mysql> quit;
```

In the *Macros* tab, switch to *Inherited and host macros*, look for the following macros and click on *Change* next to the macro value to update it:

- {\$MYSQL.DSN} - set the data source of the MySQL server (the [connection string of a named session](#) from the MySQL Zabbix agent 2 plugin configuration file). This guide uses the default data source "tcp://localhost:3306" for monitoring a MySQL server that is installed

on the same machine as Zabbix server and Zabbix agent 2.

- `{$MYSQL.PASSWORD}` - set the password of the previously [created MySQL user](#) "zbx_monitor".
- `{$MYSQL.USER}` - set the name of the previously [created MySQL user](#) "zbx_monitor".

Verify logs:

```
tail -f /var/log/zabbix/zabbix_agent2.log
```

Add user to zabbix group:

```
sudo usermod -aG zabbix user
```

[4 Monitor MySQL with Zabbix agent 2](#)