



## Introduction to USER mode & KERNEL mode

Youtube link: <a href="https://youtu.be/RK8mRIf5bMg">https://youtu.be/RK8mRIf5bMg</a>






















































































































































Image Attribution: https://commons.wikimedia.org/wiki/File:Windows\_2000\_architecture.svg
The original uploader was Grm wnr at English Wikipedia.Later versions were uploaded by Xyzzy n at en.wikipedia. / CC BY-SA (http://creativecommons.org/licenses/by-sa/3.0/)





## Scenario: Open a file in hard disk


```
#include <stdio.h>
int main()
{
    FILE* pFile = fopen ( "C:\\file.txt", "w+" );
    if( nullptr != pFile ){
        fclose( pFile );
    }
    return 0;
}
```


## Scenario: Open a file in hard disk


```
#include <stdio.h>
int main()
{
    FILE* pFile = fopen ( "C:\\file.txt", "w+" );
    if( nullptr != pFile ){
        fclose( pFile );
    }
    return 0;
}
```































```
0:000> u
ntdll!NtCreateFile:
                                          r10,rex
00007ffc`4417cb00 4c8bd1
                                          eax.55h
00007ffc`4417cb03 b855000000
00007ffc`4417cb08 f604250803fe7f01 test
                                           byte ptr [SharedUserData+0x308
                                          ntdll!NtCreateFile+0x15 (00007f
00007ffc`4417cb10 7503
                                  ine
00007ffc`4417cb12 0f05
                                  syscall
00007ffc`4417cb14 c3
                                  ret
00007ffc 4417cb15 cd2e
                                          2Eh
                                  int
00007ffc`4417cb17 c3
```

## CPU register eax is set as 55h



```
0:000> u
ntdll!NtCreateFile:
                                          r10,rex
00007ffc`4417cb00 4c8bd1
00007ffc`4417cb03 b855000000
                                          eax.55h
00007ffc`4417cb08 f604250803fe7f01 test
                                           byte ptr [SharedUserData+0x308
                                          ntdll!NtCreateFile+0x15 (00007f
00007ffc`4417cb10 7503
                                  ine
00007ffc`4417cb12 0f05
                                  syscall
00007ffc`4417cb14 c3
                                  ret
00007ffc 4417cb15 cd2e
                                          2Eh
                                  int
00007ffc`4417cb17 c3
```

Parameters are passed as stack frames



```
0:000> u
ntdll!NtCreateFile:
                                          r10, rex
00007ffc`4417cb00 4c8bd1
00007ffc`4417cb03 b855000000
                                           eax.55h
00007ffc`4417cb08 f604250803fe7f01 test
                                            byte ptr [SharedUserData+0x308
                                          ntdll!NtCreateFile+0x15 (00007f
00007ffc`4417cb10 7503
                                  ine
00007ffc`4417cb12 0f05
                                  syscall
00007ffc`4417cb14 c3
                                  ret
00007ffc 4417cb15 cd2e
                                           2Eh
                                  int
00007ffc`4417cb17 c3
                                  ret
```

**Enters into kernel mode using 'syscall'** 



```
0:000> u
ntdll!NtCreateFile:
                                          r10, rex
00007ffc`4417cb00 4c8bd1
00007ffc`4417cb03 b855000000
                                           eax.55h
00007ffc`4417cb08 f604250803fe7f01 test
                                            byte ptr [SharedUserData+0x308
                                          ntdll!NtCreateFile+0x15 (00007f
00007ffc`4417cb10 7503
                                  ine
00007ffc`4417cb12 0f05
                                  syscall
00007ffc`4417cb14 c3
                                  ret
00007ffc 4417cb15 cd2e
                                           2Eh
                                  int
00007ffc`4417cb17 c3
                                  ret
```

**Enters into kernel mode using 'syscall'** 



