

Package ‘BioAge’

May 25, 2020

Type Package

Title Biological Age Calculations Using Several Biomarker Algorithms

Version 0.1.0

Author Dayoon Kwon

Maintainer Dayoon Kwon <dk1943@nyu.edu>

Description This package measures biological aging using data from the National Health and Nutrition Examination Survey (NHANES). The package uses published biomarker algorithms to calculate three biological age measures: Klemmera-Doubal Method biological age, phenotypic age, and homeostatic dysregulation.

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 7.1.0

Depends R (>= 2.10)

Imports dplyr,
flexsurv

Suggests testthat,
knitr,
rmarkdown

VignetteBuilder knitr

R topics documented:

bioage_calc	2
bioage_nhanes	3
hd_calc	3
hd_nhanes	4
phenoage_calc	5
phenoage_nhanes	6
plot_ba	6
plot_baa	7
surv_table	8

bioage_calc	<i>bioage_calc</i>
-------------	--------------------

Description

Calculate Klemmera-Doubal Method (KDM) biological age

Usage

```
bioage_calc(data, age, biomarkers, fit = NULL, s_ba2 = NULL)
```

Arguments

data	The dataset for calculating KDM bioage
age	A character vector (length=1) indicating the name of the variable for chronological age
biomarkers	A character vector indicating the names of the variables for the biomarkers to use in calculating KDM bioage
fit	An S3 object for model fit. If the value is NULL, then the parameters to use for training KDM bioage are calculated
s_ba2	A particular fit parameter. Advanced users can modify this parameter to control the variance of bioage

Details

Calculate KDM biological age

Value

An object of class "bioage". This object is a list with two elements (data and fit)

Examples

```
#Train KDM bioage parameters
train = bioage_calc(nhanes3,age="age",
  biomarkers=c("fev","sbp","totchol","hba1c","albumin","creat","lncrp","alp","bun"))

#Use training data to calculate KDM bioage
bioage = bioage_calc(nhanes,age="age",
  biomarkers=c("fev","sbp","totchol","hba1c","albumin","creat","lncrp","alp","bun"),
  fit=train$fit,
  s_ba2=train$fit$s_ba2)

#Extract bioage dataset
data = bioage$data
```

bioage_nhanes	<i>bioage_nhanes</i>
---------------	----------------------

Description

Calculate Klemm-Dougal Method (KDM) biological age using NHANES dataset

Usage

```
bioage_nhanes(biomarkers)
```

Arguments

biomarkers	A character vector indicating the names of the variables for the biomarkers to use in calculating bioage
------------	--

Details

Calculate KDM biological age using NHANES dataset

Value

An object of class "bioage". This object is a list with two elements (data and fit)

Examples

```
#Calculate KDM bioage
bioage = bioage_nhanes(biomarkers=c("fev", "sbp", "totchol", "hba1c", "albumin", "creat", "lncrp", "alp", "bun"))

#Extract bioage dataset
data = bioage$data
```

hd_calc	<i>hd_calc</i>
---------	----------------

Description

Calculate homeostatic dysregulation (HD)

Usage

```
hd_calc(data, reference, biomarkers)
```

Arguments

data	The dataset for calculating HD
reference	The reference dataset for calculating HD
biomarkers	A character vector indicating the names of the variables for the biomarkers to use in calculating HD

Details

Calculate HD

Value

An object of class "hd". This object is a list with two elements (data and fit)

Examples

```
#Calculate HD
hd = hd_calc(nhanes,nhanes3,
             biomarkers=c("albumin_gl","lymph","mcv","glucose_mmol","rdw","creat_umol","lncrp","alp","wbc"))

#Extract bioage dataset
data = hd$data
```

hd_nhanes	<i>hd_nhanes</i>
-----------	------------------

Description

Calculate homeostatic dysregulation (HD) using NHANES dataset

Usage

```
hd_nhanes(biomarkers)
```

Arguments

biomarkers	A character vector indicating the names of the variables for the biomarkers to use in calculating HD
------------	--

Details

Calculate HD using NHANES dataset

Value

An object of class "hd". This object is a list with two elements (data and fit)

Examples

```
#Calculate HD
hd = hd_nhanes(biomarkers=c("albumin","lymph","mcv","glucose","rdw","creat","lncrp","alp","wbc"))

#Extract HD dataset
data = hd$data
```

phenoage_calc	<i>phenoage_calc</i>
---------------	----------------------

Description

Calculate Levine's phenotypic age

Usage

```
phenoage_calc(data, age, time, status, biomarkers, fit = NULL)
```

Arguments

<code>data</code>	The dataset for calculating phenoage
<code>age</code>	A character vector (length=1) indicating the name of the variable for chronological age
<code>time</code>	A character vector (length=1) indicating the name of the variable for survival time
<code>status</code>	A character vector (length=1) indicating the name of the variable for survival status
<code>biomarkers</code>	A character vector indicating the names of the variables for the biomarkers to use in calculating phenoage
<code>fit</code>	An S3 object for model fit. If the value is NULL, then the parameters to use for training phenoage are calculated

Details

Calculate phenotypic age

Value

An object of class "phenoage". This object is a list with two elements (data and fit)

Examples

```
#Train phenoage parameters
train = phenoage_calc(nhanes3, age="age",
                      biomarkers=c("albumin_gL", "lymph", "mcv", "glucose_mmol", "rdw", "creat_uml", "lnrcp", "alp", "wbc"))

#Use training data to calculate phenoage
phenoage = phenoage_calc(nhanes, age="age",
                        biomarkers=c("albumin_gL", "lymph", "mcv", "glucose_mmol", "rdw", "creat_uml", "lnrcp", "alp", "wbc"),
                        fit=train$fit)

#Extract phenoage dataset
data = phenoage$data
```

phenoage_nhanes	<i>phenoage_nhanes</i>
-----------------	------------------------

Description

Calculate Levine’s phenotypic age using NHANES dataset

Usage

phenoage_nhanes(biomarkers)

Arguments

biomarkers A character vector indicating the names of the variables for the biomarkers to use in calculating phenoage

Details

Calculate Levine’s phenotypic age using NHANES dataset

Value

An object of class "phenoage". This object is a list with two elements (data and fit)

Examples

```
#Calculate phenoage
phenoage = phenoage_nhanes(biomarkers=c("albumin_gL", "lymph", "mcv", "glucose_mmol", "rdw", "creat_umol", "lncrep

#Extract phenoage dataset
data = phenoage$data
```

plot_ba	<i>plot_ba</i>
---------	----------------

Description

Plot correlations between biological aging measures and chronological age

Usage

plot_ba(data, agevar)

Arguments

data The dataset for plotting correlations
agevar A character vector indicating the names of the biological aging measures

Details

Plot correlations between biological aging measures and chronological age

Note

Chronological age and gender variables need to be named "age" and "gender"

Examples

```
#Calculate phenoage
f1 = plot_ba(data = data, agevar = c("bioage", "phenoage", "hd"))

f1
```

plot_baa	<i>plot_baa</i>
----------	-----------------

Description

Plot correlations between biological age advancement (BAA) and chronological age

Usage

```
plot_baa(data, agevar, labels, axis_type)
```

Arguments

data	The dataset for plotting corplot
agevar	A character vector indicating the names of the interested biological age measures
labels	A character vector indicating the labels of the biological age measures Values should be formatted for displaying along diagonal of the plot Names should be used to match variables and order is preserved
axis_type	A character vector indicating the axis type (int or float) Use variable name to define the axis type

Details

Plot correlations between BAA and chronological age

Examples

```
#Create corplot of BAA with chronological age
labels = c("bioage_advance0"="KDM\nBiological\nAge",
           "phenoage_advance0"="Levine\nPhenotypic\nAge",
           "bioage_advance"="Modified-KDM\nBiological\nAge",
           "phenoage_advance"="Modified-Levine\nPhenotypic\nAge",
           "hd" = "Mahalanobis\nDistance",
           "hd_log" = "Log\nMahalanobis\nDistance")

axis_type = c("bioage_advance0"="float",
              "phenoage_advance0"="float",
```

```
      "bioage_advance"="float",
      "phenoage_advance"="flot",
      "hd"="flot",
      "hd_log"="float")

f2 = plot_baa(data,
              agevar = c("bioage_advance0",
                        "phenoage_advance0",
                        "bioage_advance",
                        "phenoage_advance",
                        "hd",
                        "hd_log"),

              labels = c("bioage_advance0"="KDM\nBiological\nAge",
                        "phenoage_advance0"="Levine\nPhenotypic\nAge",
                        "bioage_advance"="Modified-KDM\nBiological\nAge",
                        "phenoage_advance"="Modified-Levine\nPhenotypic\nAge",
                        "hd" = "Mahalanobis\nDistance",
                        "hd_log" = "Log\nMahalanobis\nDistance"),

              axis_type = c("bioage_advance0"="float",
                           "phenoage_advance0"="float",
                           "bioage_advance"="float",
                           "phenoage_advance"="flot",
                           "hd"="flot",
                           "hd_log"="float"))

f2
```

surv_table	<i>surv_table</i>
------------	-------------------

Description

Mortality validation for biological age measures

Usage

```
surv_table(data, agevar, time, status)
```

Arguments

data	The dataset for plotting corplot
agevar	A character vector indicating the names of the interested biological age measures
time	A character vector (length=1) indicating the name of the variable for survival time
status	A character vector (length=1) indicating the name of the variable for survival status

Details

Mortality validation for biological age measures, adjusting for chronological age and gender

Index

bioage_calc, [2](#)
bioage_nhanes, [3](#)

hd_calc, [3](#)
hd_nhanes, [4](#)

phenoage_calc, [5](#)
phenoage_nhanes, [6](#)
plot_ba, [6](#)
plot_baa, [7](#)

surv_table, [8](#)