第一阶段-C 语言-笔试-选择填空题

答案写在最前面的横杠空里，考试时间一小时，一小时后交卷再发放代码题，每题 3 分一个

姓名:_____ 学号:_____

专业:_____ 成绩:_____

1-5_____ **6-10**_____

一、选择题

1.
```
#include <stdio.h>
main() {
    int a, b;
    for (a = 0; a < 3; a++) {
        scanf("%d", &b);
        switch (b) {
            default: printf("%d,", ++b);
            case 1:  printf("%d,", ++b);
            case 2:  printf("%d,", ++b);
        }
    }
}
```

输入：1 2 3

输出结果是:

A. 2,3,4, B. 2,3,3,4,5,6, C. 2,2,3,4,4,4, D. 2,3,4,3,4,4,

2.
```
#include <stdio.h>
main() {
    int i;
    char c;
    scanf("%c", &c);
    for (i = 0; i < 5; i++) {
        if (i > c) continue;
        printf("%d,", i);
    }
}
```

执行时输入：0

输出结果是:

A. 0,1,2,3,4, B. 0,0,0,0,0, C. 5 D. 0,1,

3. #include <stdio.h>
main() {
    char ch = 'D';
    while (ch > 'A') {
        ch--;
        putchar(ch);
        if (ch == 'A') break;
        putchar(ch + 1);
    }
}
程序运行输出结果是:
A. CDBCA　　B. BCA　　C. CCBB　　D. CB

4. #include <stdio.h>
main() {
    int a, b;
    for (a = 0; a < 3; a++) {
        scanf("%d", &b);
        switch (b) {
            default: printf("%d,", b++);
            case 1: printf("%d,", b++);
            case 2: printf("%d,", b++);
        }
    }
}
输入: 1 2 3
输出结果是:
A. 1,2,3,　B. 1,2,2,3,4,5,　C. 1,2,3,2,3,3,　D. 1,1,1,2,2,3,

5. #include <stdio.h>
main() {
    int s[12] = {1,2,3,4,4,3,2,1,1,1,2,3}, c[5] = {0}, i;
    for(i = 0; i < 12; i++) c[s[i]]++;
    for(i = 1; i < 5; i++) printf("%d", c[i]);
    printf("\n");
}
程序运行结果是:
A. 1 2 3 4 B. 2 3 4 4 C. 4 3 3 2 D. 1 1 2 3

6. #include <stdio.h>
#include <string.h>

```
int main() {
    char str1[10] = "hello";
    char str2[10] = "world";
    strcat(str1, str2);
    printf("%d", strlen(str1));
    return 0;
}
```

以下代码的输出是什么?

A) 5 B) 10 C) 11 D) 编译错误

7.
```
#include <stdio.h>

void change(int *p) {
    *p = 20;
}

int main() {
    int a = 10;
    int *ptr = &a;
    change(ptr);
    printf("%d", a);
    return 0;
}
```

以下代码的输出是什么?

A) 10 B) 20 C) 随机值 D) 编译错误

8. 以下哪种结构体定义是正确的?

A)
```
struct Student {
    char name[20];
    int age;
} student;
```

B)
```
struct {
    char name[20];
    int age;
```

```
} Student;
```

C)
```
struct Student {
    char name[20];
    int age;
}
Student s1;
```

D) 以上都正确

9.
```
#include <stdlib.h>

int main() {
    int *arr = (int*)malloc(5 * sizeof(int));
    for(int i = 0; i < 5; i++) {
        arr[i] = i * 2;
    }
    // 使用数组...
    return 0;
}
```

以下代码存在的问题是：

A) 内存分配失败未检查　　B) 内存泄漏　　C) 数组越界访问　　D) 语法错误

10. 在单向链表中，要在头部插入新节点，正确的操作顺序是：

A)
```
1. new_node->next = head;
2. head = new_node;
```

B)
```
1. head = new_node;
2. new_node->next = head;
```

C)
```
1. new_node->next = head->next;
2. head = new_node;
```

D)
```
1. head->next = new_node;
2. head = new_node;
```