

**FOR CONTRACTORS & SUPPLIERS ONLY FOR PAYMENT FOR WORK OR SUPPLIES ACTUALLY MEASURED****WORK ORDER**

Cash Book Voucher No.

Date-

Name of Contractor or supplier :

Name of Work :-

|                                          |                     |                                                  |
|------------------------------------------|---------------------|--------------------------------------------------|
| Serial No. of this bill :                | N/A                 | No.<br>and<br>date<br>of<br>the<br>last<br>bill- |
| Reference to work order or Agreement :   | N/A                 |                                                  |
| Agreement No.                            | 48/2024-25          |                                                  |
| Date of written order to commence work : | 2025-01-09 00:00:00 |                                                  |
| St. date of Start :                      | N/A                 |                                                  |
| St. date of completion :                 | 2025-04-17 00:00:00 |                                                  |
| Date of actual completion of work :      | 2025-03-01 00:00:00 |                                                  |
| Date of measurement :                    | N/A                 |                                                  |

| Unit        | Quantity<br>executed<br>(or<br>supplied)<br>since last<br>certificate | Quantity<br>executed<br>(or<br>supplied)<br>upto<br>date as<br>per MB | S.<br>No. | Item of Work supplies<br>(Grouped under "sub-head"<br>and "sub work" of estimate)                                                                                                                                                                                                                                                                                                                     | Rate   | Upto date<br>Amount | Amount<br>Since<br>previous<br>bill (Total<br>for each<br>sub-head) | Remarks |
|-------------|-----------------------------------------------------------------------|-----------------------------------------------------------------------|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------------------|---------------------------------------------------------------------|---------|
| P.<br>point | 48.00                                                                 | 48.00                                                                 |           | Medium point (up to 6 mtr.)                                                                                                                                                                                                                                                                                                                                                                           | 472.00 | 22656.00            | 22656.00                                                            | 1.5.2   |
| P.<br>point | 52.00                                                                 | 52.00                                                                 |           | Long point (up to 10 mtr.)                                                                                                                                                                                                                                                                                                                                                                            | 662.00 | 34424.00            | 34424.00                                                            | 1.5.3   |
|             |                                                                       |                                                                       | 2         | Rewiring of 3/5 pin 6 amp. Light<br>plug point with 1.5 sq. mm<br>nominal size FR PVC insulated<br>unsheathed flexible copper<br>conductor 1.1 kV grade and 1.5<br>sq. mm nominal size FR PVC<br>insulated unsheathed flexible<br>copper earth conductor 1.1 kV<br>grade(IS:694) in recessed ISI<br>marked MMS ( IS:9537 P - III )<br>virgin material PVC conduit & it's<br>ISI marked (IS:3419-1988) |        |                     |                                                                     | 1.7     |

| Unit        | Quantity<br>executed<br>(or<br>supplied)<br>since last<br>certificate | Quantity<br>executed<br>(or<br>supplied)<br>upto<br>date as<br>per MB | S.<br>No. | Item of Work supplies<br>(Grouped under "sub-head"<br>and "sub work" of estimate)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Rate   | Upto date<br>Amount | Amount<br>Since<br>previous<br>bill (Total<br>for each<br>sub-head) | Remarks |
|-------------|-----------------------------------------------------------------------|-----------------------------------------------------------------------|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------------------|---------------------------------------------------------------------|---------|
|             |                                                                       |                                                                       |           | accessories, 1.2 mm thick MS<br>box with earth terminal of<br>required size, 6 A switch, 3/5 pin<br>6 A socket, 3.0 mm thick ISI<br>marked (IS:2036-1995) phenolic<br>laminated sheet, Al.alloy /<br>Cadmium plated iron/ brass<br>screws, cup washers, making<br>connections, testing etc. as<br>required. For specification of<br>copper Conductor, Phenolic<br>Laminated sheet's & Electrical/<br>Wiring accessories refer Chapter<br>E - 04, E - 05 & E - 07 For<br>additional technical parameters of<br>product / work refer Annexure 'A'<br>attached with this BSR |        |                     |                                                                     |         |
| P.<br>point | 102.00                                                                | 102.00                                                                |           | On board                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 136.00 | 13872.00            | 13872.00                                                            | 1.7.1   |
| Each        | 8.00                                                                  | 8.00                                                                  | 3         | P & F ISI marked (IS:3854) 6<br>amp. flush type non modular<br>switch with CM/L no. printed and<br>made out from industrial grade<br>Polycarbonate or fire resistant<br>ABS material including cutting<br>hole in tile and making<br>connection testing etc. as<br>required. All as per pre approved<br>by Engineer in charge. For<br>additional technical parameters of<br>products/ work , refer Annexure<br>"A" attached with this BSR .                                                                                                                               | 23.00  | 184.00              | 184.00                                                              | 7.1     |
| Each        | 32.00                                                                 | 32.00                                                                 | 4         | P & F ISI marked (IS :3854) 16<br>amp. flush type non modular<br>switch CM/L no. printed and<br>made out from industrial grade<br>Polycarbonate or fire resistant<br>ABS material including cutting<br>hole in tile and making<br>connection testing etc. as<br>required. All as per pre approved<br>by Engineer in charge. For<br>additional technical parameters of<br>products/ work , refer Annexure<br>"A" attached with this BSR .                                                                                                                                  | 50.00  | 1600.00             | 1600.00                                                             | 7.2     |

| Unit | Quantity<br>executed<br>(or<br>supplied)<br>since last<br>certificate | Quantity<br>executed<br>(or<br>supplied)<br>upto<br>date as<br>per MB | S.<br>No. | Item of Work supplies<br>(Grouped under "sub-head"<br>and "sub work" of estimate)                                                                                                                                                                                                                                                                                                                                                                   | Rate  | Upto date<br>Amount | Amount<br>Since<br>previous<br>bill (Total<br>for each<br>sub-head) | Remarks |
|------|-----------------------------------------------------------------------|-----------------------------------------------------------------------|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|---------------------|---------------------------------------------------------------------|---------|
| Each | 22.00                                                                 | 22.00                                                                 | 5         | Providing & Fixing of of 3/5 pin 6 amp. flush type non modular socket made out from industrial grade Polycarbonate or fire resistant ABS material, brass terminal with Porcelain based back cover & captive screws including cutting hole in tile and making connection testing etc. as required.All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR . | 33.00 | 726.00              | 726.00                                                              | 7.10    |
| Each | 36.00                                                                 | 36.00                                                                 | 6         | Providing & Fixing of 3/6 pin 16 amp flush type non modular socket made out from Industrial grade Polycarbonate or fire resistant ABS material, brass terminal with Porcelain based back cover & captive screws including cutting hole in tile and making connection testing etc. as required.All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .    | 78.00 | 2808.00             | 2808.00                                                             | 7.11    |
| Each | 12.00                                                                 | 12.00                                                                 | 7         | Providing & Fixing of ISI marked (IS:371) 6 amp surface type 3 pin ceiling rose with CM/L no. printed and made out from industrial grade Polycarbonate or fire resistant ABS material, brass terminal & captive screws including making connection testing etc. as required.All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .                      | 30.00 | 360.00              | 360.00                                                              | 7.12    |
| Each | 25.00                                                                 | 25.00                                                                 | 8         | Providing & Fixing of ISI marked (IS:1258) batten/angle lamp holder with CM/L no. printed and made out from industrial grade                                                                                                                                                                                                                                                                                                                        | 30.00 | 750.00              | 750.00                                                              | 7.13    |

| Unit | Quantity<br>executed<br>(or<br>supplied)<br>since last<br>certificate | Quantity<br>executed<br>(or<br>supplied)<br>upto<br>date as<br>per MB | S.<br>No. | Item of Work supplies<br>(Grouped under "sub-head"<br>and "sub work" of estimate)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Rate   | Upto date<br>Amount | Amount<br>Since<br>previous<br>bill (Total<br>for each<br>sub-head) | Remarks |
|------|-----------------------------------------------------------------------|-----------------------------------------------------------------------|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------------------|---------------------------------------------------------------------|---------|
| Each | 25.00                                                                 | 25.00                                                                 | 9         | <p>Polycarbonate or fire resistant ABS material, brass terminal &amp; captive screws including making connection testing etc. as required. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .</p> <p>Providing &amp; Fixing of IS 11037:1984 marked non modular socket size flush type 180 watt rotary minimum 5 step fan regulator with CM/L no. printed and made out from industrial grade Polycarbonate or fire resistant ABS material including making connection testing etc. as required. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .</p> | 219.00 | 5475.00             | 5475.00                                                             | 7.21    |
| Each | 25.00                                                                 | 25.00                                                                 | 10        | <p>Providing and fixing of power plug point with non modular accessories as per PWD specification for electrical Works with Galvanized box of 1.2 mm thick with earth terminal with suitable size phenolic laminated sheet (IS : 2036 - 1995) cover including cost of 16 amp. Switch (IS :3854) and 3/6 pin 16 amp. socket outlet making connection , testing , etc. as required. . For specification of Wiring accessories refer Chapter E - 07 related item &amp; For additional technical parameters of product / work refer Annexure 'A' attached with this BSR</p>                                                                                                                                                                                | 303.00 | 7575.00             | 7575.00                                                             | 7.36    |
|      |                                                                       |                                                                       | 11        | <p>S&amp;F following sizes (dia.) of ISI marked virgin material MMS ( IS:9537 P - III ) PVC conduit along with ISI marked (IS:3419-1988) accessories as required in</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |        |                     |                                                                     | 1.4     |

| Unit       | Quantity<br>executed<br>(or<br>supplied)<br>since last<br>certificate | Quantity<br>executed<br>(or<br>supplied)<br>upto<br>date as<br>per MB | S.<br>No. | Item of Work supplies<br>(Grouped under "sub-head"<br>and "sub work" of estimate)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Rate    | Upto date<br>Amount | Amount<br>Since<br>previous<br>bill (Total<br>for each<br>sub-head) | Remarks |
|------------|-----------------------------------------------------------------------|-----------------------------------------------------------------------|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|---------------------|---------------------------------------------------------------------|---------|
|            |                                                                       |                                                                       |           | recess including cutting the wall,<br>covering conduit and making<br>good the same as required. For<br>additional technical parameters of<br>product / work refer Annexure 'A'<br>attached with this BSR                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |         |                     |                                                                     |         |
| R.<br>mtr. | 2985.00                                                               | 2985.00                                                               |           | 20 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 40.00   | 119400.00           | 119400.00                                                           | 1.4.1   |
| R.<br>mtr. | 25.00                                                                 | 25.00                                                                 |           | 25 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 56.00   | 1400.00             | 1400.00                                                             | 1.4.2   |
|            |                                                                       |                                                                       | 12        | Supplying and drawing FR PVC<br>insulated & unsheathed flexible<br>copper conductor as per PWD<br>specification for electrical Works<br>with ISI marked (IS:694) and as<br>per IS 8130 : 2013 of 1.1 kV<br>grade . Wire should be made from<br>99.90 % purity copper, class 2<br>stranding in acc. to IS:8130/IEC<br>60228 for lower watt loss ,<br>oxygen free for less chances of<br>oxidization, insulation PVC type<br>A/C/D , flame retardant as per IS<br>10810-53, better amperage rating<br>as per IS:3961 part 5, in existing<br>surface or recessed PVC/ MS<br>conduit/casing capping making<br>connections with Copper Lugs of<br>suitable size, Ferrules,testing etc.<br>as required. OEM Must have its<br>own in house NABL lab setup for<br>all testing facilities for wires. For<br>additional technical parameters of<br>product / work refer Annexure 'A'<br>attached with this BSR |         |                     |                                                                     | 4.1     |
| Mtr.       | 90.00                                                                 | 90.00                                                                 |           | 2 x 2.5 sq. mm. + 1x1.5sqmm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 81.00   | 7290.00             | 7290.00                                                             | 4.1.7   |
| Mtr.       | 25.00                                                                 | 25.00                                                                 |           | 2 x 4.0 sq. mm. + 1 x 2.5 sq. mm.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 122.00  | 3050.00             | 3050.00                                                             | 4.1.14  |
| Set        | 15.00                                                                 | 15.00                                                                 | 13        | Plate Earthing as per IS:3043<br>with Hot dipped G.I. Earth plate<br>of size 600mm x 600mm x<br>6.0mm by embodying 3 to 4 mtr.<br>below the ground level with 20<br>mm dia. G.I. 'B' class watering<br>Pipe ,including all accessories<br>like nut, bolts, reducer, nipple,<br>wire meshed funnel, and Heavy                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 5733.00 | 85995.00            | 85995.00                                                            | 14.2    |

| Unit | Quantity<br>executed<br>(or<br>supplied)<br>since last<br>certificate | Quantity<br>executed<br>(or<br>supplied)<br>upto<br>date as<br>per MB | S.<br>No. | Item of Work supplies<br>(Grouped under "sub-head"<br>and "sub work" of estimate)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Rate  | Upto date<br>Amount | Amount<br>Since<br>previous<br>bill (Total<br>for each<br>sub-head) | Remarks        |
|------|-----------------------------------------------------------------------|-----------------------------------------------------------------------|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|---------------------|---------------------------------------------------------------------|----------------|
|      |                                                                       |                                                                       | 14        | <p>duty weather proof poly-propylene earth pit chamber with lockable Jam free lid suitable for safe working load 5000 Kg or more of size Top Dia. 225 to 260 mm, Bottom Dia 300 to 350 mm. and Height 250 to 300 mm. and embodying the pipe complete with alternate layers salt and coke/ charcoal, testing of earth resistance for value of 5 ohms or less as required &amp; must record by engineer in charge during site visit and ensure to enter in measurment book.All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .</p> <p>Supply &amp; Laying following size earth wire in horizontal or vertical run in ground/surface/recess including riveting, soldering, saddles, making connection with GI/Cu purity purity &gt;95% thimble etc. as required. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .</p> |       |                     |                                                                     | 14.6           |
| Mtr. | 45.00                                                                 | 45.00                                                                 | 15        | <p>8 SWG G.I. ( Hot Dipped ) Wire</p> <p>Providing &amp; Fixing of BEE Star rated copper wounded double ball bearing capacitor start, aluminium body &amp; Metallic blade ceiling fan Conforming to all the performance requirements laid down in IS 374:2019 including all amendments, as applicable ; &amp; Carry BIS licensing (i.e. ISI marking) with down rod up to 80 cm with secondary support safety cable ( steel rope) , cotter pin with 3 x 1.5 sq.mm pvc insulated</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 20.00 | 900.00              | 900.00                                                              | 14.6.8<br>15.7 |

| Unit | Quantity<br>executed<br>(or<br>supplied)<br>since last<br>certificate | Quantity<br>executed<br>(or<br>supplied)<br>upto<br>date as<br>per MB | S.<br>No. | Item of Work supplies<br>(Grouped under "sub-head"<br>and "sub work" of estimate)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Rate    | Upto date<br>Amount | Amount<br>Since<br>previous<br>bill (Total<br>for each<br>sub-head) | Remarks |
|------|-----------------------------------------------------------------------|-----------------------------------------------------------------------|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|---------------------|---------------------------------------------------------------------|---------|
|      |                                                                       |                                                                       |           | flexible copper conductor making connection testing etc. as required. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |         |                     |                                                                     |         |
| Each | 24.00                                                                 | 24.00                                                                 |           | 1200 mm Sweep BEE 1 Star rated (service value $\geq 4.0$ to $< 4.5$ )                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 1890.00 | 45360.00            | 45360.00                                                            | 15.7.1  |
|      |                                                                       |                                                                       | 16        | Providing & Fixing of IP20 SMD Mid Power LED batten type integrated light fixture made from Powder coated Extruded aluminium housing with in built driver , System lumen efficacy $\geq 110$ lm/Watt output, internal surge protection of 2.5 KV with Short & Open circuit protection ,THD $< 10\%$ , P. F. $\geq 0.95$ , CRI $> 80$ , life time of minimum 50000 Burning Hours with , 70% of intial Lumen maintanad till life ends , CCT 3000°K / 4000°K / 5700°K /6000°K/6500°K (As per ANSI Bin) , Maximum power consumption should not more than the specified rating and Fixture shall be of BIS standard and trade mark certificate ( T.C.). Manufactures Word Mark/ Name Engraved/ Embossing/ Screen printing on housing. OEM must have its own in house NABL lab setup for all testing facilities for LED fixtures. (LM79 & LM80) certificate / Report from OEM shall be submitted. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR . |         |                     |                                                                     | 17.1    |
| Each | 78.00                                                                 | 78.00                                                                 |           | 1170mm(+/-10%) LED batten with min. lumen output 2200 lm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 492.00  | 38376.00            | 38376.00                                                            | 17.1.1  |
|      |                                                                       |                                                                       | 17        | Providing & Fixing of 240/415 V AC MCB with positive isolation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |         |                     |                                                                     | 6.1     |

| Unit | Quantity<br>executed<br>(or<br>supplied)<br>since last<br>certificate | Quantity<br>executed<br>(or<br>supplied)<br>upto<br>date as<br>per MB | S.<br>No. | Item of Work supplies<br>(Grouped under "sub-head"<br>and "sub work" of estimate)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Rate   | Upto date<br>Amount | Amount<br>Since<br>previous<br>bill (Total<br>for each<br>sub-head) | Remarks |
|------|-----------------------------------------------------------------------|-----------------------------------------------------------------------|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------------------|---------------------------------------------------------------------|---------|
|      |                                                                       |                                                                       |           | of 10 kA breaking capacity (B/<br>C/D tripping characteristic as per<br>type of load and site requirement)<br>4 KV impulse withstand voltage,<br>ISI marked IS 8828(1996) /<br>conforming to IEC 60898-1 2002,<br>IEC 60947-2, low watt losses, trip<br>free mechanisum , energy limiting<br>of class 3 as per IEC, minimum<br>phase termination capacity of<br>35sq.mm. , conductor line load<br>reversibility , IP 20 contact<br>protection and fitted in existing<br>distribution board/sheets,<br>minimum electrical operation<br>20,000 upto 20 A rating and<br>10,000 upto 63 A, 5000 for 80 A<br>& above rating including making<br>connections, testing etc. as<br>required. OEM shall have submit<br>NABL / CPRI / ERDA<br>accrediated lab type test reports &<br>All as per pre approved by<br>Engineer in charge. For additional<br>technical parameters of product /<br>work refer Annexure 'A' attached<br>with this BSR |        |                     |                                                                     |         |
|      |                                                                       |                                                                       |           | Single pole MCB (With B/C<br>curve tripping Characteristics)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |        |                     |                                                                     | 6.1.1   |
| Each | 51.00                                                                 | 51.00                                                                 |           | 6 A to 32 A rating                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 187.00 | 9537.00             | 9537.00                                                             | 6.1.1.2 |
|      |                                                                       |                                                                       |           | Double pole MCB(With B/C<br>curve tripping Characteristics)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |        |                     |                                                                     | 6.1.2   |
| Each | 12.00                                                                 | 12.00                                                                 |           | 50/63 A rating                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 900.00 | 10800.00            | 10800.00                                                            | 6.1.2.4 |
|      |                                                                       |                                                                       | 18        | Providing & Fixing of<br>Recessed/surface mounting heavy<br>duty horizontal type Double Door<br>( Metal / Glazed )Distribution<br>board with Metal end box made<br>out from Galvanized steel /<br>CRCA sheet not less then 1.2 mm<br>thick conforming to IS-8623-1 &<br>3 / IEC 61439- 1 & 3, powder<br>painted complete with reversible<br>door (for double door DB only<br>)100 amp. insulated copper bus<br>bar/shorting link , copper neutral                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |        |                     |                                                                     | 6.1     |



| Unit | Quantity<br>executed<br>(or<br>supplied)<br>since last<br>certificate | Quantity<br>executed<br>(or<br>supplied)<br>upto<br>date as<br>per MB | S.<br>No. | Item of Work supplies<br>(Grouped under "sub-head"<br>and "sub work" of estimate)                                                                                                                                                                                                                                                                                                                                                                                                                                                | Rate    | Upto date<br>Amount | Amount<br>Since<br>previous<br>bill (Total<br>for each<br>sub-head) | Remarks  |
|------|-----------------------------------------------------------------------|-----------------------------------------------------------------------|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|---------------------|---------------------------------------------------------------------|----------|
|      |                                                                       |                                                                       |           | link, copper earth link , color<br>coded interconnecting wire set of<br>suitable rating and din<br>bar,masking sheet, making<br>internal DB terminations with<br>copper lugs, Ferrules, detachable<br>gland plate, including making<br>connections, testing etc. as<br>required. OEM shall have submit<br>NABL / CPRI / ERDA<br>accredited lab type test reports &<br>All as per pre approved by<br>Engineer in charge. For additional<br>technical parameters of product /<br>work refer Annexure 'A' attached<br>with this BSR |         |                     |                                                                     |          |
| Each | 7.00                                                                  | 7.00                                                                  |           | Metal door (single phase) IK-09<br>and IP-43 with Metal end box                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |         |                     |                                                                     | 6.10.1   |
|      |                                                                       |                                                                       |           | 8 Way (8+2)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 2184.00 | 15288.00            | 15288.00                                                            | 6.10.1.3 |
|      |                                                                       |                                                                       |           | Extra Items (With Premium)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |         |                     |                                                                     |          |
|      |                                                                       |                                                                       |           | Grand Total Rs.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |         | 427826.00           | 427826.00                                                           |          |
|      |                                                                       |                                                                       |           | Tender Premium @ 22.22%                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 22.22%  | 95063.00            | 95063.00                                                            |          |
|      |                                                                       | NIL                                                                   |           | <<<<<<< Sum of Extra Items<br>(including Tender Premium)                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |         |                     |                                                                     |          |
|      |                                                                       |                                                                       |           | Payable Amount Rs.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |         | 522889.00           | 522889.00                                                           |          |
|      |                                                                       |                                                                       |           | Less Amount Paid vide Last Bill<br>Rs.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |         | 0.00                | 0.00                                                                |          |
|      |                                                                       |                                                                       |           | <b>Net Payable Amount Rs.</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |         | <b>522889.00</b>    | <b>522889.00</b>                                                    |          |