

**FOR CONTRACTORS & SUPPLIERS ONLY FOR PAYMENT FOR WORK OR SUPPLIES ACTUALLY MEASURED****Senond & Running Bill**

|                                          |                                                                                         |                                |                |
|------------------------------------------|-----------------------------------------------------------------------------------------|--------------------------------|----------------|
| Cash Book Voucher No.                    |                                                                                         | Date-                          |                |
| Name of Contractor or supplier :         | M/s Seema Electrical Udaipur                                                            |                                |                |
| Name of Work :-                          | Electric Repair and MTC work at Govt. Ambedkar hostel Ambamata, Govardhanvilas, Udaipur |                                |                |
| Serial No. of this bill :                | Second Running Bill                                                                     | No. and date of the last bill- | Not Applicable |
| Reference to work order or Agreement :   | 1179 Dt. 09-01-2025                                                                     |                                |                |
| Agreement No.                            | 48/2024-25                                                                              |                                |                |
| Date of written order to commence work : | 2025-01-09 00:00:00                                                                     |                                |                |
| St. date of Start :                      | 2025-01-18 00:00:00                                                                     |                                |                |
| St. date of completion :                 | 2025-04-17 00:00:00                                                                     |                                |                |
| Date of actual completion of work :      | Work in Progress.                                                                       |                                |                |
| Date of measurement :                    | 2025-03-03 00:00:00                                                                     |                                |                |

| Unit | Quantity executed (or supplied) since last certificate | Quantity executed (or supplied) upto date as per MB | S. No. | Item of Work supplies (Grouped under "sub-head" and "sub work" of estimate)                                                                                                                                                                                                                                                                                                                                                                                                      | Rate    | Upto date Amount | Amount Since previous bill (Total for each sub-head) | Remarks |
|------|--------------------------------------------------------|-----------------------------------------------------|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|------------------|------------------------------------------------------|---------|
| Set  | 15.00                                                  | 15.00                                               | 13     | Plate Earthing as per IS:3043 with Hot dipped G.I. Earth plate of size 600mm x 600mm x 6.0mm by embodying 3 to 4 mtr. below the ground level with 20 mm dia. G.I. 'B' class watering Pipe ,including all accessories like nut, bolts, reducer, nipple, wire meshed funnel, and Heavy duty weather proof poly-propylene earth pit chamber with lockable Jam free lid suitable for safe working load 5000 Kg or more of size Top Dia. 225 to 260 mm, Bottom Dia 300 to 350 mm. and | 5733.00 | 85995.00         | 85995.00                                             | 14.2    |

| Unit | Quantity<br>executed<br>(or<br>supplied)<br>since last<br>certificate | Quantity<br>executed<br>(or<br>supplied)<br>upto<br>date as<br>per MB | S.<br>No. | Item of Work supplies<br>(Grouped under "sub-head"<br>and "sub work" of estimate)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Rate  | Upto date<br>Amount | Amount<br>Since<br>previous<br>bill (Total<br>for each<br>sub-head) | Remarks        |
|------|-----------------------------------------------------------------------|-----------------------------------------------------------------------|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|---------------------|---------------------------------------------------------------------|----------------|
|      |                                                                       |                                                                       | 14        | <p>Height 250 to 300 mm. and embodying the pipe complete with alternate layers salt and coke/ charcoal, testing of earth resistance for value of 5 ohms or less as required &amp; must record by engineer in charge during site visit and ensure to enter in measurment book.All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .</p> <p>Supply &amp; Laying following size earth wire in horizontal or vertical run in ground/surface/recess including riveting, soldering, saddles, making connection with GI/Cu purity purity &gt;95% thimble etc. as required. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .</p> |       |                     |                                                                     | 14.6           |
| Mtr. | 35.00                                                                 | 35.00                                                                 | 15        | <p>8 SWG G.I. ( Hot Dipped ) Wire</p> <p>Providing &amp; Fixing of BEE Star rated copper wounded double ball bearing capacitor start, aluminium body &amp; Metallic blade ceiling fan Conforming to all the performance requirements laid down in IS 374:2019 including all amendments, as applicable ; &amp; Carry BIS licensing (i.e. ISI marking) with down rod up to 80 cm with secondary support safety cable ( steel rope) , cotter pin with 3 x 1.5 sq.mm pvc insulated flexible copper conductor making connection testing etc. as required. All as per pre approved by Engineer in charge. For additional technical parameters of</p>                                                                                                                                                                          | 20.00 | 700.00              | 700.00                                                              | 14.6.8<br>15.7 |

| Unit | Quantity<br>executed<br>(or<br>supplied)<br>since last<br>certificate | Quantity<br>executed<br>(or<br>supplied)<br>upto<br>date as<br>per MB | S.<br>No. | Item of Work supplies<br>(Grouped under "sub-head"<br>and "sub work" of estimate)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Rate    | Upto date<br>Amount | Amount<br>Since<br>previous<br>bill (Total<br>for each<br>sub-head) | Remarks |
|------|-----------------------------------------------------------------------|-----------------------------------------------------------------------|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|---------------------|---------------------------------------------------------------------|---------|
|      |                                                                       |                                                                       |           | products/ work , refer Annexure<br>"A" attached with this BSR .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |         |                     |                                                                     |         |
| Each | 12.00                                                                 | 12.00                                                                 |           | 1200 mm Sweep BEE 1 Star rated<br>(service value $\geq 4.0$ to $< 4.5$ )                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 1890.00 | 22680.00            | 22680.00                                                            | 15.7.1  |
|      |                                                                       |                                                                       | 16        | Providing & Fixing of IP20 SMD<br>Mid Power LED batten type<br>integrated light fixture made from<br>Powder coated Extruded<br>aluminium housing with in built<br>driver , System lumen efficacy $\geq$<br>110 lm/Watt output, internal surge<br>protection of 2.5 KV with Short<br>& Open circuit protection ,THD $<$<br>10% , P. F. $\geq 0.95$ , CRI $> 80$ , life<br>time of minimum 50000 Burning<br>Hours with , 70% of intial Lumen<br>maintaned till life ends , CCT<br>3000°K / 4000°K / 5700°K<br>/6000°K/6500°K (As per ANSI<br>Bin) , Maximum power<br>consumption should not more<br>than the specified rating and<br>Fixture shall be of BIS standard<br>and trade mark certificate ( T.C.).<br>Manufactures Word Mark/ Name<br>Engraved/ Embossing/ Screen<br>printing on housing. OEM must<br>have its own in house NABL lab<br>setup for all testing facilities for<br>LED fixtures. (LM79 & LM80)<br>certificate / Report from OEM<br>shall be submitted. All as per pre<br>approved by Engineer in charge.<br>For additional technical<br>parameters of products/ work ,<br>refer Annexure "A" attached with<br>this BSR . |         |                     |                                                                     | 17.1    |
| Each | 78.00                                                                 | 78.00                                                                 |           | 1170mm(+/-10%) LED batten<br>with min. lumen output 2200 lm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 492.00  | 38376.00            | 38376.00                                                            | 17.1.1  |
|      |                                                                       |                                                                       | 17        | Providing & Fixing of 240/415 V<br>AC MCB with positive isolation<br>of 10 kA breaking capacity (B/<br>C/D tripping characteristic as per<br>type of load and site requirement)<br>4 KV impulse withstand voltage,<br>ISI marked IS 8828(1996) /                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |         |                     |                                                                     | 6.1     |

| Unit | Quantity<br>executed<br>(or<br>supplied)<br>since last<br>certificate | Quantity<br>executed<br>(or<br>supplied)<br>upto<br>date as<br>per MB | S.<br>No. | Item of Work supplies<br>(Grouped under "sub-head"<br>and "sub work" of estimate)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Rate   | Upto date<br>Amount | Amount<br>Since<br>previous<br>bill (Total<br>for each<br>sub-head) | Remarks |
|------|-----------------------------------------------------------------------|-----------------------------------------------------------------------|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------------------|---------------------------------------------------------------------|---------|
|      |                                                                       |                                                                       |           | conforming to IEC 60898-1 2002,<br>IEC 60947-2, low watt losses, trip<br>free mechanisum , energy limiting<br>of class 3 as per IEC, minimum<br>phase termination capacity of<br>35sq.mm. , conductor line load<br>reversibility , IP 20 contact<br>protection and fitted in existing<br>distribution board/sheets,<br>minimum electrical operation<br>20,000 upto 20 A rating and<br>10,000 upto 63 A, 5000 for 80 A<br>& above rating including making<br>connections, testing etc. as<br>required. OEM shall have submit<br>NABL / CPRI / ERDA<br>accrediated lab type test reports &<br>All as per pre approved by<br>Engineer in charge. For additional<br>technical parameters of product /<br>work refer Annexure 'A' attached<br>with this BSR |        |                     |                                                                     |         |
|      |                                                                       |                                                                       |           | Single pole MCB (With B/C<br>curve tripping Characteristics)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |        |                     |                                                                     | 6.1.1   |
| Each | 88.00                                                                 | 88.00                                                                 |           | 6 A to 32 A rating                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 187.00 | 16456.00            | 16456.00                                                            | 6.1.1.2 |
|      |                                                                       |                                                                       |           | Double pole MCB(With B/C<br>curve tripping Characteristics)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |        |                     |                                                                     | 6.1.2   |
| Each | 35.00                                                                 | 35.00                                                                 |           | 50/63 A rating                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 900.00 | 31500.00            | 31500.00                                                            | 6.1.2.4 |
|      |                                                                       |                                                                       | 18        | Providing & Fixing of<br>Recessed/surface mounting heavy<br>duty horizontal type Double Door<br>( Metal / Glazed )Distribution<br>board with Metal end box made<br>out from Galvanized steel /<br>CRCA sheet not less then 1.2 mm<br>thick conforming to IS-8623-1 &<br>3 / IEC 61439- 1 & 3, powder<br>painted complete with reversible<br>door (for double door DB only<br>)100 amp. insulated copper bus<br>bar/shorting link , copper neutral<br>link, copper earth link , color<br>coded interconnecting wire set of<br>suitable rating and din<br>bar,masking sheet, making<br>internal DB terminations with                                                                                                                                     |        |                     |                                                                     | 6.1     |

| Unit | Quantity<br>executed<br>(or<br>supplied)<br>since last<br>certificate | Quantity<br>executed<br>(or<br>supplied)<br>upto<br>date as<br>per MB | S.<br>No. | Item of Work supplies<br>(Grouped under "sub-head"<br>and "sub work" of estimate)                                                                                                                                                                                                                                                                                                                                                                                 | Rate    | Upto date<br>Amount | Amount<br>Since<br>previous<br>bill (Total<br>for each<br>sub-head) | Remarks  |
|------|-----------------------------------------------------------------------|-----------------------------------------------------------------------|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|---------------------|---------------------------------------------------------------------|----------|
|      |                                                                       |                                                                       |           | copper lugs, Ferrules, detachable<br>gland plate, including making<br>connections, testing etc. as<br>required. OEM shall have submit<br>NABL / CPRI / ERDA<br>accredited lab type test reports &<br>All as per pre approved by<br>Engineer in charge. For additional<br>technical parameters of product /<br>work refer Annexure 'A' attached<br>with this BSR                                                                                                   |         |                     |                                                                     |          |
|      |                                                                       |                                                                       |           | Metal door (single phase) IK-09<br>and IP-43 with Metal end box                                                                                                                                                                                                                                                                                                                                                                                                   |         |                     |                                                                     | 6.10.1   |
| Each | 25.00                                                                 | 25.00                                                                 |           | 8 Way (8+2)                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 2184.00 | 54600.00            | 54600.00                                                            | 6.10.1.3 |
|      |                                                                       |                                                                       |           | Extra Items (With Premium)                                                                                                                                                                                                                                                                                                                                                                                                                                        |         |                     |                                                                     |          |
| Each | 4.00                                                                  | 4.00                                                                  | E-01      | 6 A 3/5 pin shuttered socket                                                                                                                                                                                                                                                                                                                                                                                                                                      | 107.00  | 428.00              | 428.00                                                              |          |
| Each | 5.00                                                                  | 5.00                                                                  | E-02      | 6/16 A shuttered socket                                                                                                                                                                                                                                                                                                                                                                                                                                           | 176.00  | 880.00              | 880.00                                                              |          |
|      |                                                                       |                                                                       |           | Providing & Fixing of modular<br>type lockable feature socket duly<br>made out of unbreakable and fire<br>retardant vergin poly carbonate<br>with brass terminals and captive<br>screws & silver alloy contact tip<br>with IP-20 rating, including all as<br>per pre approved by Engineer in<br>charge, making connections,<br>testing etc. as required. For<br>additional technical parameters of<br>product / work refer Annexure 'A'<br>attached with this BSR |         |                     |                                                                     |          |
| Each | 5.00                                                                  | 5.00                                                                  | E-03      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 345.00  | 1725.00             | 1725.00                                                             |          |
| Each | 4.00                                                                  | 4.00                                                                  | E-04      | 6 A 3/5 pin shuttered socket                                                                                                                                                                                                                                                                                                                                                                                                                                      | 107.00  | 428.00              | 428.00                                                              |          |
| Each | 5.00                                                                  | 5.00                                                                  | E-05      | 6/16 A shuttered socket                                                                                                                                                                                                                                                                                                                                                                                                                                           | 176.00  | 880.00              | 880.00                                                              |          |
|      |                                                                       |                                                                       |           | Grand Total Rs.                                                                                                                                                                                                                                                                                                                                                                                                                                                   |         | 254648.00           | 254648.00                                                           |          |
|      |                                                                       |                                                                       |           | Tender Premium @ 22.22%                                                                                                                                                                                                                                                                                                                                                                                                                                           | 22.22%  | 56583.00            | 56583.00                                                            |          |
|      | Rs. 5306.00                                                           |                                                                       |           | <<<<<< Sum of Extra Items<br>(including Tender Premium)                                                                                                                                                                                                                                                                                                                                                                                                           |         |                     |                                                                     |          |
|      |                                                                       |                                                                       |           | Payable Amount Rs.                                                                                                                                                                                                                                                                                                                                                                                                                                                |         | 316537.00           | 316537.00                                                           |          |
|      |                                                                       |                                                                       |           | Less Amount Paid vide Last Bill<br>Rs.                                                                                                                                                                                                                                                                                                                                                                                                                            |         | 0.00                | 0.00                                                                |          |
|      |                                                                       |                                                                       |           | <b>Net Payable Amount Rs.</b>                                                                                                                                                                                                                                                                                                                                                                                                                                     |         | <b>311231.00</b>    | <b>311231.00</b>                                                    |          |