

SCHEDULE OF REINFORCEMENT (PER SPAN)
DRG. NO.SD/114

SL.No.	LOCATION	BAR MKD	SHAPE	DIA (m m)	SPACING (m m)	LENGTH (m m)	NOS	TOTAL LENGTH(m)	WEIGHT (Kg.)
1	SLAB BOTTOM ALONG- X	a1		25	125	11150	67	747.05	2914
2	SLAB BOTTOM ALONG- Y	a2		12	115	8830	94	830.02	748
3	SLAB SIDE ALONG-Y	a3		10		11900	2	23.80	17
4	SLAB TOP ALONG- X	a4		10	125	11240	64	719.36	504
5	SLAB TOP ALONG- Y	a5		10	125	9000	84	756.00	530
10	KERB- BOTOM	b1		12	-	11500	8	92.00	83
11	KERB- TOP	b2		12	-	11530	8	92.24	84
11	KERB- SIDES	b3		10	-	10840	8	86.72	61
12	KERB- STIRRUPS	b4		10	200	2870	76	218.12	153
13	Wearing Course X			12	150	7900	80	632.00	569
14	Wearing Course y			12	150	10000	67	670.00	603
									6266
			qty for 3 slabs			3	x	6266.00	18798
	OVERLAPS								
	SLAB BOTTOM ALONG- X	a1	SLAB 1,2 AND 3 (28+26+30)	25		2050	84	172.20	672
	SLAB BOTTOM ALONG- Y	a2	SLAB 1,2 AND 3 (31+33+27)	12		9600	91	873.60	787
							TOTAL		20257