
CRISP

Creative Rust Implemented Scripting Paradigm

A Modern Scripting Language

Peter Leukanič

Author

July 2026

Version 0.1.3

"Keep your code CRISP and clean."

Contents

Contents	1
1 Introduction	3
2 Getting Started	3
2.1 Installation and Running	3
2.2 Running CRISP Scripts	4
2.3 REPL Features	4
3 Variables and Types	4
3.1 Value Types	4
3.2 Variable Declaration and Assignment	5
3.3 Sigils	5
3.4 Type Introspection and Conversion	6
4 References and Pointer Semantics	7
4.1 Creating and Dereferencing	7
4.2 The Reference Sigil (&)	7
4.3 References to Collections	8
4.4 References as Function Arguments	8
4.5 Reference Semantics: Shallow vs. Deep	9
4.6 Chaining References	9
4.7 Use Cases	10
4.8 Internal Mechanism	10
4.9 Limitations and Caveats	11
4.10 Comparison with Other Languages	11
5 Binary Expressions and Operators	12
5.1 Operator Precedence Table	12
5.2 Arithmetic Operators	12
5.3 String Concatenation	13
5.4 Comparison Operators	13
5.5 Spaceship Operator	14
5.6 Logical Operators	14
5.7 Range Operator	15
5.8 Regex Operators	16
5.9 Assignment Operator	17
5.10 Ternary Operator	17
6 Control Flow	18
6.1 Conditional Statements	18
6.2 While Loops	19
6.3 For Loops	19
6.4 Break and Continue	20
6.5 Control Flow and Try/Finally	20
6.6 Return Statement	21
7 Functions and Closures	22
7.1 Named Functions	22
7.2 Function Parameters	22
7.3 Recursion	23

7.4	Lambda Functions	24
7.5	Closures	24
7.6	Functions as Values	25
7.7	Error Handling in Functions	26
7.8	Method Calls on Values	26
8	Error Handling	28
8.1	Try/Catch/Finally	28
8.2	Throw and Die	30
8.3	Control Flow Through Try/Catch	30
8.4	Assert	31
8.5	Exit	32
9	Pattern Matching	33
9.1	Basic Matching	33
9.2	Pattern Types	33
9.3	Where Guards	35
9.4	Multi-Statement Arm Bodies	36
9.5	Break and Continue in Match Arms	36
10	Regular Expressions	37
10.1	Match Operator	37
10.2	Global Match	38
10.3	Substitution	38
10.4	Regex in Expressions	38
11	Modules	39
12	System Programming with POSIX	40
12.1	Loading the POSIX Module	40
12.2	Process Management	40
12.3	File Operations (POSIX)	41
12.4	Signals	41
12.5	Users and Environment	42
12.6	POSIX Function Reference	43
13	Console Input and Output	44
13.1	Output Functions	44
13.2	Input Functions	44
13.3	Flush Semantics	45
13.4	Type Conversion Functions	46
14	Multi-Dimensional Arrays	46
14.1	Nested Array Literals	46
14.2	Chained Indexing	47
14.3	Nested Iteration	47
14.4	Operations on Nested Arrays	47
15	JSON Serialization (Planned)	48
16	Network Programming (Planned)	49
17	Performance	49

18 Comparison with Other Languages	49
19 Future Directions	50
20 Conclusion	50
21 Standard Library Reference	51
21.1 Console I/O	51
21.2 Error Handling	51
21.3 Process Control	51
21.4 Type Conversion and Introspection	51
21.5 Array Operations	51
21.6 Math and Random	52
21.7 File I/O (High-Level)	52
21.8 Method Dispatch (Value Methods)	52
21.9 POSIX Module (Opt-in via <code>use posix;</code>)	52
22 Keyword Reference	53
22.1 Control Flow Keywords	55
22.2 Built-in Functions (Not Keywords)	55

Abstract

CRISP (Creative Rust Implemented Scripting Paradigm) is a modern scripting language that combines the expressiveness of Perl 5 with the safety and performance of Rust. This paper presents the formal design, implementation, and evaluation of CRISP. Unlike traditional scripting languages, CRISP offers native regular expressions, lambda functions with return support, automatic hash key conversion, field access via dot notation, and full POSIX system call integrationall while maintaining memory safety guarantees inherited from its Rust implementation. We discuss the language architecture, standard library, and performance characteristics, and provide empirical evidence of its viability as a replacement for Perl, Python, and Bash in system scripting contexts.

Core Principles

- (1) **Perl Expressiveness:** Regular expressions, built-in functional tools, and concise syntax for text processing.
- (2) **Rust Safety:** Memory safety, zero-cost abstractions, and fearless concurrency inherited from Rust.
- (3) **Scripting Agility:** One-liners, REPL, quick prototyping, and interactive development.
- (4) **System Access:** Full POSIX system calls, file operations, and process management.

1 Introduction

The landscape of scripting languages is dominated by a trade-off between expressiveness and safety. Languages like Perl offer powerful text processing and concise syntax but lack memory safety guarantees. Languages like Python provide safety through garbage collection but incur performance overhead. Rust offers safety and performance but has a steep learning curve and is not designed for scripting.

CRISP (Creative Rust Implemented Scripting Paradigm) addresses this gap. It provides:

- **Perl-inspired syntax:** Regular expressions (`= s///`), sigils (`$`, `@`, `%`), and built-in functional tools (`map`, `filter`, `grep`)
- **Rust-powered safety:** Memory safety, no segmentation faults, use-after-free protection
- **Scripting agility:** REPL, one-liners, quick prototyping, file execution
- **System access:** Full POSIX system calls via opt-in `use posix;` module
- **Modern error handling:** `try/catch/finally` with `throw/die` keywords
- **Pattern matching:** Rust-style `match` with `where` guards

Definition: CRISP

CRISP is a tree-walking interpreted scripting language implemented in Rust, characterized by:

- Perl-inspired syntax with optional sigils (`$scalar`, `@array`, `%hash`, `&ref`)
- Native regular expressions with `match` (`=`) and substitution (`s///`)
- Lambda functions with explicit `return` and expression bodies
- Automatic hash key conversion and dot-notation field access
- Full POSIX system call integration (opt-in, namespaced)
- Console I/O with type-safe input functions and proper flush semantics
- Loop control flow with `break` and `continue`
- Variable assignment without redeclaration (`x = x + 1`)

2 Getting Started

2.1 Installation and Running

CRISP is a single binary. Build from source:

```
git clone https://github.com/user/crisp.git
cd crisp
cargo build --release
./target/release/crisp
```

2.2 Running CRISP Scripts

CRISP supports four modes of operation:

Table 1: CRISP Execution Modes

Mode	Command	Description
REPL	<code>crisp</code>	Interactive shell
Script file	<code>crisp script.csp</code>	Execute a <code>.csp</code> file
One-liner	<code>crisp -e "say 42"</code>	Inline code execution
AST dump	<code>crisp -ast script.csp</code>	Print parsed AST (debugging)

Additional CLI flags:

- `-debug` Run with verbose debug output
- `-repl` Force REPL mode
- `-version` Print version information

2.3 REPL Features

The interactive REPL supports:

- **Multiline input** Blocks and expressions span multiple lines
- **Debug toggle** `debug verbose` / `debug off` within the REPL
- **Exit** Type `exit` to quit
- **Help** Type `help` for available commands

REPL Session

```
$ crisp
> CRISP v0.1.0 - 2026
Creative Rust Implemented Scripting Paradigm
Perl-inspired . Rust-powered

Type 'exit' to quit, 'help' for commands

>>> let name = "CRISP";
>>> say "Hello, ", name, "!";
Hello, CRISP!
>>> exit
```

3 Variables and Types

3.1 Value Types

CRISP supports dynamic typing with the following value types:

Table 2: CRISP Value Types

Type	Rust Type	Example	Description
Null	<code>Value::Null</code>	<code>null</code>	Absence of value
Bool	<code>Value::Bool</code>	<code>true, false</code>	Boolean values
Int	<code>Value::Int(i64)</code>	<code>42, -7</code>	64-bit signed integer
Float	<code>Value::Float(f64)</code>	<code>3.14, -0.5</code>	64-bit floating point
Str	<code>Value::Str(Rc<String>)</code>	<code>"hello"</code>	UTF-8 string, reference-counted
Array	<code>Value::Array(Rc<RefCell<Vec>>)</code>	<code>[1, 2, 3]</code>	Dynamic, mutable array
Hash	<code>Value::Hash(Rc<RefCell<HashMap>>)</code>	<code>{name => "John"}</code>	String-keyed dictionary
Ref	<code>Value::Ref(Rc<RefCell<Value>>)</code>	<code>\expr</code>	Shared mutable reference
Function	<code>Value::NativeFn</code> or <code>Value::UserFn</code>	<code>fn(x) { ... }</code>	Callable functions

3.2 Variable Declaration and Assignment

Variables are declared with `let` and can be reassigned with `=`:

Variable Declaration and Assignment

```
# Declaration
let name = "CRISP";
let count = 0;
let @numbers = [1, 2, 3];

# Assignment (reassign existing variable)
count = count + 1;
name = "New Name";

# Assignment to undeclared variable is an error
x = 5; # Error: Undefined variable: x

# Constants
const PI = 3.14159;
# PI = 3.0; # Would be an error (immutable)
```

3.3 Sigils

CRISP supports Perl-inspired optional sigils for type annotation:

Table 3: CRISP Sigils

Sigil	Name	Example	Description
<code>\$</code>	Scalar	<code>\$name, \$count</code>	Single value (string, number, bool)
<code>@</code>	Array	<code>@items, @numbers</code>	Ordered list
<code>%</code>	Hash	<code>%config, %person</code>	Key-value dictionary
<code>&</code>	Reference	<code>&callback, &fn_ref</code>	Reference to a value

Sigils are optional CRISP infers the type from the value:

Sigil Usage

```
# With sigils (Perl style)
let $name = "CRISP";
let @fruits = ["apple", "banana"];
let %person = { name => "John", age => 30 };
let &callback = |x| => x * 2;

# Without sigils (modern style)
let name = "CRISP";
let fruits = ["apple", "banana"];
let person = { name => "John", age => 30 };
let callback = |x| => x * 2;
```

3.4 Type Introspection and Conversion

Type Functions

```
# Get the type of a value
say type(42);           # "int"
say type("hello");      # "string"
say type([1, 2, 3]);    # "array"
say type({ a => 1 });    # "hash"
say type(null);         # "null"
say type(true);         # "bool"

# Parse string to number
let n = int("42");       # Int(42)
let f = float("3.14");   # Float(3.14)

# Invalid parsing returns null
let bad = int("hello");  # null
if bad == null {
  say "Not a number!";
}

# Length of collections
let len = len("CRISP");  # 5
let len2 = len([1, 2, 3]); # 3
let len3 = len({ a => 1, b => 2 }); # 2
```

4 References and Pointer Semantics

CRISP provides shared mutable references through a pointer-like abstraction. Unlike C pointers (raw memory addresses) or C++ references (non-nullable aliases), CRISP references use reference-counted interior mutability *safe*, shared ownership of a mutable value.

4.1 Creating and Dereferencing

A reference is created with the `\` operator and dereferenced with `^`:

Creating and Dereferencing

```
# Create a reference to a value
let x = 42;
let r = \x;

# Dereference to read
say ^r;      # 42

# Dereference to write (modify through reference)
^r = 100;
say x;       # 100  the original was mutated!

# Multiple references to the same value
let a = 10;
let ref1 = \a;
let ref2 = \a;

^ref1 = 20;
say ^ref2;   # 20  both references point to the same cell
say a;       # 20
```

4.2 The Reference Sigil (&)

Variables holding references can be declared with the `&` sigil for clarity:

Reference Sigil

```
# With sigil (explicit "this is a reference")
let &counter = \0;
^counter = ^counter + 1;
say ^counter;   # 1

# Without sigil (implicit works the same)
let counter = \0;
^counter = ^counter + 1;
say ^counter;   # 1

# The sigil is a naming convention, not a type constraint
let &r = \0;
r = \100;       # reassign to reference a different value
say ^r;         # 100
```

4.3 References to Collections

References to arrays and hashes enable shared mutable access to data structures without copying:

References to Collections

```
# Reference to an array
let @data = [1, 2, 3];
let &r = \@data;

push(^r, 4);
push(^r, 5);

say @data;      # [1, 2, 3, 4, 5]
say ^r;         # [1, 2, 3, 4, 5]

# Reference to a hash
let %config = { debug => false };
let &cfgref = \%config;

# Modify through reference
let h = ^cfgref;
h["debug"] = true;

say %config["debug"]; # true
```

4.4 References as Function Arguments

Passing a reference to a function enables the function to mutate the caller's data a form of pass-by-reference:

References as Arguments

```
# Function that mutates through a reference
fn increment(&ref) {
    ^ref = ^ref + 1;
}

let x = 0;
increment(\x);
increment(\x);
increment(\x);
say x; # 3

# Swap two values through references
fn swap(&a, &b) {
    let temp = ^a;
    ^a = ^b;
    ^b = temp;
}

let first = "hello";
let second = "world";
swap(\first, \second);
say first; # world
say second; # hello
```

4.5 Reference Semantics: Shallow vs. Deep

A reference points to the *same* value, not a copy. This means changes through any reference are visible through all others:

Reference Semantics

```
# No reference independent copies
let a = [1, 2, 3];
let b = a; # shallow copy of the array handle
push(b, 4);
say a; # [1, 2, 3] unaffected
say b; # [1, 2, 3, 4]

# With reference shared ownership
let c = [1, 2, 3];
let &rc = \c;
let &rc2 = \c; # second reference to same array
push(^rc, 4);
say ^rc2; # [1, 2, 3, 4] visible through rc2
say c; # [1, 2, 3, 4] original is mutated
```

4.6 Chaining References

References can be nested a reference to a reference:

Chained References

```
let x = 42;
let r1 = \x;      # r1  x
let r2 = \r1;     # r2  r1  x

# Double dereference
say ^^r2;         # 42

# Modify through chain
^^r2 = 99;
say x;            # 99
```

4.7 Use Cases

Table 4: Reference Use Cases

Use Case	Example	Why References
Out-parameters	<code>fn read_config(&out)</code>	Function mutates caller's variable
Shared state	<code>let &state = \@log;</code>	Multiple closures access same data
Avoid copies	<code>let &big = \@large_array;</code>	Pass without cloning large structures
Event handlers	<code>counter.increment(&state)</code>	Multiple handlers mutate shared state
Circular references	<code>let %node = { next => \other }</code>	Build linked structures

4.8 Internal Mechanism

CRISP references are implemented as `Value::Ref(Rc<RefCell<Value>)`:

Table 5: Reference Internals

Component	Rust Type	Role
Rc	<code>std::rc::Rc</code>	Reference counting tracks how many references exist
RefCell	<code>std::cell::RefCell</code>	Interior mutability allows mutation through shared reference
Value	Value	The pointed-to value (can be any CRISP type)

Design Note: Why `Rc<RefCell<Value>`?

The combination of `Rc` and `RefCell` provides two guarantees:

- **Shared ownership (`Rc`):** Multiple references can coexist. The value is deallocated only when the last reference is dropped. No dangling pointers.
- **Interior mutability (`RefCell`):** Mutation through a shared reference is safe because `RefCell` enforces Rust’s borrow rules at runtime (not compile time). Attempting to mutate while another reference is borrowed causes a runtime panic rather than undefined behavior.

This is the same pattern used by Rust’s own `Rc<RefCell<T>` for shared mutable state in single-threaded contexts. CRISP is currently single-threaded, so `Rc` (not `Arc`) is sufficient.

4.9 Limitations and Caveats

- **No automatic dereferencing:** Unlike C++ references or Rust’s `Deref`, CRISP requires explicit `^` to dereference. Writing `r = 5` when `r` is a reference reassigns the reference, not the pointed-to value.
- **Single-threaded only:** `Rc` is not `Send` or `Sync`. CRISP does not currently support multi-threading, so this is not a limitation in practice. Future multi-threaded versions would use `Arc`.
- **No weak references:** All references are strong (`Rc`, not `Weak`). This means circular references will leak memory — they prevent deallocation.
- **Runtime borrow checking:** `RefCell` panics at runtime if you violate borrow rules (e.g., mutating while iterating). This is safer than C’s undefined behavior but less safe than Rust’s compile-time borrow checking.

4.10 Comparison with Other Languages

Table 6: Reference/Pointer Models Across Languages

Language	Create	Access	Safety	Notes
CRISP	<code>\x</code>	<code>^r</code>	Runtime (<code>RefCell</code>)	Shared ownership, interior mutability
C	<code>&x</code>	<code>*p</code>	None	Raw pointer, UB on misuse
C++	<code>&x</code>	Implicit	None	Non-nullable alias
Rust	<code>&x</code> / <code>&mut x</code>	Implicit	Compile-time	Borrow checker
Perl	<code>\\$x</code>	<code>\$\$r</code> / <code>\$r-></code>	Runtime (refcount)	Garbage collected
Python	Implicit	Implicit	Runtime (GC)	Everything is a reference

CRISP’s model sits between Perl (explicit `\`/`$` deref, reference-counted) and Rust (safe interior mutability pattern), with the explicitness of C pointers but the safety of runtime borrow checking.

5 Binary Expressions and Operators

CRISP provides a rich set of binary operators organized by precedence. The parser uses a Pratt parsing algorithm with defined binding powers for each operator, eliminating ambiguity in complex expressions.

5.1 Operator Precedence Table

Operators are evaluated from highest to lowest binding power. Higher in the table = tighter binding:

Table 7: Operator Precedence Highest to Lowest

Precedence	Operators	Associativity	Description
1 (highest)	**	Right	Exponentiation
2	* / %	Left	Multiplication, division, modulo
3	+ -	Left	Addition, subtraction, string concatenation
4	..	Non-associative	Range construction
5	< > <= >= <=>	Non-associative	Comparison, spaceship
6	== != = !	Non-associative	Equality, regex match
7	&&	Left	Logical AND
8		Left	Logical OR
9 (lowest)	=	Right	Assignment

5.2 Arithmetic Operators

Arithmetic Operators

```
# Basic arithmetic
let sum = 10 + 5;      # 15
let diff = 10 - 5;     # 5
let prod = 10 * 5;     # 50
let quot = 10 / 5;     # 2
let mod = 10 % 3;      # 1

# Exponentiation (right-associative)
let pow = 2 ** 3;      # 8
let chain = 2 ** 3 ** 2; # 512 (2 ** (3 ** 2) = 2 ** 9)

# Mixed types: Int + Float  Float
let mixed = 10 + 3.5;   # 13.5 (Float)

# Division always produces Float
let half = 10 / 4;      # 2.5 (Float, not truncated)

# Negative numbers
let neg = -5 + 3;       # -2
```

5.3 String Concatenation

The `+` operator concatenates strings. At least one operand must be a string; the other is converted via `.as_str()`:

String Concatenation

```
# String + String
let greeting = "Hello, " + "World!";
say greeting; # Hello, World!

# String + Number
let msg = "Value: " + 42;
say msg; # Value: 42

# String + Bool
say "Flag: " + true; # Flag: true

# Number + String works too
say 100 + " points"; # 100 points

# Chaining
let full = "CRISP" + " v" + 0 + "." + 1 + "." + 0;
say full; # CRISP v0.1.0
```

5.4 Comparison Operators

Comparison operators return `true` or `false`. They are non-associative chaining them without parentheses is an error:

Comparison Operators

```
# Numeric comparisons
say 10 > 5;           # true
say 10 < 5;           # false
say 10 >= 10;         # true
say 10 <= 5;          # false

# Equality (works across types)
say 10 == 10;         # true
say 10 == 5;          # false
say 10 != 5;          # true
say "hi" == "hi";     # true

# Floats compare as f64
say 3.14 == 3.14;     # true

# Non-associative use && for chaining
# say 1 < x < 10;      # Error!
say 1 < x && x < 10;   # Correct

# Null equality
let x = null;
say x == null;         # true
say null != 42;        # true
```

5.5 Spaceship Operator

The `<=>` (spaceship) operator returns `-1`, `0`, or `1` for less-than, equal, or greater-than:

Spaceship Operator

```
# Numeric comparison
say 3 <=> 5;          # -1 (less)
say 5 <=> 5;          # 0  (equal)
say 7 <=> 5;          # 1  (greater)

# String comparison (lexicographic)
say "apple" <=> "banana"; # -1
say "crisp" <=> "crisp";  # 0
say "zebra" <=> "apple";  # 1

# Useful for sorting callbacks
let sorted = sort(arr, |a, b| => a <=> b);
```

5.6 Logical Operators

`&&` (AND) short-circuits if the left operand is falsy, the right is never evaluated. `||` (OR) short-circuits if the left operand is truthy, the right is never evaluated:

Logical Operators

```
# AND (&&) both must be true
if x > 0 && x < 100 {
    say "x is in range";
}

# OR (||) at least one must be true
if name == "admin" || name == "root" {
    say "privileged user";
}

# Short-circuit: expensive() is never called
let x = 0;
if x != 0 && expensive() {
    say "won't happen";
}

# Short-circuit: fallback() is never called
let y = 42;
if y > 0 || fallback() {
    say "short-circuited";
}

# Combined complex conditions
if (age >= 18 && age <= 65) || has_permission {
    say "access granted";
}

# Truthiness: false, null, 0, "" are falsy
if 0 || null || false || "" {
    say "never runs";
} else {
    say "all falsy"; # this runs
}
```

5.7 Range Operator

The `..` operator creates a range. Ranges are used primarily in for loops and array slicing:

Range Operator

```
# Numeric range (inclusive start, exclusive end)
for i in 0..5 {
    say i;
}
# Output: 0 1 2 3 4

# Range stored in variable
let r = 1..10;

# Array slicing with range
let @arr = [10, 20, 30, 40, 50];
say @arr[1..3]; # [20, 30]

# String slicing
say "CRISP"[0..3]; # "CRI"
```

5.8 Regex Operators

CRISP provides `=` (match) and `!` (negated match) for regular expression testing:

Regex Operators

```
let text = "The quick brown fox";

# =~ returns boolean in scalar context
if text =~ /fox/ {
    say "Found fox!";
}

# !~ negated match
if text !~ /dragon/ {
    say "No dragons here";
}

# With g flag, =~ returns array of matches
let words = text =~ /\w+/g;
say words; # ["The", "quick", "brown", "fox"]

# Case-insensitive
if text =~ /FOX/i {
    say "case-insensitive match";
}

# Combine with logical operators
if text =~ /quick/ && text =~ /fox/ {
    say "Contains both quick and fox";
}
```

5.9 Assignment Operator

The `=` operator reassigns an existing variable. It is right-associative, enabling chained assignment:

Assignment Operator

```
# Reassignment (variable must already exist)
let x = 10;
x = 20;      # valid  x exists
x = x + 1;   # valid  self-referencing

# Right-associative chained assignment
let a = 0;
let b = 0;
a = b = 42;
say a; # 42
say b; # 42

# Assignment in expression context
let y = (x = 5) + 10;
say x; # 5
say y; # 15

# Error: assigning to undeclared variable
# z = 5; # Error: Undefined variable: z
```

5.10 Ternary Operator

The ternary `? :` operator provides inline conditional evaluation. It is right-associative and has the lowest precedence above assignment:

Ternary Operator

```
# Basic ternary
let label = score > 50 ? "pass" : "fail";

# Ternary with expressions
let max = a > b ? a : b;

# Nested ternary (right-associative)
let grade = score >= 90 ? "A"
              : score >= 80 ? "B"
              : score >= 70 ? "C"
              : "F";

# Ternary in expressions
say "You " + (age >= 18 ? "may" : "may not") + " enter.";
```

Design Note: Pratt Parsing

CRISP uses a Pratt (top-down operator precedence) parser for binary expressions. Each operator is assigned a left and right binding power:

- **Left binding power:** Determines whether this operator "grabs" the expression on its left from the previous operator. If the previous operator's right power is lower than this operator's left power, this operator wins.
- **Right binding power:** Determines whether this operator "allows" the next operator to grab its right operand. Higher right power = tighter binding on the right.
- **Associativity:** Implemented by making left binding power lower than right (left-associative, e.g., $a - b - c = (a - b) - c$) or equal (right-associative, e.g., $a = b = c = a = (b = c)$).

This approach eliminates the need for explicit precedence tables in the grammar. Precedence is encoded directly in the numeric binding powers.

6 Control Flow

6.1 Conditional Statements

CRISP supports `if`, `else if`, and `else` with block bodies:

Conditional Statements

```
# Basic if/else
let x = 42;
if x > 100 {
  say "Large";
} else {
  say "Small";
}

# if/else if/else chain
let score = 85;
if score >= 90 {
  say "A";
} else if score >= 80 {
  say "B";
} else if score >= 70 {
  say "C";
} else {
  say "F";
}

# Single-expression conditions
let name = "CRISP";
if name == "CRISP" {
  say "It's CRISP!";
}
```

6.2 While Loops

The `while` loop evaluates a condition before each iteration:

While Loops

```
# Basic while loop
let i = 0;
while i < 5 {
  say i;
  i = i + 1;
}
# Output: 0 1 2 3 4

# Infinite loop with break
let count = 0;
while true {
  say count;
  count = count + 1;
  if count >= 5 { break; }
}
# Output: 0 1 2 3 4
```

6.3 For Loops

The `for` loop iterates over arrays, hashes, strings, and ranges:

For Loops

```
# For loop over array
let @fruits = ["apple", "banana", "cherry"];
for fruit in @fruits {
  say fruit;
}
# Output: apple banana cherry

# For loop over range
for i in 0..5 {
  say i;
}
# Output: 0 1 2 3 4

# For loop over hash (iterates values)
let %ages = { alice => 25, bob => 30 };
for age in %ages {
  say age;
}
# Output: 25 30

# For loop over string (iterates characters)
for ch in "CRISP" {
  say ch;
}
# Output: C R I S P
```

6.4 Break and Continue

`break` exits the loop immediately. `continue` skips to the next iteration:

Break and Continue

```
# Break    exit loop early
let i = 0;
while true {
  say i;
  i = i + 1;
  if i >= 5 { break; }
}
# Output: 0 1 2 3 4

# Continue skip to next iteration
for i in 0..10 {
  if i % 2 == 0 { continue; } # skip evens
  say i;
}
# Output: 1 3 5 7 9

# Both together
for i in 0..10 {
  if i == 2 { continue; }
  if i == 7 { break; }
  say i;
}
# Output: 0 1 3 4 5 6
```

6.5 Control Flow and Try/Finally

`break` and `continue` propagate correctly through `try/finally` the `finally` block always executes before the signal propagates:

Break with Finally

```
while true {
  try {
    say "inside try";
    break;
  } finally {
    say "finally runs!";
  }
}
# Output:
# inside try
# finally runs!

# continue also respects finally
for i in 0..3 {
  try {
    if i == 1 { continue; }
    say "processing ", i;
  } finally {
    say "cleanup for ", i;
  }
}
# Output:
# processing 0 / cleanup for 0
# cleanup for 1
# processing 2 / cleanup for 2
```

6.6 Return Statement

`return` exits a function with an optional value. It uses a sentinel error internally to unwind the call stack:

Return Statement

```
# Return with value
fn add(a, b) {
  return a + b;
}

# Early return from condition
fn abs(x) {
  if x >= 0 { return x; }
  return -x;
}

# Return without value (returns null)
fn do_nothing() {
  return;
}
```


Design Note: Control Flow Signals

`return`, `break`, and `continue` are implemented as sentinel errors (`RuntimeError::ReturnSignal`, `BreakSignal`, `ContinueSignal`) that unwind through the call stack. This ensures they propagate correctly through nested structures like `if`, `match`, `try/catch`, and `for` loops. Using `break` or `continue` outside a loop produces a runtime error.

7 Functions and Closures

7.1 Named Functions

CRISP supports named function definition with the `fn` keyword. Functions are first-class values stored in the environment, enabling recursion and self-reference:

Named Functions

```
# Basic function definition
fn greet(name) {
  say "Hello, ", name, "!";
}

greet("CRISP"); # Hello, CRISP!

# Function with return value
fn add(a, b) {
  return a + b;
}

let result = add(3, 7);
say result; # 10

# Early return
fn abs(x) {
  if x >= 0 {
    return x;
  }
  return -x;
}

say abs(-42); # 42
say abs(42); # 42
```

7.2 Function Parameters

Functions accept positional parameters. Each parameter is bound to the corresponding argument at call time:

Function Parameters

```
# Multiple parameters
fn distance(x1, y1, x2, y2) {
  let dx = x2 - x1;
  let dy = y2 - y1;
  return sqrt(dx * dx + dy * dy);
}

# Parameters with sigils (type annotation)
fn process(@arr, %opts) {
  say "Array: ", @arr;
  say "Options: ", %opts;
}

process([1, 2, 3], { debug => true });
```

7.3 Recursion

Functions are recursive with a maximum depth of 1000 calls. The function name is available inside its own body via self-reference:

Recursion

```
# Factorial classic recursion
fn factorial(n) {
  if n <= 1 {
    return 1;
  }
  return n * factorial(n - 1);
}

say factorial(5);    # 120
say factorial(10);   # 3628800

# Fibonacci
fn fib(n) {
  if n <= 1 { return n; }
  return fib(n - 1) + fib(n - 2);
}

say fib(10);    # 55

# Mutual recursion
fn is_even(n) {
  if n == 0 { return true; }
  return is_odd(n - 1);
}

fn is_odd(n) {
  if n == 0 { return false; }
  return is_even(n - 1);
}
```

7.4 Lambda Functions

Lambdas are anonymous functions defined with pipe syntax. They come in two forms: expression-body (implicit return) and block-body (explicit return):

Lambda Functions

```
# Expression-body lambda (implicit return)
let double = |x| => x * 2;
say double(10); # 20

# Block-body lambda (explicit return)
let square = |x| => {
  let result = x * x;
  return result;
};
say square(5); # 25

# Multiple parameters
let add = |a, b| => a + b;
say add(3, 7); # 10

# Lambda as argument
let numbers = [1, 2, 3, 4, 5];
let squared = map(numbers, |n| => n * n);
say squared; # [1, 4, 9, 16, 25]

# Lambda capturing outer variables
let factor = 10;
let scale = |x| => x * factor;
say scale(5); # 50
```

7.5 Closures

Functions capture their lexical environment at definition time. Each function call creates a fresh environment that chains to the captured parent:

Closures

```
# Counter factory returns a closure
fn make_counter(start) {
  return || => {
    let current = start;
    start = start + 1;
    return current;
  };
}

let counter1 = make_counter(0);
let counter2 = make_counter(100);

say counter1(); # 0
say counter1(); # 1
say counter1(); # 2
say counter2(); # 100
say counter2(); # 101

# Each closure has its own captured environment
```

7.6 Functions as Values

Functions are first-class values: they can be stored in variables, passed as arguments, and returned from other functions:

First-Class Functions

```
# Assign function to variable
let greet = fn(name) {
  return "Hello, " + name + "!";
};
say greet("CRISP"); # Hello, CRISP!

# Pass function as argument
fn apply_twice(f, x) {
  return f(f(x));
}

let inc = |x| => x + 1;
say apply_twice(inc, 5); # 7 (inc(inc(5)) = inc(6) = 7)

# Return function from function
fn multiplier(factor) {
  return |x| => x * factor;
}

let triple = multiplier(3);
say triple(10); # 30
```

7.7 Error Handling in Functions

Functions integrate with CRISP's error handling system. Unhandled `break` or `continue` inside a function body produce a runtime error:

Function Error Handling

```
# Errors propagate through function calls
fn div(a, b) {
  if b == 0 {
    die("Division by zero");
  }
  return a / b;
}

try {
  say div(10, 0);
} catch e {
  say "Caught: ", e;
}
# Output: Caught: Division by zero

# break and continue are errors outside loops
fn broken() {
  break; # RuntimeError: break outside loop
}

# try/catch inside functions
fn safe_read(path) {
  try {
    return read_file(path);
  } catch {
    return null;
  }
}

let data = safe_read("missing.txt");
if data == null {
  say "File not found, using default";
}
```

7.8 Method Calls on Values

Values with hash type support method dispatch via the dot syntax. When a method is called, the value becomes the first argument:

Method Calls

```
# Array methods
let @arr = [1, 2, 3];
@arr.push(4);           # [1, 2, 3, 4]
say @arr.pop();         # 4
say @arr.len();         # 3
say @arr.contains(2);   # true

# String methods
say "hello world".len(); # 11
say "a,b,c".split(",");  # ["a", "b", "c"]
say "hello".contains("ell"); # true

# Hash methods
let %h = { a => 1, b => 2, c => 3 };
say %h.keys();          # ["a", "b", "c"]
say %h.values();        # [1, 2, 3]

# Chaining methods
let result = [3, 1, 2]
    .push(4)
    .filter(|x| => x % 2 == 0);
say result;             # [2, 4]
```

Design Note: Function Environment

Each function (named or lambda) captures a reference-counted pointer (`Rc<RefCell<Environment>`) to its definition environment. At call time, a new child environment is created chained to this captured parent. This provides two guarantees:

- **Lexical scoping:** Functions see the variables that existed when they were defined
- **Isolation:** Each call gets a fresh local scope that doesn't leak between invocations

The self-reference mechanism (the function's own name bound inside its body) enables recursion without requiring global name resolution at each recursive call.

8 Error Handling

CRISP provides a modern error handling system with `try/catch/finally` blocks, catchable `throw` and `die` keywords, and proper propagation of control-flow signals through error boundaries.

8.1 Try/Catch/Finally

The `try` block executes code that may produce errors. If an error occurs, the optional `catch` block receives it. The `finally` block always executes regardless of errors:

Basic Try/Catch

```
# Basic try/catch
try {
  let x = 1 / 0;
} catch e {
  say "Error: ", e;
}
# Output: Error: Division by zero

# Catch with alias syntax (catch e as err)
try {
  die("something went wrong");
} catch e as err {
  say "Caught: ", err;
}
# Output: Caught: something went wrong
```

Try/Catch/Finally

```
# Finally always executes
try {
  say "trying...";
  die("oops");
} catch e {
  say "error: ", e;
} finally {
  say "cleanup always runs";
}

# Output:
# trying...
# error: oops
# cleanup always runs

# Finally runs even without catch
try {
  say "work";
} finally {
  say "done";
}

# Output: work / done

# Nested error handling
try {
  try {
    throw "inner error";
  } catch e {
    say "inner: ", e;
  }
} catch e {
  say "outer: ", e;
}

# Output: inner: inner error
```


8.2 Throw and Die

Both `throw` and `die` produce catchable `UserError` values. They are interchangeable:

Throw and Die

```
# throw   catchable user error
try {
  throw "invalid configuration";
} catch e {
  say "Problem: ", e;
}

# die     identical behavior, also catchable
try {
  die "fatal condition";
} catch e {
  say "Recovered from: ", e;
}

# Uncaught throw/die terminates the script
throw "unrecoverable";
# Error: unrecoverable
```

8.3 Control Flow Through Try/Catch

`return`, `break`, and `continue` propagate through `try/catch/finally` correctly the `finally` block always executes before the signal continues:

Control Flow with Finally

```
# break respects finally
while true {
  try {
    say "inside";
    break;
  } finally {
    say "cleanup!";
  }
}
# Output: inside / cleanup!

# continue respects finally
for i in 0..3 {
  try {
    if i == 1 { continue; }
    say "processing ", i;
  } finally {
    say "iter ", i;
  }
}
# Output: processing 0 / iter 0 / iter 1 / processing 2 / iter 2

# return from function through finally
fn demo() {
  try {
    return "early";
  } finally {
    say "still runs!";
  }
}
say demo();
# Output: still runs! / early
```

8.4 Assert

The `assert` function verifies a condition and produces an error if it fails:

Assert

```
# Basic assertion
assert(2 + 2 == 4); # passes silently

# Assertion with custom message
let x = -1;
assert(x > 0, "x must be positive");
# Error: x must be positive
```

Design Note: Error Signals

CRISP implements four internal sentinel errors (`RuntimeError::ReturnSignal`, `BreakSignal`, `ContinueSignal`, `ExitSignal`) that unwind through the interpreter's call stack. These are not caught by `catch` blocks only real errors are. The `try/catch/finally` handler distinguishes between them:

- **Real errors:** Captured by `catch`, then `finally` executes
- **Control-flow signals:** Bypass `catch`, `finally` still executes, then the signal is re-emitted
- **ExitSignal:** Propagates through all boundaries including `try/catch` and loops. `finally` blocks execute, then the process terminates with the given exit code. Not catchable by `catch`.

This ensures `break` from inside a `try` block inside a loop works as expected the loop receives the `BreakSignal` after `finally` runs.

8.5 Exit

The `exit()` function terminates the process with an optional exit code. It produces a special `ExitSignal` that is **not catchable** by `try/catch` blocks. However, `finally` blocks still execute before the process terminates:

Exit

```
# Exit with default code 0
exit();

# Exit with specific code
exit(1);

# finally runs before exit
try {
  exit(2);
} finally {
  say "cleanup runs!";
}

# Output: cleanup runs!
# Process exits with code 2

# _exit() skips finally immediate hard exit
_exit(0); # no cleanup, process dies immediately
```

Design Note: ExitSignal vs. `_exit`

CRISP provides two exit mechanisms:

- `exit(code?)` Emits `ExitSignal`, which propagates through `finally` blocks before the process terminates. This ensures cleanup code runs. Not catchable by `catch` it always terminates.
- `_exit(code?)` Calls Rust's `std::process::exit` directly. No cleanup, no `finally`, immediate termination. Use when you need a hard stop.

The `ExitSignal` uses the same sentinel-error mechanism as `return/break/continue` to unwind the call stack, ensuring `finally` blocks execute before the interpreter propagates the signal to the top level and calls `std::process::exit`.

9 Pattern Matching

CRISP supports Rust-style pattern matching with the `match` expression. Patterns can be literal values, variable bindings, or wildcards, with optional `where` guards.

9.1 Basic Matching

Basic Match

```
# Simple value matching
let value = 42;
match value {
  0  => { say "zero"; }
  1  => { say "one"; }
  42 => { say "the answer"; }
  -  => { say "something else"; }
}
# Output: the answer

# Default case with wildcard
let x = 99;
match x {
  1  => { say "one"; }
  2  => { say "two"; }
  -  => { say "unknown: ", x; }
}
# Output: unknown: 99
```

9.2 Pattern Types

CRISP supports the following match patterns:

Table 8: Match Pattern Types

Pattern	Syntax	Example	Matches
Integer	42	42 => ...	Exact integer equality
String	"hello"	"hello" => ...	Exact string equality
Boolean	true, false	true => ...	Exact boolean match
Variable	name	n => ...	Any value, binds to name
Wildcard	_	_ => ...	Any value, no binding

Pattern Types

```
# Integer patterns
match 42 {
  0  => { say "zero"; }
  42 => { say "the answer"; }
  _  => { say "other"; }
}

# String patterns
match "hello" {
  "hello" => { say "greeting"; }
  "bye"   => { say "farewell"; }
  _       => { say "unknown"; }
}

# Boolean patterns
match true {
  true  => { say "yes"; }
  false => { say "no"; }
}

# Variable binding matches anything, binds to name
match readline("Enter: ") {
  n => { say "you entered: ", n; }
}
```

9.3 Where Guards

where guards add conditions to pattern arms. The guard expression is evaluated after the pattern matches, and the arm only fires if the guard is true:

Where Guards

```
# Type-based dispatch
let guess = read("Your guess: ");

match guess {
  n where type(n) == "int" => {
    say "Integer: ", n;
  }
  s where s == "" => {
    say "Empty input.";
  }
  _ => {
    say "Something else: ", guess;
  }
}

# Range-based guards
let score = 85;
match score {
  s where s >= 90 => { say "A"; }
  s where s >= 80 => { say "B"; }
  s where s >= 70 => { say "C"; }
  s where s >= 60 => { say "D"; }
  _ => { say "F"; }
}

# Output: B

# Complex guard expression
let x = 15;
match x {
  n where n > 0 && n % 2 == 0 => { say "positive even"; }
  n where n > 0 => { say "positive odd"; }
  n where n < 0 => { say "negative"; }
  _ => { say "zero"; }
}

# Output: positive odd
```

9.4 Multi-Statement Arm Bodies

Each arm body can contain multiple statements. The match expression returns the value of the last statement in the matched arm:

Multi-Statement Arms

```
match value {
  1 => {
    say "processing one...";
    say "done!";
  }
  2 => {
    let doubled = 2 * 2;
    say "doubled: ", doubled;
  }
  _ => {
    say "fallback";
  }
}
```

9.5 Break and Continue in Match Arms

`break` and `continue` propagate correctly from inside `match` arms when the `match` is inside a loop:

Match Inside Loops

```
# break from match inside while
let i = 0;
while true {
  i = i + 1;
  match i {
    n where n >= 5 => { break; }
    _ => { say i; }
  }
}
# Output: 1 2 3 4

# continue from match inside for
for i in 0..5 {
  match i {
    n where n % 2 == 0 => { continue; }
    _ => { say i; }
  }
}
# Output: 1 3
```

Design Note: Match Evaluation

Match arms are evaluated in order from top to bottom. The first arm whose pattern matches and whose guard (if present) evaluates to `true` wins. Only that arm's body executes. There is no fall-through between arms.

For variable-binding patterns with guards, the variable is bound in a temporary scope that includes the guard expression and the arm body. This ensures guard expressions can reference the bound variable without leaking into the outer scope.

10 Regular Expressions

CRISP includes native Perl-style regular expression support via the Rust `regex` crate. The `=` operator tests for a match, and the `s///` syntax performs substitution.

10.1 Match Operator

The `=` match operator returns a boolean in scalar context:

Regex Match

```
let text = "The quick brown fox jumps over the lazy dog";

# Basic match
let result = text =~ /fox/;
say result; # true

# Match in if condition
if text =~ /quick/ {
    say "Found quick!";
}

# Case-insensitive flag
if text =~ /FOX/i {
    say "Found fox!";
}

# Match against a variable pattern
let pattern = "brown";
if text =~ /pattern/ {
    say "Matched!";
}
```


10.2 Global Match

With the `g` flag, `=` returns an array of all matches:

Global Match

```
let text = "cat dog cat bird cat";

# Find all matches
let matches = text =~ /cat/g;
say matches; # ["cat", "cat", "cat"]

# Count occurrences
say len(matches); # 3
```

10.3 Substitution

The `s///` operator replaces matched text. Use `g` for global replacement:

Substitution

```
let text = "The quick brown fox";

# Single substitution (first occurrence)
let result = s/fox/cat/;
say result; # The quick brown cat

# Global substitution
let text2 = "one two one two";
let result2 = s/one/1/g;
say result2; # 1 two 1 two

# Using the Substitute expression directly
let modified = substitute(text, "brown", "red", false);
say modified; # The quick red fox
```

10.4 Regex in Expressions

The `Expr::Match` and `Expr::Substitute` AST nodes can be used as part of larger expressions:

Regex in Expressions

```
# Match as expression
let has_fox = text =~ /fox/;
if has_fox {
  say "Contains fox";
}

# Combine with logical operators
if text =~ /quick/ && text =~ /fox/ {
  say "Contains both quick and fox";
}
```

Design Note: Regex Implementation

Regular expressions in CRISP are powered by the Rust `regex` crate, which provides:

- **Compile-time optimization:** Patterns are compiled once and cached
- **Unicode support:** Full UTF-8 matching by default
- **Perl-compatible syntax:** Most common Perl regex features are supported
- **Safety:** No catastrophic backtracking the regex engine uses finite automata

The regex is not a first-class type patterns are passed as strings and compiled at the point of use. Capture groups (`$1`, `$2`) are not currently implemented but are planned for a future release.

11 Modules

CRISP supports modular code organization with the `use` keyword. Currently, `use posix;` is the only built-in module.

Modules

```
# Load the POSIX module
use posix;

# POSIX functions live under a namespaced hash
let pid = posix["fork"]();
let fd = posix["open"]("/tmp/test.txt", O_WRONLY | O_CREAT, 0
    o644);
posix["write"](fd, "Hello!\n", 7);
posix["close"](fd);

# posix is a regular Hash you can inspect it
for func in posix {
    say func; # lists all POSIX function names
}
```

Design Note: Module System

The module system is under active development. Currently, only `use posix;` is supported. Future releases will extend this to user-defined modules (`use mymodule;`), import paths, and selective imports. The namespaced hash pattern (each module creating its own hash) will be the standard approach for all modules.

12 System Programming with POSIX

CRISP provides full POSIX system call integration via an opt-in module. Unlike other scripting languages where system calls pollute the global namespace, CRISP loads POSIX on demand and namespaces all functions under a `posix` hash.

12.1 Loading the POSIX Module

Loading POSIX

```
# Load the POSIX module (opt-in, namespaced)
use posix;

# POSIX functions live under the posix hash
say posix["getpid"](); # prints current PID

# Console read() is NOT shadowed!
let input = readline("> ");
say input;
```

12.2 Process Management

Process Management

```
use posix;

# Fork a child process
let pid = posix["fork"]();
if pid == 0 {
  # Child process
  say "Child PID: ", posix["getpid"]();
  posix["execvp"]("ls", "-la");
} else {
  # Parent process
  say "Parent waiting for child: ", pid;
  let status = posix["waitpid"](pid, 0);
  say "Child exited with: ", status;
}

# Get process IDs
say "PID: ", posix["getpid"]();
say "PPID: ", posix["getppid"]();
```

12.3 File Operations (POSIX)

POSIX File Operations

```
use posix;

# Low-level file descriptor operations
let fd = posix["open"]("/tmp/test.txt",
    posix["O_WRONLY"] | posix["O_CREAT"], 0o644);
posix["write"](fd, "Hello POSIX!\n", 13);
posix["close"](fd);

# Write to file
let fd = posix["open"]("data.txt",
    posix["O_WRONLY"] | posix["O_CREAT"], 0o644);
posix["write"](fd, "Hello POSIX!\n", 13);
posix["close"](fd);

# Seek in file
let fd2 = posix["open"]("data.bin", posix["O_RDONLY"]);
posix["lseek"](fd2, 0, posix["SEEK_END"]);
let size = posix["lseek"](fd2, 0, posix["SEEK_CUR"]);
```

12.4 Signals

Signals

```
use posix;

# Send signal to a process
posix["kill"](pid, posix["SIGTERM"]);

# Set an alarm
posix["alarm"](5); # SIGALRM in 5 seconds
```

12.5 Users and Environment

Users and Environment

```
use posix;

# User/group IDs
say "UID: ", posix["getuid"]();
say "EUID: ", posix["geteuid"]();
say "GID: ", posix["getgid"]();

# Environment variables
let path = posix["getenv"]("PATH");
say "PATH: ", path;

posix["setenv"]("CRISP_TEST", "hello");
say posix["getenv"]("CRISP_TEST"); # hello

# Get all environment variables as hash
let env = posix["environ"]();
say env;
```

12.6 POSIX Function Reference

Table 9: POSIX Functions

Category	Function	Signature	Description
Processes			
	fork	posix["fork"]() Int	Create child process
	execvp	posix["execvp"](file, args...)	Execute program
	waitpid	posix["waitpid"](pid, opts) Int	Wait for child
	spawn	posix["spawn"](cmd, args...)	Spawn process
	getpid	posix["getpid"]() Int	Current PID
	getppid	posix["getppid"]() Int	Parent PID
Signals			
	kill	posix["kill"](pid, sig)	Send signal
	alarm	posix["alarm"](secs)	Schedule alarm
Users			
	getuid	posix["getuid"]() Int	Real UID
	geteuid	posix["geteuid"]() Int	Effective UID
	getgid	posix["getgid"]() Int	Real GID
	getegid	posix["getegid"]() Int	Effective GID
Files			
	open	posix["open"](path, flags, mode?) Int	Open file
	close	posix["close"](fd)	Close file
	read	posix["read"](fd, count) Str	Read bytes
	write	posix["write"](fd, data, len) Int	Write bytes
	lseek	posix["lseek"](fd, offset, whence) Int	Seek position
Env			
	getenv	posix["getenv"](name) Str	Get env var
	setenv	posix["setenv"](name, value)	Set env var
	environ	posix["environ"]() Hash	All env vars

Design Note: Namespaced POSIX

CRISP's decision to namespace POSIX under the `posix` hash solves the classic scripting language problem of namespace pollution. Languages like Perl and PHP expose hundreds of global functions, creating naming conflicts with user code. In CRISP:

- **Opt-in:** POSIX is only loaded when `use posix;` is explicitly invoked
- **Namespaced:** All functions live under `posix["fn"]`, never in the global scope
- **No shadowing:** Console `read()` and POSIX `posix["read"]()` coexist without conflict
- **Discoverable:** `posix` is a plain Hash iterate it with `for` or inspect with `keys()`

This pattern will extend to future modules: `use network;` creates a `network` hash, `use json;` creates a `json` hash, etc.

13 Console Input and Output

CRISP provides type-safe console I/O with proper flush semantics. Output functions support both bare syntax (Perl-style) and parenthesized syntax (Python-style).

13.1 Output Functions

Output Functions

```
# print output without newline (bare syntax)
print "Hello, ";
print "World!";
# Output: Hello, World!

# print output without newline (paren syntax)
print("Hello, ", "World!");
# Output: Hello, World!

# say output with automatic newline (bare syntax)
say "Hello, CRISP!";
# Output: Hello, CRISP!\n

# say output with automatic newline (paren syntax)
say("Hello, ", "CRISP!");
# Output: Hello, CRISP!\n

# Multiple arguments
say "Name: ", name, ", Age: ", age;

# warn output to stderr
warn("Something might be wrong");
# Output (to stderr): Warning: Something might be wrong
```

13.2 Input Functions

Three input functions are available, each with different behavior:

Table 10: Input Functions

Function	Returns	Flushes?	Description
<code>readline(prompt?)</code>	Always String	Yes	Reads a line, strips trailing newline
<code>read(prompt?)</code>	Int, Float, or String	Yes	Auto-detects numeric types
<code>input(prompt?)</code>	Always String	Yes	Python-compatible alias for <code>readline</code>

Input Functions

```
# readline  always returns String
let name = readline("What's your name? ");
say "Hello, ", name, "!";

# read  auto-detects Int, Float, or String
let age = read("How old are you? ");
match age {
  n where type(n) == "int" => { say "Age: ", n; }
  n where type(n) == "float" => { say "Weird age: ", n; }
  _ => { say "That's not a number!"; }
}

# input  Python-compatible alias
let color = input("Favorite color? ");
say "You like ", color;

# Empty input (just press Enter) returns empty string
let data = readline("> ");
if data == "" {
  say "No input provided.";
}

# EOF (Ctrl+D) returns empty string
let eof = readline();
if eof == "" {
  say "Goodbye!";
}
```

13.3 Flush Semantics

All input functions flush stdout before blocking on stdin. This guarantees the prompt is visible before the program waits for input:

Flush Guarantee

```
# This works correctly  prompt appears before blocking
let name = readline("Name: ");
# User sees: Name: _ (cursor waits here)

# Without flush, the prompt might be buffered and invisible
# CRISP guarantees flush, so this never happens
```


13.4 Type Conversion Functions

Type Conversion

```
# int()  parse string to integer, returns null on failure
let n = int("42");
say n;      # 42 (Int)

let bad = int("hello");
say bad;    # null

# float()  parse string to float, returns null on failure
let f = float("3.14");
say f;      # 3.14 (Float)

let bad2 = float("world");
say bad2;   # null

# type()  get the type of any value
say type(42);      # "int"
say type("hello"); # "string"
say type([1, 2]);  # "array"
say type(null);    # "null"
say type(true);    # "bool"

# len()  length of collection or string
say len("CRISP");      # 5
say len([1, 2, 3, 4, 5]); # 5
say len({ a => 1, b => 2 }); # 2
```

14 Multi-Dimensional Arrays

CRISP supports nested array literals, chained indexing, and nested iteration all building on the existing array primitives without special syntax or additional types.

14.1 Nested Array Literals

Arrays can contain other arrays, enabling matrix-like and jagged structures:

Nested Arrays

```
# Single-line nested array
let @matrix = [[1, 2, 3], [4, 5, 6], [7, 8, 9]];

# Multi-line nested array
let @grid = [
  [1, 2, 3],
  [4, 5, 6],
  [7, 8, 9]
];

# Jagged arrays (rows of different lengths)
let @jagged = [[1, 2], [3, 4, 5], [6]];
```

14.2 Chained Indexing

Postfix indexing chains naturally for multi-dimensional access:

Chained Indexing

```
let @matrix = [[1, 2, 3], [4, 5, 6], [7, 8, 9]];

# Single index returns a row (an array)
say @matrix[0];      # [1, 2, 3]

# Chained indexing drills into nested arrays
say @matrix[1][2];    # 6

# Deep nesting
let @cube = [[[1, 2], [3, 4]], [[5, 6], [7, 8]]];
say @cube[0][1][0];   # 3
```

14.3 Nested Iteration

for loops iterate over each level, enabling nested traversal:

Nested For Loops

```
# Print each cell of a matrix
for row in @matrix {
  for cell in row {
    say cell;
  }
}
# Output: 1 2 3 4 5 6 7 8 9

# Collect all elements into a flat array
let @flat = [];
for row in @matrix {
  for cell in row {
    @flat.push(cell);
  }
}
say @flat;  # [1, 2, 3, 4, 5, 6, 7, 8, 9]
```

14.4 Operations on Nested Arrays

All array methods work on nested arrays. `.contains()` checks for membership at each level:

Nested Array Operations

```
let @matrix = [[1, 2], [3, 4]];

# Row-level operations
let @row = @matrix[0];
say @row.contains(2);      # true

# Matrix-level operations
say @matrix.len();         # 2 (number of rows)
say @matrix[1].len();      # 2 (length of row 1)

# Map over rows
let @transformed = @matrix.map(|row| => row.map(|x| => x * 2));
say @transformed;          # [[2, 4], [6, 8]]
```

Design Note: No Special Matrix Type

CRISP does not have a special matrix or tensor type. Multi-dimensional arrays are simply arrays of arrays. This design choice provides:

- **Simplicity:** No new types, syntax, or concepts to learn
- **Flexibility:** Jagged arrays (rows of different lengths) are natural
- **Composability:** All existing array methods (`.map()`, `.filter()`, `.contains()`) work on nested arrays without modification

Future releases may add dedicated linear algebra operations (`transpose`, `reshape`, `flatten`) as array methods.

15 JSON Serialization (Planned)

JSON serialization is planned for the v0.2.0 release. The intended API:

Planned JSON API

```
# Planned syntax (not yet implemented)
use json;

let data = json::parse('{ "name": "John", "age": 30 }');
say data.name;      # John

let output = json::stringify({ name => "Alice", age => 25 });
say output;         # {"name":"Alice","age":25}
```

16 Network Programming (Planned)

TCP networking is planned for the v0.2.0 release. The intended API:

Planned Network API

```
# Planned syntax (not yet implemented)
use network;

let server = network::tcp_listen("0.0.0.0", 8080);
let client = network::tcp_accept(server);
let data = client.read(1024);
client.write("HTTP/1.1 200 OK\n\nHello!");
client.close();
```

17 Performance

Benchmark Results:

- **Startup time:** < 50 ms (warm)
- **REPL responsiveness:** < 10 ms
- **Arithmetic operations:** $\sim 10^6$ ops/sec
- **Function calls:** $\sim 10^5$ calls/sec
- **Memory usage:** ~ 2 MB baseline

18 Comparison with Other Languages

Table 11: Language Comparison

Feature	CRISP	Perl	Python	Rust	Bash
Regex	✓	✓	✗	✗	✓
Sigils	Optional	Required	✗	✗	✗
Memory Safety	✓	✗	✗	✓	✗
One-liners	✓	✓	✗	✗	✓
POSIX	✓	✓	✗	✓	✓
Lambda	✓	✓	✓	✓	✗
REPL	✓	✗	✓	✗	✗
Fast Startup	✓	✓	✗	✗	✓

19 Future Directions

CRISP continues to evolve with planned features:

Planned Features

- **Bytecode VM:** Improved performance through bytecode compilation
- **JIT Compilation:** Just-in-time compilation for hot code paths
- **Async/Await:** Native asynchronous programming support
- **Multi-threading:** Concurrent execution with thread safety
- **GUI Framework:** Native GUI applications with GTK/Qt
- **TUI Library:** Terminal user interfaces with Ratatui
- **WebAssembly:** Compilation to WASM for browser deployment
- **Package Manager:** CRISPAN for dependency management
- **VS Code Extension:** Language Server Protocol (LSP) support
- **Windows Support:** Full cross-platform compatibility

20 Conclusion

CRISP successfully combines Perl's expressiveness with Rust's safety. It provides a modern scripting experience with: - **Memory safety** guaranteed by Rust - **Perl-inspired** text processing and functional tools - **System access** through POSIX system calls - **Interactive development** via REPL - **One-liners** for quick scripting

Final Assessment

CRISP represents a significant step forward in scripting language design, bridging the gap between expressiveness and safety. It is suitable for:

- System administration scripts
- Text processing pipelines
- Quick prototyping
- Educational purposes
- Production system scripting

"Keep your code CRISP and clean."

21 Standard Library Reference

21.1 Console I/O

- `print(args...)` Output without newline. Supports bare and paren syntax.
- `say(args...)` Output with newline. Supports bare and paren syntax.
- `warn(args...)` Output to `STDERR` with "Warning:" prefix.
- `readline(prompt?)` `String` Read a line from `stdin`, strips trailing newline.
- `read(prompt?)` `Int` | `Float` | `Str` Like `readline` but auto-detects type.
- `input(prompt?)` `String` Python-compatible alias for `readline`.

21.2 Error Handling

- `die(msg)` Emit catchable `UserError`.
- `throw(msg)` Alias for `die` (catchable).
- `assert(cond, msg?)` Testing assertion.

21.3 Process Control

- `exit(code?)` Terminate process with exit code (default 0). `finally` blocks execute before termination. Not catchable.
- `_exit(code?)` Hard exit via `std::process::exit`. No cleanup, immediate termination.

21.4 Type Conversion and Introspection

- `int(value)` `Int` | `Null` Parse string to integer, returns null on failure.
- `float(value)` `Float` | `Null` Parse string to float, returns null on failure.
- `type(value)` `String` Returns type name ("int", "float", "string", "array", "hash", "bool", "null", "ref", "function").
- `len(value)` `Int` Length of string, array, or hash.

21.5 Array Operations

- `push(arr, val)` Append to array.
- `pop(arr)` `Value` Remove and return last element.
- `map(arr, callback)` `Array` Transform each element.
- `filter(arr, callback)` `Array` Keep matching elements.

21.6 Math and Random

- `rand(max?)` Int Random integer in `0..max-1` (default: `u64::MAX`).
- `sqrt(x)` Float Square root.
- `pow(base, exp)` Float Exponentiation.
- `abs(x)` Float Absolute value.
- `min(a, b, ...)` Float Minimum value.
- `max(a, b, ...)` Float Maximum value.
- `PI, E` Mathematical constants.

21.7 File I/O (High-Level)

- `read_file(path)` String Read entire file.
- `write_file(path, content)` Bool Write string to file.
- `file_exists(path)` Bool Check if file exists.

21.8 Method Dispatch (Value Methods)

Array methods: `.contains(val)`, `.push(val)`, `.pop()`, `.shift()`, `.unshift(val)`, `.len()`, `.map(callback)`, `.filter(callback)`, `.grep(callback)`, `.join(sep)`

String methods: `.contains(substr)`, `.len()`, `.split(delim)`, `.join(sep)`

Hash methods: `.keys()`, `.values()`, `.len()`

21.9 POSIX Module (Opt-in via `use posix;`)

Processes: `posix["fork"]`, `posix["execvp"]`, `posix["waitpid"]`, `posix["spawn"]`, `posix["getpid"]`, `posix["getppid"]`

Signals: `posix["kill"]`, `posix["alarm"]`

Users: `posix["getuid"]`, `posix["geteuid"]`, `posix["getgid"]`, `posix["getegid"]`

Files: `posix["open"]`, `posix["close"]`, `posix["read"]`, `posix["write"]`, `posix["lseek"]`

Environment: `posix["getenv"]`, `posix["setenv"]`, `posix["environ"]`

22 Keyword Reference

All CRISP keywords with their syntax and behavior.

Table 12: Complete CRISP Keywords v0.1.0

Keyword	Category	Description
let	Declaration	Declares a new variable with optional initialization.
const	Declaration	Declares an immutable constant (must be initialized).
fn	Function	Defines a named function with parameters and body.
return	Control Flow	Exits a function, optionally returning a value.
if	Conditional	Executes a block if condition is true.
else	Conditional	Alternative branch for if. Chains with if for else if.
while	Loop	Repeats a block while condition is true.
for	Loop	Iterates over arrays, hashes, strings, or ranges.
in	Loop	Separates loop variable from iterable in for loops.
break	Loop Control	Exits the innermost loop immediately. Error outside loops.
continue	Loop Control	Skips to the next iteration of the innermost loop. Error outside loops.
match	Pattern Matching	Branches on value against patterns with optional where guards.
where	Guard	Adds a condition to a match arm. The arm fires only if guard is true.
try	Error Handling	Introduces a block whose errors can be caught.
catch	Error Handling	Catches errors from a preceding try block.
finally	Error Handling	Block that always executes after try (and catch), regardless of errors.

Continued on next page

Table 12: Complete CRISP Keywords v0.1.0 (continued)

Keyword	Category	Description
<code>throw</code>	Error Handling	Emits a catchable <code>UserError</code> with a message. Interchangeable with <code>die</code> . <code>throw "invalid input";</code>
<code>die</code>	Error Handling	Emits a catchable <code>UserError</code> with a message. Interchangeable with <code>throw</code> . <code>die "fatal error";</code>
<code>print</code>	Output	Outputs arguments to stdout without trailing newline. <code>print "Hello, ", name; print("Hello, ", name); (paren)</code>
<code>say</code>	Output	Outputs arguments to stdout with automatic trailing newline. <code>say "Hello, ", name, "!"; say("Hello, ", name); (paren)</code>
<code>warn</code>	Output	Outputs arguments to stderr with "Warning:" prefix. <code>warn("low memory");</code>
<code>use</code>	Module	Loads an opt-in module. Currently <code>posix</code> is the only built-in module. <code>use posix; creates posix hash variable</code>
<code>true</code>	Literal	Boolean true value. <code>let flag = true;</code>
<code>false</code>	Literal	Boolean false value. <code>if done == false { ... }</code>
<code>null</code>	Literal	Represents absence of value. Returned by failed conversions. <code>let x = null; if x == null { ... }</code>

22.1 Control Flow Keywords

Table 13: Control Flow Keywords Internal Behavior

Keyword	Sentinel Error	Behavior
<code>return</code>	<code>RuntimeError::ReturnSignal(Value)</code>	Unwinds call stack. <code>finally</code> blocks execute before propagation.
<code>break</code>	<code>RuntimeError::BreakSignal</code>	Exits innermost loop. Error if used outside <code>while/for</code> .
<code>continue</code>	<code>RuntimeError::ContinueSignal</code>	Skips to next loop iteration. Error if used outside <code>while/for</code> .
<code>throw/die</code>	<code>RuntimeError::UserError(String)</code>	Catchable by <code>catch</code> . Uncaught: terminates script with message.

22.2 Built-in Functions (Not Keywords)

The following are built-in functions, not keywords they are stored in the global environment and can be reassigned:

Table 14: Built-in Functions

Function	Signature	Description
<code>assert</code>	<code>assert(cond, msg?)</code>	Testing assertion. Errors if condition is false.
<code>exit</code>	<code>exit(code?)</code> never returns	Terminates process with exit code. <code>finally</code> blocks execute. Not catchable.
<code>_exit</code>	<code>_exit(code?)</code> never returns	Hard process exit. No cleanup, skips <code>finally</code> .
<code>int</code>	<code>int(value)</code> Int Null	Parse string to integer. Returns null on failure.
<code>float</code>	<code>float(value)</code> Float Null	Parse string to float. Returns null on failure.
<code>type</code>	<code>type(value)</code> String	Returns type name: "int", "float", "string", "array", "hash", "bool", "null", "ref", "function".
<code>len</code>	<code>len(value)</code> Int	Length of string, array, or hash.
<code>push</code>	<code>push(arr, val)</code>	Append value(s) to array. Returns new length.
<code>pop</code>	<code>pop(arr)</code> Value	Remove and return last element.
<code>map</code>	<code>map(arr, callback)</code> Array	Transform each element through callback.
<code>filter</code>	<code>filter(arr, callback)</code> Array	Keep elements where callback returns true.
<code>readline</code>	<code>readline(prompt?)</code> String	Read line from stdin. Flushes stdout before blocking.
<code>read</code>	<code>read(prompt?)</code> Int Float Str	Auto-detecting input. Flushes stdout before blocking.
<code>input</code>	<code>input(prompt?)</code> String	Python-compatible alias for <code>readline</code> .
<code>rand</code>	<code>rand(max?)</code> Int	Random integer in 0..max-1. Uses xorshift64*.
<code>sqrt</code>	<code>sqrt(x)</code> Float	Square root.
<code>pow</code>	<code>pow(base, exp)</code> Float	Exponentiation.
<code>abs</code>	<code>abs(x)</code> Float	Absolute value.
<code>min</code>	<code>min(a, b, ...)</code> Float	Minimum of arguments.
<code>max</code>	<code>max(a, b, ...)</code> Float	Maximum of arguments.
<code>read_file</code>	<code>read_file(path)</code> String	Read entire file to string.
<code>write_file</code>	<code>write_file(path, content)</code> Bool	Write string to file.
<code>file_exists</code>	<code>file_exists(path)</code> Bool	Check if file exists.

References

References

- [1] Wall, L. et al. (1987). *Programming Perl*. O'Reilly Media.
- [2] Matsakis, N. & Klock, F. (2014). *The Rust Programming Language*. Mozilla.
- [3] Van Rossum, G. (1991). *Python Programming Language*. Python Software Foundation.
- [4] *Logos: Fast Lexical Analysis in Rust*. <https://github.com/maciejhirsz/logos>
- [5] *libc: Rust bindings to libc*. <https://github.com/rust-lang/libc>