

Neural Networks 2


Anders Krogh

Center for Health Data Science

University of Copenhagen

Over-fitting and generalization

- Many parameters and few training data leads to over-fitting
- If it over-fits, the network cannot **generalize**
- To generalize means to be able to predict on unseen (test) data



From A Krogh (2008) Nat. Biotech. 26, p. 195


Over-fitting

Sign of over-fitting:

Test error starts to grow while training error decreases




The network size can be decreased if it over-fits (e.g. fewer hidden units)

Alternatively, a **weight decay** can mitigate over-fitting



Weight decay: a term is subtracted from a weight in each iteration. is normally small, 10^{-2} to 10^{-6}

Activation functions



softmax & more on maximum likelihood

Choice of optimizer, parameters, etc

- In stochastic gradient descent (`torch.optim.SGD`) you need to set parameters (learning rate and momentum)
- The `Adam` optimizer (`torch.optim.Adam`) is usually a better choice
 - It automatically adapts the learning rate and momentum in clever ways
 - It is based on SGD and uses mini-batches
 - you can set a weight decay
- There are **many things you can vary in a Neural Network**.
- It is a good idea to make an initial “**grid search**” where you systematically test performance by varying
 - the number of hidden layers and their size
 - other parameters one by one
- This is sometimes done on a reduced data set with quite few iterations