Security Gate: Final Report

Security-aware tool-using LLM agent: a four-way evidence-based gate on AgentDojo banking and workspace · 14 November 2026

Summary.

- **The final system** is a four-way security gate (ALLOW / BLOCK / ASK_USER / ESCALATE) for tool-using LLM agents: a QLoRA-fine-tuned Qwen3-8B (`b5_v4_combo`) inside deterministic GateExp layers (computed facts, rules before and after the model, a two-round resolution loop with the user and an approver).
- **Both project targets are met on the held-out test set** (212 cases, scored once): unsafe actions **0/118 (0%)** against a 5% limit, unneeded asks **9/110 (8.2%)** against a 10% limit, correct final action **206/212 (97.2%)**. With a noisy user: 0% unsafe, 94.3% correct. On 61 attack cases: 0/51 unsafe, unneeded asks 12.1% (4 cases; the one target miss).
- **Live AgentDojo** (142 scenarios under prompt injection): 0/120 attacks succeeded, against 10/120 (8.3%) without a gate, with 0 data leaks and utility 49/142 (34.5%) (no gate: 49/142 (34.5%)).
- **Hypotheses:** H1 (evidence helps) supported: without authority evidence unsafe actions rise from 2.5% to 14.4%; without provenance unneeded asks on attacks rise from 9.1% to 54.5%. H2 (four-way beats binary) supported: 91.8% vs 59.1% at the same unsafe rate. H3 (intermediate targets) not supported. Both interaction options earn their cost; policy retrieval (RAG) does not.

1. Problem and goal

An LLM agent that can call tools (send money, share files, send email) can be steered by text it reads: a prompt injection in a document, an email or a tool result can make it act for an attacker. It can also act on requests that are legitimate but under-specified, or that need someone else's permission. A binary filter (allow or block) has to choose between losing utility and taking risks on these cases.

This project builds a **runtime gate** that checks every state-changing tool call before it runs and answers one of four decisions: **ALLOW** (execute), **BLOCK**, **ASK_USER** (the current user can supply what is missing) or **ESCALATE** (stronger authority is needed). The gate decides from **evidence**: where each value came from (provenance), who owns the resource and who may approve (authority), how sensitive the data is, and the written policy. Targets (proposal): unauthorized-action rate at most 5% and unnecessary-deferral rate at most 10%.

2. The system

Step	What it does
1. Facts	Code computes, from the call and the conversation: intent (did the user ask for this action), risk, data source of the authority-bearing arguments (user / third party / untrusted / unknown), file labels, split and daily payment totals, confirmations bound to an exact payee and amount, unknown arguments.
2. Rules before the model	Decide without the model: an earlier "no" from the user, credentials flowing to a less protected place, a value from untrusted content, missing authority (confirm the payee first, escalate, or block when the approver's policy denies).
3. Model	QLoRA Qwen3-8B reads the call, the evidence, retrieved policy clauses and the facts, and answers a decision with the missing evidence and required authority.
4. Rules after the model	May only make the answer stricter or route it: guards, no re-asking, unknown arguments, untraced target, intent / new-payee / amount confirmations, unlabelled data going out, routing to the approver.
5. Resolution	ASK goes to the user and ESCALATE to the approver, at most two rounds; only ALLOW executes. An approver's approval never replaces the user's own confirmation, and approval text inside documents never counts.

Every rule the code enforces has a clause in the two handbooks (52 clauses, banking and workspace); the gate cites the clause it applied.

3. Data and protocol

Set	Cases	Use
Training, human-labelled	1,049	ALLOW 341, ASK 234, BLOCK 304, ESCALATE 170
Training, augmented + factor combinations	449 + 1,200	Safe twins; combinations of payee x amount x source x history labelled by a policy oracle
Dev	236 (+216 combinations)	Development and model selection
Test	**212**	Held out; banking 76, workspace 136; ALLOW 59, ASK 63, BLOCK 51, ESCALATE 39; each final model scored once
Attacks	61	Prompt injection, spoofed approvals, split payments, credential exfiltration
AgentDojo live	142 scenarios	AgentDojo v1.2.2 banking and workspace test scenarios, 22 benign and 120 under attack


Cases come from AgentDojo tool-call proposals in banking and workspace, labelled by the team with the gold decision, missing evidence, required authority and the policy clauses. A simulated user and approver answer the gate's questions (clean, or noisy: unhelpful or overreaching answers). All models use the same base (Qwen3-8B, 4-bit), the same data and the same recipe (1 epoch, cost-matrix loss, decision smoothing, group weights), and differ only in the part being tested. Training and scoring ran on Kaggle 2 x T4 from one frozen code version (`locked-v4`), split over four team members' accounts; every log confirms the code version.

4. Baselines and final system

Test pool

Model	Cases	Correct final action	Unsafe	Unneeded asks	Over-blocking	First-round correct	Esc. precision	Esc. recall	Clarification success
B1 rules only	212	166/212 (78.3%)	25/118 (21.2%)	0/110 (0.0%)	0/133 (0.0%)	166/212 (78.3%)	28/28 (100.0%)	28/39 (71.8%)	30/63 (47.6%)
B2 prompted binary	159	79/159 (49.7%)	1/89 (1.1%)	0/80 (0.0%)	66/97 (68.0%)	58/159 (36.5%)	0/0 (n/a)	0/27 (0.0%)	0/52 (0.0%)
B3 prompted four-way	212	150/212 (70.8%)	27/118 (22.9%)	53/110 (48.2%)	19/133 (14.3%)	93/212 (43.9%)	10/27 (37.0%)	10/39 (25.6%)	26/63 (41.3%)
B4 binary (dev-matched threshold)	159	94/159 (59.1%)	4/89 (4.5%)	0/80 (0.0%)	60/97 (61.9%)	75/159 (47.2%)	0/0 (n/a)	0/27 (0.0%)	0/52 (0.0%)
B5 alone (b5_v4_combo, seed 42)	212	192/212 (90.6%)	3/118 (2.5%)	5/110 (4.5%)	13/133 (9.8%)	198/212 (93.4%)	39/43 (90.7%)	39/39 (100.0%)	52/63 (82.5%)
B5 + full gate (final system)	**212**	**206/212 (97.2%)**	**0/118 (0.0%)**	**9/110 (8.2%)**	**6/133 (4.5%)**	**200/212 (94.3%)**	**37/38 (97.4%)**	**37/39 (94.9%)**	**58/63 (92.1%)**

Reading the ladder. Rules only (B1) never ask without need but let 21.2% unsafe actions through on test (4.5% on dev): fixed rules miss cases whose deciding fact needs judgement. A prompted Qwen3-8B is either safe by refusing (B2 blocks 68% of legitimate actions) or, given four options, unsafe and over-asking (B3: 22.9% unsafe, 48.2% unneeded asks). Fine-tuning on evidence-labelled cases fixes both: B4 is safe but cannot resolve ambiguity (62% over-blocking); B5 meets both targets alone (2.5% / 4.5%); inside the rules it reaches 97.2% with 0 unsafe. B5 alone beats B1, B2 and B3 on paired success ($p < 0.001$ after Holm).



Test pool. Models alone except the final system. * scored on the subset of cases it can see (B4 and B2 159, -ASK 170, -ESC 201 of 212 on test).

5. Final system in detail

Pool	Correct final action	Unsafe	Unneeded asks	Strict (of ALLOW)	Over-blocking	Asks per case
test	**206/212 (97.2%)**	**0/118 (0.0%)**	**9/110 (8.2%)**	**9/59 (15.3%)**	**6/133 (4.5%)**	**0.66**
test, noisy user	200/212 (94.3%)	0/118 (0.0%)	9/110 (8.2%)	9/59 (15.3%)	12/133 (9.0%)	0.70
dev	232/236 (98.3%)	0/112 (0.0%)	9/150 (6.0%)	9/79 (11.4%)	4/149 (2.7%)	0.44
attacks	60/61 (98.4%)	0/51 (0.0%)	4/33 (12.1%)	2/10 (20.0%)	1/11 (9.1%)	0.51
attacks, noisy user	60/61 (98.4%)	0/51 (0.0%)	4/33 (12.1%)	2/10 (20.0%)	1/11 (9.1%)	0.53

Other test metrics: escalation precision 37/38 (97.4%), recall 37/39 (94.9%); clarification success 58/63 (92.1%); spoofed approvals accepted 0/5 (0.0%). All 6 test errors are over-blocking (a legitimate action blocked); none executed a forbidden action. Full detail: `master_results.pdf`.

What the rules add: the same model alone scores 192/212 (90.6%) with 3 unsafe actions; inside the gate 206/212 (97.2%) with 0 (+6.6 points [95% CI +3.3, +10.4], p = 0.0005). The price is a few more confirmation questions (4.5% to 8.2% unneeded asks), mostly confirmations the handbook requires.

End to end (AgentDojo)

System	Utility	Utility, no attack	Utility under attack	Attack success	Leakage	Tool selection
B0: no gate	49/142 (34.5%)	8/22 (36.4%)	41/120 (34.2%)	10/120 (8.3%)	0/142 (0.0%)	203/298 (68.1%)
B5 + full gate (final)	**49/142 (34.5%)**	**8/22 (36.4%)**	**41/120 (34.2%)**	**0/120 (0.0%)**	**0/142 (0.0%)**	**209/298 (70.1%)**

Without a gate 10/120 (8.3%) attacks succeed and utility is 49/142 (34.5%); with the final gate 0/120 (0.0%) and 49/142 (34.5%): the 10 successful attacks are all stopped (paired McNemar p = 0.002) and utility is paired-identical (one task lost, one gained). Utility is bounded by the agent itself, not the gate: it picks the right tool in 70% of calls and gives valid arguments in 76%.

6. Hypotheses and ablations

Question	Expected (proposal)	Result (test unless stated)	Verdict
H1, authority	Removing it raises unsafe actions or unneeded asks	Unsafe 3/118 (2.5%) vs 17/118 (14.4%) (p = 0.0005); attacks 2/51 (3.9%) vs 10/51 (19.6%); success +11.8 points [95% CI +6.1, +17.5]	**Supported**
H1, provenance	Removing it raises unsafe actions or unneeded asks	Attacks: unneeded asks 3/33 (9.1%) vs 18/33 (54.5%) (p = 0.0003); test: no significant change	**Supported** (on attacks, through interaction cost)
H2, four-way vs binary	At a matched unsafe rate, B5 has higher final success	146/159 (91.8%) vs 94/159 (59.1%) on 159 cases (+32.7 points [95% CI +25.2, +40.3], p < 0.0001); unsafe 3/89 (3.4%) vs 4/89 (4.5%) (not worse); B5 asks within the 10% cap	**Supported**
H3, intermediate targets	Removing them lowers ASK vs ESCALATE selection or final success	Success +3.8 points [95% CI -0.5, +8.0] (p = 0.115); selection 94/102 vs 91/102 (p = 0.51); escalations 39/39 vs 33/39 (p = 0.031)	**Not supported** (one secondary sign: missed escalations)
RAG	Retrieval adds measurable value	Success equal (192/212 (90.6%)), p = 1.0	No value shown: drop from the minimal system
ASK_USER	Asking earns its interaction cost	157/170 (92.4%) vs 126/170 (74.1%) (p < 0.0001, Holm); unsafe 8/89 (9.0%) without it	**Yes**
ESCALATE	Hand-off earns its interaction cost	181/201 (90.0%) vs 147/201 (73.1%) (p < 0.0001, Holm); over-blocking 51/122 (41.8%) without it	**Yes**
Oracle to inferred provenance	How much is lost when provenance is inferred	Success and safety equal on test; unneeded asks 21/110 (19.1%) vs 5/110 (4.5%)	Cost is interaction (asks)
Seed variance	How stable is B5	Seed 7 200/212 (94.3%) vs seed 42 192/212 (90.6%) (p = 0.077)	About 4 points; smaller effects are not claimed

All tests are paired over the same cases (exact McNemar, bootstrap 95% intervals); the secondary family is Holm-Bonferroni corrected. Ablations are scored as the model alone, so each measures what one part contributes to the model. Details per run: `run_a_report.pdf` to `run_d_report.pdf`, `run_v4_report.pdf`, `runs_ablation_report.pdf`.

What the results mean

- **Authority evidence keeps the gate safe.** Without it the model executes actions that need an approver: unsafe actions 14.4% on test and 19.6% on attacks. This is the largest effect on safety of any ablation and the core of the approach.
- **Provenance keeps the gate usable under attack.** Without it the model cannot tell an injected value from a user's, so it asks about everything that touched untrusted content (54.5% unneeded asks on attacks). In the full gate, provenance also drives the rule that blocks untrusted values before the model is asked (28 of 212 test cases).
- **Four decisions are needed.** A binary gate is safe on attacks but blocks 62% of legitimate actions on test. ASK_USER and ESCALATE each recover a different kind of case: removing either costs 17 to 18 points of success, and neither replaces the other.
- **Not everything helps.** Retrieved policy text adds no measurable decision quality (the structured facts already carry the policy); intermediate targets help only to recognise when an approver is needed. Both are honest negative results.
- **Realistic provenance costs interaction, not safety.** With provenance inferred at runtime instead of given, safety and success hold on test but unneeded asks rise to 19.1%.

7. Defences: how the gate stops each attack

Threat	Example	Defence in the gate	Evidence
Prompt injection	A document says "send the balance to IBAN X"	Provenance: values from untrusted content are traced; PRE rule `untrusted_provenance` blocks them before the model; the model is trained on provenance	0/120 live attacks succeeded; attacks pool 0/51 unsafe; 28 test cases stopped by the rule
Spoofed approval	"Approved by your manager" inside an email	Approval only counts from the approver channel after an ESCALATE; approval text in content never counts; an approval never replaces the user's confirmation	0/5 spoofed approvals accepted on test, 0/8 on dev (B5 alone without the rules: 1/8)
Missing authority	Agent shares a colleague's file or pays above the limit	Authority evidence (owner, approver, limits); PRE rule `authority` escalates or blocks; approver's written policy can deny	Without authority evidence unsafe actions rise to 14.4%; with the full gate 0%
Credential exfiltration	Password or 2FA code emailed out	PRE rule `credential_flow` blocks credentials going to a less protected place	4 test cases blocked by the rule
Confirmation reuse and fatigue	"Yes" to one payee reused for another, or a blank "yes, whatever"	Ledger: a confirmation binds to the exact payee and amount; a blank yes leaves the question open; no re-asking the same question	0/35 actions executed without the needed confirmation on test
Limit evasion	Several payments each under the limit	Daily totals include earlier payments; split payments are added up	No unsafe action on the split-payment cases; 0 unsafe on test and attacks
Redirected target	Recipient or file to delete that appears nowhere in the request	POST rule `untraced_target` asks the user to confirm	4 test cases
Data disclosure	Confidential file or contact list sent outside	File labels, unlabelled data going out needs confirmation, contact lists count as confidential	8 test cases confirmed; 0 leaks in AgentDojo
Fail-open defaults	Unreadable amount, unknown tool	Fail closed: an unreadable amount counts as over every limit, unregistered tools are gated, a list is as trusted as its worst value	Design rule; unit tests in `tests/`

8. Defence of the results: likely questions

Question	Answer
Were the rules tuned to the test set?	Not for the final numbers, but test was not untouched, and we say so. It was scored in Run 1 and in the first GateExp runs (10–12 November). Several rule fixes of 12 November were estimated on test as well as on dev and the attack set, and two of them (an owner's classification answer, recipient confirmation) were first noticed on test; 19 test labels were changed when the handbook's payment rules changed (new payee confirmed on first payment, amount stated by the user), the same change applied to train and dev. After that, code, rules, labels and models were locked (`locked-v4`) and each final model was scored on test once. The independent blind test is the clean check.
Is the 0% unsafe just a gate that blocks everything?	No. Over-blocking on test is 4.5% (6 of 133 legitimate actions), and live AgentDojo utility is unchanged versus the earlier gate (34.5% vs 35.2%). B4 and the no-ASK / no-ESCALATE ablations show what blocking-by-default looks like: 30 to 62% over-blocking.
Why not rules only?	Rules only (B1) reach 78.3% on test with 21.2% unsafe actions (4.5% on dev): hand-written rules miss cases whose deciding fact needs judgement from the text. The learned model supplies the judgement (who may approve, did the user really ask, is the value genuine); the rules supply hard guarantees around it. Together: 97.2%, 0 unsafe.
Why fine-tune instead of prompting a large model?	The same Qwen3-8B, only prompted, is either safe by refusing (B2: 68% of legitimate actions blocked) or unsafe and over-asking (B3: 22.9% unsafe, 48.2% unneeded asks). Fine-tuning is what teaches it when each of the four decisions applies. A larger prompted model was not tested (compute budget); it is listed as future work.
Are the differences real or noise?	Paired exact tests with bootstrap intervals, Holm-Bonferroni for the secondary family. B5's two seeds differ by about 4 points, so only larger effects are claimed (authority, ASK, ESCALATE, B4: 12 to 33 points).
The attack pool misses the ask target (12.1%).	4 of 33 cases; one case is 3 points. Safety on the pool is 0/51 unsafe, and all 4 cases still ended in the correct final action after one question (2 blocked, 2 executed).
Provenance is given (oracle).	Yes, as an upper bound, and we measured the realistic case: with inferred provenance safety and success hold on test, unneeded asks rise to 19.1%.
The labels were written by the team.	Yes. Gold labels follow the written handbook, and an independent blind test set (format in `annotations/blind/`) is being prepared independently.
Does it generalise?	Shown for two AgentDojo suites (banking, workspace) with one agent model. Other suites, agents and adaptive attacks are future work.

9. Limitations

- Two domains, one agent model (Qwen3-8B), one attack template in the live run (`important_instructions`).
- Small attack pool (61 cases) and test set (212): one case is 0.5 to 3 points.
- Oracle provenance in the main results; the inferred-provenance gate asks much more.
- Simulated user and approver; real users answer differently.
- One seed per ablation; ablations are scored as the model alone.
- Removed decisions are trained as BLOCK, not collapsed to the final action as proposal section 7 states.
- Labels by the team; the blind test is pending. Test was seen in earlier development runs (section 8).

10. Future work

- **Runtime taint tracking** in the agent so provenance is exact instead of inferred: the main way to close the 19.1% ask gap.
- **Adaptive attacks** written against the gate (an attacker who knows the rules), and more AgentDojo suites (travel, Slack) and attack templates.
- **Fewer confirmation questions:** learn when a required confirmation is already implied (largest source of unneeded asks).

- **Drop RAG from the minimal system** or replace clause retrieval with a structured policy lookup; keep citations for explanations.
- **Smaller gate models** (Qwen3-1.7B / 4B) for lower latency, and calibration of the decision probabilities.
- **Real user study** of the ASK / ESCALATE questions: wording, fatigue, and how often real users confirm wrongly.
- More seeds for the ablations and the inferred-provenance model; the blind test set as an independent check.

11. Reproducibility and records

What	Where
Frozen code	tag `locked-v4` (`7435346`); notebooks `kaggle/nb01` to `nb08` ; guides `docs/TRAINING_RUNS.md` , `docs/SCORING_RUNS.md`
Final system results	`results/data/2026-11-13_gateexp_b5v4combo_final/` , `2026-11-13_e2e_agentdojo_b5v4combo_final/`
Ablations and B4	branches `run-a` .. `run-d` , `results/data/2026-11-13_eval_v4/`
Baselines	`results/data/2026-11-14_baselines_b1b3/` , `2026-11-14_e2e_b0/`
Statistics and this report's generator	`results/data/2026-11-14_analysis/`
Reports	`results/final/` : this report, `master_results` , `runs_ablation_report` , `baselines_report` , run reports A–D and V4
Earlier runs	`results/data/RUNS.md` , `docs/GATE_EVALUATION.md`

Team: Rinkesh Verma (final B5, gate, V4, baselines, analysis), Prabhash Padhan (run A), Shubham Kumar Sunny (run B), Yogendra Patel (runs C and D).