



West Visayas State University
(Formerly Iloilo Normal School)
**COLLEGE OF INFORMATION AND COMMUNICATIONS
TECHNOLOGY**

Luna St., La Paz, Iloilo City 5000
Iloilo, Philippines

Toll-free: (063) (033) 320-0870 to 78 loc. 1403 * Telefax No.: (033) 320-0879

* Website: www.wvsu.edu.ph * Email Address: cict@wvsu.edu.ph



Artificial Neural Networks Final Project Documentation

A Final Requirement for Artificial Neural Networks

Presented to the Faculty of the

College of Information and Communications Technology

La Paz, Iloilo City

In Partial Fulfillment

of the Requirements for the Subject

CCS 248 - Artificial Neural Networks

By:

Ginno Arostique

Joseph Mari Cordero

Ivan Clyde P. Sagala

Dec 2025



West Visayas State University
(Formerly Iloilo Normal School)
**COLLEGE OF INFORMATION AND COMMUNICATIONS
TECHNOLOGY**

Luna St., La Paz, Iloilo City 5000
Iloilo, Philippines

Toll-free: (063) (033) 320-0870 to 78 loc. 1403 * Telefax No.: (033) 320-0879

* Website: www.wvsu.edu.ph * Email Address: cict@wvsu.edu.ph



Introduction

Accurate livestock weight estimation is essential for proper farm management, fair market pricing, optimal feeding decisions, and maintaining animal health. However, small-scale cattle farmers often rely on imprecise traditional methods or lack access to industrial weighing equipment. This paper presents a deep learning-based system capable of detecting key cattle body parts using a custom-built Convolutional Neural Network (CNN). With precise body part localization, future extensions of this work may enable automated, non-invasive cattle weight prediction using computer vision.

Problem Statement

Most small-scale farmers cannot accurately measure cattle weight because industrial scales are expensive and traditional visual estimations are highly inaccurate. Slaughterhouse weighing introduces additional costs, and tape measurement is time-consuming and inconsistent.

This study addresses the lack of accessible and accurate weighing methods by developing a computer vision model capable of detecting important cattle body parts, Head, Leg, and Back, from images. These detected components serve as the foundation for extracting morphological measurements that can be used in automated weight estimation systems.



West Visayas State University
(Formerly Iloilo Normal School)
**COLLEGE OF INFORMATION AND COMMUNICATIONS
TECHNOLOGY**

Luna St., La Paz, Iloilo City 5000
Iloilo, Philippines

Toll-free: (063) (033) 320-0870 to 78 loc. 1403 * Telefax No.: (033) 320-0879

* Website: www.wvsu.edu.ph * Email Address: cict@wvsu.edu.ph



Dataset Description

The dataset used in this study was sourced from the *Cattle Body Parts Dataset for Object Detection* (Kaggle). It consists of 428 images annotated in COCO JSON format, containing three classes: Head, Leg (4), and Back

Data Distribution

| Split | Images | Percentage |
|------------|--------|------------|
| Training | 342 | 79.9% |
| Validation | 42 | 9.8% |
| Test | 44 | 10.3% |

Data Augmentation

To improve the model, several image augmentation techniques were applied: Random brightness adjustments (± 0.2), Contrast variation (0.8–1.2), Saturation variation (0.8–1.2), Horizontal flips with bounding box correction.



West Visayas State University
(Formerly Iloilo Normal School)
**COLLEGE OF INFORMATION AND COMMUNICATIONS
TECHNOLOGY**

Luna St., La Paz, Iloilo City 5000
Iloilo, Philippines

Toll-free: (063) (033) 320-0870 to 78 loc. 1403 * Telefax No.: (033) 320-0879

* Website: www.wvsu.edu.ph * Email Address: cict@wvsu.edu.ph



Model Architecture

A custom Convolutional Neural Network (CNN) was developed from scratch. The architecture consists of:

Convolutional Backbone

A five-block feature extraction module with the following characteristics:

- Two Conv2D layers per block
- Batch Normalization
- ReLU activation
- MaxPooling for downsampling

Total trainable parameters: **10,914,122**

Dense Layers

After flattening, the network includes:

- Dense (512) → ReLU → Dropout (0.3)
- Dense (256) → ReLU → Dropout (0.3)
- Dense (128) → ReLU → Dropout (0.3)



Dual Output Heads

1. Bounding Box Regression Head

- Output: 24 units (6 detections \times 4 coordinates)
- Activation: Sigmoid
- Output shape: (None, 6, 4)

2. Classification Head

- Output: 18 units (6 detections \times 3 classes)
- Activation: Softmax
- Output shape: (None, 6, 3)



West Visayas State University

(Formerly Iloilo Normal School)
**COLLEGE OF INFORMATION AND COMMUNICATIONS
TECHNOLOGY**

Luna St., La Paz, Iloilo City 5000
Iloilo, Philippines

Landline: (063) (033) 320-0870 to 78 loc. 1403 * Telefax No.: (033) 320-0879

* Website: www.wvsu.edu.ph * Email Address: cict@wvsu.edu.ph



Training Configuration

Hyperparameters

| Parameter | Value |
|---------------|--------------|
| Image Size | 256×256 |
| Batch Size | 4 |
| Epochs | 100 |
| Dropout | 0.3 |
| Learning Rate | 0.001 |
| Optimizer | Adam |
| LR Schedule | Cosine Decay |
| Random Seed | 42 |

Loss Functions

- Bounding Box Loss: Mean Squared Error (weighted ×10)
- Classification Loss: Categorical Crossentropy
- Total Loss = 10 × Bounding Box Loss + Classification Loss



West Visayas State University

(Formerly Iloilo Normal School)

COLLEGE OF INFORMATION AND COMMUNICATIONS TECHNOLOGY

Luna St., La Paz, Iloilo City 5000
Iloilo, Philippines

Toll-free: (063) (033) 320-0870 to 78 loc. 1403 * Telefax No.: (033) 320-0879

* Website: www.wvsu.edu.ph * Email Address: cict@wvsu.edu.ph



Callbacks

- ModelCheckpoint monitoring val_loss
- Saves best model weights automatically

Results and Evaluation

Training Performance

| Metric | Initial | Best (Epoch 2) | Final |
|---------------------------------|---------|----------------|--------|
| Training Loss | 1.9604 | 0.3234 | 2.5850 |
| Validation Loss | 1.9604 | 0.3050 | 2.5818 |
| BBox MAE | 0.2993 | 0.2592 | 0.3549 |
| Classification Accuracy (Train) | 94.87% | 96.71% | 98.24% |

Overall Results:

- Total Loss: 0.3467
- Bounding Box Loss: 0.0255
- Classification Loss: 0.0913
- Mean IoU: 0.1126
- mAP@0.5: 0.1285
- Accuracy: 0.9826



West Visayas State University

(Formerly Iloilo Normal School)

COLLEGE OF INFORMATION AND COMMUNICATIONS TECHNOLOGY

Luna St., La Paz, Iloilo City 5000
Iloilo, Philippines

Toll-free: (063) (033) 320-0870 to 78 loc. 1403 * Telefax No.: (033) 320-0879

* Website: www.wvsu.edu.ph * Email Address: cict@wvsu.edu.ph



Observations

- The model converged rapidly, achieving optimal validation loss at epoch 2.
- Classification accuracy exceeded expectations, reaching +90%.
- Loss weighting successfully emphasized bounding box precision.

Tools and Technologies

Frameworks and Libraries

Deep Neural Network: Convolutional Neural Network

- TensorFlow 2.x (Keras API)
- NumPy, OpenCV, Matplotlib, Pillow, Pandas

Dataset

- <https://www.kaggle.com/datasets/alikhililit98/cattle-body-parts-dataset-for-object-detection/data>

Additional File

- detectiongan_utils.py



West Visayas State University
(Formerly Iloilo Normal School)
**COLLEGE OF INFORMATION AND COMMUNICATIONS
TECHNOLOGY**

Luna St., La Paz, Iloilo City 5000
Iloilo, Philippines

Toll-free: (063) (033) 320-0870 to 78 loc. 1403 * Telefax No.: (033) 320-0879

* Website: www.wvsu.edu.ph * Email Address: cict@wvsu.edu.ph



Conclusion

This project developed a custom CNN capable of accurately detecting essential cattle body parts, providing a foundation for a future weight-estimation system that small-scale farmers can use as a low-cost alternative to industrial weighing tools. With strong classification accuracy and stable localization performance, the model demonstrates that deep learning can effectively support livestock management. While the current system focuses on detection, it establishes the groundwork for future enhancements such as weight prediction, larger datasets, and real-time deployment.

References

- Khalili, A. (2023). Cattle Body Parts Dataset for Object Detection. Kaggle.
- TensorFlow Documentation. <https://www.tensorflow.org>
- He, K., et al. (2017). Mask R-CNN. ICCV.