

Lecture 17 – Debugging

Learning Objectives:

1. Become proficient in the use of the R language

1.8 Learn the basics of debugging interactively and non-interactively in R.

3. Learn the basic principles of software design.

3.6 Learn effective strategies for debugging code interactively and non-interactively.

3.7 Practice defensive coding.

Midterm survey is on Canvas!

Debugging strategy

Hadley Wickham's Steps for Debugging (from *Advanced R*)

1. **Google it!** Googling will sometimes yield a solution.

- Remove variable and function names
- Read and understand the post, why the error occurs, and why the fix works.
- Read a variety of posts to see if the fixes are consistent or if there are other options.

2. **Make it repeatable.** Form a hypothesis and test it until it works out.

- Copy code into separate script and run it that way.
- Create an automated test.

3. **Find out where it is.** Critical step to find where in the script the error originates.

- Use `traceback()` to find error
- For functions, define parameters manually and run line-by-line
- For for loops, define your looped parameter and run line-by-line
- There are tools!

4. **Fix it and test it.** Be sure to make the error a test!

Tools that will help: RStudio's debugger

Visualizing problems

traceback()

RStudio

post-refactoring_generate_grid2d.R* x plotahair x 17-debugging-exampecode.R x

Function: plotahair (GlobalEnv) (Read-only)

```
1 function(hairxCenterx, hairxCentery, hdia, dx, no, plotit){
2   h1 <- circle(c(hairxCenterx, hairxCentery), 0.5 * hdia, "dx")
3   if(plotit == 1){
4     points(hairxCenterx, hairxCentery, pch = 19, cex = 2.5)
5     text(hairxCenterx, hairxCentery, labels = no, col = "red")
6   }
7   return(h1)
8 }
```

Environment History Connections Tutorial

plotahair()

Values

dx dx

Traceback ☒ Show internals

```
→ eval(substitute(browse(skipCalls = skip), list(skip = 7 ...
eval(substitute(browse(skipCalls = skip), list(skip = 7 ...
(function () at post-refactoring_generate_grid2d.R:0
seq.default(-(radius + 0.01), radius + 0.01, by = dx) at
```

Files Plots Packages Help Viewer

New Folder Delete Rename More

n) > courses > CS510 > CourseInfoFall2020 > LectureNotes > 12-Refactor

	Name	Size	Modified
	..		
	12-Refactor-slides.key	1.2 MB	Oct 12, 2020, 2:54 F
	12-Refactor-slides.pdf	647.9 KB	Oct 12, 2020, 2:54 F
	12-Refactor.aux	757 B	Oct 12, 2020, 12:14
	12-Refactor.log	17 KB	Oct 12, 2020, 12:14
	12-Refactor.out	0 B	Oct 12, 2020, 12:14
	12-Refactor.pdf	56.7 KB	Oct 12, 2020, 12:14
	12-Refactor.synctex.gz	17.3 KB	Oct 12, 2020, 12:14
	12-Refactor.tex	7.7 KB	Oct 12, 2020, 12:14
	a_matter_of_perspective_hd_00...	360.3 KB	Oct 12, 2020, 3:12 F
	post-code1.png	132.4 KB	Oct 12, 2020, 1:11 F
	post-code2.png	133.8 KB	Oct 12, 2020, 1:18 F
	pre-code1.png	159.3 KB	Oct 12, 2020, 1:10 F
	pre-code2.png	171.5 KB	Oct 12, 2020, 1:16 F
	Refactoring_example		

Console ~/Dropbox (Chapman)/courses/CS510/CourseInfoFall2020/LectureNotes/12-Refactor/Refactoring_example/

Next Previous Continue Stop

Error in del/by : non-numeric argument to binary operator

Enter a frame number, or 0 to exit

```
1: source("~/Dropbox (Chapman)/courses/CS510/CourseInfoFall2020/LectureNotes/12-Refactor/Refactoring_exampl
2: withVisible(eval(ei, envir))
3: eval(ei, envir)
4: eval(ei, envir)
5: post-refactoring_generate_grid2d.R#177: makehairs(parameters$angle[j], parameters$gap[j], j, nohairs, pl
6: post-refactoring_generate_grid2d.R#137: plotahair(hairx, hairy, hdia, dx, i, plotit)
7: post-refactoring_generate_grid2d.R#69: circle(c(hairxCenterx, hairxCentery), 0.5 * hdia, "dx")
8: post-refactoring_generate_grid2d.R#41: seq(-(radius + 0.01), radius + 0.01, by = dx)
9: seq.default(-(radius + 0.01), radius + 0.01, by = dx)
```

Selection: 6

Called from: eval(substitute(browse(skipCalls = skip), list(skip = 7 - which)),
envir = sys.frame(which))

Browse[1]> |

Debugger functions

Non-interactive debugging

Stick with the general strategy, but there are fewer tools to help.

Check common problems:

- Did you run the code in a clean session?
- Is the working directory different?
- Is the path environment different?
- Is the R_LIBS path different?

Use `dump.frames()` (like `recover()` in interactive mode):


```
dump_and_quit <- function() {  
  # Save debugging info to file las.dump.rda  
  dump.frames(to.file = TRUE)  
  # Quits R with error status  
  q(status = 1)  
}  
  
options(error = dump_and_quit)
```

Tools that will help: flow package

To install: `remotes::install_github("moodymudskipper/flow")`

Draws flow charts of functions. Useful for a deep dive into analysis pipelines.

<https://moodymudskipper.github.io/flow/articles/Draw-a-function.html>



Also see:

debugr package

wrapr package

Defensive programming

“Fail fast.”

- Be strict about what you accept.
- Avoid functions that use non-standard evaluation.
- Avoid functions that return different types of output depending on their input.

Additional Resources

**<https://adv-r.hadley.nz/debugging.html#non-interactive-debugging> –
Debugging, *Advanced R***

**<https://data-flair.training/blogs/debugging-in-r-programming/> –
R Debug Essentials**

**<https://support.rstudio.com/hc/en-us/articles/205612627-Debugging-with-RStudio> –
Debugging with RStudio**

<https://rdr.io/cran/wrapr/f/vignettes/DebugFnW.Rmd> – wrapr Debug Vignette

**<https://cran.r-project.org/web/packages/debugr/vignettes/debugr.html> –
debugr package vignette**

Code Peer-Review Form:

<https://forms.gle/F22aWV8VKGjqvoaa6>

Procedure for peer-reviewing code:

- 1. Download the release specified on Canvas.**
- 2. Open and enter the directory.**
- 3. Read and follow the instructions in the README.**
- 4. If no instructions are provided, either:**
 - open RStudio project and source first R script.**
 - setwd() and source first R script.**
- 5. Fill out the form.**