

# LogPulse AI - Incident Report

Generated : 2026-05-29 00:22:55 UTC

Trace ID : 8e69cedd-e69b-4434-a4bf-c0319f527ab8

## 1 - Incident Summary

**Incident ID :** 8e69cedd  
**Category :** Database  
**Severity :** SeverityLevel.FATAL  
**Source :** PostgreSQL  
**Cache :** MISS

## 2 - Raw Log

[2026-05-26 14:32:01] ERROR [postgres-db-01] pid=1234 192.168.1.10:5432 FATAL: remaining connection slots are reserved for non-replication superuser

## 3 - Classification

**Category :** Database  
**Severity :** SeverityLevel.FATAL  
**Summary :** Connection pool exhausted on postgres-db-01  
**Source :** PostgreSQL

## 4 - Diagnosis

**Root Cause :** Based on the matched playbook 'Database Connection Refused/Timed Out Post Node Maintenance', the likely root cause is a Database incident matching the pattern: Connection pool exhausted on postgres-db-01.

**Confidence :** 51%

**Reasoning :** Gemini unavailable; diagnosis derived from playbook 'Database Connection Refused/Timed Out Post Node Maintenance' (RAG confidence=0.5121).

**Source Tier :** playbook\_fallback

**Used History :** No

**Used Playbook :** Yes

## 5 - Proposed Solution

### Explanation:

Gemini unavailable; remediation derived from playbook 'Database Connection Refused/Timed Out Post Node Maintenance' (RAG confidence=0.5121). Review the playbook steps and adapt commands to the live environment before execution.

Steps:

- 1. Identify the Kubernetes node currently hosting the database pod using `kubectl get pod <db-pod-name> -o wide`.
- 2. SSH into the identified node.
- 3. Check the status of the `kube-proxy` service on the node: `sudo systemctl status kube-proxy.service`.
- 4. Review `kube-proxy` logs on the node for errors or warnings: `sudo journalctl -u kube-proxy.service --since '1 hour ago'`.
- 5. Inspect `iptables` rules: `sudo iptables -L -n -v`. Look for missing or incorrect rules related to Kubernetes services and the database Service IP.
- 6. If `kube-proxy` is stopped or unhealthy, restart it: `sudo systemctl restart kube-proxy.service`.
- 7. If the issue persists after `kube-proxy` is confirmed healthy, consider restarting the database pod to force `kube-proxy` to re-establish rules specifically for its Service.

6 - Risk Assessment

Risk Level : RISKLEVEL.SAFE

Safe Commands (0):

(none)

Flagged Commands (0):

(none)

7 - Operator Decision

Decision : OPERATORDECISION.APPROVED

Executed At : 2026-05-28T21:22:51.226858+00:00

8 - Historical Context

Times Seen : 1

First occurrence -- no prior incidents.

9 - Incident Timeline

[21:22:55] WORKFLOW\_COMPLETED -> Completed in 4098ms