

LogPulse AI - Incident Report

Generated : 2026-05-29 11:17:51 UTC

Trace ID : 35a3c798-8862-4fe4-9902-52d33238eec7

1 - Incident Summary

Incident ID : 35a3c798
Category : Database
Severity : SeverityLevel.FATAL
Source : PostgreSQL
Cache : MISS

2 - Raw Log

[2026-05-26 14:32:01] ERROR [postgres-db-01] pid=1234 192.168.1.10:5432 FATAL: remaining connection slots are reserved for non-replication superuser

3 - Classification

Category : Database
Severity : SeverityLevel.FATAL
Summary : Connection pool exhausted on postgres-db-01
Source : PostgreSQL

4 - Diagnosis

Root Cause : Based on the matched playbook 'Database Connection Refused/Timed Out Post Node Maintenance', the likely root cause is a Database incident matching the pattern: Connection pool exhausted on postgres-db-01.

Confidence : 51%

Reasoning : Gemini unavailable; diagnosis derived from playbook 'Database Connection Refused/Timed Out Post Node Maintenance' (RAG confidence=0.5121).

Source Tier : playbook_fallback

Used History : No

Used Playbook : Yes

5 - Proposed Solution

Explanation:

Gemini unavailable; remediation derived from playbook 'Database Connection Refused/Timed Out Post Node Maintenance' (RAG confidence=0.5121). Review the playbook steps and adapt commands to the live environment before execution.

Steps:

- 1. Identify the Kubernetes node currently hosting the database pod using `kubectl get pod <db-pod-name> -o wide`.
- 2. SSH into the identified node.
- 3. Check the status of the `kube-proxy` service on the node: `sudo systemctl status kube-proxy.service`.
- 4. Review `kube-proxy` logs on the node for errors or warnings: `sudo journalctl -u kube-proxy.service --since '1 hour ago'`.
- 5. Inspect `iptables` rules: `sudo iptables -L -n -v`. Look for missing or incorrect rules related to Kubernetes services and the database Service IP.
- 6. If `kube-proxy` is stopped or unhealthy, restart it: `sudo systemctl restart kube-proxy.service`.
- 7. If the issue persists after `kube-proxy` is confirmed healthy, consider restarting the database pod to force `kube-proxy` to re-establish rules specifically for its Service.

6 - Risk Assessment

Risk Level : RISKLEVEL.SAFE

Safe Commands (0):

(none)

Flagged Commands (0):

(none)

7 - Operator Decision

Decision : OPERATORDECISION.APPROVED

Executed At : 2026-05-29T08:17:45.860048+00:00

8 - Historical Context

Times Seen : 1

First occurrence -- no prior incidents.

9 - Incident Timeline

[08:17:50] WORKFLOW_COMPLETED -> Completed in 4712ms