

LogPulse AI - Incident Report

Generated : 2026-06-01 11:19:30 UTC

Trace ID : 5a56033e-daba-419e-b3de-a129746aa342

1 - Incident Summary

Incident ID : 5a56033e
Category : Security
Severity : SeverityLevel.CRITICAL
Source : OS
Cache : MISS

2 - Raw Log

```
2026-05-30 14:33:21 ERROR sshd[2847]: Failed password for root from 185.220.101.42 port 54832
ssh2. Failed password for root from 185.220.101.42 port 54833 ssh2. Failed password for root from
185.220.101.42 port 54834 ssh2. Maximum authentication attempts exceeded. Possible brute force
attack detected.
```

3 - Classification

Category : Security
Severity : SeverityLevel.CRITICAL
Summary : Multiple failed SSH login attempts for root user; maximum authentication attempts exceeded.
Source : OS

4 - Diagnosis

Root Cause : The system has a weak SSH configuration, likely permitting root login with passwords, which exposed it to a brute-force attack.

Confidence : 90%

Reasoning : The raw log indicates a brute-force attack against the root user via SSH. The retrieved playbook directly addresses 'Weak SSH Configuration or Exposed SSH Daemon on Nodes' and suggests disabling 'PermitRootLogin' and 'PasswordAuthentication', which are the underlying vulnerabilities enabling such an attack.

Source Tier : llm
Used History : No
Used Playbook : Yes

5 - Proposed Solution

Explanation:

Gemini unavailable; playbook 'Weak SSH Configuration or Exposed SSH Daemon on Nodes' was retrieved (RAG confidence=0.5348) but contained no executable commands -- only narrative guidance was found. Review the playbook manually and construct the appropriate commands before execution.

Steps:

- 1. Audit `/etc/ssh/sshd_config` on affected nodes for insecure settings.
- 2. Disable `PasswordAuthentication`, `PermitRootLogin`. Enforce key-based authentication only.
- 3. Restrict SSH access to specific jump hosts/IPs via firewall rules or `AllowUsers`/`AllowGroups` in `sshd_config`.
- 4. Restart `sshd` service (`sudo systemctl restart sshd`). For nodes that don't require SSH, ensure `sshd` is stopped and disabled.

6 - Risk Assessment

Risk Level : RISKLEVEL.SAFE

Safe Commands (0):

(none)

Flagged Commands (0):

(none)

7 - Operator Decision

Operator rejected -- no execution.

8 - Historical Context

Times Seen : 1

First occurrence -- no prior incidents.

9 - Incident Timeline

[08:12:06] INCIDENT_RECEIVED -> Incident received (trace_id=5a56033e...)
[08:12:06] CACHE_MISS -> Cache miss -- routing to classifier
[08:12:16] INCIDENT_CLASSIFIED -> Security / Critical
[08:12:20] RAG_RETRIEVED -> Playbook retrieved (filtered) -- Security conf=0.53
[08:12:29] ROOT_CAUSE_GENERATED -> The system has a weak SSH configuration, likely permitting root login with passwords, which exposed it to a brute-force
[08:14:30] SOLUTION_GENERATED -> 4 step(s) from playbook
[08:14:30] RISK_ASSESSED -> safe -- 0 flagged
[08:19:30] WORKFLOW_COMPLETED -> Completed in 443886ms