

LogPulse AI - Incident Report

Generated : 2026-06-01 11:49:43 UTC

Trace ID : 67850011-ab38-45c8-bc22-2a881bc5d8b2

1 - Incident Summary

Incident ID : 67850011
Category : Security
Severity : SeverityLevel.CRITICAL
Source : OS
Cache : MISS

2 - Raw Log

```
2026-05-30 03:21:45 ERROR sshd[2847]: Failed password for root from 185.220.101.42 port 54832
ssh2. Failed password for root from 185.220.101.42 port 54833 ssh2. Failed password for root from
185.220.101.42 port 54834 ssh2. Maximum authentication attempts exceeded from 185.220.101.42.
Possible brute force attack detected on bastion-01.
```

3 - Classification

Category : Security
Severity : SeverityLevel.CRITICAL
Summary : Multiple failed SSH passwords for root from same IP; maximum attempts exceeded;
possible brute force attack detected.
Source : OS

4 - Diagnosis

Root Cause : The SSH daemon on bastion-01 is configured to allow password authentication and/or root login, making it vulnerable to brute-force attacks, likely without sufficient IP-based access restrictions.

Confidence : 95%

Reasoning : The raw log and classification clearly indicate a brute-force SSH attack against the root user. The retrieved playbook directly points to 'Weak SSH Configuration or Exposed SSH Daemon on Nodes' and suggests disabling 'PasswordAuthentication' and 'PermitRootLogin' as resolution steps, which directly aligns with the observed attack.

Source Tier : llm
Used History : No
Used Playbook : Yes

5 - Proposed Solution

Explanation:

The SSH daemon on bastion-01 is vulnerable to brute-force attacks due to allowing password authentication and root login, and lacking sufficient IP-based access restrictions.

Steps:

1. Audits the SSH daemon configuration on bastion-01 for insecure settings related to password authentication and root login.
2. Blocks the attacker IP (185.220.101.42) from accessing SSH on bastion-01.
3. Disables password authentication in the SSH daemon configuration on bastion-01.
4. Disables root login via SSH on bastion-01.
5. Restarts the SSH daemon on bastion-01 to apply the new configuration changes.

Commands:

```
$ ssh bastion-01 "sudo grep -E '^(PasswordAuthentication|PermitRootLogin)' /etc/ssh/sshd_config"
$ ssh bastion-01 "sudo iptables -A INPUT -s 185.220.101.42 -p tcp --dport 22 -j DROP"
$ ssh bastion-01 "sudo sed -i 's/^\PasswordAuthentication yes/PasswordAuthentication no/'
/etc/ssh/sshd_config"
$ ssh bastion-01 "sudo sed -i 's/^\PermitRootLogin yes/PermitRootLogin no/' /etc/ssh/sshd_config"
$ ssh bastion-01 "sudo systemctl restart sshd"
```

6 - Risk Assessment

Risk Level : **RISKLEVEL.WARNING**

Safe Commands (4):

```
[OK] ssh bastion-01 "sudo grep -E '^(PasswordAuthentication|PermitRootLogin)' /etc/ssh/sshd_config"
[OK] ssh bastion-01 "sudo iptables -A INPUT -s 185.220.101.42 -p tcp --dport 22 -j DROP"
[OK] ssh bastion-01 "sudo sed -i 's/^\PasswordAuthentication yes/PasswordAuthentication no/' /etc/ssh/sshd_config"
[OK] ssh bastion-01 "sudo sed -i 's/^\PermitRootLogin yes/PermitRootLogin no/' /etc/ssh/sshd_config"
```

Flagged Commands (1):

```
[!] ssh bastion-01 "sudo systemctl restart sshd" [systemctl\s+(stop|restart)]
```

7 - Operator Decision

Operator rejected -- no execution.

8 - Historical Context

Times Seen : 1

First occurrence -- no prior incidents.

9 - Incident Timeline

```
[08:43:38] INCIDENT_RECEIVED -> Incident received (trace_id=67850011...)
[08:43:38] CACHE_MISS -> Cache miss -- routing to classifier
```

```
[08:43:47] INCIDENT_CLASSIFIED -> Security / Critical
[08:43:52] RAG_RETRIEVED -> Playbook retrieved (filtered) -- Security conf=0.57
[08:43:56] ROOT_CAUSE_GENERATED -> The SSH daemon on bastion-01 is configured to allow password authentication and/or root login, making it vulnerable to b
[08:44:41] SOLUTION_GENERATED -> 5 step(s), 5 command(s)
[08:44:41] RISK_ASSESSED -> warning -- 1 flagged
[08:49:41] WORKFLOW_COMPLETED -> Completed in 362597ms
```