

LogPulse AI - Incident Report

Generated : 2026-06-01 11:29:56 UTC

Trace ID : 69e560ae-5749-47d1-87a9-c354bdaa423c

1 - Incident Summary

Incident ID : 69e560ae
Category : Security
Severity : SeverityLevel.CRITICAL
Source : OS
Cache : MISS

2 - Raw Log

```
2026-05-30 14:33:21 ERROR sshd[2847]: Failed password for root from 185.220.101.42 port 54832
ssh2. Failed password for root from 185.220.101.42 port 54833 ssh2. Failed password for root from
185.220.101.42 port 54834 ssh2. Maximum authentication attempts exceeded. Possible brute force
attack detected.
```

3 - Classification

Category : Security
Severity : SeverityLevel.CRITICAL
Summary : Multiple failed SSH login attempts for root user; maximum authentication attempts exceeded.
Source : OS

4 - Diagnosis

Root Cause : An insecure SSH configuration allowed password authentication and root login, exposing the system to a brute-force attack attempt from an external IP.
Confidence : 95%
Reasoning : The raw log indicates a brute-force attack on the root user via SSH. The retrieved playbook directly identifies 'Weak SSH Configuration or Exposed SSH Daemon on Nodes' as the underlying issue, with resolution steps to disable password authentication and root login.
Source Tier : llm
Used History : No
Used Playbook : Yes

5 - Proposed Solution

Explanation:

Gemini unavailable; playbook 'Weak SSH Configuration or Exposed SSH Daemon on Nodes' was retrieved (RAG confidence=0.5348) but contained no executable commands -- only narrative guidance was found. Review the playbook manually and construct the appropriate commands before execution.

Steps:

- 1. Audit `/etc/ssh/sshd_config` on affected nodes for insecure settings.
- 2. Disable `PasswordAuthentication`, `PermitRootLogin`. Enforce key-based authentication only.
- 3. Restrict SSH access to specific jump hosts/IPs via firewall rules or `AllowUsers`/`AllowGroups` in `sshd_config`.
- 4. Restart `sshd` service (`sudo systemctl restart sshd`). For nodes that don't require SSH, ensure `sshd` is stopped and disabled.

6 - Risk Assessment

Risk Level : **RISKLEVEL.SAFE**

Safe Commands (0):

(none)

Flagged Commands (0):

(none)

7 - Operator Decision

Operator rejected -- no execution.

8 - Historical Context

Times Seen : 1

First occurrence -- no prior incidents.

9 - Incident Timeline

```
[08:22:57] INCIDENT_RECEIVED -> Incident received (trace_id=69e560ae...)
[08:22:57] CACHE_MISS -> Cache miss -- routing to classifier
[08:23:05] INCIDENT_CLASSIFIED -> Security / Critical
[08:23:08] RAG_RETRIEVED -> Playbook retrieved (filtered) -- Security conf=0.53
[08:23:11] ROOT_CAUSE_GENERATED -> An insecure SSH configuration allowed password authentication
and root login, exposing the system to a brute-force attac
[08:24:55] SOLUTION_GENERATED -> 4 step(s) from playbook
[08:24:55] RISK_ASSESSED -> safe -- 0 flagged
[08:29:55] WORKFLOW_COMPLETED -> Completed in 418394ms
```