

Comsats University Islamabad Department of Computer Science Mid Term Examination, Spring 2022

Class Section .

BSCS - 3A.3B

Subject

Object Oriented Programming

matrix tot .

Ms-Sanceha-Aamir Dis Rowal Bullish Marks: -

40

Time: -

90 minutes

Dated: - May 13, 2022

1. Give short answers for the following:

- a. Does an object created with a copy constructor reference the same memory location that the original
- b. What is the purpose of creating private methods in class?
- c. What is the use of this operator?
- d. When do we declare a class as abstract?
- e. Which class is present at the top level of all inheritance hierarchies?
- 2. Consider the following Mutable class. Convert it to an Immutable one.

(5 marks) (10 min) [CLO 3]

```
class Marks (
  private int oopMarks;
  private int dsaMarks;
  public int getDsaMarks() {
     return dsaMarks;
  public void setDsaMarks(int dsaMarks) {
     this.dsaMarks = dsaMarks;
  public void setOopMarks(int oopMarks) {
     this.oopMarks = oopMarks;
  public int getOopMarks() {
     return oopMarks;
  public int totalMarks() {
     return getDsaMarks() + getOopMarks();
class Student (
  String name;
  String rollNumber,
  Marks marks;
  public Student(){
```

```
public Student(String name, String rollNumber, Marks marks) {
  this name = rame;
  this roll Number = roll Number:
  this marks = marks;}
public String getName() {
   return name;
 public void setName(String name) {
   this name = name,
 public String getRollNumber() {
   return roll. Number,
 public void setRollNumber(String rollNumber) {
    this roll Number = roll Number,
 public void setMarks(Marks marks) {
    this.marks = marks:
 public Marks getMarks() (
  return marks:
```

Consider the following code and write the output.

(3 marks) (5 min) [CLO 1]

```
class Marks {
    private int oopMarks;
    private int dsaMarks;

    public int getDsaMarks() {
        return dsaMarks;

    public void setDsaMarks(int dsaMarks) {
        this dsaMarks = dsaMarks;

    }

    public void setOopMarks(int oopMarks) {
        this doopMarks = oopMarks;

        public int getOopMarks() {
            return oopMarks;
    }

    public int totalMarks() {
            return getDsaMarks() + getOopMarks();
    }
```

```
class Student (
    Marks marks;
   public void setMarks(Marks marks) {
    this.marks = marks;
  public Marks getMarks() {
   return marks;
  }
public class MyClass {
public static void main(String args[]) {
  Student std = new Student();
  Marks marks:
  System.out.println(std.getMarks());
  marks = new Marks();
  std.setMarks(marks);
  System.out.println(std.getMarks());
  System.out.println(std.getMarks().getOopMarks());
  std.getMarks().setOopMarks(85);
  System.out.println(std.getMarks().getOopMarks());
```

Write output of following code:

(3 marks) (5 min) [CLO 1]

```
public class TestExample {
public static int a;
public int b;
public void increament (){ a++; b++; }
public void display() { System.out.println(a + " "+ b); }
Class runner
Public static void main(String args[])(
TestExample t1 = new TestExample();
TestExample t2 = new TestExample();
t1.increament();
t2.increament();
System.out.println(TestExample.a);
System.out.println(t1.a);
System.out.println(t2.a);
```

5. Write the output for the following scenario: (4 marks) (5 min) [CLO 1]

Suppose you have a parent class Animal that has a method speak() which returns: Awk.

- Cat has a speak method that returns: Meow.
- Bird does not have a speak method.
- Dog has a speak method that returns: Woof.
- Pig does not have a speak method.
- Cow has a speak method that returns: Moo.

What is the output from looping through the array a created below and asking each element to speak()?

Animal[] a = { new Cat(), new Cow(), new Dog(), new Pig(), new Bird() }

- Create design (class diagram) for Hotel Management System using the following classes (10 marks) (20 min) [CLO 2]
 - a. Person
 - b. Client
 - c. Staff
 - d. Room
 - e. Booking

Following points must be considered.

- a. Each class should have at least two data members.
- b. All possible is-a and has-a relationships must be considered.
- c. The system should display information about a client.
- d. The system should display information about a room.
- e. The system should show the final cost of booking.

Note: You may incorporate concept of abstract class.

7. Consider the following classes. Complete the class "Shop" and write the definition of method "countExpiredProducts". [Hint: Has-a relationship] (4 marks) (10 min) [CLO 3]

```
as name = name; this.dateOfExpiry = dateOfExpiry; this.price = price;
  public String getName() { return name; }
 public Date getDateOfExpiry() { return dateOfExpiry; }
 public double getPrice() { return price; }
public class Shop {
Product [] p_array = new Product[100];
String location;
public Shop(String location) {
this.location = location;
public void addAProduct( Product p)
for (int i = 0; i < 100; i++)
if (p_array [i]==null)
 p_array[i] = p;
 break:
// count all products that have expired
 public int countExpiredProducts()
 // To do
 }
```

8. A new housing scheme has been announced with certain advertising campaign to sale the property. Two types of plots are available; residential plots and commercial plots. The definition for general 'Plot' class is provided. You need to define ResidentialPlot and CommercialPlot classes.

Note: Tax calculation is as follows:

- •If occupation is "Government" a discount of 2 percent on residential plot price is applicable •Tax of 10 percent on residential plot price is applicable.

•If occupation is "Government" a discount of 3 percent on Commercial plot price is applicable • Tax of 15 percent on commercial plot price is applicable.

In runner class call the 'calculateTax' method polymorphically to calculate tax for 10 Maria residential and 12 Maria commercial plot for best (10 marks) (10 and 12 Marla commercial plot for both government and private sector employee.

```
public class Customer (
 private String name;
  private int age;
  private String occupation;
 public Customer(String name, int age, String occupation) {
    this.name = name;
    this.age = age,
    this occupation = occupation;
  public String getName() {
    return name:
  public void setName(String name) {
    this.name = name;
  public int getAge() {
    return age;
  public void setAge(int age) (
    this.age = age;
 public String getOccupation() {
    return occupation;
  public void setOccupation(String occupation) {
    this occupation = occupation;
protected int plotnumber;
  protected int sizeInMarlas.
  protected double cost,
  protected Customer customer;
  public Plot(int plotnumber, double size, double cost, Customer customer) (
     this sizeInMarias = size;
     this cost = cost,
     this customer = customer;
  public abstract double calculateTax();
```