# Deep Learning

April 18, 2019

Data Science CSCI 1951A

Brown University

Instructor: Ellie Pavlick

HTAs: Wennie Zhang, Maulik Dang, Gurnaaz Kaur

#### Announcements

 Extra Office Hours next week—talk to me about your project woes (getting close to your last chance)


# Today

- Deep Learning roughly what is it?
- Why is it such a big deal (now)?
- Should I use deep learning for my thing?


$$\sum_{i=1}^n (Y_i - \hat{Y})^2$$

minimize 
$$\sum_{i=1}^n (Y_i - \hat{Y})^2$$


minimize 
$$\sum_{i=1}^n (Y_i - \hat{Y})^2$$



minimize 
$$\sum_{i=1}^n (Y_i - \hat{Y})^2$$




# Linear Regression




# Linear Regression


$$y = wX + b$$



$$y = \vec{w} \cdot \vec{x}$$



X W



X








X


W

y

$$y = \vec{w} \cdot \vec{x}$$




$$y = \vec{w} \cdot \vec{x}$$



X W


$$y = \vec{w} \cdot \vec{x}$$

Feature Weight







$$y = \vec{w} \cdot \vec{x}$$



# Logistic Regression



$$y = 1 \text{ if } \vec{w} \cdot \vec{x} > \tau \text{ else } 0$$




$$y = 1 \text{ if } \vec{w} \cdot \vec{x} > \tau \text{ else } 0$$
"activation function"



X

=






X W




$$y = 1 \text{ if } \vec{w} \cdot \vec{x} > \tau \text{ else } 0$$



x w1 h w2 y


$$y = 1 \text{ if } \vec{w} \cdot \vec{x} > \tau \text{ else } 0$$

just a logistic regression



x w1 h w2


$$y=1 \text{ if } \vec{w} \cdot \vec{x} > \tau \text{ else } 0$$
 and another



x w1 h w2 y


$$y = 1 \text{ if } \vec{w} \cdot \vec{x} > \tau \text{ else } 0$$

so many logistic regressions




x w1 h w2 y


$$y = 1 \text{ if } \vec{w} \cdot \vec{x} > \tau \text{ else } 0$$



$$y = 1 \text{ if } \vec{w} \cdot \vec{x} > \tau \text{ else } 0$$




$$y = 1 \text{ if } \vec{w} \cdot \vec{x} > \tau \text{ else } 0$$




x w1 h w2 y


$$y = \vec{w} \cdot \vec{x}$$




x w y



$$y = W_2 \cdot (W_1 \cdot \vec{x})$$




x w1 w2 y



x w1 w2 y

$$y = W_2 \cdot (W_1 \cdot \vec{x})$$

$$f = \mathcal{L}(W_2 \cdot g(\vec{x}))$$
$$g = W_1 \cdot \vec{x}$$



x w1 w2 y

$$y = W_2 \cdot (W_1 \cdot \vec{x})$$

$$f = \mathcal{L}(W_2 \cdot g(\vec{x}))$$

$$g = W_1 \cdot \vec{x}$$


x w1

$$\frac{\partial loss}{\partial s}$$

$$\frac{\partial f}{\partial x} = \frac{\partial f}{\partial g} \frac{\partial g}{\partial x}$$


Chain Rule!

#### The most basic network




#### The most basic network


$$y = 1 \text{ if } \vec{w} \cdot \vec{x} > \tau \text{ else } 0$$




### The most basic network

$$y = 1 \text{ if } \vec{w} \cdot \vec{x} > \tau \text{ else } 0$$





#### tons of nonlinear parameters = tons of flexibility





NNs have been around since forever (the 80s!! :-0)

- NNs have been around since forever (the 80s!! :-0)
- A vanilla MLP can theoretically approximate any function ("universal approximator")

- NNs have been around since forever (the 80s!! :-0)
- A vanilla MLP can theoretically approximate any function ("universal approximator")
- (Note: "can" != "do")

Recently became viable for a few reasons, e.g....

- Recently became viable for a few reasons, e.g....
- Backprop (/autodiff): now we can build deep networks and actually train them

- Recently became viable for a few reasons, e.g....
- Backprop (/autodiff): now we can build deep networks and actually train them
- GPUs: and we can train them fast

- Recently became viable for a few reasons, e.g....
- Backprop (/autodiff): now we can build deep networks and actually train them
- GPUs: and we can train them fast
- Data: and we can train on enough data that they actually converge to something useful

"Its how the brain works."

"Its how the brain works." —> NO!

- "Its how the brain works." —> NO!
- End-to-end training—optimize directly for the thing you care about

- "Its how the brain works." —> NO!
- End-to-end training—optimize directly for the thing you care about
- Dense/denoised representations—similar inputs get similar predictions


- "Its how the brain works." —> NO!
- End-to-end training—optimize directly for the thing you care about
- Dense/denoised representations—similar inputs get similar predictions (like MF, more in a bit)

- "Its how the brain works." —> NO!
- End-to-end training—optimize directly for the thing you care about
- Dense/denoised representations—similar inputs get similar predictions (like MF, more in a bit)
- Uniform representations across sub-disciplines of AI (i.e. vision, language, sensor inputs)—"its all just vectors anyway"


#### NNs as classifiers

- You already have linear regression, naive bayes, logistic regression, svm...
- Now you have neural nets too!

## Multilayer Perceptron




## Multilayer Perceptron



"Feed Forward Net"


"Fully Connected Layer"

## Multilayer Perceptron




Arbitrary, non-linear combinations of input features. No prior on the structure of those features.

# Convolutional Neural Net (CNN)




# Convolutional Neural Net (CNN)




Used for vision. Assumes spatial structure to the data.

#### Recurrent Neural Net (RNN)



#### Recurrent Neural Net (RNN)



Used for language (and other things). Assumes linear/temporal structure to the data.




 Train a model to do some task T1 (for which you have a lot of data)

- Train a model to do some task T1 (for which you have a lot of data)
- Let the model converge. Now your hidden states contain whatever features were good for T1

- Train a model to do some task T1 (for which you have a lot of data)
- Let the model converge. Now your hidden states contain whatever features were good for T1
- Maybe these features are good for some other task T2 too? Maybe you can now do T2 with less training?

## "Pretraining"

- Train a model to do some task T1 (for which you have a lot of data)
- Let the model converge. Now your hidden states contain whatever features were good for T1
- Maybe these features are good for some other task T2 too? Maybe you can now do T2 with less training?



#### Factorization of the term-context matrix

	the	congress	parliament	US	UK
the	1	1	1	1	1
congress	1	1	0	1	0
parlaiment	1	0	1	1	1
US UK	1	1	1	1	0
	1	0	1	0	1

#### the con- parlia- US UK Embeddings

the congress parlaiment US

US UK

1	1	1	1	1
1	1	0	1	0
1	0	1	1	1
1	1	1	1	
1	0	1	0	1


Embeddings!

the	-0.60
ongress	-0.48
parliament	-0.43
uS.	-0.48

	-0.60	-0.39	0.70	0.00
	-0.48	0.50	-0.12	-0.71
t	-0.43	-0.58	-0.69	0.00
	-0.48	0.50	-0.12	0.71
	0.02	0.79	0.02	-0.44
				i


-0.65	-0.34	-0.51	-0.34	-0.31
0.02	-0.54	0.34	-0.54	0.56
-0.42	0.02	0.79	0.02	-0.44
-0.63	0.27	0.00	0.37	0.63
-0.04	0.73	0.00	-0.68	0.04

one hot encoding, i.e.: the word "congress"





#### Word Embeddings predict one hot encoding of next word, i.e.:

the word "stagnated"




W2W1





Actually the same as the MF embeddings (assuming a linear network...)
Levy and Goldberg (2014)



Allows parameter sharing over similar words.


INPUT


For your homework: Skipgram

w(t-2) w(t-1) w(t) w(t+1) Given a word, predict the words that come to its left w(t+2) and right...

PROJECTION

OUTPUT





 Mostly require (massive!) supervised learning. Better use of deep RL/unsupervised pretraining?


- Mostly require (massive!) supervised learning. Better use of deep RL/unsupervised pretraining?
- Feature engineering has been replaced with architecture engineering/hyperparameter hacking. Metalearning?


- Mostly require (massive!) supervised learning. Better use of deep RL/unsupervised pretraining?
- Feature engineering has been replaced with architecture engineering/hyperparameter hacking. Metalearning?
- End-to-end-training hurts generalizability. Inductive biases on the hypothesis space?


- Mostly require (massive!) supervised learning. Better use of deep RL/unsupervised pretraining?
- Feature engineering has been replaced with architecture engineering/hyperparameter hacking. Metalearning?
- End-to-end-training hurts generalizability. Inductive biases on the hypothesis space?
- The <u>big</u> reason: its really really hard to formulate most problems as ML problems


Do you have a ton of data?


Do you have a ton of data?



























work.



bye:)