

Convolutional Networks 1

CS 287

Quiz

Neural language models can be poor at assigning very high probability to high confidence decisions, for instance `major league baseball` or `united states of america`.

Give a high-level explanation of why this might occur compared to an n-gram model. Describe a variant of the Bengio model that is able to incorporate extra parameters to allow for rare cases that should have high probability.

Answer

Dense + Sparse with important conjunction features.

Contents

Text Classification Review

Convolutions

Applications

Vision

Answer I

Sentiment

Good Sentences

- ▶ A thoughtful, provocative, insistently humanizing film.
- ▶ Occasionally melodramatic, it's also extremely effective.
- ▶ Guaranteed to move anyone who ever shook, rattled, or rolled.

Bad Sentences

- ▶ A sentimental mess that never rings true.
- ▶ This 100-minute movie only has about 25 minutes of decent material.
- ▶ Here, common sense flies out the window, along with the hail of bullets, none of which ever seem to hit Sascha.

Review Linear Models for Classification

Linear model,

$$\hat{\mathbf{y}} = f(\mathbf{x}\mathbf{W} + \mathbf{b})$$

- ▶ $\mathbf{W} \in \mathbb{R}^{d_{\text{in}} \times d_{\text{out}}}$, $\mathbf{b} \in \mathbb{R}^{1 \times d_{\text{out}}}$; model parameters
- ▶ $f : \mathbb{R}^{d_{\text{out}}} \mapsto \mathbb{R}^{d_{\text{out}}}$; activation function
- ▶ Sometimes $\mathbf{z} = \mathbf{x}\mathbf{W} + \mathbf{b}$ informally “score” vector.
- ▶ Note \mathbf{z} and $\hat{\mathbf{y}}$ are not one-hot.

Class prediction,

$$\hat{c} = \arg \max_{i \in \mathcal{C}} \hat{y}_i = \arg \max_{i \in \mathcal{C}} (\mathbf{x}\mathbf{W} + \mathbf{b})_i$$

Features 1: Sparse Bag-of-Words Features

Representation is counts of input words,

- ▶ \mathcal{F} ; the vocabulary of the language.
- ▶ $\mathbf{x} = \sum_i \delta(f_i)$

Example: Movie review input,

A sentimental mess

$$\begin{aligned}\mathbf{x} &= \delta(\text{word:A}) + \delta(\text{word:sentimental}) \\ &+ \delta(\text{word:mess})\end{aligned}$$

$$\mathbf{x}^\top = \begin{bmatrix} 1 \\ \vdots \\ 0 \\ 0 \end{bmatrix} + \begin{bmatrix} 0 \\ \vdots \\ 0 \\ 1 \end{bmatrix} + \begin{bmatrix} 0 \\ \vdots \\ 1 \\ 0 \end{bmatrix} = \begin{bmatrix} 1 \\ \vdots \\ 1 \\ 1 \end{bmatrix} \begin{matrix} \text{word:A} \\ \vdots \\ \text{word:mess} \\ \text{word:sentimental} \end{matrix}$$

Features 2: Sparse Bag-of-Bigrams Features

Representation is counts of input bigrams,

- ▶ \mathcal{F} ; the vocabulary of the bigram language.
- ▶ $\mathbf{x} = \sum_i \delta(f_i)$

Example: Movie review input,

A sentimental mess

$$\begin{aligned}\mathbf{x} &= \delta(\text{word:A}) + \delta(\text{bigram:A:sentimental}) \\ &+ \delta(\text{word:sentimental}) + \delta(\text{bigram:sentimental:mess}) \\ &+ \delta(\text{word:mess})\end{aligned}$$

Features 3: Continuous Bag-of-Words Features

$$\mathbf{x} = \sum_{i=1}^k v(f_i; \theta) = \sum_{i=1}^k \delta(f_i) \mathbf{w}^0$$

- ▶ \mathcal{F} ; the vocabulary of the language.
- ▶ $\mathbf{x} = \sum_i \delta(f_i)$

Example: Movie review input,

$$\mathbf{x} = v(\text{word:A}) + v(\text{word:sentimental}) + v(\text{word:mess})$$

$$\mathbf{x}^\top = \begin{bmatrix} 0.2 \\ \vdots \\ 1.2 \\ -0.5 \end{bmatrix} + \begin{bmatrix} 0.8 \\ \vdots \\ 1.0 \\ -1.0 \end{bmatrix} + \begin{bmatrix} 0.1 \\ \vdots \\ 9.2 \\ -2.0 \end{bmatrix} = \begin{bmatrix} 1.1 \\ \vdots \\ 11.4 \\ -3.5 \end{bmatrix}$$

Features 4: Continuous Bag-of-Bigrams Features?

Representation is counts of input bigrams,

- ▶ \mathcal{F} ; the vocabulary of the bigram language.
- ▶ $\mathbf{x} = \sum_i \delta(f_i)$

Example: Movie review input,

A sentimental mess

$$\begin{aligned}\mathbf{x} &= v(\text{word:A}) + v_2(\text{bigram:A:sentimental}) \\ &+ v(\text{word:sentimental}) + v_2(\text{bigram:sentimental:mess}) \\ &+ v(\text{word:mess})\end{aligned}$$

Neural Network

One-layer multi-layer perceptron architecture,

$$NN_{MLP1}(\mathbf{x}) = g(\mathbf{x}\mathbf{W}^1 + \mathbf{b}^1) \mathbf{W}^2 + \mathbf{b}^2$$

- ▶ $\mathbf{x}\mathbf{W} + \mathbf{b}$; *perceptron*
- ▶ \mathbf{x} is the dense representation in $\mathbb{R}^{1 \times d_{\text{in}}}$
- ▶ $\mathbf{W}^1 \in \mathbb{R}^{d_{\text{in}} \times d_{\text{hid}}}$, $\mathbf{b}^1 \in \mathbb{R}^{1 \times d_{\text{hid}}}$; first affine transformation
- ▶ $\mathbf{W}^2 \in \mathbb{R}^{d_{\text{hid}} \times d_{\text{out}}}$, $\mathbf{b}^2 \in \mathbb{R}^{1 \times d_{\text{out}}}$; second affine transformation
- ▶ $g : \mathbb{R}^{d_{\text{hid}} \times d_{\text{hid}}}$ is an *activation non-linearity* (often pointwise)
- ▶ $g(\mathbf{x}\mathbf{W}^1 + \mathbf{b}^1)$ is the *hidden layer*

Contents

Text Classification Review

Convolutions

Applications

Vision

Windowed Classification

Alternative method, windows into MLP.

Goal: predict t_5 .

- ▶ Windowed word model.

$$w_1 \ w_2 \ [w_3 \ w_4 \ w_5 \ w_6 \ w_7] \ w_8$$

- ▶ w_3, w_4 ; left context
- ▶ w_5 ; Word of interest
- ▶ w_6, w_7 ; right context
- ▶ d_{win} ; size of window ($d_{\text{win}} = 5$)

All Window for Classification

Idea: Use window at each location.

$$\begin{bmatrix} w_1 & w_2 & w_3 & w_4 & w_5 \end{bmatrix} w_6 \ w_7 \ w_8$$

$$w_1 \begin{bmatrix} w_2 & w_3 & w_4 & w_5 & w_6 \end{bmatrix} w_7 \ w_8$$

$$w_1 \ w_2 \begin{bmatrix} w_3 & w_4 & w_5 & w_6 & w_7 \end{bmatrix} w_8$$

\vdots

Each maps from window of embeddings to d_{hid}

Convolution Formally

Let our input be the embeddings of the full sentence, $\mathbf{X} \in \mathbb{R}^{n \times d^0}$

$$\mathbf{X} = [v(w_1), v(w_2), v(w_3), \dots, v(w_n)]$$

Define a window model as $NN_{window} : \mathbb{R}^{1 \times (d_{win} d^0)} \mapsto \mathbb{R}^{1 \times d_{hid}}$,

$$NN_{window}(\mathbf{x}_{win}) = \mathbf{x}_{win} \mathbf{W}^1 + \mathbf{b}^1$$

The convolution is defined as $NN_{conv} : \mathbb{R}^{n \times d^0} \mapsto \mathbb{R}^{(n-d_{win}+1) \times d_{hid}}$,

$$NN_{conv}(\mathbf{X}) = \tanh \begin{bmatrix} NN_{window}(\mathbf{X}_{1:d_{win}}) \\ NN_{window}(\mathbf{X}_{2:d_{win}+1}) \\ \vdots \\ NN_{window}(\mathbf{X}_{n-d_{win}+1:n}) \end{bmatrix}$$

Pooling

- ▶ Unfortunately $NN_{conv} : \mathbb{R}^{n \times d^0} \mapsto \mathbb{R}^{(n-d_{win}+1) \times d_{hid}}$.
- ▶ Need to map down to d_{out} for different n
- ▶ Recall pooling operations.
- ▶ Pooling “over-time” operations $f : \mathbb{R}^{n \times m} \mapsto \mathbb{R}^{1 \times m}$
 1. $f_{max}(\mathbf{X})_{1,j} = \max_i X_{i,j}$
 2. $f_{min}(\mathbf{X})_{1,j} = \min_i X_{i,j}$
 3. $f_{mean}(\mathbf{X})_{1,j} = \sum_i X_{i,j} / n$

$$f(\mathbf{X}) = \begin{bmatrix} \Downarrow & \Downarrow & \dots \\ \Downarrow & \Downarrow & \dots \\ & \vdots & \\ \Downarrow & \Downarrow & \dots \end{bmatrix} = [\dots]$$

Putting it together

$$\hat{y} = \text{softmax}(f_{\max}(NN_{\text{conv}}(\mathbf{X}))\mathbf{W}^2 + \mathbf{b}^2)$$


- ▶ $\mathbf{W}^2 \in \mathbb{R}^{d_{\text{hid}} \times d_{\text{out}}}$, $\mathbf{b}^2 \in \mathbb{R}^{1 \times d_{\text{out}}}$
- ▶ Final linear layer \mathbf{W}^2 uses learned window features

Multiple Convolutions

$$\hat{y} = \text{softmax}([f(NN_{conv}^1(\mathbf{X})), f(NN_{conv}^2(\mathbf{X})), \dots, f(NN_{conv}^f(\mathbf{X}))]\mathbf{W}^2 + \mathbf{b}^2)$$

- ▶ Concat several convolutions together.
- ▶ Each NN^1 , NN^2 , etc uses a different d_{win}
- ▶ Allows for different window-sizes (similar to multiple n-grams)

Convolution Diagram (Kim, 2014)



► $n = 9$, $d_{\text{hid}} = 4$, $d_{\text{out}} = 2$

► red- $d_{\text{win}} = 2$, blue- $d_{\text{win}} = 3$, (ignore back channel)

Convolutional Vocabulary

- ▶ **kernel size** or **filter width** ; window size d_{win}
- ▶ **filter**; column of matrix \mathbf{W}^1 in $\mathbb{R}^{(d^0 \times d_{\text{win}}) \times 1}$
- ▶ **feature map**; column of NN_{conv} , d_{hid} of these
- ▶ **fully-connected layer**; affine or linear + activation
- ▶ **random, static, non-static**; embedding layer setup

Classification Results

Model	MR	SST-1	SST-2	Subj	TREC	CR	MPQA
CNN-rand	76.1	45.0	82.7	89.6	91.2	79.8	83.4
CNN-static	81.0	45.5	86.8	93.0	92.8	84.7	89.6
CNN-non-static	81.5	48.0	87.2	93.4	93.6	84.3	89.5
CNN-multichannel	81.1	47.4	88.1	93.2	92.2	85.0	89.4
RAE (Socher et al., 2011)	77.7	43.2	82.4	—	—	—	86.4
MV-RNN (Socher et al., 2012)	79.0	44.4	82.9	—	—	—	—
RNTN (Socher et al., 2013)	—	45.7	85.4	—	—	—	—
DCNN (Kalchbrenner et al., 2014)	—	48.5	86.8	—	93.0	—	—
Paragraph-Vec (Le and Mikolov, 2014)	—	48.7	87.8	—	—	—	—

Contents

Text Classification Review

Convolutions

Applications

Vision


Language Applications: Semantic Role Labeling

He would n't accept anything of value from those he was writing about

[A0 He] [AM-MOD would] [AM-NEG n't] [V accept] [A1 anything of value] from [A2 those he was writing about]

- ▶ V: verb
- ▶ A0: acceptor
- ▶ A1: thing accepted
- ▶ A2: accepted-from
- ▶ A3:attribute
- ▶ AM-MOD: modal
- ▶ AM-NEG: negation

Other Language Applications (Collobert et al. 2011)



C&W SRL


- ▶ First given a verb w_i e.g. accept.
- ▶ Then consider a word w_j e.g. n't
- ▶ For a word w_k features are

$$v(w_k), v_2(\text{cap}(w_k)), v_3(i - k), v_4(j - k)$$

- ▶ Convolution over sentence is used to predict role.
- ▶ $O(n \times |\text{verbs}|)$ convolutions per sentence


Feed-forward NLM (Bengio, Ducharme, and Vincent 2003)

$$p(w_t | w_1, \dots, w_{t-1}) = \text{softmax}(\mathbf{P}\mathbf{h}_{t-1} + \mathbf{q})$$



NLM Issue

Issue: The fundamental unit of information is still the **word**



Separate embeddings for “trading”, “trade”, “trades”, etc.

Character-level CNN (CharCNN)

a b s u r d i t y

Character-level CNN (CharCNN)


$\mathbf{C} \in \mathbb{R}^{d \times l}$: Representation of *absurdity*

0.4	-0.8	2.2	0.1	0.5	-0.4	0.4	-0.4	0.1
0.1	1.2	1.5	-0.8	-1.5	0.2	0.1	1.2	0.7
0.2	0.1	-1.2	0.2	-0.2	0.3	0.2	-1.3	-0.1
-0.2	-0.5	0.1	0.2	-0.3	0.3	-0.1	1.0	-0.3

a b s u r d i t y


Character-level CNN (CharCNN)

$\mathbf{H} \in \mathbb{R}^{d \times w}$: Convolutional filter matrix of width $w = 3$




Character-level CNN (CharCNN)

$$\mathbf{f}[1] = \langle \mathbf{C}[:, 1:3], \mathbf{H} \rangle$$



Character-level CNN (CharCNN)

$$\mathbf{f}[1] = \langle \mathbf{C}[:, 1:3], \mathbf{H} \rangle$$




Character-level CNN (CharCNN)

$$\mathbf{f}[2] = \langle \mathbf{C}[* , 2 : 4], \mathbf{H} \rangle$$





Character-level CNN (CharCNN)

$$\mathbf{f}[T-2] = \langle \mathbf{C}[* , T-2 : T], \mathbf{H} \rangle$$



Character-level CNN (CharCNN)

$$y[1] = \max_i \{f[i]\}$$




Character-level CNN (CharCNN)

Each filter picks out a character n -gram




Character-level CNN (CharCNN)

$$\mathbf{f}'[1] = \langle \mathbf{C}[* , 1 : 2], \mathbf{H}' \rangle$$




Character-level CNN (CharCNN)

$$y[2] = \max_i \{f'[i]\}$$



Character-level CNN (CharCNN)

Many filter matrices (25–200) per width (1–7)



Learned Word Representations (In Vocab)

(Based on cosine similarity)

	In Vocabulary				
	<i>while</i>	<i>his</i>	<i>you</i>	<i>richard</i>	<i>trading</i>
Word Embedding	<i>although</i>	<i>your</i>	<i>conservatives</i>	<i>jonathan</i>	<i>advertised</i>
	<i>letting</i>	<i>her</i>	<i>we</i>	<i>robert</i>	<i>advertising</i>
	<i>though</i>	<i>my</i>	<i>guys</i>	<i>neil</i>	<i>turnover</i>
	<i>minute</i>	<i>their</i>	<i>i</i>	<i>nancy</i>	<i>turnover</i>
Characters (before highway)	<i>chile</i>	<i>this</i>	<i>your</i>	<i>hard</i>	<i>heading</i>
	<i>whole</i>	<i>hhs</i>	<i>young</i>	<i>rich</i>	<i>training</i>
	<i>meanwhile</i>	<i>is</i>	<i>four</i>	<i>richer</i>	<i>reading</i>
	<i>white</i>	<i>has</i>	<i>youth</i>	<i>richter</i>	<i>leading</i>
Characters (after highway)	<i>meanwhile</i>	<i>hhs</i>	<i>we</i>	<i>eduard</i>	<i>trade</i>
	<i>whole</i>	<i>this</i>	<i>your</i>	<i>gerard</i>	<i>training</i>
	<i>though</i>	<i>their</i>	<i>doug</i>	<i>edward</i>	<i>traded</i>
	<i>nevertheless</i>	<i>your</i>	<i>i</i>	<i>carl</i>	<i>trader</i>

Learned Word Representations (In Vocab)

(Based on cosine similarity)

	In Vocabulary				
	<i>while</i>	<i>his</i>	<i>you</i>	<i>richard</i>	<i>trading</i>
Word Embedding	<i>although</i>	<i>your</i>	<i>conservatives</i>	<i>jonathan</i>	<i>advertised</i>
	<i>letting</i>	<i>her</i>	<i>we</i>	<i>robert</i>	<i>advertising</i>
	<i>though</i>	<i>my</i>	<i>guys</i>	<i>neil</i>	<i>turnover</i>
	<i>minute</i>	<i>their</i>	<i>i</i>	<i>nancy</i>	<i>turnover</i>
Characters (before highway)	<i>chile</i>	<i>this</i>	<i>your</i>	<i>hard</i>	<i>heading</i>
	<i>whole</i>	<i>hhs</i>	<i>young</i>	<i>rich</i>	<i>training</i>
	<i>meanwhile</i>	<i>is</i>	<i>four</i>	<i>richer</i>	<i>reading</i>
	<i>white</i>	<i>has</i>	<i>youth</i>	<i>richter</i>	<i>leading</i>
Characters (after highway)	<i>meanwhile</i>	<i>hhs</i>	<i>we</i>	<i>eduard</i>	<i>trade</i>
	<i>whole</i>	<i>this</i>	<i>your</i>	<i>gerard</i>	<i>training</i>
	<i>though</i>	<i>their</i>	<i>doug</i>	<i>edward</i>	<i>traded</i>
	<i>nevertheless</i>	<i>your</i>	<i>i</i>	<i>carl</i>	<i>trader</i>

Learned Word Representations (OOV)


Out-of-Vocabulary			
	<i>computer-aided</i>	<i>misinformed</i>	<i>loooooook</i>
Characters (before highway)	<i>computer-guided</i>	<i>informed</i>	<i>look</i>
	<i>computerized</i>	<i>performed</i>	<i>cook</i>
	<i>disk-drive</i>	<i>transformed</i>	<i>looks</i>
	<i>computer</i>	<i>inform</i>	<i>shook</i>
Characters (after highway)	<i>computer-guided</i>	<i>informed</i>	<i>look</i>
	<i>computer-driven</i>	<i>performed</i>	<i>looks</i>
	<i>computerized</i>	<i>outperformed</i>	<i>looked</i>
	<i>computer</i>	<i>transformed</i>	<i>looking</i>

Learned Word Representations (OOV)

Out-of-Vocabulary			
Characters (before highway)	<i>computer-aided</i>	<i>misinformed</i>	<i>loooooook</i>
	<i>computer-guided</i>	<i>informed</i>	<i>look</i>
	<i>computerized</i>	<i>performed</i>	<i>cook</i>
	<i>disk-drive</i>	<i>transformed</i>	<i>looks</i>
	<i>computer</i>	<i>inform</i>	<i>shook</i>
Characters (after highway)	<i>computer-guided</i>	<i>informed</i>	<i>look</i>
	<i>computer-driven</i>	<i>performed</i>	<i>looks</i>
	<i>computerized</i>	<i>outperformed</i>	<i>looked</i>
	<i>computer</i>	<i>transformed</i>	<i>looking</i>


Convolutional Filters

For each filter, visualize 100 substrings with the highest filter response




Convolutional Filters

For each filter, visualize 100 substrings with the highest filter response



Character N -gram Representations



Prefixes, Suffixes, Hyphenated, Others

Prefixes: character n -grams that start with 'start-of-word' character, such as $\{un, \{mis$. Suffixes defined similarly.

Contents


Text Classification Review

Convolutions

Applications

Vision

Visual Classification



Speech Convolutions

softmax
fully connected, 4096
fully connected, 4096
max pooling, $2 \times$
convolution, 3×3 , 384
convolution, 3×3 , 384
convolution, 3×3 , 384
max pooling, 2×2
convolution, 3×3 , 192
convolution, 3×3 , 192
convolution, 3×3 , 192
max pooling, 2×2
convolution, 3×3 , 96
convolution, 3×3 , 96
input (31x41)

Visual Convolution

