

Sequence Models 3

CS 287

Review: Markov Models

- ▶ In general, intractable to solve sequence prediction,

$$\arg \max_{c_{1:n}} f(\mathbf{x}, c_{1:n})$$

- ▶ Today, focus on (first-order) Markov models,


$$f(\mathbf{x}, c_{1:n}) = \sum_{i=1}^n \log \hat{y}(c_{i-1})_{c_i}$$

- ▶ Can extend these ideas to higher-order models.

$$f(\mathbf{x}, c_{1:n}) = \sum_{i=1}^n \log \hat{y}(c_{i-2}, c_{i-1})_{c_i}$$


Review: Greedy Search

$$f(\mathbf{x}, c_{1:n}) = \sum_{i=1}^n \log \hat{y}(c_{i-1})_{c_i}$$




Review: Greedy Search

$$f(\mathbf{x}, c_{1:n}) = \sum_{i=1}^n \log \hat{y}(c_{i-1})_{c_i}$$




Review: Greedy Search

$$f(\mathbf{x}, c_{1:n}) = \sum_{i=1}^n \log \hat{y}(c_{i-1})_{c_i}$$




Review: Greedy Search

$$f(\mathbf{x}, c_{1:n}) = \sum_{i=1}^n \log \hat{y}(c_{i-1})_{c_i}$$




Review: Greedy Search

$$f(\mathbf{x}, c_{1:n}) = \sum_{i=1}^n \log \hat{y}(c_{i-1})_{c_i}$$



Review: Dynamic Programming over a Lattice

- ▶ Several different varieties: Viterbi, forward, backward
- ▶ Recursive Definition:
 - ▶ Base Case: Start with the score for sequence of length 1.
 - ▶ Inductive Case: Compute all sequences of length i from $i - 1$



Review: Viterbi Algorithm

procedure VITERBI

$\pi \in \mathbb{R}^{(n+1) \times \mathcal{C}}$ initialized to $-\infty$

$\pi[0, \langle s \rangle] = 0$

for $i = 1$ to n **do**

for $c_i \in \mathcal{C}$ **do**

$\pi[i, c_i] = \max_{c_{i-1}} \pi[i-1, c_{i-1}] + \log \hat{y}(c_{i-1})_{c_i}$

return $\max_{c_n \in \mathcal{C}} \pi[n, c_n]$

- ▶ Time Complexity?
- ▶ Space Complexity?

Quiz: Reverse it

Each of the algorithms goes left-to-right (forward) when producing a sequence. Sometimes you can derive right-to-left versions of these algorithms. Consider right-to-left cases of the following. Which are possible to run, how does the algorithm change, and do you get the same solutions?

1. Right-to-left greedy search on a Markov model.
2. Right-to-left Viterbi search on a Markov model.
3. Right-to-left greedy search on an RNN model

Answer: R-to-L Greedy Search

- ▶ In general, may not work.
- ▶ May require computing and renormalizing one step in the past ($O(|\mathcal{C}|^2)$)
- ▶ Likely gives a different solution than forward greedy.

procedure GREEDYSEARCH

$s = 0$

▷ Running score

$c_{n+1} = \langle /s \rangle$

▷ Final Symbol

for $i = n$ to 1 **do**

$c_i \leftarrow \arg \max_{c'_i} \hat{y}(c'_i)_{c_{i+1}}$

$s \leftarrow s + \log \hat{y}(c_i)_{c_{i+1}}$

return c, s

Answer: R-to-L Greedy Search (worst-case)

$$f(\mathbf{x}, c_{1:n}) = \sum_{i=1}^n \log \hat{y}(c_{i-1})_{c_i}$$

O
I-PER
I-ORG
I-LOC

Mayor

O
I-PER
I-ORG
I-LOC

DeBlasio


O
I-PER
I-ORG
I-LOC

from

O	O
I-PER	I-PER
I-ORG	I-ORG
I-LOC	I-LOC


New

York




Answer: R-to-L Greedy Search (worst-case)

$$f(\mathbf{x}, c_{1:n}) = \sum_{i=1}^n \log \hat{y}(c_{i-1})_{c_i}$$




Answer: R-to-L Greedy Search (worst-case)

$$f(\mathbf{x}, c_{1:n}) = \sum_{i=1}^n \log \hat{y}(c_{i-1})_{c_i}$$




Answer: R-to-L Greedy Search (worst-case)

$$f(\mathbf{x}, c_{1:n}) = \sum_{i=1}^n \log \hat{y}(c_{i-1})_{c_i}$$



Answer: R-to-L Greedy Search (worst-case)

$$f(\mathbf{x}, c_{1:n}) = \sum_{i=1}^n \log \hat{y}(c_{i-1})_{c_i}$$



Answer: Backward Viterbi

- ▶ Same speed, same results.
- ▶ Similar inductive rule applies.
- ▶ Construct sequences starting at the end.

procedure BACKWARDVITERBI

$\pi \in \mathbb{R}^{(n+1) \times \mathcal{C}}$ initialized to $-\infty$

$\pi[n+1, \langle /s \rangle] = 0$


for $i = n$ to 1 **do**

for $c_i \in \mathcal{C}$ **do**


$\pi[i, c_i] = \max_{c'_{i+1}} \pi[i+1, c'_{i+1}] + \log \hat{y}(c_i)_{c'_{i+1}}$

return $\max_{c_1 \in \mathcal{C}} \pi[1, c_1]$


Backward Viterbi




Backward Viterbi




Mayor



DeBlasio




from




New

York


Backward Viterbi



Mayor



DeBlasio




from


New

York

Backward Viterbi



Backward Viterbi



Answer: Right-to-Left Greedy RNN

- ▶ Does not work.
- ▶ Have suffix $c_n \dots c_i$ but RNN is prefix-function $\hat{\mathbf{y}}(c_1, \dots c_i)$.
- ▶ Backward greedy would require enumerating all prefixes.

Alternative Solution: Backward RNN

- ▶ Can train RNN in the reverse direction.
- ▶ RNN suffix transducer trained on $\hat{\mathbf{y}}(c_n, \dots c_i)$.
- ▶ However note this is a **different** model.
- ▶ Even if you had exact search, this may yield a different output.

Today's Lecture

- ▶ More Dynamic Programming
 - ▶ Max-Marginals
 - ▶ Forward-Backward
 - ▶ Probabilistic Marginals
 - ▶ Pruning
- ▶ Next Lecture: Conditional Random Fields

Question 1: Tag Fill-In

Assume we are given $c_{1:i-1}$ and $c_{i+1:n}$,

O	O	O	O	O
I-PER	I-PER	I-PER	I-PER	I-PER
I-ORG	I-ORG	I-ORG	I-ORG	I-ORG
I-LOC	I-LOC	I-LOC	I-LOC	I-LOC
Mayor	DeBlasio	from	New	York

What is the best completion, i.e.

$$\arg \max_{c'_i} f(\mathbf{x}, c_{1:i-1} : c'_i : c_{i+1:n})$$

Question 1: Tag Fill-In

Assume we are given $c_{1:i-1}$ and $c_{i+1:n}$,

O	O	O	O	O
I-PER	I-PER	I-PER	I-PER	I-PER
I-ORG	I-ORG	I-ORG	I-ORG	I-ORG
I-LOC	I-LOC	I-LOC	I-LOC	I-LOC
Mayor	DeBlasio	from	New	York

What is the best completion, i.e.

$$\arg \max_{c'_i} f(\mathbf{x}, c_{1:i-1} : c'_i : c_{i+1:n})$$

Answer

- ▶ Markov model. Score involving c_i are local (c_{i-1} and c_{i+1}).
- ▶ Can solve by looking one-step forward and backward

$$\arg \max_{c'_i} f(\mathbf{x}, c_{1:n}) = \arg \max_{c'_i} \log \hat{y}(c_{i-1})_{c'_i} + \log \hat{y}(c'_i)_{c_{i+1}}$$

- ▶ Can be solved in $O(|\mathcal{C}|)$ or $O(|\mathcal{C}|^2)$ depending on model.

Exercise 2: Sequence fill-in

Assume we **are not** given $c_{1:i-1}$ and $c_{i+1:n}$,

O	O	O	O	O
I-PER	I-PER	I-PER	I-PER	I-PER
I-ORG	I-ORG	I-ORG	I-ORG	I-ORG
I-LOC	I-LOC	I-LOC	I-LOC	I-LOC
Mayor	DeBlasio	from	New	York

What is the score of the max sequence through each tag, i.e.

$$M(i, c'_i) = \max_{c_{1:i-1}, c_{i+1:n}} f(\mathbf{x}, c_{1:i-1} : c'_i : c_{i+1:n})$$

Answer

- ▶ Markov property. Two prefix and suffix score can be independent.
- ▶

$$\begin{aligned} M(i, c'_i) &= \max_{c_{1:i-1}:c_{i+1:n}} f(\mathbf{x}, c_{1:i-1} : c'_i : c_{i+1:n}) \\ &= \max_{c_{1:i-1}} \log \hat{y}(c'_{i-1})_{c'_i} + \sum_{j=1}^i \log \hat{y}(c_{j-1})_{c_j} \\ &\quad + \max_{c_{i+1:n}} \log \hat{y}(c'_i)_{c_{i+1}} + \sum_{j=i+1}^n \log \hat{y}(c_j)_{c_{j+1}} \end{aligned}$$

Viterbi Forward-Backward


$$\begin{aligned} & \max_{c_{1:i-1}} \log \hat{y}(c'_{i-1})_{c'_i} + \sum_{j=1}^i \log \hat{y}(c_{j-1})_{c_j} \\ & + \max_{c_{i+1:n}} \log \hat{y}(c'_i)_{c_{i+1}} + \sum_{j=i+1}^n \log \hat{y}(c_j)_{c_{j+1}} \end{aligned}$$

- Forward Viterbi scores (max prefix)

$$\pi^\alpha[i, c'_i] = \max_{c_{1:i-1}} \log \hat{y}(c'_{i-1})_{c'_i} + \sum_{j=1}^i \log \hat{y}(c_{j-1})_{c_j}$$

- Backward Viterbi scores (max suffix)

$$\pi^\beta[i, c'_i] = \max_{c_{i+1:n}} \log \hat{y}(c'_i)_{c_{i+1}} + \sum_{j=i+1}^n \log \hat{y}(c_j)_{c_{j+1}}$$



Mayor

DeBlasio

from

New

York


Computing All Max-Marginals

$$\arg \max_{c_i} \max_{c_{1:i-1}:c_{i+1:n}} f(\mathbf{x}, c_{1:n})$$

- ▶ Compute π^α using Viterbi forward
- ▶ Compute π^β using Viterbi backward
- ▶ Compute the argmax


$$M(i, c'_i) = \pi^\alpha[i, c'_i] + \pi^\beta[i, c'_i]$$

- ▶ Time complexity?
- ▶ Space complexity?




Mayor


DeBlasio




from



New




York




Mayor

DeBlasio


from




New



York






Mayor

DeBlasio

from

New

York




Mayor

DeBlasio

from

New

York




Mayor

DeBlasio

from

New

York




Mayor

DeBlasio

from

New

York



Mayor

DeBlasio

from

New

York


Max-Marginals with Backpointers

- ▶ Can also include forward and backward backpointers
- ▶ Get best sequence through any tag in $O(n|\mathcal{C}|^2)$.

Max-Marginal Property


If c_i^* is part of highest-scoring sequence then max-marginal at $M(i, c_i^*)$ is $\max_{c_{1:n}} f(\mathbf{x}, c_{1:n})$ and by definition is at least as large as any other max-marginal $M(j, c_j)$ for all j, c_j .

Pruning by Bounding (Sketch)



- ▶ First run greedy over full problem.
- ▶ Score $s^{(greedy)}$ is less than optimal.


Pruning by Bounding (Sketch)



- ▶ Each edge is the **max** of the edges in the full lattice.
- ▶ Can compute max-marginals M in much less time.

Pruning by Bounding (Sketch)

- ▶ For all j, c_j , if $M(j, c_j) < s^{greedy}$ can prune.
- ▶ Running Viterbi over pruned lattice is provably optimal.



Contents

Probabilistic Models

Marginals

Let us return to the case of discriminative probabilistic models.

- ▶ Model of

$$p(\mathbf{y} = \delta(c_{1:n}) | \mathbf{x})$$



Exercise 3: Smoothing

Assume we are given $c_{1:i-1}$ and $c_{i+1:n}$,

O	O	O	O	O
I-PER	I-PER	I-PER	I-PER	I-PER
I-ORG	I-ORG	I-ORG	I-ORG	I-ORG
I-LOC	I-LOC	I-LOC	I-LOC	I-LOC
Mayor	DeBlasio	from	New	York

What is the probability of \mathbf{y}_i , i.e.

$$p(\mathbf{y}_i = \delta(c_i) | \mathbf{y}_{1:i-1} = \delta(c_{1:i-1}), \mathbf{y}_{i+1:n} = \delta(c_{i+1:n}), \mathbf{x})$$

Answer

- ▶ Same idea. Score involving c_i are local ($i - 1$ and $i + 1$).
- ▶ Can compute “smoothing” distribution from local information

$$\begin{aligned} p(\mathbf{y}_i = \delta(c_i) | \mathbf{y}_{1:i-1}, \mathbf{y}_{i+1:n}, \mathbf{x}) &\propto p(\mathbf{y}_i | \mathbf{y}_{i-1}) p(\mathbf{y}_{i+1} | \mathbf{y}_i) \\ &= \hat{y}(c_{i-1})_{c'_i} \hat{y}(c'_i)_{c_{i+1}} \end{aligned}$$

Exercise 4

Assume we **are not** given $c_{1:i-1}$ and $c_{i+1:n}$.

O	O	O	O	O
I-PER	I-PER	I-PER	I-PER	I-PER
I-ORG	I-ORG	I-ORG	I-ORG	I-ORG
I-LOC	I-LOC	I-LOC	I-LOC	I-LOC
Mayor	DeBlasio	from	New	York

What is the best completed sequence, i.e.

$$p(\mathbf{y}_i = \delta(c_i) | \mathbf{x})$$

Answer: Marginalization

- Similar idea. Score involving c_i are local ($i - 1$ and $i + 1$).

$$\begin{aligned} p(\mathbf{y}_i = \delta(c'_i) | \mathbf{x}) &= \sum_{c_{1:i-1}:c_{i+1:n}} p(\mathbf{y}_i = \delta(c'_i), \mathbf{y}_{1:i-1, i+1:n} | \mathbf{x}) \\ &= \sum_{c_{1:i-1}} p(\mathbf{y}_{1:i-1} | \mathbf{x}) p(\mathbf{y}_i = \delta(c'_i) | \mathbf{y}_{i-1}, \mathbf{x}) \\ &\times \sum_{c_{i+1:n}} p(\mathbf{y}_{i+1} | \mathbf{y}_i =, \mathbf{x}) p(\mathbf{y}_{i+1:n} | \mathbf{x}) \\ &= \sum_{c_{1:i-1}} \hat{y}(c_{i-1})_{c'_i} \prod_{j=1}^{i-1} \hat{y}(c_{j-1})_{c_j} \\ &\times \sum_{c_{i+1:n}} \hat{y}(c'_i)_{c_{i+1}} \prod_{j=i+1}^n \hat{y}(c_j)_{c_{j+1}} \end{aligned}$$

Answer: Marginalization

- Similar idea. Score involving c_i are local ($i - 1$ and $i + 1$).

$$\begin{aligned} p(\mathbf{y}_i = \delta(c'_i) | \mathbf{x}) &= \sum_{c_{1:i-1}:c_{i+1:n}} p(\mathbf{y}_i = \delta(c'_i), \mathbf{y}_{1:i-1, i+1:n} | \mathbf{x}) \\ &= \sum_{c_{1:i-1}} p(\mathbf{y}_{1:i-1} | \mathbf{x}) p(\mathbf{y}_i = \delta(c'_i) | \mathbf{y}_{i-1}, \mathbf{x}) \\ &\times \sum_{c_{i+1:n}} p(\mathbf{y}_{i+1} | \mathbf{y}_i, \mathbf{x}) p(\mathbf{y}_{i+1:n} | \mathbf{x}) \\ &= \sum_{c_{1:i-1}} \hat{y}(c_{i-1})_{c'_i} \prod_{j=1}^{i-1} \hat{y}(c_{j-1})_{c_j} \\ &\times \sum_{c_{i+1:n}} \hat{y}(c'_i)_{c_{i+1}} \prod_{j=i+1}^n \hat{y}(c_j)_{c_{j+1}} \end{aligned}$$

Forward and Backward

- ▶ Forward scores (sum over prefixes)

$$\alpha[i, c'_i] = \sum_{c_{1:i-1}} \hat{y}(c_{i-1})_{c'_i} \prod_{j=1}^{i-1} \hat{y}(c_{j-1})_{c_j}$$

- ▶ Backward scores (sum over suffixes)

$$\beta[i, c'_i] = \sum_{c_{i+1:n}} \hat{y}(c'_i)_{c_{i+1}} \prod_{j=i+1}^n \hat{y}(c_j)_{c_{j+1}}$$

Forward Algorithm

procedure FORWARD

$$\alpha \in \mathbb{R}^{\{0, \dots, n\} \times \mathcal{C}}$$

$$\alpha[0, \langle s \rangle] = 1$$

for $i = 1$ to n **do**

for $c_i \in \mathcal{C}$ **do**

$$\alpha[i, c_i] = \sum_{c_{i-1}} \alpha[i-1, c_{i-1}] \times \hat{y}(c_{i-1})_{c_i}$$

return α

Backward Algorithm

procedure BACKWARD

$\beta \in \mathbb{R}^{\{1, \dots, n+1\} \times \mathcal{C}}$

$\beta[n+1, \langle s \rangle] = 1$


for $i = n$ to 1 **do**

for $c_i \in \mathcal{C}$ **do**

$\beta[i, c_i] = \sum_{c_{i+1}} \beta[i+1, c_{i+1}] \times \hat{y}(c_i)_{c_{i+1}}$

return β

Exercise 5: Edge Marginals



What is the probability of using an edge, i.e.

$$p(\mathbf{y}_i = \delta(c'_i), \mathbf{y}_{i+1} = \delta(c'_{i+1}), |\mathbf{x})$$


Edge Marginals

$$\hat{y}(c'_i)_{c'_{i+1}} \times \sum_{c_{1:i-1}} \hat{y}(c_{i-1})_{c'_i} \prod_{j=1}^{i-1} \hat{y}(c_{j-1})_{c_j} \\ \times \sum_{c_{i+2:n}} \hat{y}(c'_{i+1})_{c_{i+1}} \prod_{j=i+1}^n \hat{y}(c_j)_{c_{j+1}}$$

- ▶ Compute α using Forward
- ▶ Compute β using Backward
- ▶ Multiply in the edge

$$\hat{y}(c'_i)_{c'_{i+1}} \alpha[i, c'_i] \times \beta[i+1, c'_{i+1}]$$

Edge Marginal



Marginals versus Max-Marginals

- ▶ Max-Marginals: Most-likely sequence through decision
- ▶ Marginals: Sum of sequences through decision.
- ▶ Possibly very different values.
- ▶ Edge with highest marginal may not be in best sequence.

Edge Marginal Decoding

- ▶ For all i

$$p(y_i = \delta(c_i), y_{i+1} = \delta(c_{i+1}) | \mathbf{x})$$

- ▶ But this is a Markov model!
- ▶ Replace lattice with edge marginals

$$f(\mathbf{x}, c_{1:n}) = \sum_i \log p(y_i = \delta(c_i), y_{i+1} = \delta(c_{i+1}) | \mathbf{x})$$

- ▶ Posterior decoding.

$$\arg \max_{c_{1:n}} f(\mathbf{x}, c_{1:n})$$