


| SN | Program | Page No. |
|-----------|--|-----------------|
| 1 | Write a C++ program to draw a circle. | 2 |
| 2 | Circle through Midpoint Algorithm | 3 |
| 3 | Ellipse Program | 6 |
| 4 | Full Graph Program | 8 |
| 5 | Different Functions at Object | 9 |
| 6 | Draw a Line with the help of C++ program. | 12 |
| 7 | Another C++ program to draw a line at different points. | 13 |
| 8 | C++ program to draw a graphical image (lineCode). | 14 |
| 9 | C++ program to move a circle along the screen. | 22 |
| 10 | C++ program to draw a moving circle. | 24 |
| 11 | C++ program to draw a rectangle. | 26 |
| 12 | C++ program to draw a square. | 27 |
| 13 | Write a C++ program that draws 2D and 3D rectangles with patterns and colors on Windows BGI using bar() and bar3d() functions in graphical programming. | 28 |
| 14 | Write a C++ program that draws an arc and ellipse on BGI Window using ellipse() and fillellipse() functions in graphical programming. | 29 |
| 15 | Write a program that draws ellipse and circle with patterns and colors on Windows BGI using setfillstyle() and floodfill() functions in graphical programming. | 30 |

1. Write a C++ program to draw a circle.

```
#include <graphics.h>
#include <stdlib.h>
#include <stdio.h>
#include <conio.h>
int main(void)
{
    /* request auto detection */
    int gdriver = DETECT, gmode, errorcode;
    int midx, midy;
    /* initialize graphics and local variables */
    initgraph(&gdriver, &gmode, "C:\\\\TURBOC3\\\\BGI");
    /* read result of initialization */
    errorcode = graphresult();
    if (errorcode != grOk) /* an error occurred */
    {
        printf("Graphics error: %s\\n", grapherrormsg(errorcode));
        printf("Press any key to halt:");
        getch();
        exit(1); /* terminate with an error code */
    }
    setcolor(getmaxcolor());
    /* draw the circle */
    circle(200,200, 100);
    /* clean up */
    getch();
    closegraph();
    return 0;
}
```



2. Circle through Midpoint Algorithm

```
#include <stdlib.h>
#include <graphics.h>
#include <math.h>
#include <conio.h>
#include <iostream>
using namespace std;
int xc, yc, showat=10;
char ruf[10];
void tellpoint(int *num1, int *num2)
{
    int color; color=getcolor();
    int a,b;
    a = xc+*num1; b = getmaxy()-yc+*num2;
    outtextxy(400,showat,itoa(a,ruf,10)); outtextxy(422,showat,","); outtextxy(429,showat,itoa(b,ruf,10));
    a=xc-*num1; b=getmaxy()-yc+*num2; setcolor(10);
    outtextxy(455,showat,itoa(a,ruf,10)); outtextxy(477,showat,","); outtextxy(484,showat,itoa(b,ruf,10));
    a=xc+*num1; b=getmaxy()-yc-*num2; setcolor(20);
    outtextxy(510,showat,itoa(a,ruf,10)); outtextxy(532,showat,","); outtextxy(539,showat,itoa(b,ruf,10));
    a=xc-*num1; b=getmaxy()-yc-*num2; setcolor(30);

    outtextxy(565,showat,itoa(a,ruf,10)); outtextxy(587,showat,","); outtextxy(594,showat,itoa(b,ruf,10));
    showat+=10;
    a = xc+*num2; b = getmaxy()-yc+*num1; setcolor(110);

    outtextxy(400,showat,itoa(a,ruf,10)); outtextxy(422,showat,","); outtextxy(429,showat,itoa(b,ruf,10));
    a=xc+*num2; b=getmaxy()-yc-*num1; setcolor(70);
    outtextxy(455,showat,itoa(a,ruf,10)); outtextxy(477,showat,","); outtextxy(484,showat,itoa(b,ruf,10));
    a=xc-*num2; b=getmaxy()-yc+*num1; setcolor(140);
    outtextxy(510,showat,itoa(a,ruf,10)); outtextxy(532,showat,","); outtextxy(539,showat,itoa(b,ruf,10));
    a=xc-*num2; b=getmaxy()-yc-*num1; setcolor(150);
    outtextxy(565,showat,itoa(a,ruf,10)); outtextxy(587,showat,","); outtextxy(594,showat,itoa(b,ruf,10));
    setcolor(color); showat+=10;
```

```

}
void drawpoint(int x, int y)
{
    putpixel (xc+x, yc+y, 30);    putpixel (xc-x, yc+y, 30);    putpixel (xc+x, yc-y, 30);
    putpixel (xc-x, yc-y, 30);    putpixel (xc+y, yc+x, 30);    putpixel (xc-y, yc+x, 30);
    putpixel (xc+y, yc-x, 30);    putpixel (xc-y, yc-x, 30);
}
int main()
{
    int gdriver=DETECT, gmode, ecode;
    initgraph(&gdriver, &gmode, "c:\\Turboc3\\bgi");
    ecode = graphresult();
    if (ecode != grOk)
    {
        cout << "Graphic error ...";
        cout << "Press any key ...";
        getch();
        exit(1);
    }
    int x,y,r, Pk;
    char comma;
    cout <<"Enter the Radius of the circle :\\t";
    cin >> r;
    cout << "Enter the Center of the circle (x,y) :\\t";
    cin >>xc >>comma >>yc;
    yc = getmaxy()-yc;
    x=0;
    y=r;
    drawpoint(x,y);
    tellpoint(&x, &y);
    Pk = 1 - r;
    while (x<y)
    {
        if (Pk<0)
            x +=1;
        else
        {

```

```

x +=1;

        y -=1;

    }

    drawpoint(x,y);
    tellpoint(&x, &y);

```

```

if (Pk<0)

    Pk = Pk + 2*x +1;

else

    Pk = Pk + 2*(x-y) +1;

```

```

}

    getch();

    return 0;

}

```


Windows BGI

D:\#New\#dev\mine\Circle through MidPoint Algorithm\Circle through

```

Enter the Radius of the circle :      100
Enter the Center of the circle (x,y) : 100 100

```



3. Ellipse Program

```
#include <stdio.h>
#include <conio.h>
#include <iostream>
#include <graphics.h>
#include <stdlib.h>
#include <math.h>
#define ROUND(x) ((int)(x+0.5))
using namespace std;
float xc,yc,rx,ry;
void drawpoint(int x, int y){
    putpixel(xc+x,yc+y,10);
    putpixel(xc-x,yc+y,10);
    putpixel(xc+x,yc-y,10);
    putpixel(xc-x,yc-y,10);}
int main(){
    float x,y;
    int gdriver=DETECT, gmode, ecode;
    char comma;
    initgraph(&gdriver, &gmode, "C:\\TURBOC3\\BGI");
    /* read result of initialization */
    ecode = graphresult();
    if (ecode != grOk){
        printf("Graphics error:\n");
        printf("Press any key...");
        getch();
        exit(1);
    }
    float p;
    cout<<"Enter Center of Ellip (x,y): ";
    cin>>xc>>comma>>yc;
    cout<<"Enter Radius along X-Axis: ";
    cin>>rx;
    cout<<"Enter Radius along Y-Axis: ";
    cin>>ry;
    yc = getmaxy()-yc;
```

```


x=0;
y=ry;
drawpoint(x,y);
p=ROUND(ry*ry-rx*rx*ry+0.25*(rx*rx)); //ry2-rx2*ry+(.25*rx2)
while((ry*ry)*x<(rx*rx)*y)
{
    x=x+1;
    if(p>=0)
    {
        y=y-1;
        p=p+2*(ry*ry)*x+ry*ry-2*(rx*rx)*y;
    }
    else
    {
        p=p+2*(ry*ry)*x+ry*ry;
    }
    drawpoint(x,y);
}
p=ROUND(ry*ry*((x+.5)*(x+.5))+rx*rx*((y-1)*(y-1))-(rx*rx)*(ry*ry));
while(y>0)
{
    y=y-1;
    if(p<=0)
    {
        x=x+1;
        p=p-2*(rx*rx)*y+rx*rx+2*(ry*ry)*x;
    }
    else
    {
        p=p-2*(rx*rx)*y+rx*rx;
    }
    drawpoint(x,y);
}
getch();
closegraph();
}

```

```

D:\#New\#dev\mine\Ellipse\Ellipse.exe
Enter Center of Ellip (x,y): 50 50
Enter Radius along X-Axis: 100
Enter Radius along Y-Axis: 100

```



4. Full Graph Program

```
#include<iostream>
#include <graphics.h>
#include <stdlib.h>
#include <stdio.h>
#include <conio.h>
using namespace std;
int main(void)
{
    /* request auto detection */
    int gdriver = DETECT, gmode, errorcode;
    int xmax, ymax;
    /* initialize graphics and local variables */
    initgraph(&gdriver, &gmode, "C:\\\\TURBOC3\\\\BGI");
    /* read result of initialization */
    errorcode = graphresult();
    if (errorcode != grOk)
    {printf("Graphics error: %s\\n", grapherrormsg(errorcode));
      printf("Press any key to halt:");
      getch();
      exit(1); }
    setcolor(getmaxcolor());
    xmax = getmaxx();
    ymax = getmaxy();
    for(int i=10;i<xmax;i+=10)
    line(i,0,i,ymax);
    for(int i=10;i<ymax;i+=10)
    line(0,i,xmax,i);
    getch();
    closegraph();
    return 0;
}
```




5. Different Functions at Object

```
#include<iostream>
#include <graphics.h>
#include <stdlib.h>
#include <stdio.h>
#include <conio.h>
using namespace std;

int arr[10]={50,50, 50,100, 100,100, 100,50, 75,25};
int i;

void draw(){
    for(i=0;i<=6;i+=2)
        line(arr[i],arr[i+1],arr[i+2],arr[i+3]);
        line(arr[i],arr[i+1],arr[0],arr[1]); }

void translate(int tx, int ty){
    for(i=0;i<=8;i+=2)
        {arr[i]=arr[i]+tx;
```

```




        arr[i+1]=arr[i+1]+ty;}
    }
void scaling_inc(int sx, int sy){
    for(i=0;i<=8;i+=2){
        arr[i]=arr[i]*sx;
        arr[i+1]=arr[i+1]*sy;}
    }
void scaling_dec(int sx, int sy){
    for(i=0;i<=8;i+=2){
        arr[i]=arr[i]/sx;
        arr[i+1]=arr[i+1]/sy;}}
void rotate(float cos, float sin){
    for(i=0;i<=8;i+=2){
        arr[i]=(arr[i]*cos)-(arr[i+1]*sin);
        arr[i+1]=(arr[i+1]*cos)+(arr[i]*sin);}
    }
int main(void){
    int gdriver = DETECT, gmode, errorcode;
    int xmax, ymax;
    initgraph(&gdriver, &gmode, "C:\\\\TURBOC3\\\\BGI");
    errorcode = graphresult();
    if (errorcode != grOk){
        printf("Graphics error: %s\\n", grapherrormsg(errorcode));
        printf("Press any key to halt:");
        getch();
        exit(1);}
    char c;
    draw();
    do{    c=getch();
        switch(c){
            case '5':
                rotate(0.9396,0.3420);
                break;
            case '1':
                scaling_inc(2,2);
                break;
            case '3':

```

```


        scaling_dec(2,2);
        break;
        case '2':
            translate(0,10);
            break;
        case '6':
            translate(10,0);
            break;
        case '4':
            translate(-10,0);
            break;
        case '8':
            translate(0,-10);
            break;
    }
    cleardevice();
    draw();
}
while(c!='q');
getch();
closegraph();
return 0;
}

```



6. Draw a Line with the help of C++ program.

```
#include <iostream>
#include <graphics.h>
#include <stdlib.h>
#include <stdio.h>
#include <conio.h>
using namespace std;
int main(void)
{
    /* request auto detection */
    int gdriver=DETECT, gmode, errorcode;
    initgraph(&gdriver,&gmode,"C:\\\\TURBOC3\\\\BGI");
    int xmax, ymax;
    errorcode = graphresult();
    /* an error occurred */
    if (errorcode != grOk)
    {
        printf("Graphics error: %s\\n", grapherrormsg(errorcode));
        printf("Press any key to halt:");
        getch();
        exit(1);
    }
    setcolor(getmaxcolor());
    /* draw a diagonal line */
    line(50, 50, 100,100);
    cout<<"that was line";
    getch();
    closegraph();
    return 0;
}
```




7. Another C++ program to draw a line at different points.

```
#include <iostream>
#include <graphics.h>
#include <stdlib.h>
#include <stdio.h>
#include <conio.h>
using namespace std;
int main(void)
{
    int gdriver = DETECT, gmode, errorcode;
    int xmax, ymax;
    /* initialize graphics and local variables */
    initgraph(&gdriver, &gmode, "C:\\\\TURBOC3\\\\BGI");
    /* read result of initialization */
    errorcode = graphresult();
    /* an error occurred */
    if (errorcode != grOk)
    {
        printf("Graphics error: %s\\n", grapherrormsg(errorcode));
        printf("Press any key to halt:");
        getch();
        exit(1);
    }
    setcolor(getmaxcolor());

    /* draw a diagonal line */
    line(15, 50, 150, 200);

    /* clean up */
    cout<<"that was line";
    getch();
    closegraph();
    return 0;
}
```



8. C++ program to draw a graphical image (lineCode).

```
#include <graphics.h>
#include <stdlib.h>
#include <stdio.h>
#include <conio.h>
int main(void)
{
    /* request auto detection */
    int gdriver = DETECT, gmode, errorcode;
    int xmax, ymax;

    /* initialize graphics and local variables */
    initgraph(&gdriver, &gmode, "C:\\\\turbo3\\\\bgi");

    /* read result of initialization */
    errorcode = graphresult();
    /* an error occurred */
    if (errorcode != grOk)
    {
        printf("Graphics error: %s\\n", grapherrormsg(errorcode));
        printf("Press any key to halt:");
        getch();
        exit(1);
    }

    setcolor(getmaxcolor());
    xmax = getmaxx();
    ymax = getmaxy();

    /* draw a diagonal line */
    line(50, 450, 400, 450);
    line(75, 150, 60, 450);
    line(100, 150, 115, 450);
    line(375, 150, 390, 450);
    line(350, 150, 335, 450);
```

line(125,325,125,450);
line(325,325,325,450);

line(145,300,145,450);
line(305,300,305,450);

line(175,275,175,450);
line(275,275,275,450);

line(185,315,185,437);
line(265,315,265,437);
line(185,315,265,315);

line(195,325,195,437);
line(255,325,255,437);
line(195,325,255,325);

line(195,437,175,437);
line(255,437,275,437);

line(200,330,200,450);
line(250,330,250,450);
line(200,330,250,330);
line(200,370,250,370);
line(200,375,250,375);

line(205,380,205,450);
line(245,380,245,450);
line(205,380,245,380);
line(205,385,245,385);

line(125,350,145,340);
line(145,340,175,340);

line(275,340,305,340);

line(305,340,325,350);

line(150,360,170,360);

line(150,360,150,400);

line(170,360,170,400);

line(150,400,170,400);

line(130,365,140,360);

line(140,360,140,400);

line(130,365,130,405);

line(130,405,140,400);

line(150,410,170,410);

line(150,410,150,445);

line(170,410,170,445);

line(150,445,170,445);

line(140,410,140,445);

line(130,415,130,450);

line(130,415,140,410);

line(130,450,140,445);

//Right Windowz

line(280,360,300,360);

line(280,360,280,400);

line(300,360,300,400);

line(280,400,300,400);

line(280,410,300,410);

line(280,410,280,445);

line(300,410,300,445);

line(280,445,300,445);

line(310,360,310,400);

line(310,360,320,365);

line(310,360,310,400);

line(310,400,320,405);


```
line(320,365,320,405);
```

```
line(310,410,310,445);
```

```
line(320,415,320,450);
```

```
line(310,410,320,415);
```

```
line(310,445,320,450);
```

```
//tomb arc
```

```
arc(225,275,0,65,60);
```

```
arc(225,275,115,180,60);
```

```
//right little tomb
```

```
arc(325,325,0,180,5);
```

```
line(325,315,325,320);
```

```
line(323,325,327,325);
```

```
// Right menaar tomb....
```

```
arc(362.5,150,0,180,20);
```

```
line(343,150,382,150);
```

```
line(362.5,122,358,130);
```

```
line(362.5,122,366,130);
```

```
line(362.5,122,362.5,150);
```

```
arc(362.5,150,0,180,16);
```

```
arc(362.5,150,0,180,12);
```

```
arc(362.5,150,0,180,8);
```

```
arc(362.5,150,0,180,4);
```

```
// Left Menaar Tomb....
```

```
arc(87.5,150,0,180,20);
```

```
line(68,150,107,150);
```

```
line(87.5,122,87.5,150);
```

```
line(87.5,122,82.5,130);
```

```
line(87.5,122,92.5,130);
```

```
arc(87.5,150,0,180,16);
```

```
arc(87.5,150,0,180,12);
```

```
arc(87.5,150,0,180,8);
```

```
arc(87.5,150,0,180,4);
```

```
// left little tomb arc
```

```
arc(125,325,0,180,5);  
line(123,325,127,325);  
line(125,315,125,320);
```

```
arc(225,275,0,180,55);  
arc(225,275,0,180,50);  
arc(225,275,0,180,45);  
arc(225,275,0,180,40);  
arc(225,275,0,180,35);  
arc(225,275,0,180,30);  
arc(225,275,0,180,25);  
arc(225,275,0,180,20);  
arc(225,275,0,180,15);  
arc(225,275,0,180,10);  
arc(225,275,0,180,5);
```

```
line(200,220,250,220);  
line(225,220,225,275);
```

```
// arc(350,150,0,180,10);  
line(165,275,285,275);  
line(225,205,200,220);  
line(225,205,250,220);  
line(225,205,225,220);
```

```
line(225,205,230,220);  
line(225,205,235,220);  
line(225,205,240,220);  
line(225,205,245,220);
```

```
line(225,205,220,220);  
line(225,205,215,220);  
line(225,205,210,220);  
line(225,205,205,220);
```

```
line(225,200,225,205);
```

```
arc(145,300,0,180,6);  
line(143,300,147,300);  
line(145,290,145,294);
```

```
arc(305,300,0,180,6);  
line(303,300,307,300);  
line(305,290,305,294);
```

```
line(62,400,113,400);  
line(57,390,118,390);  
line(57,390,62,400);  
line(59,390,62,400);  
line(61,390,62,400);  
line(60,390,62,400);  
line(62,390,62,400);
```

```
line(118,390,113,400);  
line(116,390,113,400);  
line(114,390,113,400);  
line(113,390,113,400);
```

```
line(65,325,109,325);  
line(60,315,114,315);  
line(60,315,65,325);  
line(62,315,65,325);  
line(63,315,65,325);  
line(64,315,65,325);  
line(65,315,65,325);  
line(114,315,109,325);  
line(112,315,109,325);  
line(110,315,109,325);  
line(109,315,109,325);
```

```
line(71,225,104,225);  
line(65,215,110,215);  
line(65,215,71,225);  
line(67,215,71,225);
```

line(69,215,71,225);
line(70,215,71,225);
line(110,215,104,225);
line(108,215,104,225);
line(106,215,104,225);
line(105,215,104,225);

line(337,400,388,400);
line(332,390,393,390);
line(332,390,337,400);
line(334,390,337,400);
line(336,390,337,400);
line(337,390,337,400);
line(393,390,388,400);
line(391,390,388,400);
line(389,390,388,400);
line(388,390,388,400);

line(341,325,384,325);
line(336,315,389,315);
line(336,315,341,325);
line(338,315,341,325);
line(340,315,341,325);
line(389,315,384,325);
line(387,315,384,325);
line(385,315,384,325);
line(384,315,384,325);

line(346,225,379,225);
line(341,215,384,215);
line(341,215,346,225);
line(343,215,346,225);
line(345,215,346,225);
line(346,215,346,225);

line(384,215,379,225);
line(382,215,379,225);

```
line(380,215,379,225);
```

```
line(379,215,379,225);
```

```
/* clean up */
```


```
getch();
```

```
closegraph();
```

```
return 0;
```

```
}
```

Windows BGI



9. C++ program to move a circle along the screen.

```
#include <iostream>
#include <graphics.h>
#include <stdlib.h>
#include <stdio.h>
#include <conio.h>
#include <dos.h>
using namespace std;
int main()
{
    int gdriver = DETECT, gmode, errorcode;
    int xmax, ymax;
    initgraph(&gdriver, &gmode, "c:\\\\turbo3\\bgi");
    errorcode = graphresult();
    if (errorcode != grOk)
    {
        printf("Graphics error: %s\\n", grapherrormsg(errorcode));
        printf("Press any key to halt:");
        getch();
        exit(1);
    }
    xmax = getmaxx();
    ymax = getmaxy();
    {
        while(!kbhit())
    {
        for(int i=0;i<=800;i+=10)
        {
            delay (100);


            cleardevice();
            printf("\\n \\t Move The Circle On The Sren");
            circle(i,100,100);
        }
        for(int i=800;i>=20;i-=10)
        {
            delay(100);
```

```

        cleardevice();
        printf("\n \t Move The Circle On The Screen");
        circle(i-50,100,100);
    }

    getch();
    closegraph();
    return 0;
}
}

```



```

D:\#New\#dev\mine\Moves a Circle along the Screen\Moves a Circle along the Screen.exe
Move The Circle On The Screen
Move The Circle On The Screen
Move The Circle On The Screen
Move The Circle On The Screen
Move The Circle On The Screen
Move The Circle On The Screen
Move The Circle On The Screen
Move The Circle On The Screen
Move The Circle On The Screen
Move The Circle On The Screen
Move The Circle On The Screen
Move The Circle On The Screen
Move The Circle On The Screen
Move The Circle On The Screen
Move The Circle On The Screen
Move The Circle On The Screen
Move The Circle On The Screen
Move The Circle On The Screen
Move The Circle On The Screen
Move The Circle On The Screen
Move The Circle On The Screen
Move The Circle On The Screen
Move The Circle On The Screen
Move The Circle On The Screen
Move The Circle On The Screen
Move The Circle On The Screen
Move The Circle On The Screen

```





10. C++ program to draw a moving circle.

```
#include <iostream>
#include <graphics.h>
#include <stdlib.h>
#include <stdio.h>
#include <conio.h>
#include <dos.h>
using namespace std;
int main(void)
{
    /* request auto detection */
    int gdriver = DETECT, gmode, errorcode;
    int xmax, ymax;
    int i;
    /* initialize graphics and local variables */
    initgraph(&gdriver, &gmode, "C:\\TURBOC3\\BGI");
    /* read result of initialization */
    errorcode = graphresult();
    /* an error occurred */
    if (errorcode != grOk)
    {
        printf("Graphics error: %s\n", grapherrormsg(errorcode));
        printf("Press any key to halt:");
        getch();
    }
}
```




```

    exit(1);
}

{
    while(!kbhit())
{
    for(int i=0;i<=500;i+=10)
        delay(100);
        cleardevice();
        circle(i,50,50);}
for(i=550;i>=20;i-=10)
{
    delay(100);
    circle(i-50,50,50);}
}
/* clean up */
getch();
closegraph();
return 0;
}

```



11. C++ program to draw a rectangle.

```
#include <graphics.h>
#include <stdlib.h>
#include <stdio.h>
#include <conio.h>
int main()
{
    int gdriver = DETECT, gmode, errorcode;
    int xmax, ymax;
    initgraph(&gdriver, &gmode, "c:\\turbo3\\bgi");
    errorcode = graphresult();
    if (errorcode != grOk)
    {
        printf("Graphics error: %s\n", grapherrormsg(errorcode));
        printf("Press any key to halt:");
        getch();
        exit(1);
    }
    setcolor(getmaxcolor());
    xmax = getmaxx();
    ymax = getmaxy() ;
    int left = getmaxx() / 2 ;


    int top = getmaxy() / 2 - 50;
    int right = getmaxx() / 5;
    int bottom = getmaxy() / 2 + 50;
    printf("\n Display the Retangler");
    rectangle(left,top,right,bottom);
    getch();
    closegraph();
    return 0;
```



12. C++ program to draw a square.

```
#include <graphics.h>
#include <stdlib.h>
#include <stdio.h>
#include <conio.h>
int main()
{
    int gdriver = DETECT, gmode, errorcode;
    int xmax, ymax;
    initgraph(&gdriver, &gmode, "c:\\turbo3\\bgi");
    errorcode = graphresult();
    if (errorcode != grOk)
    {
        printf("Graphics error: %s\n", grapherrormsg(errorcode));
        printf("Press any key to halt:");
        getch();
        exit(1);
    }
    setcolor(getmaxcolor());
    xmax = getmaxx();
    ymax = getmaxy() ;

    int left = getmaxx()/2-50 ;
    int top = getmaxy()/ 2 - 50;
    int right = getmaxx()/2+50;
    int bottom = getmaxy()/2+50;
    rectangle(left,top,right,bottom);
    getch();
    closegraph();
    return 0;
}
```




13. Write a C++ program that draws 2D and 3D rectangles with patterns and colors on Windows BGI using bar() and bar3d() functions in graphical programming.

```
#include <iostream>
#include <graphics.h>
using namespace std;
int main()
{
    int gd=DETECT, gm, err,x=30,y=30;
    initgraph(&gd,&gm,"");
    err=graphresult();
    if(err!=grOk)
    {
        cout<<"Graphics Error "<<grapherrormsg(err);
        exit(1);
    }
    setcolor(BLUE);
    setfillstyle(3,LIGHTRED);
    bar(30,30,100,150);
    setfillstyle(11,CYAN);
    bar3d(150,30,220,150,10,1);
    getch();
    closegraph();
    return 0;
}
```



14. Write a C++ program that draws an arc and ellipse on BGI Window using ellipse() and fillellipse() functions in graphical programming.

```
#include <iostream>
#include <graphics.h>
using namespace std;
int main()
{
    int gd=DETECT, gm, err;
    initgraph(&gd,&gm,"");
    err=graphresult();
    if(err!=grOk)
    {
        cout<<"Graphics Error "<<grapherrormsg(err);
        exit(1);
    }
    ellipse(130,70,90,180,100,50);
    fillellipse(130,150,100,50);
    getch();
    closegraph();
    return 0;
}
```



15. Write a program that draws ellipse and circle with patterns and colors on Windows BGI using setfillstyle() and floodfill() functions in graphical programming.

```
#include <iostream>
#include <graphics.h>
using namespace std;
int main()
{
    int gd=DETECT, gm, err,x=30,y=30;
    initgraph(&gd,&gm,"");
    err=graphresult();
    if(err!=grOk)
    {
        cout<<"Graphics Error "<<grapherrormsg(err);
        exit(1);
    }
    setcolor(RED);
    setfillstyle(8,10);
    fillellipse(100,50,50,25);
    circle(150,150,50);
    floodfill(150,150,4);
    getch();
    closegraph();
    return 0;
}
```

