

Instructions

CS 6650 – Final Project Report

Smriti Reddy Uravakonda, Darsh Pandya
Northeastern University

December 2025

1 Instructions

This document explains how to build and run the Manager–Worker distributed monitoring system. The system supports any number of managers (minimum 3 for Raft) and any number of workers.

2 Requirements

- Linux environment (Khoury cluster)
- g++ with C++17 support
- make
- Bash shell

3 Build the Project

Khoury Linux Cluster Instructions

3.1 Login

```
ssh yourusername@linux-xx.khoury.northeastern.edu
```

3.2 Transfer Project

```
scp -r distributed-cluster-monitoring-system \  
yourusername@linux-xx.khoury.northeastern.edu:~
```

3.3 Compile and Run

```
cd distributed-cluster-monitoring-system  
make clean  
make
```

This produces two executables: `manager` and `worker_bin`.

3.4 Run Automated Test Script

```
chmod +x run_tests_auto.sh  
./run_tests_auto.sh
```

It demonstrates leader election, failover, quorum loss, and recovery.

4 Running Managers (manual testing if required)

4.1 General Syntax

```
./manager <node_id> <raft_port> <peer_list>
```

- <node_id> — unique ID (e.g., node1)
- <raft_port> — unique RAFT port (e.g., 5001)
- <peer_list> — comma-separated list of other managers

4.2 Example: Single Manager

```
./manager node1 5001 ""
```

(Yes, the quotes are important)

4.3 Example: Three Managers

```
./manager node1 5001 node2:5002,node3:5003
```

```
./manager node2 5002 node1:5001,node3:5003
```

```
./manager node3 5003 node1:5001,node2:5002
```

4.4 Example: Four Managers

```
./manager node1 5001 node2:5002,node3:5003,node4:5004
```

```
./manager node2 5002 node1:5001,node3:5003,node4:5004
```

```
./manager node3 5003 node1:5001,node2:5002,node4:5004
```

```
./manager node4 5004 node1:5001,node2:5002,node3:5003
```

4.5 Example: N Managers

Each manager must:

1. Have a unique node ID
2. Have a unique RAFT port
3. List all other managers in its peer list

5 Running Workers

5.1 General Syntax

```
./worker_bin <worker_id>
```

5.2 Example

```
./worker_bin worker1
```

```
./worker_bin worker2
```

```
./worker_bin worker3
```

6 Cluster State Output

Worker state is written by the leader to `workers.json`, updated every few seconds.

```
{
  "workers": [
    {
      "id": "worker1",
      "online": true,
      "last_seen_seconds_ago": 1,
      "status": "active"
    }
  ]
}
```

7 Stopping All Processes

```
pkill -f "./manager"
pkill -f "./worker_bin"
```

8 Logs

Manager logs:

```
node_<node_id>.log
```

Worker logs:

```
<worker_id>.log
```

View logs:

```
tail -n 50 node_node1.log
```

9 Recommended Configuration

- At least 3 managers for Raft
- Prefer odd numbers (3, 5, 7)
- Any number of workers may be used

Managers and workers can be added or removed dynamically, and the cluster maintains eventual consistency.